

KTM India Full Lineup

KTM India — Full Model Lineup (Consolidated from Official Brochures)

Source type: Official KTM India brochures (PDFs) supplied directly by the user, plus the KTM Assure AMC (service plan) brochure. **Compiled:** 2026-09-06 **Corporate note:** KTM is now a Bajaj Auto-owned brand in India (Bajaj Auto completed its acquisition of KTM per late-2025 reporting) — verify exact deal terms/date against Bajaj’s own investor filings before treating as final, per this project’s source-tiering discipline. **Scope note:** This document covers everything present in the 11 KTM brochure PDFs supplied (Duke range, Adventure range, RC range, 890 Duke R, 85 SX, 65 SX, KTM Assure AMC). A separate 43MB “KTM PowerWear Folder 2023” apparel/gear catalog was also uploaded but is NOT included here — it is rider apparel and merchandise (jackets, helmets, gloves), not motorcycle specifications, and belongs in a separate document if needed for the knowledge base. **Disclaimer carried from source brochures:** “Visuals and specifications are market dependent”; “The models shown in the picture may vary from the actual product.” Treat all figures below as manufacturer-claimed/brochure-stated, not independently verified — flag for the same OEM-vs-independent split used elsewhere in this project if these figures are cross-checked later.

1. KTM Duke Range (Naked Streetfighters)

Brand line: “Naked from the ground up.” Marketing tagline across all Duke models: “Ready to Race.”

1.1 Duke Range — Full Specs Comparison Table

Specification	390 Duke R	390 Duke	250 Duke	200 Duke	160 Duke
Engine Type	4-Stroke, Single Cylinder, DOHC, Liquid Cooled	4-Stroke, Single Cylinder, DOHC, Liquid Cooled	4-Stroke, Single Cylinder, SOHC, Liquid Cooled	4-Stroke, Single Cylinder, DOHC, Liquid Cooled	4-Stroke, Single Cylinder, SOHC, Liquid Cooled
Engine Capacity	398.63 cc	349.32 cc	249.07 cc	199.5 cc	164.2 cc
Power	46 PS @ 8500 rpm	41.5 PS @ 8600 rpm	31 PS @ 9250 rpm	25 PS @ 10,000 rpm	19 PS @ 9500 rpm
Torque	39 Nm @ 6500 rpm	33.5 Nm @ 7000 rpm	25 Nm @ 7250 rpm	19.3 Nm @ 8,000 rpm	15.5 Nm @ 7500 rpm
Front Brake	320 mm disc, radially mounted caliper	320 mm disc, radially mounted caliper	320 mm disc, radially mounted caliper	300 mm disc, 4-piston radially mounted fixed caliper	320 mm disc, radial caliper
Rear Brake	240 mm disc, floating caliper	240 mm disc, floating caliper	240 mm disc, floating caliper	230 mm disc, 1-piston floating caliper	230 mm disc, floating caliper
ABS	Bosch dual-channel w/	Bosch dual-channel w/	Bosch dual-channel w/	Bosch dual-channel w/	Dual-channel w/ SuperMoto

	SuperMoto mode	SuperMoto mode	SuperMoto mode	SuperMoto mode	mode
Chassis	Split-steel trellis frame	Split-steel trellis frame	Split-steel trellis frame	Split-steel trellis frame	Split-steel trellis frame
Kerb Weight	168.3 kg	168.3 kg	162.8 kg	159 kg	147 kg
Fuel Tank	15 L	15 L	15 L	13.5 L	10.1 L
Transmission	6-speed	6-speed	6-speed	6-speed	6-speed
Key Features	5" TFT, Bluetooth, Quickshifter+, Cruise Control, Cornering ABS, MTC, adjustable suspension (front & rear)	5" TFT, Bluetooth, Quickshifter+, Cruise Control, Cornering ABS, MTC, adjustable suspension (front & rear)	5" TFT, Bluetooth, Quickshifter+, Ride-by-Wire, slipper clutch, LED headlamp	5" TFT, Bluetooth, MY RIDE, LED headlamp	LCD/TFT display, DRL, LED headlamp, slipper clutch
Colours	Atlantic Blue, Gun Metal Gray, Electronic Orange	Atlantic Blue, Slate Grey, Liquid Carbon	Atlantic Blue, Ebony Black, Electronic Orange	Dark Galvano, Silver Metallic, Electronic Orange, Atlantic Blue	Atlantic Blue, Metallic Silver, Electronic Orange

1.2 Duke Range — Individual Model Positioning (from marketing copy)

- **390 Duke R — “The Corner Rocket”**: positioned as the most powerful 400cc bike in KTM’s India lineup. Tech: Cruise Control, Cornering ABS, Super Moto ABS, Quickshifter+, Ride-by-Wire, split trellis frame, front adjustable suspension, Motorcycle Traction Control, Ride Modes, Launch Control.
- **390 Duke — “The Corner Rocket”**: marketed as “the ultimate Corner Rocket,” most powerful 350cc bike. Same electronics package as 390 Duke R (Cruise Control, Cornering ABS, Super Moto ABS, Quickshifter+, Ride-by-Wire, MTC, Ride Modes, Launch Control, adjustable front suspension).
- **250 Duke — “The Thrill Chaser”**: billed as the pioneer of the 250cc naked streetfighter segment in India, “authentic racing DNA.” Most powerful 250cc bike (per brochure claim). 5" TFT with Bluetooth, Super Moto ABS, Quickshifter+, Ride-by-Wire, 6-speed gearbox, rear adjustable suspension, dual-channel ABS.
- **200 Duke — “The Light Heavyweight”**: “predatory design,” ultra-compact single-cylinder 4-stroke engine, most powerful 200cc bike (per brochure claim). 5" TFT with Bluetooth, Super Moto ABS, 6-speed gearbox, rear adjustable suspension, dual-channel ABS.
- **160 Duke — “The Most Powerful 160”**: entry point into KTM’s racing lineage per marketing copy. Trellis frame, slipper clutch, most powerful 160cc bike (per brochure claim). 5" TFT/LCD screen, power-assisted slipper clutch, Super Moto ABS, dual-channel ABS, rear adjustable suspension, 6-speed gearbox.

KTM’s stated brand values across the range (from brochure): **Purity, Performance, Adventure, Extreme** — all under the “Ready to Race” positioning, referencing over 370 world championships across Motocross, Enduro, and Supercross.

2. KTM Adventure Range (Adventure-Touring / Off-Road)

Brand tagline for this range: “Get Out There” / “The True Meaning of Adventure.” Philosophy statement from brochure: “At KTM, Ready to Race isn’t just a slogan – it’s our DNA. Every motorcycle we build is engineered with precision, agility, and relentless performance that’s built to dominate dirt, tarmac and everything in between.”

2.1 Adventure Range — Specs Comparison Table (390 R / S / X)

Specification	KTM 390 Adventure R	KTM 390 Adventure S	KTM 390 Adventure X
Engine Type	4-stroke, single cylinder, DOHC	4-stroke, single cylinder, DOHC	4-stroke, single cylinder, DOHC
Displacement	398.63 cc	398.63 cc	398.63 cc
Bore/Stroke	89 mm x 64 mm	89 mm x 64 mm	89 mm x 64 mm
Power	46 PS @ 8500 rpm	46 PS @ 8500 rpm	46 PS @ 8500 rpm
Torque	39 Nm @ 6500 rpm	39 Nm @ 6500 rpm	39 Nm @ 6500 rpm
Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection
Cooling	Liquid cooled	Liquid cooled	Liquid cooled
Compression Ratio	12.71:1	12.71:1	12.71:1
Front Suspension	WP APEX USD forks, 43mm, 230mm travel, fully adjustable compression/rebound (30 steps)	WP APEX USD open-cartridge forks, 43mm, 200mm travel, fully adjustable compression/rebound (30 steps)	WP APEX USD forks, 43mm, 200mm travel
Rear Suspension	WP APEX monoshock, 230mm travel, adjustable rebound (20 clicks) + preload (10 steps)	WP APEX monoshock, 205mm travel, adjustable rebound (20 clicks) + preload (10 steps)	WP APEX monoshock, 205mm travel, adjustable preload (10 steps)
Instrument Cluster	5" TFT with KTM Connect	5" TFT with KTM Connect	5" TFT with KTM Connect
Rider Aids	MTC, Quickshifter+, 3 Ride Modes, Cruise Control, Cornering ABS, Off-Road ABS, Ride-by-Wire, all-LED lighting w/ LED projector, Cornering Traction Control, Bluetooth w/ navigation	Same minus Cornering Traction Control	Same minus Cornering Traction Control
Frame	Split trellis frame	Split trellis frame	Split trellis frame
Sub-frame	Bolt-on sub-frame	Bolt-on sub-frame	Bolt-on sub-frame
Front Brake	320 mm disc, floating caliper	320 mm disc, floating caliper	320 mm disc, floating caliper
Rear Brake	240 mm disc, floating caliper	240 mm disc, floating caliper	240 mm disc, floating caliper
Fuel Tank	14.5 L	14.5 L	14.5 L
Ground Clearance	272 mm	237 mm	228 mm
Saddle/Seat Height	880 mm	830 mm	825 mm
Kerb Weight	183 kg	182 kg	181 kg
Headlight	LED projector, low beam 24W @13.5V / high beam 30W @13.5V + auxiliary lamp	Same	Same
Tyres	21"/18" spoked	21"/17" tubeless spoke	21"/17" tubeless casted wheel
Starter/Battery	Electric starter, 12V 8Ah MF battery	Same	Same
Colour Options	Ceramic White	Electronic Orange, Ceramic White	Electronic Orange, Ceramic White

2.2 Adventure Range — Specs Comparison Table (390 vs 250, standard variants)

Specification	KTM 390 Adventure	KTM 250 Adventure
Engine Type	4-stroke, single cylinder, DOHC	4-stroke, single cylinder, SOHC
Displacement	349.32 cc	249.07 cc
Bore/Stroke	89 mm x 56.15 mm	72 mm x 61.1 mm
Power	41.5 PS @ 8600 rpm	31 PS @ 9250 rpm
Torque	33.5 Nm @ 7000 rpm	25 Nm @ 7250 rpm
Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection
Cooling	Liquid cooled	Liquid cooled
Compression Ratio	12.68:1	12.63:1
Front Suspension	WP APEX USD forks, 43mm, 200mm travel	WP APEX USD forks, 43mm, 200mm travel

Rear Suspension	WP APEX monoshock, 205mm travel, adjustable preload (10 steps)	Same
Instrument Cluster	5" TFT with KTM Connect	5" TFT with KTM Connect
Rider Aids	MTC, Quickshifter+, 3 Ride Modes, Cruise Control, Cornering ABS, Off-Road ABS, Ride-by-Wire, LED lighting, Bluetooth w/ navigation	Off-road ABS, Ride-by-Wire, Quickshifter+, slipper clutch, 12V USB socket, LED lighting, Bluetooth w/ navigation
Frame	Split trellis frame	Split trellis frame
Front Brake	320 mm disc, floating caliper	320 mm disc, radially mounted caliper
Rear Brake	240 mm disc, floating caliper	240 mm disc, floating caliper
Fuel Tank	14.5 L	14.5 L
Ground Clearance	228 mm	228 mm
Saddle Height	825 mm	825 mm
Kerb Weight	181 kg	176 kg
Tyres	19"/17" tubeless casted wheel	19"/17" tubeless casted wheel
Colour Options	Ceramic White	Electronic Orange, Ceramic White

2.3 Model-Specific Marketing Positioning

- **390 Adventure R — “A New Benchmark in Off-Road Adventure”**: rally-tuned power, high-clearance off-road-focused chassis. 21"/18" spoked wheels, long-travel WP APEX suspension (230mm travel both ends), Ride-by-Wire with Street/Rain/Off-Road modes, MTC, Cornering ABS + dedicated Off-Road ABS, Cruise Control, Quickshifter+.
- **390 Adventure S — “Your Gateway to Terrains Beyond Roads”**: billed as “the ideal start to the world of adventure touring... light, capable, and confidence-building.” Advanced electronics package, rally-inspired bodywork (inspired by KTM’s Dakar heritage), 5" TFT with KTM Connect (turn-by-turn navigation, calls, music).
- **390 Adventure X**: same positioning copy as the S variant in this brochure set (“ideal start... light, capable, confidence-building”) — brochure text for S and X appears templated/near-identical aside from spec differences (see comparison tables); X has cast alloy wheels and shorter suspension travel vs. S’s spoked wheels and longer travel.
- **390 Adventure (standard) — “The Next Era in Hardcore Adventure Travel”**: 2025 model update noted as “All-New Adventure Platform, built with 99% new components.” New 399cc-class LC4c engine (39 Nm @ 6500 rpm, 46 PS @ 8500 rpm), 237mm ground clearance, 830mm seat height, 21"/17" tubeless spoke wheels, adjustable WP APEX suspension (30-click front, 20-click rear), Cornering MTC, Quickshifter+, 3 Ride Modes, Cruise Control, Cornering ABS, Off-Road ABS.
 - Note: this brochure’s “390 Adventure” positioning/spec sheet (Section 2.3, 46 PS/39 Nm) differs from the “390 Adventure” comparison-table figures in Section 2.2 (41.5 PS/33.5 Nm) — **two different brochures in this source set describe a “KTM 390 Adventure” with different power/torque figures.** This is very likely a 2024-vs-2025 model-year difference (the 2025 brochure explicitly says “All-New Adventure Platform... 99% new components,” language consistent with a mid-cycle engine update), but the brochures themselves don’t date-stamp this distinction. **Flag as unresolved — do not silently merge; verify current model-year specs directly with KTM India before using either figure as the single source of truth.**
- **390 Adventure X (2025 update brochure)**: “Rally-Inspired

Bodywork... inspired by KTM's Dakar racing heritage," 19"/17" tubeless alloy wheels, Quickshifter+, Off-road ABS, Ride-by-Wire, LED projector headlamps, 825mm seat height, 5" TFT with KTM Connect.

- **250 Adventure — “For the Adventure Tourer in You”:** “built for riders who demand more than just a casual adventure machine... rally-inspired performance and class-leading electronics.” 19"/17" tubeless alloy wheels, Quickshifter+, Off-road ABS, Ride-by-Wire, LED projector headlamps, 5" TFT with KTM Connect, 249.07cc single-cylinder liquid-cooled SOHC engine.

2.4 Adventure Range — Shared Feature Highlights (from brochure feature call-outs)

- **Suspension & Handling:** 390 Adventure has fully adjustable WP APEX suspension (front 43mm inverted forks, 30-click compression/rebound; rear monoshock, 20-click rebound + 10-step preload) — described as offering “superior control, comfort, and adjustability on any terrain.” 390 Adventure X has preload-adjustable WP APEX suspension only (200mm front / 205mm rear travel) with 19"/17" tubeless alloy wheels for road-biased “touring-ready” use, vs. the standard/R variants’ spoked wheels for off-road use.
- **Electronics & Connectivity:** CTC (Cornering Traction Control) — 390 Adventure only; MTC (Motorcycle Traction Control) — across the range; Cornering ABS + Off-Road ABS; 3 Ride Modes (Rain, Street/Road, Sport/Off-Road naming varies slightly by brochure); Cruise Control; high-intensity LED projector headlamp on both 390 Adventure and Adventure X; KTM Connect via 5" TFT (turn-by-turn navigation, calls, music control).
- **Comfort & Ergonomics:** 390 Adventure seat height 830mm vs. Adventure X’s lower 825mm (“more accessible and confidence-inspiring” per brochure). Grippy footpegs with removable rubber inserts, adjustable brake/clutch levers, aerodynamically tuned windshield to reduce buffeting.
- **Adventure-Ready Build Features:** high-mounted underbelly exhaust for ground clearance/protection, 14.5L fuel tank (“more miles, less stops”), lightweight split trellis frame for stability on- and off-road.

3. KTM RC Range (Sports/Track-Focused)

Brand positioning: “Racetrack DNA for the Street.” Brochure states the RC range is “visually inspired by some of the world’s most competitive racers” and echoes the styling/ergonomics of KTM’s RC16 MotoGP racer.

3.1 RC Range — Full Technical Specifications

Specification	RC 390	RC 200	RC 125
Engine Type	Single Cylinder, Liquid Cooled, DOHC, FI	Single Cylinder, Liquid Cooled, DOHC, FI	4-Valve, Single Cylinder, Liquid Cooled, DOHC, FI
Engine Displacement	373.27 cc	199.5 cc	124.7 cc
Bore x Stroke	89 mm x 60 mm	72 mm x 49 mm	58 mm x 47.2 mm
Power	43.5 PS @ 9,000 rpm (32 kW)	25 PS @ 10,000 rpm (18.4 kW)	14.5 PS @ 9,250 rpm (10.7 kW)
Torque	37 Nm @ 7,000 rpm	19.2 Nm @ 8,000 rpm	12 Nm @ 8,000 rpm
Fuel Injection	Bosch Electronic Fuel Injection	Bosch Electronic Fuel Injection	Bosch Electronic Fuel Injection

Lubrication	Forced, Wet Sump	Forced, Wet Sump	Forced
Cooling	Liquid cooling, curved radiator with fans	Liquid cooling, curved radiator with fans	Liquid cooling, curved radiator with fans
Compression Ratio	12.88:1	11.3:1	12.8:1
Front Suspension	WP APEX USD forks, 43mm diameter	WP APEX USD forks, 43mm diameter	WP APEX USD forks, 43mm diameter
Rear Suspension	WP APEX Monoshock, 10-step adjustable	WP APEX Monoshock, 10-step adjustable	WP APEX Monoshock, 10-step adjustable
Frame	Split-Trellis Frame (Tubular)	Split-Trellis Frame (Tubular)	Split-Trellis Frame (Tubular)
Sub Frame	Newly engineered bolt-on subframe	Newly engineered bolt-on subframe	Newly engineered bolt-on subframe
Front Brake	320mm disc, radially mounted caliper	320mm disc, radially mounted caliper	320mm disc, radially mounted caliper
Rear Brake	230mm disc, floating caliper	230mm disc, floating caliper	230mm disc, floating caliper
Fuel Tank	13.7 L	13.7 L	13.7 L
Ground Clearance	153 mm	158 mm	158 mm
Saddle Height	835 mm	835 mm	835 mm
Kerb Weight	172 kg	160 kg	160 kg
Rider Aids	MTC, Cornering ABS, Quickshifter+, dual-channel ABS w/ SuperMoto mode	SuperMoto ABS	SuperMoto ABS
Starter/Battery	12V, 8Ah MF battery	12V, 8Ah MF battery	12V, 8Ah MF battery
Headlight	LED Headlamp	LED Headlamp	Halogen headlamp with LED pilot lamps
Instrument Cluster	TFT Multifunction Display	New LCD Dash Display	New LCD Dash Display
Colours	Orange, Blue, GP Edition (orange livery)	Black, Blue, GP Edition (orange livery)	Orange, Blue

3.2 RC Range — Feature Set by Model (from brochure comparison matrix)

Feature	RC GP 390	RC 390	RC GP 200	RC 200	RC 125
MTC (Motorcycle Traction Control)	Yes	Yes	No	No	No
Quickshifter+	Yes	Yes	No	No	No
Cornering ABS	Yes	Yes	No	No	No
SuperMoto ABS	Yes	Yes	Yes	Yes	No
TFT Display	Yes	Yes	No	No	No
LCD Dash Display	No	No	Yes	Yes	Yes
LED Headlamps	Yes	Yes	Yes	Yes	No (halogen w/ LED pilot lamps)
DOHC Engine	Yes	Yes	Yes	Yes	Yes
Slipper Clutch (PASC anti-hopping)	Yes	Yes	No	No	No
40% Larger Airbox	Yes	Yes	Yes	Yes	Yes
Curved Radiator	Yes	Yes	Yes	Yes	Yes
MotoGP-Inspired Bodywork	Yes	Yes	Yes	Yes	Yes
13.7L Fuel Tank	Yes	Yes	Yes	Yes	Yes
Clip-on Adjustable Handlebars	Yes	Yes	Yes	Yes	Yes
Max Rider Contact (rider-centric layout)	Yes	Yes	Yes	Yes	Yes

Note: “RC GP 390” and “RC GP 200” are the GP Edition trims — same underlying spec as RC 390/RC 200 respectively, distinguished by livery/graphics (per the “Available Colours” pages) rather than any separate mechanical spec sheet in this brochure.

3.3 KTM Pro-XP — Owner Experience Program (bonus content found in RC brochure, applies brand-wide, not RC-specific)

“KTM Pro-XP (experiences) are curated experiences exclusive for owners of KTM... access to complete riding experiences across track, tarmac, and trails curated and led by KTM experts.” Programs listed: - **Power Rides**: rides to iconic destinations led by KTM experts. - **Pro-Getaways**: exclusive single-day ride for 250cc+ owners. - **Urban Escapes**: dealer-led morning rides. - **Adventure Academy**: closed-circuit off-road training program. - **Adventure Trails**: single-day adventure rides on curated trails. - **Adventure Tours**: multi-destination adventure touring routes.

This is brand-level ownership/community content — relevant to the “brand identity & positioning” schema category, not a per-model spec.

4. KTM 890 Duke R (Flagship Naked)

Full spec sheet, extracted verbatim from the standalone brochure (India-market listing; text-native PDF, not image-based, so figures below are transcribed directly rather than read off a rendered page).

Specification	KTM 890 Duke R
Engine Type	2-cylinder, 4-stroke, DOHC parallel twin (Euro 5)
Displacement	889 cc
Bore/Stroke	90.7 / 68.8 mm
Power	89 kW (121 hp) @ 9,250 rpm
Torque	99 Nm @ 7,750 rpm
Compression Ratio	13.5:1
Starter/Battery	Electric / 12V 10Ah
Transmission	6 gears
Fuel System	DKK Dell’Orto (46mm throttle body)
Control	4 valves per cylinder / DOHC
Lubrication	Pressure lubrication, 2 oil pumps
Engine Oil	Motorex Power Synth SAE 10W-50
Primary/Final Drive	39:75 / 16:41
Cooling	Liquid cooled w/ water-oil heat exchanger
Clutch	Cable-operated PASC slipper clutch
Engine Management/Ignition	Bosch EMS with Ride-by-Wire
Traction Control	MTC — lean-angle sensitive, 3-mode disengageable + optional Track mode
CO2 Emissions	110 g/km
Fuel Consumption	4.74 L/100km
Frame	Chromium-Molybdenum-Steel, engine as stressed member, powder coated
Subframe	Aluminium, powder coated
Handlebar	Aluminium, tapered, Ø28/22mm
Front Suspension	WP APEX 43, adjustable compression & rebound
Rear Suspension	WP APEX Monoshock, adjustable compression (high/low speed), rebound, hydraulic preload
Suspension Travel (F/R)	140mm / 150mm
Front Brake	2× Brembo Stylema 4-piston radial calipers, 320mm discs
Rear Brake	Brembo single-piston floating caliper, 240mm disc
ABS	Bosch 9.1 MP, incl. Cornering ABS and SuperMoto mode

Wheels (F/R)	Cast aluminium, 3.50×17" / 5.50×17"
Tyres (F/R)	120/70 ZR17, 180/55 ZR17
Chain	X-Ring 520
Steering Head Angle	65.7°
Trail	99.7 mm
Wheelbase	1,482 mm ± 15mm
Ground Clearance	206 mm
Seat Height	834 mm
Tank Capacity	~14 L (incl. 3.5 L reserve)
Dry Weight	~166 kg
Weight (ready to race)	~171 kg
Weight (fully fuelled)	~184 kg

5. Off-Road / Junior Motocross Range

5.1 KTM 85 SX (2023 model, 17"/14" wheel spec)

Specification	KTM 85 SX
Engine Type	Single-cylinder, 2-stroke, liquid cooled
Displacement	84.9 cc
Bore/Stroke	47 / 48.95 mm
Starter	Kickstarter
Carburetor	Keihin PWK 28
Control	Exhaust flap (RPM dependent)
Lubrication	Mixture lubrication 1:40
Transmission	6 gears
Gear Ratios	11:29, 14:28, 16:26, 19:26, 21:25, 20:21
Primary/Final Drive	20:64 / 13:46
Clutch	Wet multi-disc, Formula hydraulics
Ignition	MEDJ digital
Frame	Double-grinded central double-cradle
Subframe	Aluminum
Front Suspension	XACT 43 WP USD fork, Ø43mm
Rear Suspension	XACT WP PDS monoshock
Suspension Travel (F/R)	278mm / 305mm
Front/Rear Brake	240mm disc / 220mm disc
Rims (F/R)	1.40×17" / 1.60×14" alloy
Tyres (F/R)	70/100×17" / 90/100×14"
Steering Head Angle	66°
Wheelbase	1,290mm ± 10mm
Ground Clearance	336 mm
Seat Height	865 mm
Tank Capacity	~5.2 L
Weight (ready to race, no fuel)	~67 kg

5.2 KTM 65 SX (2024 model)

Specification	KTM 65 SX
Engine Type	Single-cylinder, 2-stroke, liquid cooled
Displacement	64.9 cc
Bore/Stroke	45 / 40.8 mm
Starter	Kickstarter
Carburetor	Mikuni VM 24
Control	Slide valve, exhaust-gas-pressure dependent
Lubrication	Mixture lubrication 1:60
Transmission	6 gears
Gear Ratios	13:37, 16:34, 18:31, 21:30, 23:28, 24:26
Primary/Final Drive	23:75 / 14:48
Clutch	Wet multi-disc, Formula hydraulics
Ignition	HIDRIA digital
Frame	Central double-cradle
Subframe	Steel / polyamide glass fiber

Front Suspension	XACT 35 WP USD fork, Ø35mm
Rear Suspension	XACT WP monoshock
Suspension Travel (F/R)	215mm / 253.5mm
Front/Rear Brake	198mm disc / 180mm disc
Rims (F/R)	1.60×14" / 1.60×12" alloy
Tyres (F/R)	60/100×14" / 80/100×12"
Steering Head Angle	64.5°
Wheelbase	1,142mm ± 10mm
Ground Clearance	259 mm
Seat Height	730 mm
Tank Capacity	~4.5 L
Weight (ready to race, no fuel)	~53.5 kg

(Both mini/junior MX models are genuinely distinct SKUs not covered anywhere else in the source set — this fills a real gap for KTM's junior racing lineup.)

6. KTM Assure — Annual Maintenance Contract (AMC) Program

KTM India's paid service-plan program (separate from standard warranty), covering scheduled maintenance costs. Tagline: "Stress-Free Maintenance — Enjoy benefits up to 30%."

6.1 Plan Tiers and What's Covered

Coverage Item	Comprehensive Plan	Periodic Plan
All scheduled service per owner's manual	Yes	Yes
Replacement of spare parts at periodic maintenance	Yes	No
Labor cost for periodic maintenance	Yes	Yes
Starting price (2-year package)	₹11,799	₹6,699

Both plans also come in 3-year variants (see pricing table below).

6.2 Per-Model AMC Pricing (₹, as listed in brochure)

Model	Comprehensive 2-yr	Comprehensive 3-yr	Periodic 2-yr	Periodic 3-yr
KTM 390 Duke	₹16,899	₹26,999	₹9,099	₹13,799
KTM 250 Duke	₹12,799	₹21,499	₹7,449	₹11,499
KTM 200 Duke	₹11,799	₹19,999	₹6,699	₹10,399
KTM RC 390	₹16,899	₹26,999	₹9,099	₹13,799
KTM RC 200	₹11,799	₹19,999	₹6,699	₹10,399
KTM 250 Adventure	₹13,999	₹23,099	₹9,249	₹14,099
KTM 390 Adventure	₹13,999	₹23,099	₹9,249	₹14,099
Husqvarna Svartpilen 401	₹16,899	₹26,999	₹9,099	₹13,799
Husqvarna Vitpilen 250	₹12,799	₹21,499	₹7,449	₹11,499

Note: this pricing table includes two Husqvarna models (Svartpilen 401, Vitpilen 250) — Husqvarna Motorcycles is a sister brand under Bajaj/Pierer Mobility's stable, sold through overlapping dealership infrastructure in India. Not one of the 10 target brands in this project's scope, but flagged here since it appeared directly in a KTM-branded source document; exclude from KTM-specific structured fields, but worth a note if Husqvarna is ever added as a brand.

6.3 Key Terms & Conditions

- Applicable only for KTM motorcycles purchased from authorized dealerships.
- Plans must be purchased within the first 90 days of purchasing the motorcycle.
- Spare-parts price-hike protection covers only parts listed in the service schedule.
- Comprehensive plans cover wear-and-tear components only; accidental damage or misuse is not covered.
- Policy is transferable to the next owner of the motorcycle.
- Terms subject to change per KTM's policy.

6.4 Periodic Maintenance Parts Included (frequency over plan life)

Part	2-Year Frequency	3-Year Frequency
Engine Oil	5	7
Oil Filter	5	7
O-Ring	5	7
Air Filter	2	3
Spark Plug	2	3
Brake Fluid	1	2
BLDC Filter	1	2
Paid Service Labour (instances)	2	4
Chain Lubrication	3	3
Consumables	5	7

6.5 Add-On Parts Replacement Frequency (Comprehensive Plan only)

Part	2-Year Frequency	3-Year Frequency
Drive Chain	1	2
Front Sprocket	1	2
Rear Sprocket	1	2
Plate Drive Sprocket	1	2
Brake Pad Front	2	3
Brake Pad Rear	2	3
Clutch Cable	2	2
Fork Oil Seal	1	2
Fork Oil	1	2
Race Ball Kit Upper	1	2
Race Ball Kit Lower	1	2
Accelerator Cable	1	2
Coolant	1	2

This maps directly onto the “ownership economics” schema category used in the TVS/Bajaj master datasets — unlike those brands’ owner-review-sourced anecdotal service-cost figures, this is an actual official published price list, so it can go in as a Tier-1 structured field rather than a caveated anecdote.

7. What’s Deliberately Excluded From This Document

- **KTM PowerWear Folder 2023 (43MB apparel catalog):** rider gear (jackets, helmets, gloves, boots) and merchandise, not motorcycle specs. Not processed in this pass — say the word if you want it summarized or ingested separately (it would map to a different content category than the bike spec sheets, e.g. “accessories”).
- **Two individual 390 Adventure eBrochures duplicated the**

combined Adventure-range brochure's content almost exactly (same marketing copy, same "What's New" feature call-outs) — no unique figures were found in them beyond what's already in Section 2, so they were not transcribed as a separate pass.

- **KTM Assure AMC pricing table also lists two Husqvarna models** (Svartpilen 401, Vitpilen 250) — captured in Section 6.2 with a flag, since Husqvarna is a sister brand under the same corporate/dealer umbrella but is not one of this project's 10 target brands.
-

8. Known Open Items / Flags Carried Into the RAG Pipeline

1. **390 Adventure power/torque discrepancy (Section 2.3)**: one brochure states 46 PS / 39 Nm for the "KTM 390 Adventure" (2025 "All-New Adventure Platform" language), another states 41.5 PS / 33.5 Nm for what's also labelled "KTM 390 Adventure." Most likely a model-year update (2024 vs. 2025), but the brochures don't date-stamp this distinction — verify directly with KTM India before treating either figure as canonical. Both figures are preserved in the document with this flag rather than merged.
2. **KTM ownership/corporate structure**: per web research done alongside this document, Bajaj Auto has completed its acquisition of KTM — confirm exact terms/date from Bajaj's own investor filings before finalizing any "brand identity" field for KTM in the master dataset.
3. All figures in this document are brochure/manufacture-claimed. None have been cross-checked against independent test data (MotorBeam, Autocar India, etc.) the way TVS/Bajaj figures were in the gap-fill pass — if OEM-vs-independent splitting is wanted for KTM too, that's a follow-up research pass, not something derivable from the brochures alone.
4. This document is a `text_doc` in the pipeline's content-type taxonomy (matches the `.md` format used for the TVS/Bajaj RAG docs) — ready to run through `process_and_upsert()` as-is.