fnmatch — Unix-style Glob Pattern Matching

Purpose: Handle Unix-style filename comparisons.

The `fnmatch` module is used to compare filenames against glob-style patterns such as used by Unix shells.

Simple Matching

`fnmatch()` compares a single filename against a pattern and returns a boolean, indicating whether or not they match. The comparison is case-sensitive when the operating system uses a case-sensitive file system.

```
# fnmatch_fnmatch.py

import fnmatch
import os

pattern = 'fnmatch_*.py'
print('Pattern :', pattern)
print()

files = os.listdir('.')
for name in sorted(files):
    print('Filename: {:<25} {}'.format(
        name, fnmatch.fnmatch(name, pattern)))
```

In this example, the pattern matches all files starting with `'fnmatch_'` and ending in `'.py'`.

```
$ python3 fnmatch_fnmatch.py

Pattern : fnmatch_*.py

Filename: fnmatch_filter.py         True
Filename: fnmatch_fnmatch.py        True
Filename: fnmatch_fnmatchcase.py    True
Filename: fnmatch_translate.py      True
Filename: index.rst                 False
```

To force a case-sensitive comparison, regardless of the file system and operating system settings, use `fnmatchcase()`.

```
# fnmatch_fnmatchcase.py

import fnmatch
import os

pattern = 'FNMATCH_*.PY'
print('Pattern :', pattern)
print()

files = os.listdir('.')

for name in sorted(files):
    print('Filename: {:<25} {}'.format(
        name, fnmatch.fnmatchcase(name, pattern)))
```

Since the OS X system used to test this program uses a case-sensitive file system, no files match the modified pattern.

```
$ python3 fnmatch_fnmatchcase.py

Pattern : FNMATCH_*.PY

Filename: fnmatch_filter.py         False
Filename: fnmatch_fnmatch.py        False
```

```
Filename: fnmatch_fnmatchcase.py    False
Filename: fnmatch_translate.py      False
Filename: index.rst                 False
```

Filtering

To test a sequence of filenames, use `filter()`, which returns a list of the names that match the pattern argument.

```
# fnmatch_filter.py

import fnmatch
import os
import pprint

pattern = 'fnmatch_*.py'
print('Pattern :', pattern)

files = list(sorted(os.listdir('.')))

print('\nFiles   :')
pprint.pprint(files)

print('\nMatches :')
pprint.pprint(fnmatch.filter(files, pattern))
```

In this example, `filter()` returns the list of names of the example source files associated with this section.

```
$ python3 fnmatch_filter.py

Pattern : fnmatch_*.py

Files   :
['fnmatch_filter.py',
 'fnmatch_fnmatch.py',
 'fnmatch_fnmatchcase.py',
 'fnmatch_translate.py',
 'index.rst']

Matches :
['fnmatch_filter.py',
 'fnmatch_fnmatch.py',
 'fnmatch_fnmatchcase.py',
 'fnmatch_translate.py']
```

Translating Patterns

Internally, `fnmatch` converts the glob pattern to a regular expression and uses the re module to compare the name and pattern. The `translate()` function is the public API for converting glob patterns to regular expressions.

```
# fnmatch_translate.py

import fnmatch

pattern = 'fnmatch_*.py'
print('Pattern :', pattern)
print('Regex   :', fnmatch.translate(pattern))
```

Some of the characters are escaped to make a valid expression.

```
$ python3 fnmatch_translate.py

Pattern : fnmatch_*.py
Regex   : (?s:fnmatch_.*\.py)\Z
```

See also

- Standard library documentation for fnmatch

- glob – The glob module combines `fnmatch` matching with `os.listdir()` to produce lists of files and directories matching patterns.
- re – Regular expression pattern matching.

glob — Filename Pattern Matching

linecache — Read Text Files Efficiently

Quick Links

This page was last updated 2018-03-18.

Navigation

glob — Filename Pattern Matching
linecache — Read Text Files Efficiently

The output from all the example programs from PyMOTW-3 has been generated with Python 3.7.1, unless otherwise noted. Some of the features described here may not be available in earlier versions of Python.

Looking for examples for Python 2?

This Site

Module Index
Index

Other Writing

Blog
The Python Standard Library By Example