

In computer science, a double-ended queue (dequeue, often abbreviated to deque, pronounced deck) is an abstract data type that generalizes a queue, for which elements can be added to or removed from either the front (head) or back (tail).

Deque interfaces can be implemented using various types of collections such as `LinkedList` or `ArrayDeque` classes. For example, deque can be declared as:

```
Deque deque = new LinkedList<>();  
or  
Deque deque = new ArrayDeque<>();
```

You can find more details about Deque [here](#).

In this problem, you are given  $N$  integers. You need to find the maximum number of unique integers among all the possible contiguous subarrays of size  $M$ .

*Note:* Time limit is **3** second for this problem.

### Input Format

The first line of input contains two integers  $N$  and  $M$ : representing the total number of integers and the size of the subarray, respectively. The next line contains  $N$  space separated integers.

### Constraints

$$1 \leq N \leq 100000$$
$$1 \leq M \leq 100000$$
$$M \leq N$$

The numbers in the array will range between  $[0, 10000000]$ .

### Output Format

Print the *maximum* number of unique integers among all possible contiguous subarrays of size  $M$ .

### Sample Input

```
6 3  
5 3 5 2 3 2
```

### Sample Output

```
3
```

### Explanation

In the sample testcase, there are 4 subarrays of contiguous numbers.

$s_1 = \langle 5, 3, 5 \rangle$  - Has **2** unique numbers.

$s_2 = \langle 3, 5, 2 \rangle$  - Has **3** unique numbers.

$s_3 = \langle 5, 2, 3 \rangle$  - Has **3** unique numbers.

$s_4 = \langle 2, 3, 2 \rangle$  - Has **2** unique numbers.

In these subarrays, there are **2, 3, 3, 2** unique numbers, respectively. The maximum amount of unique numbers among all possible contiguous subarrays is **3**.