

This challenge uses the famous [KMP algorithm](#). It isn't really important to understand how KMP works, but you should understand what it calculates.

A KMP algorithm takes a string,  $S$ , of length  $N$  as input. Let's assume that the characters in  $S$  are indexed from  $1$  to  $N$ ; for every prefix of  $S$ , the algorithm calculates the length of its longest valid [border](#) in linear complexity. In other words, for every  $i$  (where  $1 \leq i \leq N$ ) it calculates the largest  $l$  (where  $0 \leq l \leq i - 1$ ) such that for every  $p$  (where  $1 \leq p \leq l$ ) there is  $S[p] = S[i - l + p]$ .

Here is an implementation example of KMP:

```
kmp[1] = 0;
for (i = 2; i <= N; i = i + 1){
    l = kmp[i - 1];
    while (l > 0 && S[i] != S[l + 1]){
        l = kmp[l];
    }
    if (S[i] == S[l + 1]){
        kmp[i] = l + 1;
    }
    else{
        kmp[i] = 0;
    }
}
```

Given a sequence  $x_1, x_2, \dots, x_{26}$ , construct a string,  $S$ , that meets the following conditions:

1. The frequency of letter ' $a$ ' in  $S$  is exactly  $x_1$ , the frequency of letter ' $b$ ' in  $S$  is exactly  $x_2$ , and so on.
2. Let's assume characters of  $S$  are numbered from  $1$  to  $N$ , where  $\sum_{i=1}^n x_i = N$ . We apply the KMP algorithm to  $S$  and get a table,  $kmp$ , of size  $N$ . You must ensure that the sum of  $kmp[i]$  for all  $i$  is minimal.

If there are multiple strings which fulfill the above conditions, print the [lexicographically](#) smallest one.

### Input Format

A single line containing **26** space-separated integers describing sequence  $x$ .

### Constraints

- The sum of all  $x_i$  will be a positive integer  $\leq 10^6$ .

### Output Format

Print a single string denoting  $S$ .

### Sample Input

```
2 2 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
```

### Sample Output

```
aabb
```

### Explanation

The output string must have two ' $a$ ' and two ' $b$ '. There are several such strings but we must ensure that sum of  $kmp[i]$  for all  $1 \leq i \leq 4$  is minimal. See the figure below:

kmp table for s="aabb"	
1	0
2	1
3	0
4	0
sum = 1	

kmp table for s="bbaa"	
1	0
2	1
3	0
4	0
sum = 1	

kmp table for s="abba"	
1	0
2	0
3	0
4	1
sum = 1	

kmp table for s="baba"	
1	0
2	0
3	1
4	2
sum = 3	

kmp table for s="abab"	
1	0
2	0
3	1
4	2
sum = 3	

kmp table for s="baab"	
1	0
2	0
3	0
4	1
sum = 1	

The minimum sum is **1**. Among all the strings that satisfy both the condition, "aabb" is the lexicographically smallest.