

Two strings, ***a*** and ***b***, are called anagrams if they contain all the same characters in the same frequencies. For example, the anagrams of CAT are CAT, ACT, TAC, TCA, ATC, and CTA.

Complete the function in the editor. If ***a*** and ***b*** are case-insensitive anagrams, print "Anagrams"; otherwise, print "Not Anagrams" instead.

### Input Format

The first line contains a string denoting ***a***.  
The second line contains a string denoting ***b***.

### Constraints

- $1 \leq \text{length}(a), \text{length}(b) \leq 50$
- Strings ***a*** and ***b*** consist of English alphabetic characters.
- The comparison should NOT be case sensitive.

### Output Format

Print "Anagrams" if ***a*** and ***b*** are case-insensitive anagrams of each other; otherwise, print "Not Anagrams" instead.

### Sample Input 0

```
anagram
margana
```

### Sample Output 0

```
Anagrams
```

### Explanation 0

**Character Frequency: anagram** **Frequency: margana**

A or a	3	3
G or g	1	1
N or n	1	1
M or m	1	1
R or r	1	1

The two strings contain all the same letters in the same frequencies, so we print "Anagrams".

### Sample Input 1

```
anagramm
marganaa
```

### Sample Output 1

```
Not Anagrams
```

### Explanation 1

**Character Frequency: anagramm** **Frequency: marganaa**

A or a	3	4
G or g	1	1
N or n	1	1
M or m	2	1
R or r	1	1

The two strings don't contain the same number of a's and m's, so we print "Not Anagrams".

### Sample Input 2

```
Hello
```

hello

## Sample Output 2

Anagrams

## Explanation 2

**Character Frequency: Hello Frequency: hello**

E or e	1	1
H or h	1	1
L or l	2	2
o or o	1	1

The two strings contain all the same letters in the same frequencies, so we print "Anagrams".