

# Rajalakshmi Engineering College

Name: Sai Prapanch.H  
Email: 241901093@rajalakshmi.edu.in  
Roll no: 241901093  
Phone: 9840908718  
Branch: REC  
Department: I CSE (CS) FB  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 2\_MCQ\_Updated

Attempt : 1  
Total Mark : 20  
Marks Obtained : 18

#### Section 1 : MCQ

1. What is the correct way to add a node at the beginning of a doubly linked list?

**Answer**

```
void addFirst(int data){ Node* newNode = new Node(data);  newNode->next = head;      if (head != NULL) {      head->prev = newNode;  }  head = newNode;      }
```

**Status : Correct**

**Marks : 1/1**

2. Which code snippet correctly deletes a node with a given value from a doubly linked list?

```
void deleteNode(Node** head_ref, Node* del_node) {  if (*head_ref == NULL || del_node == NULL) {
```

```

    return;
}
if (*head_ref == del_node) {
    *head_ref = del_node->next;
}
if (del_node->next != NULL) {
    del_node->next->prev = del_node->prev;
}
if (del_node->prev != NULL) {
    del_node->prev->next = del_node->next;
}
free(del_node);
}

```

### Answer

Deletes the first occurrence of a given data value in a doubly linked list.

**Status :** Correct

**Marks :** 1/1

3. What will be the output of the following program?

```

#include <stdio.h>
#include <stdlib.h>

```

```

struct Node {
    int data;
    struct Node* next;
    struct Node* prev;
};

```

```

int main() {
    struct Node* head = NULL;
    struct Node* tail = NULL;
    for (int i = 0; i < 5; i++) {
        struct Node* temp = (struct Node*)malloc(sizeof(struct Node));
        temp->data = i + 1;
        temp->prev = tail;
        temp->next = NULL;
        if (tail != NULL) {

```

```

        tail->next = temp;
    } else {
        head = temp;
    }
    tail = temp;
}
struct Node* current = head;
while (current != NULL) {
    printf("%d ", current->data);
    current = current->next;
}
return 0;
}

```

**Answer**

1 2 3 4 5

**Status :** Correct

**Marks :** 1/1

4. What will be the output of the following code?

```

#include <stdio.h>
#include <stdlib.h>

```

```

struct Node {
    int data;
    struct Node* next;
    struct Node* prev;
};

```

```

int main() {
    struct Node* head = NULL;
    struct Node* temp = (struct Node*)malloc(sizeof(struct Node));
    temp->data = 2;
    temp->next = NULL;
    temp->prev = NULL;
    head = temp;
    printf("%d\n", head->data);
    free(temp);
}

```

```
    return 0;  
}
```

**Answer**

2

**Status : Correct**

**Marks : 1/1**

5. Which of the following is true about the last node in a doubly linked list?

**Answer**

Its next pointer is NULL

**Status : Correct**

**Marks : 1/1**

6. What is a memory-efficient double-linked list?

**Answer**

Each node has only one pointer to traverse the list back and forth

**Status : Wrong**

**Marks : 0/1**

7. Which of the following information is stored in a doubly-linked list's nodes?

**Answer**

All of the mentioned options

**Status : Correct**

**Marks : 1/1**

8. Consider the provided pseudo code. How can you initialize an empty two-way linked list?

Define Structure Node

data: Integer

prev: Pointer to Node

next: Pointer to Node

End Define

Define Structure TwoWayLinkedList

head: Pointer to Node

tail: Pointer to Node

End Define

**Answer**

```
struct TwoWayLinkedList* list = malloc(sizeof(struct TwoWayLinkedList)); list->head = NULL; list->tail = NULL;
```

**Status : Correct**

**Marks : 1/1**

9. Which of the following is false about a doubly linked list?

**Answer**

Implementing a doubly linked list is easier than singly linked list

**Status : Correct**

**Marks : 1/1**

10. What is the main advantage of a two-way linked list over a one-way linked list?

**Answer**

Two-way linked lists allow for traversal in both directions.

**Status : Correct**

**Marks : 1/1**

11. How do you reverse a doubly linked list?

**Answer**

By swapping the next and previous pointers of each node

**Status : Correct**

**Marks : 1/1**

12. What does the following code snippet do?

```
struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
newNode->data = value;
newNode->next = NULL;
newNode->prev = NULL;
```

**Answer**

Creates a new node and initializes its data to 'value'

**Status :** Correct

**Marks :** 1/1

13. Consider the following function that refers to the head of a Doubly Linked List as the parameter. Assume that a node of a doubly linked list has the previous pointer as prev and the next pointer as next.

Assume that the reference of the head of the following doubly linked list is passed to the below function 1 <--> 2 <--> 3 <--> 4 <--> 5 <--> 6. What should be the modified linked list after the function call?

Procedure fun(head\_ref: Pointer to Pointer of node)

temp = NULL

current = \*head\_ref

While current is not NULL

temp = current->prev

current->prev = current->next

current->next = temp

current = current->prev

End While

If temp is not NULL

\*head\_ref = temp->prev

End If

End Procedure

**Answer**

6 <--> 5 <--> 4 <--> 3 <--> 2 <--> 1.

**Status :** Correct

**Marks :** 1/1

14. How do you delete a node from the middle of a doubly linked list?

**Answer**

All of the mentioned options

**Status : Correct**

**Marks : 1/1**

15. Which of the following statements correctly creates a new node for a doubly linked list?

**Answer**

```
struct Node* newNode = (struct Node*) malloc(sizeof(struct Node));
```

**Status : Correct**

**Marks : 1/1**

16. What will be the effect of setting the prev pointer of a node to NULL in a doubly linked list?

**Answer**

The node will become the new head

**Status : Correct**

**Marks : 1/1**

17. Where Fwd and Bwd represent forward and backward links to the adjacent elements of the list. Which of the following segments of code deletes the node pointed to by X from the doubly linked list, if it is assumed that X points to neither the first nor the last node of the list?

A doubly linked list is declared as

```
struct Node {  
    int Value;  
    struct Node *Fwd;  
    struct Node *Bwd;  
};
```

**Answer**

```
X->Bwd->Fwd = X->Bwd ; X->Fwd->Bwd = X->Fwd;
```

**Status :** Wrong

**Marks :** 0/1

18. Which pointer helps in traversing a doubly linked list in reverse order?

**Answer**

prev

**Status :** Correct

**Marks :** 1/1

19. How many pointers does a node in a doubly linked list have?

**Answer**

2

**Status :** Correct

**Marks :** 1/1

20. What happens if we insert a node at the beginning of a doubly linked list?

**Answer**

The previous pointer of the new node is NULL

**Status :** Correct

**Marks :** 1/1



# Rajalakshmi Engineering College

Name: Sai Prapanch.H  
Email: 241901093@rajalakshmi.edu.in  
Roll no: 241901093  
Phone: 9840908718  
Branch: REC  
Department: I CSE (CS) FB  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 2\_COD\_Question 1

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Your task is to create a program to manage a playlist of items. Each item is represented as a character, and you need to implement the following operations on the playlist.

Here are the main functionalities of the program:

Insert Item: The program should allow users to add items to the front and end of the playlist. Items are represented as characters. Display Playlist: The program should display the playlist containing the items that were added.

To implement this program, a doubly linked list data structure should be used, where each node contains an item character.

***Input Format***

The input consists of a sequence of space-separated characters, representing the items to be inserted into the doubly linked list.

The input is terminated by entering - (hyphen).

### ***Output Format***

The first line of output prints "Forward Playlist: " followed by the linked list after inserting the items at the end.

The second line prints "Backward Playlist: " followed by the linked list after inserting the items at the front.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: a b c -

Output: Forward Playlist: a b c

Backward Playlist: c b a

### ***Answer***

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct Node {  
    char item;  
    struct Node* next;  
    struct Node* prev;  
};
```

```
// You are using GCC
```

```
void insertAtEnd(struct Node** head, char item) {
```

```
    //type your code here
```

```
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
```

```
    newNode->item=item;
```

```
    newNode->next=NULL;
```

```
    newNode->prev=NULL;
```

```
    if(*head == NULL){
```

```
        *head = newNode;
```

```
    return;
```

```

    }
    struct Node* last= *head;
    while(last->next!=NULL){
        last=last->next;
    }
    last->next=newNode;
    newNode->prev=last;
}
void displayForward(struct Node* head) {
    //type your code here
    struct Node* current =head;
    while(current!=NULL){
        printf("%c ", current->item);
        current=current->next;
    }
    printf("\n");
}

```

```

void displayBackward(struct Node* tail) {
    //type your code here
    struct Node* current = tail;
    if(current!=NULL){
        while(current->next !=NULL){
            current=current->next;
        }
    }
    while(current!=NULL){
        printf("%c ",current->item);
        current=current->prev;
    }
    printf("\n");
}

```

```

void freePlaylist(struct Node* head) {
    //type your code here
    struct Node* current=head;
    struct Node* next;
    while(current!=NULL){
        next=current->next;
        free(current);
        current=next;
    }
}

```

```
}  
int main() {  
    struct Node* playlist = NULL;  
    char item;  
  
    while (1) {  
        scanf("%c", &item);  
        if (item == '-') {  
            break;  
        }  
        insertAtEnd(&playlist, item);  
    }  
  
    struct Node* tail = playlist;  
    while (tail->next != NULL) {  
        tail = tail->next;  
    }  
  
    printf("Forward Playlist: ");  
    displayForward(playlist);  
  
    printf("Backward Playlist: ");  
    displayBackward(tail);  
  
    freePlaylist(playlist);  
  
    return 0;  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Sai Prapanch.H  
Email: 241901093@rajalakshmi.edu.in  
Roll no: 241901093  
Phone: 9840908718  
Branch: REC  
Department: I CSE (CS) FB  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 2\_COD\_Question 2

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Moniksha, a chess coach organizing a tournament, needs a program to manage participant IDs efficiently. The program maintains a doubly linked list of IDs and offers two functions: Append to add IDs as students register, and Print Maximum ID to identify the highest ID for administrative tasks.

This tool streamlines tournament organization, allowing Moniksha to focus on coaching her students effectively.

##### ***Input Format***

The first line consists of an integer  $n$ , representing the number of participant IDs to be added.

The second line consists of  $n$  space-separated integers representing the participant IDs.

### **Output Format**

The output displays a single integer, representing the maximum participant ID.

If the list is empty, the output prints "Empty list!".

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 3

163 137 155

Output: 163

### **Answer**

```
#include <stdio.h>
#include <stdlib.h>
```

```
struct Node {
    int data;
    struct Node* prev;
    struct Node* next;
};
```

```
struct Node* head = NULL;
```

```
void append(int value) {
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->data = value;
    newNode->prev = NULL;
    newNode->next = NULL;
```

```
    if (head == NULL) {
        head = newNode;
        return;
    }
```

```
    struct Node* temp = head;
```

```
while (temp->next != NULL)
    temp = temp->next;

temp->next = newNode;
newNode->prev = temp;
}

void printMax() {
    if (head == NULL) {
        printf("Empty list!\n");
        return;
    }

    int max = head->data;
    struct Node* temp = head->next;

    while (temp != NULL) {
        if (temp->data > max)
            max = temp->data;
        temp = temp->next;
    }

    printf("%d\n", max);
}

int main() {
    int n, id;

    scanf("%d", &n);

    if (n == 0) {
        printMax();
        return 0;
    }

    for (int i = 0; i < n; i++) {
        scanf("%d", &id);
        append(id);
    }

    printMax();
}
```

```
} return 0;
```

**Status :** Correct

**Marks :** 10/10



# Rajalakshmi Engineering College

Name: Sai Prapanch.H  
Email: 241901093@rajalakshmi.edu.in  
Roll no: 241901093  
Phone: 9840908718  
Branch: REC  
Department: I CSE (CS) FB  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 2\_COD\_Question 3

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Bob is tasked with developing a company's employee record management system. The system needs to maintain a list of employee records using a doubly linked list. Each employee is represented by a unique integer ID.

Help Bob to complete a program that adds employee records at the front, traverses the list, and prints the same for each addition of employees to the list.

##### ***Input Format***

The first line of input consists of an integer N, representing the number of employees.

The second line consists of N space-separated integers, representing the employee IDs.

### **Output Format**

For each employee ID, the program prints "Node Inserted" followed by the current state of the doubly linked list in the next line, with the data values of each node separated by spaces.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 4

101 102 103 104

Output: Node Inserted

101

Node Inserted

102 101

Node Inserted

103 102 101

Node Inserted

104 103 102 101

### **Answer**

```
#include <iostream>
using namespace std;
```

```
struct node {
    int info;
    struct node* prev, * next;
};
```

```
struct node* start = NULL;
```

```
void traverse(){
    node* temp = start;
    while(temp!=NULL){
        printf("%d ",temp->info);
        temp=temp->next;
    }
    printf("\n");
}
```

```
void insertAtFront(int data) {
    node* newNode = (node*)malloc(sizeof(node));
    newNode->info = data;
    newNode->prev = NULL;
    newNode->next = start;

    if (start != NULL) {
        start->prev = newNode;
    }

    start = newNode;

    printf("Node Inserted\n");
}

int main() {
    int n, data;
    cin >> n;
    for (int i = 0; i < n; ++i) {
        cin >> data;
        insertAtFront(data);
        traverse();
    }
    return 0;
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Sai Prapanch.H  
Email: 241901093@rajalakshmi.edu.in  
Roll no: 241901093  
Phone: 9840908718  
Branch: REC  
Department: I CSE (CS) FB  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 2\_COD\_Question 4

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Ravi is developing a student registration system for a college. To efficiently store and manage the student IDs, he decides to implement a doubly linked list where each node represents a student's ID.

In this system, each student's ID is stored sequentially, and the system needs to display all registered student IDs in the order they were entered.

Implement a program that creates a doubly linked list, inserts student IDs, and displays them in the same order.

##### ***Input Format***

The first line contains an integer N the number of student IDs.

The second line contains N space-separated integers representing the student IDs.

### **Output Format**

The output should display the single line containing N space-separated integers representing the student IDs stored in the doubly linked list.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

10 20 30 40 50

Output: 10 20 30 40 50

### **Answer**

```
// You are using GCC
```

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
typedef struct Node {  
    int data;  
    struct Node* prev;  
    struct Node* next;  
} Node;
```

```
Node* createNode(int data) {  
    Node* newNode = (Node*)malloc(sizeof(Node));  
    newNode->data = data;  
    newNode->prev = NULL;  
    newNode->next = NULL;  
    return newNode;  
}
```

```
void insertEnd(Node** head, Node** tail, int data) {  
    Node* newNode = createNode(data);  
    if (*head == NULL) {  
        *head = *tail = newNode;  
    } else {  
        (*tail)->next = newNode;  
    }
```

```
        newNode->prev = *tail;
        *tail = newNode;
    }
}
```

```
void displayList(Node* head) {
    Node* temp = head;
    while (temp != NULL) {
        printf("%d ", temp->data);
        temp = temp->next;
    }
}
```

```
int main() {
    int N;
    scanf("%d", &N);

    Node* head = NULL;
    Node* tail = NULL;

    for (int i = 0; i < N; i++) {
        int id;
        scanf("%d", &id);
        insertEnd(&head, &tail, id);
    }

    displayList(head);
    return 0;
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Sai Prapanch.H  
Email: 241901093@rajalakshmi.edu.in  
Roll no: 241901093  
Phone: 9840908718  
Branch: REC  
Department: I CSE (CS) FB  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 2\_COD\_Question 5

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Ashwin is tasked with developing a simple application to manage a list of items in a shop inventory using a doubly linked list. Each item in the inventory has a unique identification number. The application should allow users to perform the following operations:

Create a List of Items: Initialize the inventory with a given number of items. Each item will be assigned a unique number provided by the user and insert the elements at end of the list.

Delete an Item: Remove an item from the inventory at a specific position.

Display the Inventory: Show the list of items before and after deletion.

If the position provided for deletion is invalid (e.g., out of range), it should

display an error message.

### ***Input Format***

The first line contains an integer n, representing the number of items to be initially entered into the inventory.

The second line contains n integers, each representing the unique identification number of an item separated by spaces.

The third line contains an integer p, representing the position of the item to be deleted from the inventory.

### ***Output Format***

The first line of output prints "Data entered in the list:" followed by the data values of each node in the doubly linked list before deletion.

If p is an invalid position, the output prints "Invalid position. Try again."

If p is a valid position, the output prints "After deletion the new list:" followed by the data values of each node in the doubly linked list after deletion.

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 4

1 2 3 4

5

Output: Data entered in the list:

node 1 : 1

node 2 : 2

node 3 : 3

node 4 : 4

Invalid position. Try again.

### ***Answer***

```
#include <stdio.h>
```

```
#include <stdlib.h>
```



```
typedef struct Node {  
    int data;  
    struct Node* prev;  
    struct Node* next;  
} Node;
```

```
Node* head = NULL;
```

```
void append(int data) {  
    Node* newNode = (Node*)malloc(sizeof(Node));  
    newNode->data = data;  
    newNode->prev = NULL;  
    newNode->next = NULL;  
  
    if (head == NULL) {  
        head = newNode;  
        return;  
    }  
}
```

```
Node* temp = head;  
while (temp->next != NULL)  
    temp = temp->next;
```

```
temp->next = newNode;  
newNode->prev = temp;  
}
```

```
void display() {  
    Node* temp = head;  
    int count = 1;  
    while (temp != NULL) {  
        printf(" node %d : %d\n", count++, temp->data);  
        temp = temp->next;  
    }  
}
```

```
int countNodes() {  
    int count = 0;  
    Node* temp = head;  
    while (temp != NULL) {  
        count++;  
        temp = temp->next;  
    }  
}
```

```

    }
    return count;
}

void deleteAtPosition(int position) {
    int total = countNodes();

    if (position <= 0 || position > total) {
        printf("Invalid position. Try again.\n");
        return;
    }

    Node* temp = head;

    for (int i = 1; i < position; i++) {
        temp = temp->next;
    }

    if (temp == head) {
        head = temp->next;
        if (head)
            head->prev = NULL;
    } else {
        temp->prev->next = temp->next;
        if (temp->next)
            temp->next->prev = temp->prev;
    }

    free(temp);

    printf("After deletion the new list:\n");
    display();
}

int main() {
    int n, data, pos;

    scanf("%d", &n);

    for (int i = 0; i < n; i++) {

```

```
scanf("%d", &data);  
append(data);  
}
```

```
printf("Data entered in the list:\n");  
display();
```

```
scanf("%d", &pos);
```

```
deleteAtPosition(pos);
```

```
return 0;  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Sai Prapanch.H  
Email: 241901093@rajalakshmi.edu.in  
Roll no: 241901093  
Phone: 9840908718  
Branch: REC  
Department: I CSE (CS) FB  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 2\_CY

Attempt : 1  
Total Mark : 30  
Marks Obtained : 20

### Section 1 : Coding

#### 1. Problem Statement

You are required to implement a program that deals with a doubly linked list.

The program should allow users to perform the following operations:

Insertion at the End: Insert a node with a given integer data at the end of the doubly linked list.  
Insertion at a given Position: Insert a node with a given integer data at a specified position within the doubly linked list.  
Display the List: Display the elements of the doubly linked list.

#### ***Input Format***

The first line of input consists of an integer n, representing the number of elements to be initially inserted into the doubly linked list.

The second line consists of  $n$  space-separated integers, denoting the elements to be inserted at the end.

The third line consists of integer  $m$ , representing the new element to be inserted.

The fourth line consists of an integer  $p$ , representing the position at which the new element should be inserted (1-based indexing).

### ***Output Format***

If  $p$  is valid, display the elements of the doubly linked list after performing the insertion at the specified position.

If  $p$  is invalid, display "Invalid position" in the first line and the second line prints the original list.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 5

10 25 34 48 57

35

4

Output: 10 25 34 35 48 57

### ***Answer***

-

**Status :** Skipped

**Marks :** 0/10

## **2. Problem Statement**

Vanessa is learning about the doubly linked list data structure and is eager to play around with it. She decides to find out how the elements are inserted at the beginning and end of the list.

Help her implement a program for the same.

### ***Input Format***

The first line of input contains an integer N, representing the size of the doubly linked list.

The next line contains N space-separated integers, each representing the values to be inserted into the doubly linked list.

### ***Output Format***

The first line of output prints the integers, after inserting them at the beginning, separated by space.

The second line prints the integers, after inserting at the end, separated by space.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 5

1 2 3 4 5

Output: 5 4 3 2 1

1 2 3 4 5

### ***Answer***

```
// You are using GCC
```

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
typedef struct Node {  
    int data;  
    struct Node* next;  
    struct Node* prev;  
} Node;
```

```
void insert_at_beginning(Node** head, int data) {  
    Node* new_node = (Node*)malloc(sizeof(Node));  
    new_node->data = data;  
    new_node->next = *head;  
    new_node->prev = NULL;  
    if (*head != NULL) {  
        (*head)->prev = new_node;  
    }
```

```

    }
    *head = new_node;
}

void insert_at_end(Node** head, int data) {
    Node* new_node = (Node*)malloc(sizeof(Node));
    new_node->data = data;
    new_node->next = NULL;
    if (*head == NULL) {
        new_node->prev = NULL;
        *head = new_node;
        return;
    }
    Node* temp = *head;
    while (temp->next != NULL) {
        temp = temp->next;
    }
    temp->next = new_node;
    new_node->prev = temp;
}

```

```

void traverse(Node* head) {
    Node* temp = head;
    while (temp != NULL) {
        printf("%d ", temp->data);

        temp = temp->next;
    }
    printf("\n");
}

```

```

void free_list(Node* head) {
    Node* temp;
    while (head != NULL) {
        temp = head;
        head = head->next;
        free(temp);
    }
}

```

```

int main() {
    int n;

```

```

scanf("%d", &n);

Node* head1 = NULL;
Node* head2 = NULL;

for (int i = 0; i < n; i++) {
    int val;
    scanf("%d", &val);
    insert_at_beginning(&head1, val);
    insert_at_end(&head2, val);
}

traverse(head1);
traverse(head2);

free_list(head1);
free_list(head2);

return 0;
}

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Imagine Anu is tasked with finding the middle element of a doubly linked list. Given a doubly linked list where each node contains an integer value and is inserted at the end, implement a program to find the middle element of the list. If the number of nodes is even, return the middle element pair.

#### **Input Format**

The first line of input consists of an integer N, representing the number of nodes in the doubly linked list.

The second line consists of N space-separated integers, representing the values of the nodes in the doubly linked list.

#### **Output Format**

The first line of output prints the space-separated elements of the doubly linked list.



The second line prints the middle element(s) of the doubly linked list, depending on whether the number of nodes is odd or even.

Refer to the sample outputs for the formatting specifications.

### **Sample Test Case**

Input: 5

10 20 30 40 50

Output: 10 20 30 40 50  
30

### **Answer**

```
// You are using GCC
```

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
typedef struct Node {  
    int data;  
    struct Node* next;  
    struct Node* prev;  
} Node;
```

```
void insert_at_end(Node** head, int data) {  
    Node* new_node = (Node*)malloc(sizeof(Node));  
    new_node->data = data;  
    new_node->next = NULL;  
    if (*head == NULL) {  
        new_node->prev = NULL;  
        *head = new_node;  
        return;  
    }  
    Node* temp = *head;  
    while (temp->next != NULL) {  
        temp = temp->next;  
    }  
    temp->next = new_node;  
    new_node->prev = temp;  
}
```

```
void traverse(Node* head) {  
    Node* temp = head;  
    while (temp != NULL) {  
        printf("%d ", temp->data);  
        temp = temp->next;  
    }  
    printf("\n");  
}
```

```
void find_middle(Node* head, int n) {  
    Node* temp = head;  
    int mid = n / 2;  
    for (int i = 0; i < mid; i++) {  
        temp = temp->next;  
    }  
    if (n % 2 == 0) {  
        printf("%d %d ", temp->prev->data, temp->data);  
    } else {  
        printf("%d ", temp->data);  
    }  
}
```

```
void free_list(Node* head) {  
    Node* temp;  
    while (head != NULL) {  
        temp = head;  
        head = head->next;  
        free(temp);  
    }  
}
```

```
int main() {  
    int n;  
    scanf("%d", &n);  
  
    Node* head = NULL;  
    for (int i = 0; i < n; i++) {  
        int val;  
        scanf("%d", &val);  
        insert_at_end(&head, val);  
    }  
}
```

```
traverse(head);  
find_middle(head, n);  
  
free_list(head);  
  
return 0;  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Sai Prapanch.H  
Email: 241901093@rajalakshmi.edu.in  
Roll no: 241901093  
Phone: 9840908718  
Branch: REC  
Department: I CSE (CS) FB  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 2\_PAH

Attempt : 1  
Total Mark : 50  
Marks Obtained : 50

### Section 1 : Coding

#### 1. Problem Statement

Riya is developing a contact management system where recently added contacts should appear first. She decides to use a doubly linked list to store contact IDs in the order they are added. Initially, new contacts are inserted at the front of the list. However, sometimes she needs to insert a new contact at a specific position in the list based on priority.

Help Riya implement this system by performing the following operations:

Insert contact IDs at the front of the list as they are added. Insert a new contact at a given position in the list.

#### ***Input Format***

The first line of input consists of an integer N, representing the initial size of the linked list.

The second line consists of N space-separated integers, representing the values of the linked list to be inserted at the front.

The third line consists of an integer position, representing the position at which the new value should be inserted (position starts from 1).

The fourth line consists of integer data, representing the new value to be inserted.

### ***Output Format***

The first line of output prints the original list after inserting initial elements to the front.

The second line prints the updated linked list after inserting the element at the specified position.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 4

10 20 30 40

3

25

Output: 40 30 20 10

40 30 25 20 10

### ***Answer***

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
typedef struct Node {  
    int data;  
    struct Node* next;  
    struct Node* prev;  
} Node;
```

```
Node* createNode(int data){
```

```
    Node* newNode = (Node*)malloc(sizeof(Node));
```

```

    newNode->data = data;
    newNode->next = NULL;
    newNode->prev = NULL;
    return newNode;
}

void insertAtFront(Node** head, int data) {
    Node* newNode = createNode(data);
    if (*head != NULL) {
        newNode->next = *head;
        (*head)->prev = newNode;
    }
    *head = newNode;
}

void insertAtPosition(Node** head, int position, int data) {
    if (position < 1) return;
    Node* newNode = createNode(data);
    if (position == 1) {
        newNode->next = *head;
        if (*head != NULL) (*head)->prev = newNode;
        *head = newNode;
        return;
    }
    Node* temp = *head;
    for (int i = 1; temp != NULL && i < position - 1; i++) {
        temp = temp->next;
    }
    if (temp == NULL) return;
    newNode->next = temp->next;
    newNode->prev = temp;
    if (temp->next != NULL) temp->next->prev = newNode;
    temp->next = newNode;
}

void printList(Node* head) {
    while (head != NULL) {
        printf("%d ", head->data);
        head = head->next;
    }
    printf("\n");
}

```

```

int main() {
    int n, data, position;
    Node* head = NULL;

    scanf("%d", &n);
    for (int i = 0; i < n; i++) {
        scanf("%d", &data);
        insertAtFront(&head, data);
    }

    scanf("%d %d", &position, &data);

    printList(head);
    insertAtPosition(&head, position, data);
    printList(head);

    return 0;
}

```

**Status :** Correct

**Marks : 10/10**

## 2. Problem Statement

Tom is a software developer working on a project where he has to check if a doubly linked list is a palindrome. He needs to write a program to solve this problem. Write a program to help Tom check if a given doubly linked list is a palindrome or not.

### ***Input Format***

The first line consists of an integer N, representing the number of elements in the linked list.

The second line consists of N space-separated integers representing the linked list elements.

### ***Output Format***

The first line displays the space-separated integers, representing the doubly linked list.

The second line displays one of the following:

1. If the doubly linked list is a palindrome, print "The doubly linked list is a palindrome".
2. If the doubly linked list is not a palindrome, print "The doubly linked list is not a palindrome".

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 5

1 2 3 2 1

Output: 1 2 3 2 1

The doubly linked list is a palindrome

### **Answer**

```
// You are using GCC
```

```
// You are using GCC
```

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
typedef struct Node {  
    int data;  
    struct Node* next;  
    struct Node* prev;  
} Node;
```

```
Node* createNode(int data) {  
    Node* newNode = (Node*)malloc(sizeof(Node));  
    newNode->data = data;  
    newNode->next = NULL;  
    newNode->prev = NULL;  
    return newNode;  
}
```

```
void insertAtEnd(Node** head, int data) {  
    Node* newNode = createNode(data);  
    if (*head == NULL) {  
        *head = newNode;
```



```
        return;
    }
    Node* temp = *head;
    while (temp->next != NULL) {
        temp = temp->next;
    }
    temp->next = newNode;
    newNode->prev = temp;
}
```

```
void printList(Node* head) {
    Node* temp = head;
    while (temp != NULL) {
        printf("%d ", temp->data);
        temp = temp->next;
    }
    printf("\n");
}
```

```
int isPalindrome(Node* head) {
    if (head == NULL) return 1;
    Node* tail = head;
    while (tail->next != NULL) {
        tail = tail->next;
    }
    while (head != tail && head->prev != tail) {
        if (head->data != tail->data) {
            return 0;
        }
        head = head->next;
        tail = tail->prev;
    }
    return 1;
}
```

```
int main() {
    int n, data;
    Node* head = NULL;
```

```
    scanf("%d", &n);
    for (int i = 0; i < n; i++) {
        scanf("%d", &data);
```

```

        insertAtEnd(&head, data);
    }

    printList(head);
    if (isPalindrome(head)) {
        printf("The doubly linked list is a palindrome\n");
    } else {
        printf("The doubly linked list is not a palindrome\n");
    }

    return 0;
}

```

**Status :** Correct

**Marks : 10/10**

### 3. Problem Statement

Rohan is a software developer who is working on an application that processes data stored in a Doubly Linked List. He needs to implement a feature that finds and prints the middle element(s) of the list. If the list contains an odd number of elements, the middle element should be printed. If the list contains an even number of elements, the two middle elements should be printed.

Help Rohan by writing a program that reads a list of numbers, prints the list, and then prints the middle element(s) based on the number of elements in the list.

#### ***Input Format***

The first line of the input consists of an integer  $n$  the number of elements in the doubly linked list.

The second line consists of  $n$  space-separated integers representing the elements of the list.

#### ***Output Format***

The first line prints the elements of the list separated by space. (There is an extra space at the end of this line.)

The second line prints the middle element(s) based on the number of elements.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

20 52 40 16 18

Output: 20 52 40 16 18

40

### **Answer**

```
// You are using GCC
```

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
typedef struct Node {  
    int data;  
    struct Node* next;  
    struct Node* prev;  
} Node;
```

```
Node* createNode(int data) {  
    Node* newNode = (Node*)malloc(sizeof(Node));  
    newNode->data = data;  
    newNode->next = NULL;  
    newNode->prev = NULL;  
    return newNode;  
}
```

```
void insertAtEnd(Node** head, int data) {  
    Node* newNode = createNode(data);  
    if (*head == NULL) {  
        *head = newNode;  
        return;  
    }  
    Node* temp = *head;  
    while (temp->next != NULL) {  
        temp = temp->next;  
    }  
}
```

```

    temp->next = newNode;
    newNode->prev = temp;
}

void printList(Node* head) {
    while (head != NULL) {
        printf("%d ", head->data);
        head = head->next;
    }
    printf("\n");
}

void findMiddle(Node* head) {
    if (head == NULL) return;
    Node* slow = head;
    Node* fast = head;
    while (fast != NULL && fast->next != NULL) {
        slow = slow->next;
        fast = fast->next->next;
    }
    if (fast == NULL) {
        printf("%d %d\n", slow->prev->data, slow->data);
    } else {
        printf("%d\n", slow->data);
    }
}

int main() {
    int n, data;
    Node* head = NULL;

    scanf("%d", &n);
    for (int i = 0; i < n; i++) {
        scanf("%d", &data);
        insertAtEnd(&head, data);
    }

    printList(head);
    findMiddle(head);

    return 0;
}

```

Status : Correct

Marks : 10/10

#### 4. Problem Statement

Pranav wants to clockwise rotate a doubly linked list by a specified number of positions. He needs your help to implement a program to achieve this. Given a doubly linked list and an integer representing the number of positions to rotate, write a program to rotate the list clockwise.

##### **Input Format**

The first line of input consists of an integer n, representing the number of elements in the linked list.

The second line consists of n space-separated linked list elements.

The third line consists of an integer k, representing the number of places to rotate the list.

##### **Output Format**

The output displays the elements of the doubly linked list after rotating it by k positions.

Refer to the sample output for the formatting specifications.

##### **Sample Test Case**

Input: 5  
1 2 3 4 5  
1

Output: 5 1 2 3 4

##### **Answer**

```
// You are using GCC
#include <stdio.h>
#include <stdlib.h>
```

```
typedef struct Node {
    int data;
```

```
    struct Node* next;
    struct Node* prev;
} Node;
```

```
Node* createNode(int data) {
    Node* newNode = (Node*)malloc(sizeof(Node));
    newNode->data = data;
    newNode->next = NULL;
    newNode->prev = NULL;
    return newNode;
}
```

```
void insertAtEnd(Node** head, int data) {
    Node* newNode = createNode(data);
    if (*head == NULL) {
        *head = newNode;
        return;
    }
    Node* temp = *head;
    while (temp->next != NULL) {
        temp = temp->next;
    }
    temp->next = newNode;
    newNode->prev = temp;
}
```

```
void printList(Node* head) {
    Node* temp = head;
    while (temp != NULL) {
        printf("%d ", temp->data);
        temp = temp->next;
    }
    printf("\n");
}
```

```
void rotateClockwise(Node** head, int k) {
    if (*head == NULL || k == 0) return;
```

```
    Node* temp = *head;
    int length = 1;
    while (temp->next != NULL) {
        temp = temp->next;
```

```

        length++;
    }

    k = k % length;
    if (k == 0) return;

    temp->next = *head; // Connect last node to first
    (*head)->prev = temp;

    int steps = length - k;
    while (steps--) {
        temp = temp->next;
    }

    *head = temp->next;
    (*head)->prev = NULL;
    temp->next = NULL;
}

int main() {
    int n, data, k;
    Node* head = NULL;

    scanf("%d", &n);
    for (int i = 0; i < n; i++) {
        scanf("%d", &data);
        insertAtEnd(&head, data);
    }

    scanf("%d", &k);
    rotateClockwise(&head, k);
    printList(head);

    return 0;
}

```

**Status :** Correct

**Marks :** 10/10

## 5. Problem Statement

Bala is a student learning about the doubly linked list and its

functionalities. He came across a problem where he wanted to create a doubly linked list by appending elements to the front of the list.

After populating the list, he wanted to delete the node at the given position from the beginning. Write a suitable code to help Bala.

### ***Input Format***

The first line contains an integer N, the number of elements in the doubly linked list.

The second line contains N integers separated by a space, the data values of the nodes in the doubly linked list.

The third line contains an integer X, the position of the node to be deleted from the doubly linked list.

### ***Output Format***

The first line of output displays the original elements of the doubly linked list, separated by a space.

The second line prints the updated list after deleting the node at the given position X from the beginning.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 5

10 20 30 40 50

2

Output: 50 40 30 20 10

50 30 20 10

### ***Answer***

```
// You are using GCC
```

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
typedef struct Node {
```



```
int data;
struct Node* next;
struct Node* prev;
} Node;
```

```
Node* createNode(int data) {
    Node* newNode = (Node*)malloc(sizeof(Node));
    newNode->data = data;
    newNode->next = NULL;
    newNode->prev = NULL;
    return newNode;
}
```

```
void insertAtFront(Node** head, int data) {
    Node* newNode = createNode(data);
    if (*head != NULL) {
        newNode->next = *head;
        (*head)->prev = newNode;
    }
    *head = newNode;
}
```

```
void deleteAtPosition(Node** head, int position) {
    if (*head == NULL || position < 1) return;
    Node* temp = *head;

    for (int i = 1; temp != NULL && i < position; i++) {
        temp = temp->next;
    }

    if (temp == NULL) return;
    if (temp->prev) temp->prev->next = temp->next;
    if (temp->next) temp->next->prev = temp->prev;
    if (*head == temp) *head = temp->next;
    free(temp);
}
```

```
void printList(Node* head) {
    while (head != NULL) {
        printf("%d ", head->data);
        head = head->next;
    }
}
```

```
        printf("\n");
    }

    int main() {
        int n, data, position;
        Node* head = NULL;

        scanf("%d", &n);
        for (int i = 0; i < n; i++) {
            scanf("%d", &data);
            insertAtFront(&head, data);
        }

        scanf("%d", &position);
        printList(head);
        deleteAtPosition(&head, position);
        printList(head);

        return 0;
    }
```

**Status :** Correct

**Marks :** 10/10