

```
mysql> create database practice3;  
Query OK, 1 row affected (0.01 sec)
```

```
mysql> use practice3;  
Database changed
```

```
mysql> CREATE TABLE employees(  
->     emp_id INT PRIMARY KEY,  
->     emp_name VARCHAR(50),  
->     dept_id INT,  
->     salary DECIMAL(10,2)  
-> );  
Query OK, 0 rows affected (0.05 sec)
```

```
mysql> CREATE TABLE employees(  
->     emp_id INT PRIMARY KEY,  
->     emp_name VARCHAR(50),  
->     dept_id INT,  
->     salary DECIMAL(10,2)  
-> );  
ERROR 1050 (42S01): Table 'employees' already exists
```

```
mysql> CREATE TABLE employee_audit(  
->     audit_id INT AUTO_INCREMENT PRIMARY KEY,  
->     emp_id INT,  
->     emp_name VARCHAR(50),  
->     action_type VARCHAR(20),  
->     action_time TIMESTAMP DEFAULT CURRENT_TIMESTAMP  
-> );  
Query OK, 0 rows affected (0.02 sec)
```

```
mysql> select * from employees;
Empty set (0.00 sec)
```

```
mysql> DELIMITER $$
mysql> CREATE TRIGGER after_employee_insert
-> AFTER INSERT ON employees
-> FOR EACH ROW
-> BEGIN
->     INSERT INTO employee_audit
->     (emp_id, emp_name, action_type)
->     VALUES
->     (NEW.emp_id, NEW.emp_name, 'INSERT');
-> END $$
```

```
Query OK, 0 rows affected (0.01 sec)
```

```
mysql> DELIMITER ;
mysql> INSERT INTO employees
-> VALUES (106, 'Arjun', 1, 52000);
Query OK, 1 row affected (0.01 sec)
```

```
mysql> select * from employees_audit;
ERROR 1146 (42S02): Table 'practice3.employees_audit' doesn't exist
mysql> select * from employee_audit;
```

audit_id	emp_id	emp_name	action_type	action_time
1	106	Arjun	INSERT	2026-08-17 12:26:29

```
1 row in set (0.00 sec)
```

```
mysql> DELETE FROM employees
-> WHERE emp_id = 106;
Query OK, 1 row affected (0.00 sec)
```

```
mysql> DELIMITER $$
mysql> CREATE TRIGGER after_employee_delete
-> AFTER DELETE ON employees
-> FOR EACH ROW
-> BEGIN
->     INSERT INTO employee_audit
->     (emp_id, emp_name, action_type)
->     VALUES
->     (OLD.emp_id, OLD.emp_name, 'DELETE');
-> END $$
Query OK, 0 rows affected (0.01 sec)
```

```
mysql> DELIMITER ;
mysql> UPDATE employees
-> SET salary = 60000
-> WHERE emp_id = 101;
Query OK, 0 rows affected (0.00 sec)
Rows matched: 0  Changed: 0  Warnings: 0
```

```
mysql> DELIMITER $$
mysql> CREATE TRIGGER after_employee_update
-> AFTER UPDATE ON employees
-> FOR EACH ROW
-> BEGIN
->     INSERT INTO employee_audit
->     (emp_id, emp_name, action_type)
->     VALUES
->     (NEW.emp_id, NEW.emp_name, 'UPDATE');
-> END $$
```

Query OK, 0 rows affected (0.02 sec)

```
mysql> DELIMITER ;
mysql> DELIMITER $$
mysql> CREATE TRIGGER check_salary
-> BEFORE INSERT ON employees
-> FOR EACH ROW
-> BEGIN
->     IF NEW.salary < 20000 THEN
->         SIGNAL SQLSTATE '45000'
->         SET MESSAGE_TEXT = 'Salary cannot be less than 20000';
->     END IF;
-> END $$
```

Query OK, 0 rows affected (0.01 sec)

```

mysql> DELIMITER ;
mysql> INSERT INTO employees
  -> VALUES (107, 'Ravi', 1, 15000);
ERROR 1644 (45000): Salary cannot be less than 20000
mysql> VALUES (107, 'Ravi', 1, 25000);
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual
t syntax to use near '(107, 'Ravi', 1, 25000)' at line 1
mysql> insert into employees
  -> values (107, 'Ravi',1,25000);
Query OK, 1 row affected (0.01 sec)

mysql> INSERT INTO employees VALUES (108, 'Meena', 1, 30000);
Query OK, 1 row affected (0.01 sec)

mysql> DELIMITER $$
mysql> CREATE TRIGGER prevent_salary_reduction
  -> BEFORE UPDATE ON employees
  -> FOR EACH ROW
  -> BEGIN
  ->     IF NEW.salary < OLD.salary THEN
  ->         SIGNAL SQLSTATE '45000'
  ->         SET MESSAGE_TEXT = 'Salary reduction is not allowed';
  ->     END IF;
  -> END $$
Query OK, 0 rows affected (0.01 sec)

mysql> DELIMITER ;
mysql> UPDATE employees
  -> SET salary = 40000
  -> WHERE emp_id = 101;
Query OK, 0 rows affected (0.00 sec)
Rows matched: 0  Changed: 0  Warnings: 0

mysql> UPDATE employees
  -> SET salary = 60000

```

```
mysql> DELIMITER ;
mysql> UPDATE employees
    -> SET salary = 40000
    -> WHERE emp_id = 101;
Query OK, 0 rows affected (0.00 sec)
Rows matched: 0  Changed: 0  Warnings: 0
```

```
mysql> UPDATE employees
    -> SET salary = 60000
    -> WHERE emp_id = 101;
Query OK, 0 rows affected (0.00 sec)
Rows matched: 0  Changed: 0  Warnings: 0
```

```
mysql> select * from employees;
```

emp_id	emp_name	dept_id	salary
107	Ravi	1	25000.00
108	Meena	1	30000.00

```
2 rows in set (0.00 sec)
```

```
mysql> |
```