

```
1. #include <stdio.h>
```

```
#include <sys/types.h>
```

```
#include <sys/stat.h>
```

```
int main()
```

```
{
```

```
    if (mkfifo("myfifo", 0666) == -1)
```

```
    {
```

```
        perror("mkfifo");
```

```
        return 1;
```

```
    }
```

```
    printf("FIFO created\n");
```

```
    return 0;
```

```
}
```

```
saranya@saisaranya:~$ gcc fifo_create.c -o fifo_create
saranya@saisaranya:~$ ./fifo_create
FIFO created
saranya@saisaranya:~$ ls -l myfifo
prw-r--r-- 1 root root 0 Sep 29 02:50 myfifo
saranya@saisaranya:~$ ./fifo_create
mkfifo: File exists
saranya@saisaranya:~$
```

```
2. #include <stdio.h>
```

```
#include <fcntl.h>
```

```
#include <unistd.h>
```

```
int main()
```

```
{
```

```
    int fd;
```

```
    char buffer[100];
```

```
    fd = open("myfifo", O_RDONLY);
```

```
    read(fd, buffer, sizeof(buffer));
```

```
    printf("Received: %s\n", buffer);
```

```
close(fd);

return 0;

}
```

```
saranya@saisaranya:~$ gcc fifo_read.c -o fifo_read
saranya@saisaranya:~$ ./fifo_read
Received: Hello from Writer
saranya@saisaranya:~$
```

3. #include <stdio.h>

#include <fcntl.h>

#include <unistd.h>

#include <string.h>

```
int main()
```

```
{
```

```
    int fd;
```

```
    char message[] = "Hello from Writer";
```

```
    fd = open("myfifo", O_WRONLY);
```

```
    write(fd, message, strlen(message) + 1);
```

```
    close(fd);
```

```
    printf("Message sent\n");
```

```
    return 0;
```

```
}
```

```
saranya@saisaranya:~$ gcc fifo_write.c -o fifo_write
saranya@saisaranya:~$ ./fifo_write
Message sent
saranya@saisaranya:~$
```