

19. To Register Handlers, Configure Signal Actions, Handle Interrupts, Manage Signal Context, Verify Stability, Test Signal Events.

Code:

```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <signal.h>
#include <string.h>

volatile sig_atomic_t signal_count = 0;

/* Signal handler */
void signalHandler(int sig, siginfo_t *info, void *context) {
    (void)context;
    signal_count++;
    printf("\n--- Signal Event ---\n");
    if (sig == SIGINT) {
        printf("Received SIGINT (Ctrl+C)\n");
    }
    else if (sig == SIGTERM) {
        printf("Received SIGTERM\n");
    }
    else if (sig == SIGUSR1) {
        printf("Received SIGUSR1\n");
    }

    if (info != NULL) {
        printf("Sender PID: %d\n",
            info->si_pid);
    }

    printf("Signal count: %d\n",
        signal_count);
}

/* Register signal handlers */
void registerHandlers() {
    struct sigaction action;
    memset(&action, 0, sizeof(action));

    /*
     * Use extended signal information.
     */
    action.sa_sigaction = signalHandler;

    /*
     * SA_SIGINFO allows the handler
     * to receive signal context.
     */
    action.sa_flags = SA_SIGINFO;
    sigemptyset(&action.sa_mask);

    /* Register SIGINT */
    if (sigaction(SIGINT, &action, NULL) == -1) {
        perror("sigaction SIGINT");
        exit(1);
    }

    /* Register SIGTERM */
    if (sigaction(SIGTERM, &action, NULL) == -1) {
```

```
        /* Register SIGTERM */
        if (sigaction(SIGTERM, &action, NULL) == -1) {
            perror("sigaction SIGTERM");
            exit(1);
        }

        /* Register SIGUSR1 */
        if (sigaction(SIGUSR1, &action, NULL) == -1) {
            perror("sigaction SIGUSR1");
            exit(1);
        }

        printf("Signal handlers registered successfully.\n");
    }

    /* Display current signal mask */
    void displaySignalMask() {
        sigset_t mask;
        if (sigprocmask(SIG_SETMASK, NULL, &mask) == -1) {
            perror("sigprocmask");
            return;
        }
        printf("\nSignal Mask Status:\n");
        printf("SIGINT : %s\n",
            sigismember(&mask, SIGINT)
            ? "Blocked"
            : "Not Blocked");
        printf("SIGTERM : %s\n",
            sigismember(&mask, SIGTERM)
            ? "Blocked"
            : "Not Blocked");
        printf("SIGUSR1 : %s\n",
            sigismember(&mask, SIGUSR1)
            ? "Blocked"
            : "Not Blocked");
    }

    int main() {
        printf("Signal Handler Management System\n");
        printf("-----\n");
        printf("Process PID: %d\n",
            getpid());

        /* Register handlers */
        registerHandlers();

        /* Display signal mask */
        displaySignalMask();

        printf("\nSignal tests:\n");
        printf("1. Press Ctrl+C to generate SIGINT.\n");
        printf("2. The program will continue running.\n");
        printf("3. Press Ctrl+\\ only if you want to terminate it.\n\n");

        /*
         * Generate SIGUSR1 from the same process.
         */
    }
}
```

```

/*
 * Generate SIGUSR1 from the same process.
 */
printf("Sending SIGUSR1...\n");

if (kill(getpid(), SIGUSR1) == -1) {
    perror("kill");
}

printf("\nWaiting for signal events...\n");

/*
 * Main loop remains stable even after
 * receiving handled signals.
 */
for (int i = 1; i <= 10; i++) {

    printf("Program running... %d/10\n", i);

    sleep(1);
}

printf("\nProgram completed normally.\n");
printf("Total signals handled: %d\n",
        signal_count);

return 0;
}
|

```

Result:

```

ketana_saisharan134@API-5CD1366K5L:~/SKILL$ nano Skill19a.c
ketana_saisharan134@API-5CD1366K5L:~/SKILL$ gcc Skill19a.c -o s19a
saisharan134@API-5CD1366K5L:~/SKILL$ ./s19a
Signal Handler Management System
-----
Process PID: 3362
Signal handlers registered successfully.

Signal Mask Status:
SIGINT : Not Blocked
SIGTERM : Not Blocked
SIGUSR1 : Not Blocked

Signal tests:
1. Press Ctrl+C to generate SIGINT.
2. The program will continue running.
3. Press Ctrl+\ only if you want to terminate it.

Sending SIGUSR1...

--- Signal Event ---
Received SIGUSR1
Sender PID: 3362
Signal count: 1

Waiting for signal events...
Program running... 1/10
Program running... 2/10
Program running... 3/10
Program running... 4/10
Program running... 5/10
Program running... 6/10
Program running... 7/10
Program running... 8/10
Program running... 9/10
Program running... 10/10

Program completed normally.
Total signals handled: 1
ketana_sindhu@KetaZone:~$ |

```

To Capture SIGINT, Forward Signals, Protect Shell Process, Terminate Foreground Jobs, Update Job States, Test Interrupt Handling.

Code:

```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <signal.h>
#include <sys/wait.h>

pid_t foreground_pid = -1;

/* SIGINT handler for the shell */
void handleSIGINT(int sig) {
    (void)sig;
    printf("\nShell received SIGINT.\n");

    /*
     * If a foreground job exists,
     * forward SIGINT to that job.
     */
    if (foreground_pid > 0) {
        printf("Forwarding SIGINT to foreground job %d...\n",
            foreground_pid);
        kill(foreground_pid, SIGINT);
    }
    else {
        printf("Shell is protected from termination.\n");
        printf("No foreground job is running.\n");
    }
}

/* Create foreground job */
void runForegroundJob() {
    int status;
    foreground_pid = fork();
    if (foreground_pid < 0) {
        perror("fork");
        return;
    }

    /* Child process */
    if (foreground_pid == 0) {
        /*
         * Restore default SIGINT behavior
         * for the child.
         */
        signal(SIGINT, SIG_DFL);

        printf("Foreground job started.\n");
        printf("Child PID: %d\n",
            getpid());

        /*
         * Long-running foreground task.
         */
        for (int i = 1; i <= 20; i++) {
```

```
            /*
             * Long-running foreground task.
             */
            for (int i = 1; i <= 20; i++) {
                printf("Foreground job running... %d/20\n",
                    i);
                sleep(1);
            }
            printf("Foreground job completed normally.\n");
            exit(0);
        }

        /* Parent waits for foreground job */
        printf("Foreground job started with PID %d.\n",
            foreground_pid);
        printf("Press Ctrl+C to interrupt the job.\n\n");
        waitpid(foreground_pid, &status, 0);

        /*
         * Check how the job ended.
         */
        if (WIFSIGNALED(status)) {
            printf("\nForeground job terminated by signal %d.\n",
                WTERMSIG(status));
        }
        else if (WIFEXITED(status)) {
            printf("\nForeground job exited normally.\n");
            printf("Exit status: %d\n",
                WEXITSTATUS(status));
        }
        else {
            /*
             * Job is no longer active.
             */
            foreground_pid = -1;
        }
    }
}

int main() {
    /*
     * Register SIGINT handler for shell.
     */
    signal(SIGINT, handleSIGINT);
    printf("SIGINT Forwarding Shell\n");
    printf("-----\n");
    printf("Shell PID: %d\n",
        getpid());
    printf("Shell is protected from Ctrl+C.\n");
    printf("\nStarting foreground job...\n\n");
    runForegroundJob();
```

```

/*
 * Register SIGINT handler for shell.
 */
signal(SIGINT, handleSIGINT);

printf("SIGINT Forwarding Shell\n");
printf("-----\n");

printf("Shell PID: %d\n",
       getpid());

printf("Shell is protected from Ctrl+C.\n");

printf("\nStarting foreground job...\n\n");

runForegroundJob();

printf("\nShell remains active after job termination.\n");
printf("SIGINT handling test completed successfully.\n");

return 0;
}

```

Result:

```

saisharan134@APL-5CD1366K5L:~/SKILL$ nano Skill19b.c
saisharan134@APL-5CD1366K5L:~/SKILL$ gcc Skill19b.c
saisharan134@APL-5CD1366K5L:~/SKILL$ nano Skill19b.c
saisharan134@APL-5CD1366K5L:~/SKILL$ gcc Skill19b.c -o s19b
saisharan134@APL-5CD1366K5L:~/SKILL$ ./s19b
SIGINT Forwarding Shell
-----
Shell PID: 3467
Shell is protected from Ctrl+C.

Starting foreground job...

Foreground job started with PID 3468.
Press Ctrl+C to interrupt the job.

Foreground job started.
Child PID: 3468
Foreground job running... 1/20
Foreground job running... 2/20
Foreground job running... 3/20
Foreground job running... 4/20
Foreground job running... 5/20
Foreground job running... 6/20
Foreground job running... 7/20
Foreground job running... 8/20
Foreground job running... 9/20
Foreground job running... 10/20
Foreground job running... 11/20
Foreground job running... 12/20
Foreground job running... 13/20
Foreground job running... 14/20
Foreground job running... 15/20
Foreground job running... 16/20
Foreground job running... 17/20
Foreground job running... 18/20
Foreground job running... 19/20
Foreground job running... 20/20
Foreground job completed normally.

Foreground job exited normally.
Exit status: 0

Shell remains active after job termination.
SIGINT handling test completed successfully.
saisharan134@APL-5CD1366K5L:~/SKILL$ |

```