

Process Synchronization and Child Process Monitoring Using waitpid().

Code –

```
GNU nano 8.7.1
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <sys/wait.h>

int main() {
    pid_t pid;
    int status;

    printf("Parent Process Started\n");
    printf("Parent PID: %d\n", getpid());

    // Create child process
    pid = fork();

    if (pid < 0) {
        perror("fork failed");
        return 1;
    }

    else if (pid == 0) {
        // Child process
        printf("\nChild Process Started\n");
        printf("Child PID: %d\n", getpid());

        // Simulate some work
        printf("Child is working...\n");
        sleep(3);

        printf("Child Process Completed\n");

        // Exit with status 0
        exit(0);
    }

    else {
        // Parent process
        printf("\nParent is waiting for child...\n");

        // Synchronize with child using waitpid()
        pid_t result = waitpid(pid, &status, 0);

        if (result == -1) {
            perror("waitpid failed");
            return 1;
        }

        // Monitor child termination
        if (WIFEXITED(status)) {
            printf("\nChild process terminated normally.\n");
            printf("Child PID: %d\n", result);
            printf("Child Exit Status: %d\n",
                WEXITSTATUS(status));
        }

        else {
```

```

        // Parent process
        printf("\nParent is waiting for child...\n");

        // Synchronize with child using waitpid()
        pid_t result = waitpid(pid, &status, 0);

        if (result == -1) {
            perror("waitpid failed");
            return 1;
        }

        // Monitor child termination
        if (WIFEXITED(status)) {
            printf("\nChild process terminated normally.\n");
            printf("Child PID: %d\n", result);
            printf("Child Exit Status: %d\n",
                WEXITSTATUS(status));
        }

        else {
            printf("\nChild process terminated abnormally.\n");
        }
    }

    printf("\nParent Process Completed\n");

    return 0;
}
|
```

Result:

```
saisharan134@APL-5CD1366K5L:~/SKILL$  
ketana_sindhu@KetaZone:~/SKILL$ nano Skill7a.c  
ketana_sindhu@KetaZone:~/SKILL$ gcc Skill7a.c -o s7a  
ketana_sindhu@KetaZone:~/SKILL$ ./s7a  
Parent Process Started  
Parent PID: 1838  
  
Parent is waiting for child...  
  
Child Process Started  
Child PID: 1839  
Child is working...  
Child Process Completed  
  
Child process terminated normally.  
Child PID: 1839  
Child Exit Status: 0  
  
Parent Process Completed  
ketana_sindhu@KetaZone:~/SKILL$ |
```

To Retrieve PATH Variable, Parse Search Directories, Locate Executables, Verify Permissions, Handle Missing Commands, Test Command Resolution.

```
GNU nano 8.7.1  
#include <stdio.h>  
#include <stdlib.h>  
#include <string.h>  
#include <unistd.h>  
#include <sys/stat.h>  
  
#define MAX_PATH 4096  
#define MAX_COMMAND 100  
  
/* Check whether a file is executable */  
int isExecutable(const char *path) {  
  
    struct stat fileInfo;  
  
    if (stat(path, &fileInfo) != 0)  
        return 0;  
  
    /* Check if it is a regular file and executable */  
    if (S_ISREG(fileInfo.st_mode) &&  
        access(path, X_OK) == 0) {  
  
        return 1;  
    }  
  
    return 0;  
}  
  
/* Search command in PATH */  
char *findCommand(const char *command) {  
  
    char *path = getenv("PATH");  
  
    if (path == NULL) {  
        return NULL;  
    }  
  
    /* Make a copy because strtok modifies the string */  
    char *pathCopy = strdup(path);  
  
    if (pathCopy == NULL) {  
        return NULL;  
    }  
  
    char *directory = strtok(pathCopy, ":");  
  
    static char fullPath[MAX_PATH];  
  
    while (directory != NULL) {  
  
        snprintf(fullPath,  
                 sizeof(fullPath),  
                 "%s/%s",  
                 directory,  
                 command);  
  
        if (isExecutable(fullPath)) {  
  
            free(pathCopy);  
            return fullPath;  
        }  
    }  
}
```

```

GNU nano 8.7.1
        command);

        if (isExecutable(fullPath)) {
            free(pathCopy);
            return fullPath;
        }

        directory = strtok(NULL, ":");
    }

    free(pathCopy);
    return NULL;
}

int main() {
    char command[MAX_COMMAND];

    printf("Command Resolution Using PATH\n");
    printf("-----\n");

    /* Retrieve PATH variable */
    char *path = getenv("PATH");

    if (path == NULL) {
        printf("Error: PATH variable not found.\n");
        return 1;
    }

    printf("PATH variable retrieved successfully.\n\n");
    printf("Enter command to search: ");
    scanf("%99s", command);

    /* Search for executable */
    char *result = findCommand(command);

    if (result != NULL) {
        printf("\nCommand found!\n");
        printf("Command      : %s\n", command);
        printf("Executable   : %s\n", result);
        printf("Permissions  : Executable\n");
        printf("Status       : Command can be executed.\n");
    }

    else {
        printf("\nCommand not found!\n");
        printf("Command      : %s\n", command);
        printf("Status       : No executable found in PATH.\n");
    }

    return 0;
}
|

```

Result:

```

ketana_sindhu@Ketazone:~/SKILL$ nano Skill7b.c
saisharan134@APL-5CD1366K5L:~/SKILL$ gcc Skill7b.c -o s7b
saisharan134@APL-5CD1366K5L:~/SKILL$ ./s7b
Command Resolution Using PATH
-----
PATH variable retrieved successfully.

Enter command to search: ls

Command found!
Command      : ls
Executable   : /usr/bin/ls
Permissions  : Executable
Status       : Command can be executed.
saisharan134@APL-5CD1366K5L:~/SKILL$ ./s7b
Command Resolution Using PATH
-----
PATH variable retrieved successfully.

Enter command to search: gcc

Command found!
Command      : gcc
Executable   : /usr/bin/gcc
Permissions  : Executable
Status       : Command can be executed.
saisharan134@APL-5CD1366K5L:~/SKILL$ ./s7b
Command Resolution Using PATH
-----
PATH variable retrieved successfully.

Enter command to search: hello123

Command not found!
Command      : hello123
Status       : No executable found in PATH.
saisharan134@APL-5CD1366K5L:~/SKILL$ |

```