

Code:

```
1 #include <stdio.h>
2 #include <fcntl.h>
3 #include <unistd.h>
4 #include <stdlib.h>
5
6 int main()
7 {
8     int source_fd, dest_fd;
9     char source[100], destination[100];
10    char buffer[1024];
11    ssize_t bytes_read, bytes_written;
12
13    // Accept source file name
14    printf("Enter source file name: ");
15    scanf("%99s", source);
16
17    // Accept destination file name
18    printf("Enter destination file name: ");
19    scanf("%99s", destination);
20
21    // Open source file for reading
22    source_fd = open(source, O_RDONLY);
23
24    if (source_fd == -1)
25    {
26        perror("Error opening source file");
27        return 1;
28    }
29
30    // Open/Create destination file for writing
31    dest_fd = open(destination, O_WRONLY | O_CREAT | O_TRUNC, 0644);
32
33    if (dest_fd == -1)
34    {
35        perror("Error opening destination file");
36        close(source_fd);
37        return 1;
38    }
39
40    // Read from source and write to destination
41    while ((bytes_read = read(source_fd, buffer, sizeof(buffer))) > 0)
42    {
43        bytes_written = write(dest_fd, buffer, bytes_read);
44
45        if (bytes_written == -1)
46        {
47            perror("Error writing to destination file");
48            close(source_fd);
49            close(dest_fd);
50            return 1;
51        }
52    }
53
54    if (bytes_read == -1)
55    {
56        perror("Error reading source file");
57    }
58    else
59    {
60        printf("File copied successfully.\n");
61    }
62
63    // Close both files
64    close(source_fd);
65    close(dest_fd);
66
67    return 0;
68 }
```

Output:

```
saisurendra@SaiSurendra:~$ gcc Experiment2.c -o Experiment2
saisurendra@SaiSurendra:~$ ./Experiment2
Enter source file name: Program1.c
Enter destination file name: Program4.c
File copied successfully.
```