TABLE OF COLUMN REINFORCEMENTS							
S.No	COLUMN NAME	Nos	SIZE	REINFORCEMENT LONGITUDINAL TIES		SECTION	STIRRUPS
			(IN FEET)				
1)	C1	2	9"X1'3"	4 # 16mmØ	8mm@6"c/c	4 # 16mmØ	
2)	C2	5	9"X1'3"	4 # 16mmØ + 2 # 12mmØ	8mm@6"c/c	4 # 16mmØ + 2 # 12mmØ	+
3)	С3	5	9"X1'6"	4 # 16mmØ + 4 # 12mmØ	8mm@6"c/c	4 # 16mmØ 4 # 12mmØ	+

2. WORK TO FIGURED DIMENSIONS ONLY.

DRAWINGS AND SPECIFICATIONS.

3.THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL RELEVANT

## **SPECIFICATIONS:**

- \* Use Concrete of Grade M20
- \* Use TOR Steel of Grade Fe500
- \* Provide Cover of 50mm for Foundations.

Thirukampuliyur, Bypass,

Karur, Tamil Nadu 639002

- \* Provide Cover of 25mm for Beams 20mm for slabs.
- \* SBC of soil is taken as 200 kN/m<sup>2</sup>
- \* Designed for G+1 Floors only.

