Bejavada Sai Teja

Github | Linkedin | b.saiteja.ai@gmail.com | +91 6301105642

Vallabhapuram, Guntur, Andhra Pradesh

Education

B.Tech CSE at **Bennett University**, Uttar Pradesh 2

Dean's List recipient (2024) - Achieved twice for academic excellence (C

Coursework: Data Structures & Algorithms, Object-Oriented Programming, Database Management Systems, Operatin

Intermediate Education at **Sri Chaitanya Junior College**, AP 2

Technical Skills

Languages	Java, Python
Java Core	OOP, SOLID Principles, Design Patterns (Singleton, Factory, Strategy, Observer)
Frameworks	FastAPI
Databases	PostgreSQL
Tools	Git, Docker
Core	Data Structures & Algorithms, Low-Level System Design

Projects

Parking Lot System (LLD) | *Java, OOP, Design Patterns, SOLID Principles* 2026

- Designed and implemented a full Parking Lot Management System from scratch using core Java, demonstrating strong command of OOP principles – encapsulation, inheritance, and abstraction – across entities like `ParkingLot`, `ParkingFloor`, `ParkingSpot`, and `Ticket`.
- Applied the **Strategy Pattern** for extensible fee calculation, enabling plug-and-play fee strategies (flat rate, hourly, vehicle-type-based) without modifying core logic – adhering to the Open/Closed Principle.
- Implemented the **Singleton Pattern** for the `ParkingLot` instance and leveraged the **Factory Pattern** for vehicle and spot creation, ensuring controlled instantiation and clean separation of concerns.

SkillLens | *Python, FastAPI, Gemini, BAAI/bge, SPLADE, Endee* 2026

- Built an AI-powered resume screening tool using a full RAG pipeline combining dense (BAAI/bge-base-en-v1.5) and sparse (SPLADE++) embeddings via hybrid vector search in Endee, enabling semantic retrieval beyond simple keyword matching.
- Engineered a resume-level ranking algorithm that aggregates per-chunk similarity scores by averaging each resume's top-3 matches, preventing score dilution across long documents.
- Integrated Gemini for dual-purpose prompt enhancement – rewriting queries for optimal retrieval while inferring desired result count from phrasing, eliminating manual configuration.