

Lec-30

clear()

Purpose: Clears the text from an input field (like a text box or text area).

- Used when dealing with input fields (`<input>` or `<textarea>`) to remove any existing text before entering new text.

Text Box with Preloaded Text



`Thread.sleep(ms)` in Java is a method used to pause the execution of the current thread for a specified number of milliseconds.

```
WebElement textBoxField = driver.findElement(By.id("textbox1"));
textBoxField.clear();
```

WebElement textAreaField =

```
driver.findElement(By.xpath("//h2[text()='Text Area Field Two']/following::textarea"));
```

```
textAreaField.clear();
```

getText()

Purpose: Retrieves the visible (inner) text of a web element.

- It returns only the **text** that is visible to the user, ignoring hidden text (like those inside `display: none` elements).

```
WebElement textElement = driver.findElement(By.id("pah"));
String retrievedText = textElement.getText();

System.out.println(retrievedText);
```

```
WebElement button = driver.findElement(By.id("but2"));
String textOnButton = button.getText();
System.out.println(textOnButton);
```

If we can't get text with `getText()`, we can go with `getAttribute()`

getTitle()

Purpose: Retrieves the title of the current webpage.

- Useful for verifying page transitions or checking if a user is on the expected page.

```
driver.get("https://omayo.blogspot.com/");

String pageTitleOne = driver.getTitle();
System.out.println(pageTitleOne);

WebElement selenium143Link = driver.findElement(By.id("link1"));
selenium143Link.click();

String pageTitleTwo = driver.getTitle();
System.out.println(pageTitleTwo);
```

When we click on **Selenium143Link**, we go to other page. So, we get diff title.

getCurrentUrl()

Purpose: Retrieves the URL of the currently loaded page.

- Used to verify page navigation or to check if redirection happened.

```
String pageURLOne = driver.getCurrentUrl();  
System.out.println(pageURLOne);
```

```
String pageURLTwo = driver.getCurrentUrl();  
System.out.println(pageURLTwo);
```

Lec-31

close()

Purpose: Closes the current browser window that the WebDriver is controlling.

- If there is only **one open window**, `close()` will **terminate the session**.
- If multiple windows are open, it will close only the current active window.

After performing our testing, we need to close the browser.

```
driver.close();
```

Behavior:

- Does **not** close all windows; it only closes the one that WebDriver is currently controlling.

quit()

Purpose: Closes **all** browser windows opened by the WebDriver and terminates the session.

- Unlike `close()`, `quit()` shuts down all browser instances opened during the test.

Behavior:

- It completely **ends the WebDriver session**, making the browser unresponsive to further WebDriver commands.

```
WebElement selenium143Link = driver.findElement(By.id("selenium143"));
selenium143Link.click();

WebElement openPopupLink = driver.findElement(By.linkText("Open a popup window"));
openPopupLink.click();

Thread.sleep(3000);

driver.quit();
```

Closes all the 3 opened browser tabs.

`getAttribute(String attributeName)`

Purpose: Retrieves the value of a specified attribute of a web element.

- Used to get attributes like `value`, `href`, `id`, `class`, `src`, etc.

Behavior:

- If the attribute exists, it returns the value.
- If the attribute does **not** exist, it returns `null`.

```
WebElement searchButton = driver.findElement(By.cssSelector("td[class='gsc-search-button'] > input"));
```

We need to get text of label of searchText,

```
String textOnButton = searchButton.getAttribute("value");
System.out.println(textOnButton);
```

isEnabled()

Purpose: Checks if a web element (like a button or input field) is **enabled** (clickable/usable) or **disabled**.

Behavior:

- Returns **true** if the element is enabled.
- Returns **false** if the element is disabled (e.g., `<input disabled>`)

Sometimes a button might be disabled, then, we can't click on it. To check if it is enabled, we can use this method.

```
boolean state = button.isEnabled();  
  
if(state) {  
    System.out.println("Button is in enabled state");  
}  
else {  
    System.out.println("Button is in disabled state");  
}
```

Difference Between `linkText()` and `partialLinkText()`

Method	Behavior
<code>By.linkText("Full Link Text")</code>	Finds a link by exact text match.
<code>By.partialLinkText("Partial")</code>	Finds a link containing the given text.

```
WebElement compendiumLink = driver.findElement(By.partialLinkText("compendium"))  
compendiumLink.click();
```