Solutions -- Topic 12, Dynamic Programming

Copyright (c) 2020 Dan Suthers. All rights reserved. These solution notes may only be used by instructors, TAs and students in ICS 311 Fall 2020 at the University of Hawaii.

Longest Simple Path in a Directed Acyclic Graph

Given a **directed weighted acyclic graph G=(V,E)** and two vertices **s** (start) and **t** (target), develop a **dynamic programming approach** for finding a **longest weighted simple path** from **s** to **t**.

1. Characterize the Structure of an Optimal Solution

Let **p** be a **longest path from u to t**. If u = t then p is simply $\langle u \rangle$ and has zero weight. Consider when $u \neq t$. Then p has at least two vertices and looks like: $\mathbf{p} = \langle \mathbf{u}, \mathbf{v} \dots \mathbf{t} \rangle$ (it is possible that $\mathbf{v} = \mathbf{t}$).

Let $p' = \langle v ... t \rangle$ and prove that p' must be a longest simple path from v to t. (This is a proof of optimal substructure.)

Solution:

(Cut and paste argument:) Suppose that p' as defined above were *not* a longest simple path from v to t. Then there must exist some path p'' that is a longer simple path from v to t; that is (extending our w notation), w(p'') > w(p'). We can construct a new path p* from u to t consisting of $u \to v \to p'' \to t$. This is a legal path because G is acyclic, so u cannot occur in p''. The length of this path p* is $w(p^*) = w(u,v) + w(p'') > w(u,v) + w(p') = w(p)$

contradicting our definition of p as the longest simple path from u to t. Therefore, p' must be a longest simple path from v to t, and the problem exhibits optimal substructure.

2. Recursively define the value of an optimal solution:

Let **dist[u]** be the distance of a longest path from u to t. **Fill out the definition to** reflect the above structure:

$$dist[u] = 0 if u = t$$

$$max_{v \in Adi[u]} \{w(u,v) + dist[v]\} if u \neq t$$

3. Compute the value of an optimal solution (simple recursive version):
Write a recursive procedure that computes the <u>value</u> of an optimal solution as defined by the above recursive definition. <u>Do not memoize yet</u>; that's the next step.

Solution: (Notice how the code follows the mathematical definition.)

4. Compute the value of an optimal solution (dynamic programming version):

Memoize your procedure by passing the array dist[1..|v|] that records longest path distances dist[u] from each vertex u to t. Assume that the caller has initialized all entries of dist to $-\infty$.

Solution (additions highlighted):

5. Analyze the runtime of your solution in #4 in terms of |V| and |E|

Include

- (a) the runtime to initialize dist and
- (b) the runtime of Longest-Path-Value-Memoized itself.
- (c) the resulting total runtime

This requires aggregating across loops.

- (a) $\Theta(|V|)$ to fill in the entries.
- **(b)** $\Theta(|E|)$ since in aggregate across all calls each edge is processed once(*), and all other operations are constant. (*) can be argued two ways: it is a DAG, so we never return to the same vertex, and even if we did we would just be doing constant lookup of paths we saved in dist.
- (c) Total: $\Theta(|V| + |E|)$.