

Control Systems

G V V Sharma*

CONTENTS

1	Signal Flow Graph	1
1.1	Mason's Gain Formula . . .	1
1.2	Matrix Formula	1
2	Bode Plot	1
2.1	Introduction	1
2.2	Example	1
3	Second order System	1
3.1	Damping	1
3.2	Example	1
4	Routh Hurwitz Criterion	1
4.1	Routh Array	1
4.2	Marginal Stability	1
4.3	Stability	1
4.4	Example	1
5	State-Space Model	1
5.1	Controllability and Observability	1
5.2	Second Order System	1
5.3	Example	1
5.4	Example	1
6	Nyquist Plot	1
7	Compensators	2
7.1	Phase Lead	2
7.2	Example	2
8	Gain Margin	2
8.1	Introduction	2
8.2	Example	2
9	Phase Margin	2

10 Oscillator

2

Abstract—This manual is an introduction to control systems based on GATE problems. Links to sample Python codes are available in the text.

Download python codes using

```
svn co https://github.com/gadepall/school/trunk/
control/codes
```

1 SIGNAL FLOW GRAPH

1.1 Mason's Gain Formula

1.2 Matrix Formula

2 BODE PLOT

2.1 Introduction

2.2 Example

3 SECOND ORDER SYSTEM

3.1 Damping

3.2 Example

4 ROUTH HURWITZ CRITERION

4.1 Routh Array

4.2 Marginal Stability

4.3 Stability

4.4 Example

5 STATE-SPACE MODEL

5.1 Controllability and Observability

5.2 Second Order System

5.3 Example

5.4 Example

6 NYQUIST PLOT

6.1. Find the range of k such that given characteristic equation

$$s(s^3 + 2s^2 + s + 1) + k(s^2 + s + 1) = 0 \quad (6.1.1)$$

is stable.

*The author is with the Department of Electrical Engineering, Indian Institute of Technology, Hyderabad 502285 India e-mail: gadepall@iith.ac.in. All content in this manual is released under GNU GPL. Free and open source.

Solution: The General form of characteristic equation :

$$1 + G(s)H(s) = 0 \quad (6.1.2)$$

For a system to be marginally stable , nyquist plot passes through $(-1,0j)$. Generally we will draw nyquist plot for open loop gain $G(s)H(s)$. So, $1+G(s)H(s)$ passes through $(0,0j)$

$$\text{Realpart} = \omega^4 - \omega^2(k+1) + k = 0 \quad (6.1.3)$$


$$\text{Imaginarypart} = -\omega^3 + \omega(w+1) = 0 \quad (6.1.4)$$

By equating real and imaginary to 0 .We get,

$$k = 0 \quad (6.1.5)$$

as minimum value sysstem to be stable.

6.2. For a nyquist plot,no.of clock wise encirclements around the point $(-1,0j)$ for a open loop transfer function gives the total no. right hand side zeros , can verify it through nyquist plot



The following python code generates the nyquist plot :

```
codes/ee18btech11042_1.py
```

6.3. Verifying k value using Routh-hurwitz criterion
Characteristic equation(polynomial):

$$\begin{vmatrix} s^4 & 1 & k+1 & k \\ s^3 & 2 & k+1 & 0 \\ s^2 & \frac{k+1}{2} & k & 0 \\ s^1 & \frac{(k-1)^2}{2} & 0 & 0 \\ s^0 & k & 0 & 0 \end{vmatrix}$$

From this we can say for

system to be stable,all values of determinant should be greater than 0.So,minimun value of k is,

$$k = 0 \quad (6.3.1)$$

The range of k system to be stable

$$0 < k < \infty \quad (6.3.2)$$

6.4. We can verify it through following python code

```
codes/ee18btech11042_2.py
```

7 COMPENSATORS

7.1 Phase Lead

7.2 Example

8 GAIN MARGIN

8.1 Introduction

8.2 Example

9 PHASE MARGIN

10 OSCILLATOR