



ITEM	Part Name	Material
①	Static plate	Copper alloy
②	Movable	Copper alloy
③	Key	POM
④	Cover	PA66
⑤	Case	PA66
⑥	Spring	Stainless steel
⑦	Contact	Au Alloy

Specification :

1. Rating: 12VAC/DC Max, 2V DC Min; 10mA AC/DC Max, 10  $\mu$ A DC Min.
2. Contact resistance: 200m $\Omega$  Max.
3. Insulation resistance: 100M $\Omega$  Min (DC 100V).
4. Withstand voltage: AC 100V (50~60Hz) for 1 minute.
5. Bounce time: 5ms Max. (at 16 in/sec. actuation speed).
6. Operation force: 60  $\pm$  15gf.
7. Pretravel: 2.0  $\pm$  0.6mm.
8. Total travel: 4.0mm Max.
9. Operation life: 50,000,000 cycles min.

For and on behalf of SINGAPORES  
XKB INDUSTRIAL PRECISION CO., LIMITED  
香港星坤工業精密有限公司

DEN

PRODUCT:

键盘开关

REV:

CHK

# : MAJOR DIMENSION

% : ORDER DIMENSION

Authorized Signatures(s)

Q: RRB4S-X-RD X-001

SHEET: 1/1