LabFlow

Sign in

LabFlow is invite-only for now. Your account was created for you.

Email

sajad@example.com

Password

Forgot it? Ask the admin.

Sign in

Answers you can verify.

Your library

4 papers. Each one is read in the background, one at a time.

Upload paper

Drop a PDF here, or choose a file
Born-digital English papers up to 25 MB. Scanned PDFs aren't supported yet.

YOUR PAPERS

Attention Is All You Need
Vaswani et al. · NeurIPS 2017 · added Oct 10
Ready
15 pages · 39 passages
Ask this paper

Deep Residual Learning for Image Recognition
He et al. · CVPR 2016 · added just now
Reading
Started 18 s ago
Ask this paper

BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding
Devlin et al. · NAACL 2019 · added just now
Queued
Next after the paper above
Ask this paper

Adam: A Method for Stochastic Optimization
Kingma and Ba · ICLR 2015 · added Oct 11
Failed
Ollama isn't running. Start it, then retry.
Retry

SHARED DEMO LIBRARY Indexed ahead of time and read-only, for both accounts.

Ready Read-only
Language Models are Few-Shot Learners
Brown et al. · NeurIPS 2020
Ask this paper

Ready Read-only
Denoising Diffusion Probabilistic Models
Ho, Jain, and Abbeel · NeurIPS 2020
Ask this paper

Ready Read-only
Generative Adversarial Nets
Goodfellow et al. · NeurIPS 2014
Ask this paper

Which optimizer and learning rate did the authors use?

LabFlow from 1 passage

The authors trained the Transformer with the Adam optimizer, using $\beta_1 = 0.9$, $\beta_2 = 0.98$ and $\varepsilon = 10^{-9}$ p. 7. The learning rate was not fixed: it rose linearly for the first 4,000 warm-up steps, then fell in proportion to the inverse square root of the step number p. 7.

$$lrate = d_{\text{model}}^{-0.5} \cdot \min(step_num^{-0.5}, step_num$$

SOURCES p. 7 §5.3 Optimizer

How long did training take?

LabFlow writing

The base models trained for 100,000 steps, about 12 hours on eight P100 GPUs p. 7. The big models trained for 300,000 steps, which

Ask a follow-up...

Stop

5.2 Hardware and Schedule

5.3 Optimizer

Cited in answer 1 · p. 7

We used the Adam optimizer [20] with $\beta_1 = 0.9$, $\beta_2 = 0.98$ and $\varepsilon = 10^{-9}$. We varied the learning rate over the course of training, according to the formula:

$$lrate = d_{\text{model}}^{-0.5} \cdot \min(step_num^{-0.5}, step_num \cdot warmup_steps^{-1.5})$$

5.4 Regularization

Which dataset did they use to evaluate summarization?

LabFlow no passage supports an answer

Not in this paper. These were the closest passages, and none of them mentions summarization.

p. 8 **§6.1 Machine Translation** Show in PDF

On the WMT 2014 English-to-German translation task, the big transformer model outperforms the best previously reported models...

p. 9 **§6.3 English Constituency Parsing** Show in PDF

To evaluate if the Transformer can generalize to other tasks we performed experiments on English constituency parsing...

TRY ASKING

Which tasks did they evaluate on?

Which datasets did they train on?

Ask about this paper...

Every claim cites a page. If the paper doesn't say, LabFlow says so.

Which optimizer and learning rate did the authors use?

LabFlow from 1 passage

The authors trained the Transformer with the Adam optimizer, using $\beta_1 = 0.9$, $\beta_2 = 0.98$ and $\varepsilon = 10^{-9}$ p. 7. The learning rate was not fixed: it rose linearly for the first 4,000 warm-up steps, then fell in proportion to the inverse square root of the step number p. 7.

$$lrate = d_{\text{model}}^{-0.5} \cdot \min(step_num^{-0.5}, step_num$$

SOURCES p. 7 §5.3 Optimizer

How long did training take?

LabFlow writing

The base models trained for 100,000 steps, about 12 hours on eight P100 GPUs p. 7. The big models trained for 300,000 steps, which

Ask a follow-up...

Stop

5.2 Hardware and Schedule

5.3 Optimizer

Cited in answer 1 · p. 7

We used the Adam optimizer [20] with $\beta_1 = 0.9$, $\beta_2 = 0.98$ and $\varepsilon = 10^{-9}$. We varied the learning rate over the course of training, according to the formula:

$$lrate = d_{\text{model}}^{-0.5} \cdot \min(step_num^{-0.5}, step_num \cdot warmup_steps^{-1.5})$$

5.4 Regularization