

Rajalakshmi Engineering College

Name: Sajine Santhakumar
Email: 240701459@rajalakshmi.edu.in
Roll no: 240701459
Phone: 9952076750
Branch: REC
Department: I CSE FE
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 7_COD_Question 3

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

In a messaging application, users maintain a contact list with names and corresponding phone numbers. Develop a program to manage this contact list using a dictionary implemented with hashing.

The program allows users to add contacts, delete contacts, and check if a specific contact exists. Additionally, it provides an option to print the contact list in the order of insertion.

Input Format

The first line consists of an integer n , representing the number of contact pairs to be inserted.

Each of the next n lines consists of two strings separated by a space: the name of the contact (key) and the corresponding phone number (value).

The last line contains a string k, representing the contact to be checked or removed.

Output Format

If the given contact exists in the dictionary:

1. The first line prints "The given key is removed!" after removing it.
2. The next n - 1 lines print the updated contact list in the format: "Key: X; Value: Y" where X represents the contact's name and Y represents the phone number.

If the given contact does not exist in the dictionary:

1. The first line prints "The given key is not found!".
2. The next n lines print the original contact list in the format: "Key: X; Value: Y" where X represents the contact's name and Y represents the phone number.

Refer to the sample outputs for the formatting specifications.

Sample Test Case

Input: 3

Alice 1234567890

Bob 9876543210

Charlie 4567890123

Bob

Output: The given key is removed!

Key: Alice; Value: 1234567890

Key: Charlie; Value: 4567890123

Answer

```
#include <stdio.h>
```

```
#include <string.h>
```

```
#define MAX 50
```

```
#define NAME_LEN 11
```

```
#define PHONE_LEN 11
```

```
typedef struct {
```

```

    char name[NAME_LEN];
    char phone[PHONE_LEN];
} Contact;
int main() {
    int n, i, found = 0, index = -1;
    Contact contacts[MAX];
    char key[NAME_LEN];
    scanf("%d", &n);
    for (i = 0; i < n; i++) {
        scanf("%s %s", contacts[i].name, contacts[i].phone);
        scanf("%s", key);
        for (i = 0; i < n; i++) {
            if (strcmp(contacts[i].name, key) == 0) {
                found = 1;
                index = i;
                break;
            }
        }
        if (found) {
            printf("The given key is removed!\n");
            for (i = index; i < n - 1; i++) {
                contacts[i] = contacts[i + 1];
            }
            n--;
        } else {
            printf("The given key is not found!\n");
        }
        for (i = 0; i < n; i++) {
            printf("Key: %s; Value: %s\n", contacts[i].name, contacts[i].phone);
        }
        return 0;
    }
}

```

Status : Correct

Marks : 10/10