License Create API

Production integration reference for creating mobile application licences

Endpoint at a glance

Property	Value
Method	POST
Primary URL	https://activate.imcbs.com/t-erp/mobileapp/api/license/create/
Content type	application/json
Success codes	201 Created when at least one licence is created; 200 OK when all requested licences are skipped
Error code	400 Bad Request for invalid JSON, missing fields, invalid project/package pairs, or T-ERP restrictions

> Scope note: This document reflects the current Django implementation and route configuration. The view is CSRF-exempt and does not declare an authentication decorator; secure the endpoint at the gateway or add authentication before exposing it beyond a trusted integration boundary.

Behavior summary

The API accepts one company payload and a non-empty list of project/package selections. It validates every selection before creating any records. A company is matched by exact email: an existing company is reused, and a licence already present for that company and project is returned as skipped_existing. New licences are created with a generated license_key, an automatic billing-history record, licence type new, and an active status.

Route behavior

Route	T-ERP rule	Validity
/t-erp/mobileapp/api/license/create/	Each selected project must have t_erp enabled	14 days

1. Request

Send a JSON object with corporate details, company details, and at least one project/package pair. Project and package values are exact matches: spelling, spaces, and capitalization are significant.

Minimal valid request

```
{
  "corporate": {
    "name": "Corporate Name",
    "place": "Optional place"
  },
  "company": {
    "name": "Company Name",
    "place": "Optional place",
    "email": "company@domain.com",
    "contact_no": "+91 9000000000",
    "country": "India",
    "is_active": true
  },
  "projects": [
    { "project": "Exact Project Name", "package": "Exact Package Name" }
  ]
}
```

Request fields

Field	Type	Required	Description
corporate.name	string	Yes	Corporate/store name. Required only when the company email is new.
corporate.place	string	No	Corporate/store place. Defaults to empty string.
company.name	string	Yes	Company/shop name. If email already exists, the stored name wins.
company.place	string	No	Company/shop place. Defaults to empty string.
company.email	string	Yes	Used as client_id and company reuse key. Maximum 50 characters.
company.contact_no	string	No	Company contact number.
company.country	string	No	Defaults to India. Currency is derived server-side.
company.is_active	boolean	No	Defaults to true.
projects	array	Yes	Non-empty array. Each project may appear once only.
projects[].project	string	Yes	Exact project name.
projects[].package	string	Yes	Exact package name belonging to that project.

cURL example

```
curl -X POST \
  "https://activate.imcbs.com/t-erp/mobileapp/api/license/create/" \
  -H "Content-Type: application/json" \
  -d @request.json
```

2. Processing rules

The operation is transactional. The request is fully validated before creation, and licence creation runs inside a single database transaction.

Rule	Implementation behavior
Project matching	Exact project_name match. Missing projects return 400. Duplicate names in the same request return 400.
Package matching	The package must exist under the selected project and match exactly. A package from another project is rejected.
T-ERP eligibility	Every selected project must have t_erp enabled, otherwise the entire request is rejected.
Company reuse	Shop is found by company.email. Existing store/shop details and client_id are reused as-is.
Duplicate licence	If the company already has a licence for a selected project, that item is skipped with status skipped_existing.
Users / login limit	Uses package.users_count. If zero, null, or otherwise unlimited, falls back to 50.
Validity	T-ERP route: 14 days. Regular route, if enabled later: 30 days.
Billing	Creates a billing-history record with bill_status true and payment_status Not Paid.
Currency	Derived from country using the server-side country mapping; no currency_code request field is accepted.

Bulk request example

```
{
  "corporate": { "name": "IMC Developments", "place": "India" },
  "company": {
    "name": "Acme Retail",
    "email": "ops@acme.example",
    "country": "India"
  },
  "projects": [
    { "project": "Trellisco Alpha", "package": "Prime" },
    { "project": "Trellisco Beta", "package": "Prime" }
  ]
}
```

Important: If one project/package entry is invalid, no new company, licence, or billing record is created for the request.

3. Success response

A successful response returns the company identity and one result item per requested project. HTTP 201 indicates that at least one licence was created. HTTP 200 indicates all requested project licences already existed and were skipped.


```
{
  "success": true,
  "message": "2 licence(s) created, 0 skipped (a licence already exists for this company under the project).",
  "reused_existing_company": false,
  "created_count": 2,
  "skipped_count": 0,
  "corporate": {
    "name": "IMC Developments",
    "place": "India",
    "store_id": 123
  },
  "company": {
    "name": "Acme Retail",
    "place": "",
    "email": "ops@acme.example",
    "contact_no": "",
    "country": "India",
    "currency_code": "INR",
    "client_id": "ops@acme.example"
  },
  "results": [
    {
      "project": "Trellisco Alpha",
      "package": "Prime",
      "status": "created",
      "license_key": "generated-key",
      "users_count": 10,
      "login_limit": 10,
      "expiry_date": "2026-12-01T10:30:00+00:00"
    }
  ]
}
```


Response fields

Field	Meaning
success	Always true for a successful operation.
reused_existing_company	true when the email matched an existing shop.
created_count / skipped_count	Counts of created and skipped result items.
corporate	Resolved corporate/store identity, including store_id.
company	Resolved company/shop identity. client_id equals the email used for matching.
results[].status	created or skipped_existing.
results[].license_key	Returned only for created licences.
results[].expiry_date	ISO 8601 timestamp for the created licence.

Mixed create and skip

When an existing email has a licence for one selected project but not another, the response can contain both statuses. The existing company is reused once, the already-licensed project is skipped, and the remaining project is created.

4. Error responses

Errors use the same compact shape and do not create partial records.

```
{
  "success": false,
  "error": "company.email is required (client_id is set from it)"
}
```

HTTP	Example condition	Example error
400	Malformed JSON	Invalid JSON body
400	Missing corporate name	corporate.name is required
400	Missing company email	company.email is required (client_id is set from it)
400	Email over 50 characters	company.email is too long to be used as client_id (max 50 chars)
400	Missing projects	projects is required and must be a non-empty list...
400	Unknown project	Project '...' not found. Project name must match exactly...
400	Unknown package	Package '...' not found for project '...'...
400	Duplicate project	Project '...' is listed more than once...
400	T-ERP disabled	Project '...' is not enabled for the T-ERP licence create API...
400	No branch configured	No branch configured for project '...' and default branch...

Integration checklist

Check	Action
OK	Use the trailing slash exactly as shown in the URL.
OK	Send Content-Type: application/json.
OK	Use the exact project and package names configured in IMC.
OK	Treat 201 and 200 as successful HTTP responses.
OK	Inspect each results[] item; a successful request may include skipped_existing items.
OK	Persist license_key and expiry_date for created items.
OK	Do not send currency_code; the server derives it from country.
OK	Protect the endpoint with gateway authentication or add an application authentication layer before production exposure.

Implementation reference

Generated from the current route and view implementation in auto_licence/urls.py and auto_licence/views.py. The API contract should be updated if the server-side validation, authentication, or response schema changes.