Multimodal Contradiction Detection on a COCO-Derived Benchmark: Comparing CLIP-Based Models and Qwen2.5-VL

Saj Patel, Prathamesh Swar
COMP 646, Rice University
[sp258, ps165]@rice.edu

Abstract

Multimodal contradiction detection asks whether an image supports or conflicts with a caption, but common image-text datasets do not isolate contradiction types in a controlled way. We build a COCO-derived binary benchmark with 4,552 examples from 2,276 source families, balanced between entailment and contradiction and organized into action, attribute, object, and count edits with family-level train/validation/test splits. On the final 684-example comparison set, a cross-attention classifier over frozen OpenAI CLIP ViT-B/32 token states reaches 96.5% accuracy, outperforming a frozen CLIP linear probe (89.6%), raw CLIP thresholding (62.6%), and zero-shot Qwen2.5-VL-3B-Instruct (76.3%). The largest gap appears on count edits, suggesting that supervised fusion over frozen vision-language features is more reliable than raw similarity or zero-shot prompting for structured contradiction detection.

1. Introduction

Modern vision-language models are strong on image-text retrieval and caption-aligned matching [9], but high alignment does not guarantee reliable visual grounding when a caption conflicts with the image. Multimodal contradiction detection is stricter: the model must decide whether a caption is supported by the image rather than merely related to it.

Existing benchmarks do not isolate contradiction types in a compact, controlled way. Microsoft COCO [11] provides broad visual coverage, but it is not designed for structured contradiction analysis. We build a COCO-derived benchmark from `val2017` captions, apply meaning-preserving synonym edits for entailment, introduce targeted contradiction edits, and split data at the source-family level to prevent leakage across train, validation, and test.

2. Related Work

FOIL-COCO shows that controlled caption edits expose failures in image-language grounding [1]. SNLI-VE studies visual entailment over image-sentence pairs [2]. NLVR2 frames truth evaluation over paired photographs and human-written statements, with examples involving quantities, comparisons, and relations [3]. These datasets motivate our binary formulation, but our benchmark keeps the edit operation explicit so each contradiction has a known source caption and edit family.

Recent compositionality benchmarks show that high retrieval or captioning performance does not imply fine-grained grounding. Winoground tests caption-image matching under word reordering [4]. ARO studies attribution, relation, and word-order sensitivity [5]. VALSE evaluates linguistic phenomena through valid foils, while SugarCrepe argues for hard negatives that reduce exploitable dataset bias [6, 7]. Our benchmark is narrower, but it gives a controlled testbed for action, attribute, object, and count contradictions.

The work also connects to hallucination evaluation. POPE probes whether large vision-language models mention objects that are not present in the image [8]. Our task is complementary: instead of evaluating free-form generations, the benchmark asks whether a model rejects a supplied caption when a targeted edit makes the caption false. CLIP gives a direct similarity baseline [9]; Qwen2.5-VL gives a modern zero-shot reference [10].

3. Benchmark Construction

We build the benchmark from a subset of COCO 2017 `val2017` captions [11]. A *source family* contains one original caption and all edited captions derived from it. We retain a family only when it yields both an entailment edit and at least one contradiction edit, then split at the family level so near-duplicate variants never cross train, validation, and test.

The final benchmark contains 2,276 source families, 4,552 examples, and 1,239 unique images. The split is



Figure 1. Final benchmark composition. Stacked horizontal bars show example counts for each edit family, colored by split (train/validation/test), with totals shown at right. The benchmark is balanced overall between entailment and contradiction, but contradiction subfamilies remain uneven because some clean edits are easier to generate from COCO captions than others.

3,186 train, 682 validation, and 684 test examples. Each family contributes one entailment and one contradiction. Entailment rows use synonym edits such as *people* → *individuals* or *couch* → *sofa*. Contradiction rows use four rule families: action edits (*sitting* → *running*), attribute edits (*blue* → *red*), object edits (*couch* → *bench*), and count edits (*two* → *one*).

Before inclusion, edits are filtered for phrase integrity, grammatical agreement, and object replacements already present in the image metadata. Coverage is therefore intentionally uneven: 683 action, 642 count, 567 object, and 384 attribute contradictions. Figure 1 summarizes the benchmark.

4. Models and Experimental Setup

We compare four systems built around two concrete pretrained checkpoints. The shared backbone for the first three systems is **OpenAI CLIP ViT-B/32** (‘`openai/clip-vit-base-patch32`‘), a dual-encoder model with about 151.3M parameters across its vision and text towers [9]. Our zero-shot reference is **Qwen2.5-VL-3B-Instruct** (‘`Qwen/Qwen2.5-VL-3B-Instruct`‘), a 3.75B-parameter vision-language model according to the Hugging Face checkpoint metadata [10]. After these first mentions, we refer to them as CLIP and Qwen2.5-VL for brevity.

Raw CLIP uses CLIP ViT-B/32 to compute cosine similarity between normalized image and text embeddings, then predicts contradiction or entailment with a threshold fit on validation data. This is a natural baseline, but cosine similarity is a retrieval score rather than a calibrated contradiction classifier. **Linear Probe** keeps the same CLIP backbone frozen and trains a classifier on the pooled image embedding, pooled text embedding, and raw CLIP score. **Cross-Attention** also keeps CLIP frozen, but replaces pooled-only features with token-level fusion: image and text token states are projected to hidden size 256, fused



Figure 2. Raw CLIP validation threshold sweep. The blue and dashed green curves show macro-F1 and accuracy as the contradiction threshold τ varies, and the star marks the selected validation threshold $\tau = 0.2907$. This diagnostic shows that raw CLIP needs an explicit decision rule rather than relying on cosine similarity alone.

with 4-head cross-attention, mean pooled, and fed to a binary classifier. This adds explicit image-text interactions that help on localized edits such as counts or attributes. **Qwen2.5-VL** is used zero-shot: it receives the image and edited caption and returns a JSON label indicating contradiction or entailment.

For the learned CLIP models, we train only the added classifier layers and keep the CLIP backbone frozen throughout. Validation sweeps select the best linear probe (30 epochs, batch size 16, learning rate 5×10^{-4}) and cross-attention model (35 epochs, batch size 4, learning rate 10^{-4}). Raw CLIP uses the best validation threshold $\tau = 0.2907$, and Figure 2 shows the validation sweep that selects this operating point. The learned models also use validation-based early stopping so runs can terminate once accuracy plateaus instead of always consuming the full epoch budget. In the final run, all four systems are compared on the same 684-example evaluation set; this comparison set equals the full test split. We report overall accuracy, class-specific F1, and per-family accuracy by edit type.

5. Results

Table 1 shows the main quantitative comparison on the 684-example evaluation set. Raw CLIP similarity is a weak baseline on this task, while both learned CLIP-based classifiers improve sharply over thresholding alone. The cross-attention model is strongest overall at 96.5% accuracy, followed by the linear probe at 89.6%. Qwen2.5-VL is a useful zero-shot reference, but it remains well below the learned CLIP models on this controlled benchmark. Figure 3 adds an optimization view of the two learned CLIP models: under the same early-stopping procedure, the linear probe continues improving until epoch 25 and stops at epoch 27, while cross-attention peaks by epoch 8 and stops at epoch 10. This gap suggests that the token-level



Figure 3. Validation-accuracy traces for the selected learned CLIP models. Stars mark the best validation epoch retained for checkpoint selection, and dashed lines mark the stop epoch under early stopping. The linear probe stopped after 27 epochs, while cross-attention stopped after 10.



Figure 4. Per-family accuracy on the final 684-example evaluation set. Count edits are the hardest family for the zero-shot Qwen baseline, while cross-attention remains strong across all edit types.

fusion model reaches a stable solution much earlier than the pooled-feature linear probe on this benchmark.

Model	Accuracy	Contradiction F1	Entailment F1
Raw CLIP	0.626	0.619	0.632
Linear Probe	0.896	0.897	0.895
Cross-Attention	0.965	0.965	0.965
Qwen2.5-VL	0.763	0.709	0.800

Table 1. Final comparison on the 684-example evaluation set. Accuracy is overall binary accuracy; Contradiction F1 and Entailment F1 are class-specific F1 scores. Higher is better.

Figure 4 breaks accuracy down by edit family. Cross-attention remains strongest across every family, while the linear probe loses more accuracy on attribute edits. Count contradictions are the clearest stress test because they require exact visual grounding rather than coarse semantic similarity. Figure 5 shows eight examples: four contradiction cases on the top row and four entailment synonym cases on the bottom row.

Error Analysis. The strongest separation appears on count contradictions. In Figure 4, each cell reports per-family accuracy for one model-family pair. The count row shows the widest spread: Cross-Attention reaches 0.980 accuracy, compared with 0.941 for the linear probe, 0.529 for raw CLIP, and only 0.186 for Qwen. Qwen's overall accuracy remains higher than raw CLIP because it is strong on entailment synonyms (0.950), but it often treats number edits as semantically compatible with the image, as Figure 5 illustrates. Attribute edits are the second clearest separator: Cross-Attention reaches 0.902 accuracy, while the linear probe drops to 0.686, Qwen to 0.627, and raw CLIP to 0.490.

Qwen also shows class bias: contradiction recall is 0.576, far below entailment recall of 0.950. Cross-attention remains balanced across classes, with 0.965 F1 for contradiction and 0.965 F1 for entailment.

6. Discussion

The main technical result is that structured contradiction detection benefits from supervised fusion over frozen CLIP features, not only larger zero-shot model scale. The benchmark is useful because it separates broad caption plausibility from precise grounding: Qwen's 0.763 accuracy looks competitive at first glance, but the per-family results show large failures on count edits and contradiction recall.

A second takeaway is that the performance gap between raw CLIP and the learned CLIP models points to decision calibration, not representation quality alone. Raw cosine similarity retains broad semantic alignment, yet the learned models show that contradiction detection benefits from training a classifier to attend to fine-grained mismatches.

The family-level split strengthens the comparison because models cannot rely on memorizing near-duplicate caption variants across train and test. The strong cross-attention result is therefore better read as controlled grounding evidence than as template matching.

The potential industry impact is in verification rather than generation. Captioning systems support search, accessibility, moderation, shopping catalogs, and media archives. A lightweight contradiction detector offers a second-stage check before a caption is shown to a user, stored as metadata, or used for retrieval. Count and attribute errors matter because small visual mistakes change user-facing meaning in product listings, safety reports, and automated alt-text workflows.

7. Limitations and Conclusion

This benchmark is built from synthetic single-phrase edits over a COCO subset, so it should be read as controlled evidence rather than a complete measure of multimodal reasoning. It inherits biases from COCO captions, COCO object annotations, and the pretrained models, and it does not test multi-edit or commonsense-heavy contradictions.



Figure 5. Qualitative model behavior on eight test examples. The top row shows contradiction edits and the bottom row shows entailment synonym edits. Each panel includes the image, source caption, edited caption, and paired model predictions.

Another limitation is that the benchmark focuses on English caption edits drawn from one source dataset, so the conclusions may not transfer directly to broader domains, multilingual settings, or naturally occurring human-written contradictions. The evaluation is also limited to one CLIP backbone and one zero-shot Qwen configuration.

Within that scope, the ranking is clear: learned CLIP-based fusion, especially cross-attention over frozen token states, is substantially more reliable than raw similarity thresholding and stronger than zero-shot Qwen2.5-VL on this benchmark.

AI Acknowledgment Statement. **Tool:** OpenAI Codex, GPT-5. **Prompts:** We used the tool for code cleanup, prose review, repository checks, LaTeX report editing, and submission-readiness checks. **Verification and Alignment:** We reviewed and revised all AI-supported output for accuracy, course alignment, and consistency with the project code, metrics, figures, and final claims. **Link:** No link available.

References

[1] Ravi Shekhar et al. FOIL it! Find one mismatch between image and language caption. *ACL*, 2017.
[2] Ning Xie et al. Visual entailment: A novel task for fine-grained image understanding. *arXiv:1901.06706*, 2019.
[3] Alane Suhr et al. A corpus for reasoning about natural language grounded in photographs. *ACL*, 2019.
[4] Tristan Thrush et al. Winoground: Probing vision and language models for visio-linguistic compositionality. *CVPR*, 2022.
[5] Mert Yuksekgonul et al. When and why vision-language models behave like bags-of-words, and what to do about it? *ICLR*, 2023.
[6] Letitia Parcalabescu et al. VALSE: A task-independent benchmark for vision and language models centered on linguistic phenomena. *ACL*, 2022.
[7] Cheng-Yu Hsieh et al. SugarCrepe: Fixing hackable benchmarks for vision-language compositionality. *arXiv:2306.14610*, 2023.
[8] Yifan Li et al. Evaluating object hallucination in large vision-language models. *EMNLP*, 2023.
[9] Alec Radford et al. Learning transferable visual models from natural language supervision. *arXiv:2103.00020*, 2021.
[10] Shuai Bai et al. Qwen2.5-VL technical report. *arXiv:2502.13923*, 2025.
[11] Tsung-Yi Lin et al. Microsoft COCO: Common objects in context. *ECCV*, 2014.