



Optocoupler, Phototransistor Output, Quad Channel, SOP-16, Half Pitch Mini-Flat Package



1179076



DESCRIPTION

The SFH6916 has a GaAs infrared emitter, which is optically coupled to a silicon planar phototransistor detector, and is incorporated in a 16 pin 50 mil lead pitch miniflat package. It features a high current transfer ratio, low coupling capacitance, and high isolation voltage. The coupling devices are designed for signal transmission between two electrically separated circuits.

FEATURES

- SOP (small outline package)
- Isolation test voltage, 3750 V_{RMS} (1.0 s)
- High collector emitter voltage, V_{CEO} = 70 V
- Low saturation voltage
- Fast switching times
- Temperature stable
- Low coupling capacitance
- End stackable, 0.050" (1.27 mm) spacing
- Lead (Pb)-free component
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC


RoHS
COMPLIANT

AGENCY APPROVALS

- UL1577, file no. E52744 system code U
- DIN EN 60747-5-5 available with option 1

ORDER INFORMATION

| PART | REMARKS |
|---------|-------------------------|
| SFH6916 | CTR 50 to 300 %, SOP-16 |

ABSOLUTE MAXIMUM RATINGS ⁽¹⁾

| PARAMETER | TEST CONDITION | SYMBOL | VALUE | UNIT |
|-------------------------------------------------------------|----------------------------------------------------|-------------------|--------------------|------------------|
| INPUT | | | | |
| Reverse voltage | | V _R | 6.0 | V |
| DC forward current | | I _F | 50 | mA |
| Surge forward current | t _p ≤ 10 μs | I _{FSM} | 2.5 | A |
| Total power dissipation | | P _{diss} | 80 | mW |
| OUTPUT | | | | |
| Collector emitter voltage | | V _{CE} | 70 | V |
| Emitter collector voltage | | V _{EC} | 7.0 | V |
| Collector current | | I _C | 50 | mA |
| | t _p = 1.0 ms | I _C | 100 | mA |
| Total power dissipation per channel | | P _{diss} | 150 | mW |
| COUPLER | | | | |
| Isolation test voltage between emitter and detector (1.0 s) | | V _{ISO} | 3750 | V _{RMS} |
| Isolation resistance | V _{IO} = 500 V, T _{amb} = 25 °C | R _{IO} | ≥ 10 ¹² | Ω |
| | V _{IO} = 500 V, T _{amb} = 100 °C | R _{IO} | ≥ 10 ¹¹ | Ω |
| Storage temperature range | | T _{stg} | - 55 to + 125 | °C |

ABSOLUTE MAXIMUM RATINGS (1)

| PARAMETER | TEST CONDITION | SYMBOL | VALUE | UNIT |
|---------------------------|--------------------------------------------------------------------|-----------|--------------|------|
| COUPLER | | | | |
| Ambient temperature range | | T_{amb} | - 55 to +100 | °C |
| Junction temperature | | T_j | 100 | °C |
| Soldering temperature (2) | max. 10 s dip soldering distance to seating plane ≥ 1.5 mm | | 260 | °C |
| Total power dissipation | | P_{tot} | 700 | mW |

Notes(1) $T_{amb} = 25$ °C, unless otherwise specified.

Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute maximum ratings for extended periods of the time can adversely affect reliability.

(2) Refer to reflow profile for soldering conditions for surface mounted devices.

ELECTRICAL CHARACTERISTICS (1)

| PARAMETER | TEST CONDITION | SYMBOL | MIN. | TYP. | MAX. | UNIT |
|--------------------------------------|---------------------------------|-------------|------|------|------|------|
| INPUT (2) | | | | | | |
| Forward voltage | $I_F = 5$ mA | V_F | | 1.15 | 1.4 | V |
| Reverse current | $V_R = 6.0$ V | I_R | | 0.01 | 10 | μA |
| Capacitance | C_O | C_O | | 14 | | pF |
| Thermal resistance | | R_{thja} | | 1000 | | K/W |
| OUTPUT | | | | | | |
| Collector emitter leakage current | $V_{CE} = 20$ V | I_{CEO} | | | 100 | nA |
| Collector emitter capacitance | $V_{CE} = 5.0$ V, $f = 1.0$ MHz | C_{CE} | | 2.8 | | pF |
| Thermal resistance | | R_{thja} | | 500 | | K/W |
| COUPLER | | | | | | |
| Collector emitter saturation voltage | $I_F = 20$ mA, $I_C = 1.0$ mA | V_{CEsat} | | 0.1 | 0.4 | V |
| Coupling capacitance | $f = 1.0$ MHz | C_C | | 1.0 | | pF |

Notes(1) $T_{amb} = 25$ °C, unless otherwise specified.


Minimum and maximum values are testing requirements. Typical values are characteristics of the device and are the result of engineering evaluation. Typical values are for information only and are not part of the testing requirements.

(2) $T_{amb} = 25$ °C (except where noted).**CURRENT TRANSFER RATIO**

| PARAMETER | TEST CONDITION | SYMBOL | MIN. | TYP. | MAX. | UNIT |
|------------------------|----------------------------------|--------|------|------|------|------|
| Current transfer ratio | $I_F = 5.0$ mA, $V_{CC} = 5.0$ V | CTR | 50 | | 300 | % |


SWITCHING CHARACTERISTICS

| PARAMETER | TEST CONDITION | SYMBOL | MIN. | TYP. | MAX. | UNIT |
|----------------------|---------------------------------------------------|-----------|------|------|------|------|
| NON-SATURATED | | | | | | |
| Rise time | $I_C = 2.0$ mA, $V_{CC} = 10$ V, $R_L = 100$ Ω | t_r | | 4.0 | | μs |
| Fall time | $I_C = 2.0$ mA, $V_{CC} = 10$ V, $R_L = 100$ Ω | t_f | | 3.0 | | μs |
| Turn-on time | $I_C = 2.0$ mA, $V_{CC} = 10$ V, $R_L = 100$ Ω | t_{on} | | 5.0 | | μs |
| Turn-off time | $I_C = 2.0$ mA, $V_{CC} = 10$ V, $R_L = 100$ Ω | t_{off} | | 4.0 | | μs |
| SATURATED | | | | | | |
| Rise time | $I_F = 16.0$ mA, $V_{CC} = 5.0$ V, $R_L = 1.9$ kΩ | t_r | | 15 | | μs |
| Fall time | $I_F = 16.0$ mA, $V_{CC} = 5.0$ V, $R_L = 1.9$ kΩ | t_f | | 0.5 | | μs |
| Turn-on time | $I_F = 16.0$ mA, $V_{CC} = 5.0$ V, $R_L = 1.9$ kΩ | t_{on} | | 1.0 | | μs |
| Turn-off time | $I_F = 16.0$ mA, $V_{CC} = 5.0$ V, $R_L = 1.9$ kΩ | t_{off} | | 30 | | μs |



isfh6916_01

Fig. 1 - Switching Operation (Without Saturation)



isfh6916_02

Fig. 2 - Switching Operation (With Saturation)

SAFETY AND INSULATION RATINGS


| PARAMETER | TEST CONDITION | SYMBOL | MIN. | TYP. | MAX. | UNIT |
|---------------------------------------------------------|----------------|------------|------|-----------|------|------|
| Climatic classification (according to IEC 68 part 1) | | | | 55/100/21 | | |
| Comparative tracking index | | CTI | 175 | | 399 | |
| Peak transient overvoltage | | V_{IOTM} | 6000 | | | V |
| Peak insulation voltage | | V_{IORM} | 707 | | | V |
| Safety rating - power output | | P_{SO} | | | 350 | mW |
| Safety rating - input current | | I_{SI} | | | 150 | mA |
| Safety rating - temperature | | T_{SI} | | | 175 | °C |
| Creepage distance | | | 5 | | | mm |
| Clearance distance | | | 5 | | | mm |

Note

As per IEC 60747-5-2, § 7.4.3.8.1, this optocoupler is suitable for "safe electrical insulation" only within the safety ratings. Compliance with the safety ratings shall be ensured by means of protective circuits.


TYPICAL CHARACTERISTICS

$T_{amb} = 25\text{ °C}$, unless otherwise specified




isfh6916_03

Fig. 3 - Diode Forward Voltage vs. Forward Current




isfh6916_04

Fig. 4 - Collector Current vs. Collector Emitter Voltage




isfh6916_05

Fig. 5 - Collector to Emitter Dark Current vs. Ambient Temperature




isfh6916_09

Fig. 8 - Current Transfer Ratio vs. Forward Current




isfh6916_06

Fig. 6 - Collector Current vs. Collector Emitter Saturation Voltage




isfh6916_10

Fig. 9 - Switching Time vs. Load Resistance



isfh6916_07

Fig. 7 - Normalized Output Current vs. Ambient Temperature



isfh6916_11

Fig. 10 - Switching Time vs. Load Resistance





Fig. 11 - Switching Time Measurement

PACKAGE DIMENSIONS in inches (millimeters)



**OZONE DEPLETING SUBSTANCES POLICY STATEMENT**

It is the policy of Vishay Semiconductor GmbH to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively.
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA.
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

We reserve the right to make changes to improve technical design
and may do so without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.