

Basic monitoring

ONTAP System Manager

Lenida Vorwerk December 04, 2020

This PDF was generated from https://docs.netapp.com/us-en/ontap/smbc/smbc_admin_monitoring.html on December 18, 2020. Always check docs.netapp.com for the latest.

Table of Contents

Basic monitoring.															1
Dasic monitoring.	 														

Basic monitoring

There are several SM-BC components and operations you can monitor.

ONTAP mediator

During normal operation, the Mediator state should be connected. If it is in any other state, this might indicate an error condition. You can review the Event Management System (EMS) messages to determine the error and appropriate corrective actions.

EMS Name	Description
sm.mediator.added	Mediator is added successfully
sm.mediator.removed	Mediator is removed successfully
sm.mediator.unusable	Mediator is unusable due to a corrupted Mediator server
sm.mediator.misconfigured	Mediator is repurposed or the Mediator package is no longer installed on the Mediator server
sm.mediator.unreachable	Mediator is unreachable
sm.mediator.removed.force	Mediator is removed from the cluster using the "force" option
sm.mediator.cacert.expiring	Mediator certificate authority (CA) certificate is due to expire in 30 days or less
sm.mediator.serverc.expiring	Mediator server certificate is due to expire in 30 days or less
sm.mediator.clientc.expiring	Mediator client certificate is due to expire in 30 days or less
sm.mediator.cacert.expired	Mediator certificate authority (CA) certificate has expired
sm.mediator.serverc.expired	Mediator server certificate has expired
sm.mediator.clientc.expired	Mediator client certificate has expired
sm.mediator.in.quorum	All the SM-BC records are resynchronized with Mediator

Planned failover operations

You can monitor status and progress of a planned failover operation using the snapmirror failover show command. For example:

```
ClusterB::> snapmirror failover start -destination-path vs1:/cg/dcg1
```

Once the failover operation is complete, you can monitor the Synchronous SnapMirror protection status from the new destination cluster. For example:

```
ClusterA::> snapmirror show
```

You can also review the following messages to determine if there is an error and take the appropriate corrective actions.

EMS Name	Description							
smbc.pfo.failed	SMBC planned failover operation failed. Destination path:							
smbc.pfo.start. Destination path:	SMBC planned failover operation started							

Automatic unplanned failover operations

During an unplanned automatic failover, you can monitor the status of the operation using the snapmirror
failover show command. For example:

```
ClusterB::> snapmirror failover show -instance
Start Time: 9/23/2020 22:03:29

Source Path: vs1:/cg/scg3

Destination Path: vs3:/cg/dcg3

Failover Status: completed

Error Reason:

End Time: 9/23/2020 22:03:30

Primary Data Cluster: cluster-2

Last Progress Update: -

Failover Type: unplanned

Error Reason codes: -
```

You can also review the following messages to determine if there is an error and take the appropriate corrective actions.

EMS Name	Description							
smbc.aufo.failed	SnapMirror automatic planned failover operation failed. Destination path:							
smbc.aufo.start. Destination path:	SMBC planned failover operation started							
smbc.aufo.completed:	SnapMirror automatic planned failover operation completed. Destination path:							
smbc.aufo.failover.incapable	block.giveback.during.aufo							

SM-BC availability

You can check the availability of the SM-BC relationship using a series of commands, either on the primary cluster, the secondary cluster, or both.

Commands you use include the snapmirror mediator show command on both the primary and secondary

cluster to check the connection and quorum status, the snapmirror show command, and the volume show command. For example:

```
SMBC A::*> snapmirror mediator show
Mediator Address Peer Cluster Connection Status Quorum Status
------ -----
10.236.172.86 SMBC B
                      connected
                                  true
SMBC B::*> snapmirror mediator show
Mediator Address Peer Cluster Connection Status Quorum Status
10.236.172.86 SMBC_A connected true
SMBC B::*> snapmirror show -expand
Progress
     Destination Mirror Relationship Total
Source
Last
Path Type Path State Status Progress Healthy
Updated
vs0:/cg/cg1 XDP vs1:/cg/cg1_dp Snapmirrored InSync -
                                         true -
vs0:vol1 XDP vs1:vol1 dp Snapmirrored InSync - true -
2 entries were displayed.
SMBC_A::*> volume show -fields is-smbc-master,smbc-consensus,is-smbc-
failover-capable -volume vol1
vserver volume is-smbc-master is-smbc-failover-capable smbc-consensus
vs0 vol1 true false
                                     Consensus
SMBC B::*> volume show -fields is-smbc-master, smbc-consensus, is-smbc-
failover-capable -volume vol1 dp
vserver volume is-smbc-master is-smbc-failover-capable smbc-consensus
_____
vs1 vol1 dp false
                    true
                                     No-consensus
```

Copyright Information

Copyright © 2020 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.