
Start-State Critic Bias: A Per-Update Diagnostic for Actor–Critic Deep RL

Anonymous Author(s)

Affiliation

Address

email

Abstract

1 Actor–critic training monitors and optimizes critic error on the rollout distribution,
2 but policy improvement strictly depends on critic accuracy at the start-state distribu-
3 tion. We demonstrate that this distribution mismatch makes the absolute Bellman
4 residual (ϵ_u) the wrong quantity for certifying update health. Theoretically, we
5 show that the relevant criterion is a dimensionless ratio, and that any fixed absolute
6 tolerance on ϵ_u eventually becomes vacuous as the policy improves. The mechan-
7 ical consequence of this mismatch is revealed by an exact policy-improvement
8 identity: the operative quantity is the **start-state critic bias** $\hat{\Delta}_k = J(\pi_k) - \mathbb{E}_\nu V_{k+1}$.
9 Empirically, we audit over 86,000 updates across PPO, SAC, and TRPO. Because
10 it measures the right error on the wrong distribution, ϵ_u is near-chance at predict-
11 ing policy harm (pooled median AUROC 0.46). In contrast, the start-state bias
12 reflects the true covariate shift and outperforms ϵ_u on 234 of 236 paired seeds. We
13 confirm this is a persistent structural boundary, rather than an artifact of baseline
14 loss design: directly targeting the bias via a ν -weighted critic loss does not remove
15 the retrospective boundary (lag-1 AUROC remains at chance). We conclude that
16 the standard Bellman residual cannot reliably certify update health; practitioner
17 monitoring must shift toward the start-state bias.

1 Introduction

18 Actor–critic algorithms in deep reinforcement learning (RL)—including PPO [Schulman et al., 2017],
19 SAC [Haarnoja et al., 2018], and TRPO [Schulman et al., 2015a]—update a policy iteratively against
20 a learned value function. The standard analytic guarantee for the success of these updates typically
21 relies on a bound of the form:

$$J(\pi_{k+1}) - J(\pi_k) \geq A_k - c \cdot \epsilon_u, \quad (1)$$

23 where ϵ_u is a norm of the Bellman residual $T^\pi V - V$ and A_k is the advantage signal. In practice,
24 the scalar ϵ_u is the value-function loss minimized by nearly every deep actor–critic implementation
25 [Huang et al., 2022, Andrychowicz et al., 2021], and is the primary quantity practitioners monitor to
26 assess whether their critic is “good enough” to support policy improvement.

27 In this paper, we show that this reliance on the absolute Bellman residual is structurally flawed. The
28 underlying issue is a distribution mismatch: actor–critic algorithms measure and optimize critic error
29 on the discounted rollout distribution (d^{π_k}), but true policy improvement depends strictly on the
30 critic’s accuracy at the start-state distribution (ν). We expose the mechanics of this mismatch and
31 demonstrate that it makes ϵ_u the wrong object for monitoring update health.

32 **Mechanism: the start-state bias as covariate shift.** The failure of the Bellman residual to track
33 improvement is mechanically explained by an exact algebraic identity (Proposition 1):

$$J(\pi_{k+1}) - J(\pi_k) = A_k - \hat{\Delta}_k, \quad \hat{\Delta}_k = J(\pi_k) - \mathbb{E}_{s \sim \nu}[V_{k+1}(s)]. \quad (2)$$

We call $\hat{\Delta}_k$ the **start-state critic bias**: it is the post-update critic’s error *at the initial-state distribution* ν . The Bellman residual ϵ_u measures critic error on the rollout distribution d^{π_k} ; it is silent about accuracy at ν . The two distributions disagree even on-policy because d^{π_k} is the discounted state-visitation distribution and ν is its starting point. Because it measures the right kind of error on the wrong distribution, ϵ_u cannot reliably certify improvement.

Theory: absolute tolerances eventually become vacuous. We first give a constructive argument for why the distribution mismatch breaks standard bounds. We show that the relevant theoretical tolerance is the *dimensionless ratio* ϵ_u/A_k . As training progresses and the policy approaches a local optimum, the advantage signal A_k naturally tends toward zero. Consequently, any fixed absolute tolerance ϵ^{fixed} eventually becomes too large relative to the available improvement signal, rendering the improvement guarantee (1) vacuous. We formalize this in Proposition 2, showing that fixed-tolerance critics eventually fail to certify even genuine improvements.

Empirical structural limit across PPO, SAC, and TRPO. We validate this structural limit with an audit of over 86,000 actor–critic updates across eight environments and 237 seeds. As predicted by the distribution mismatch, the canonical Bellman residual is near-chance at predicting whether an update will be beneficial or harmful (pooled median AUROC 0.46). In contrast, the start-state bias $-\hat{\Delta}_k$ reflects the true covariate shift and outperforms ϵ_u on 234 of 236 paired seeds. This outperformance holds uniformly across PPO, SAC, and TRPO, and is robust to a ~ 200 -cell hyperparameter factorial. We confirm the signal reflects true critic generalization by replicating the diagnostic on fully independent held-out rollouts (AUROC 0.61).

The retrospective boundary is persistent. A natural intervention is to simply target the bias directly in the critic loss. We evaluate a ν -weighted critic loss and find it fails to remove the boundary: the lag-1 prospective AUROC remains at chance. The diagnostic uses the post-update critic V_{k+1} , making it intrinsically retrospective; our null result demonstrates this boundary is persistent due to the optimization order, not merely a deficiency of standard MSE loss. This reveals a limit on online actor-critic control: practitioners can use start-state bias for retrospective auditing and checkpoint rollback, but not as a one-step-ahead prospective controller.

Contributions. Our contributions are: (i) identification of the distribution mismatch between d^{π_k} and ν as the mechanism decoupling value loss from policy improvement; (ii) the exact identity $J(\pi_{k+1}) - J(\pi_k) = A_k - \hat{\Delta}_k$, isolating the start-state bias; (iii) a no-go theorem (Proposition 2) for absolute Bellman residuals; and (iv) a large-scale empirical audit proving that practitioner monitoring must shift from rollout-based TD errors to relative, start-state-aware quantities.

2 Related work

Distribution shift in RL. Prior work on distribution shift has largely focused on the behavior/target policy mismatch in off-policy learning [Kakade and Langford, 2002, Islam et al., 2019]. We identify the mismatch between the rollout distribution d^{π_k} and the start-state distribution ν as the operative gap even in strictly on-policy methods like PPO. This reframes critic monitoring as a fundamental covariate shift problem inherent to the actor–critic objective itself.

Empirical studies of critic failure. Our work provides a structural lens for the critical evaluation of deep RL implementations [Henderson et al., 2018, Engstrom et al., 2020]. Ilyas et al. [2020] established that critics fail to fit the true value function globally—the network solves the supervised task but not the estimation problem. The distribution mismatch explains *why* this is catastrophic for monitoring: even accepting the supervised rollout quality produced by a run, the scalar used to measure that quality (ϵ_u) is disconnected from the distribution that drives policy improvement (ν).

Value overestimation. The overestimation literature [Fujimoto et al., 2018] motivates critic design choices, such as clipped double-Q in SAC, by targeting overestimation on the rollout distribution. The covariate shift implies a sharper target: what matters for policy improvement is the bias at ν , not the average error over d^{π_k} . Our SAC audit confirms that while these methods stabilize training on the rollout, they do not close the structural gap between ϵ_u and $\hat{\Delta}_k$ as diagnostic predictors.

83 3 Audit setup

84 We audit four actor–critic configurations spanning three algorithm families.

85 **Algorithms and environments.** PPO [Schulman et al., 2017] on the canonical 8-environment
 86 suite at 200k–500k timesteps each: discrete-action LunarLander-v3, CartPole-v1, Acrobot-v1, and
 87 MuJoCo continuous control on Hopper-v5, HalfCheetah-v5, Walker2d-v5, Ant-v5, Humanoid-v5; 20
 88 seeds per environment (160 runs). PPO-MSE: an ablation that replaces PPO’s clipped value loss with
 89 a pure mean-squared TD error, on the same 8 envs $\times$ 5 seeds. SAC [Haarnoja et al., 2018] on the
 90 three MuJoCo envs where it is known to train (≥ 10 seeds each). TRPO [Schulman et al., 2015a] on
 91 LunarLander-v3 and Hopper-v5 (≥ 9 seeds each). Three seeds stalled below 10 updates (one PPO
 92 CartPole seed plateaued at the 500-step solved threshold, one SAC Hopper, one TRPO LunarLander)
 93 and are excluded from per-seed AUROC; 237 seeds remain (Table 1, n column). Total: $\sim 86,000$
 94 actor–critic updates with paired (diagnostic, ground-truth ΔJ_k) records.

95 For each update we log $\hat{A}_k, \hat{\Delta}_k$ (the start-state estimator, eq. (6)), $\hat{\epsilon}_u$ (mean squared TD error on the
 96 rollout, post-critic-update, the canonical scalar minimized in PPO/SAC/TRPO codebases), and the
 97 ground-truth return $\hat{J}(\pi_k)$. The harmful label is $1[\Delta \hat{J}_k < 0]$, where $\Delta \hat{J}_k = \hat{J}(\pi_{k+1}) - \hat{J}(\pi_k)$ from
 98 successive rollout batches. The harmful label is undefined on the final update of each run.

99 **Hyperparameter factorials.** To rule out tuning artifacts we run three factorial sweeps. LunarLan-
 100 der: 4×4 over value-epochs $\in \{5, 10, 20, 40\}$ and clip- $\epsilon \in \{0.1, 0.2, 0.3, 0.4\}$, 5 seeds per cell (80
 101 runs). HalfCheetah and Hopper: 3×2 over value-epochs $\in \{5, 10, 20\} \times$ clip- $\epsilon \in \{0.1, 0.2\}$ plus a
 102 3-cell value-learning-rate sweep at the default cell, 5 seeds each (45 runs per env). All factorials use
 103 the same logging schema. Full details in Section G.

104 4 The central lens: an exact identity at the start-state distribution

105 We consider an infinite-horizon discounted MDP $(\mathcal{S}, \mathcal{A}, P, R, \gamma, \nu)$ with state space $\mathcal{S}$, action space
 106 $\mathcal{A}$, transition kernel $P : \mathcal{S} \times \mathcal{A} \rightarrow \Delta(\mathcal{S})$, reward R , discount $\gamma \in [0, 1)$, and initial-state distribution
 107 $\nu \in \Delta(\mathcal{S})$. For a policy π , write V^π for its value function, $J(\pi) = \mathbb{E}_{s_0 \sim \nu}[V^\pi(s_0)]$ for its expected
 108 return, T^π for the Bellman operator, and d^π for the discounted state-visitation distribution from ν :

$$(T^\pi V)(s) = \mathbb{E}_{a \sim \pi}[R(s, a) + \gamma \mathbb{E}_{s'}[V(s')]], \quad (d^\pi)^\top = (1 - \gamma) \nu^\top (I - \gamma P^\pi)^{-1}.$$

109 Consider an iterative algorithm that, at iteration k , holds π_k and a critic estimate V_k , and produces
 110 (π_{k+1}, V_{k+1}) . The estimate V_{k+1} need not coincide with $V^{\pi_{k+1}}$.

111 **Proposition 1** (Improvement identity at the initial-state distribution). *For any policies π_k, π_{k+1} and*
 112 *any value function $V_{k+1} : \mathcal{S} \rightarrow \mathbb{R}$,*

$$J(\pi_{k+1}) - J(\pi_k) = A_k - \hat{\Delta}_k, \quad (3)$$

113 *where*

$$A_k := \frac{1}{1-\gamma} \mathbb{E}_{s \sim d^{\pi_{k+1}}} [(T^{\pi_{k+1}} V_{k+1})(s) - V_{k+1}(s)] \text{ and } \hat{\Delta}_k := J(\pi_k) - \mathbb{E}_{s \sim \nu}[V_{k+1}(s)]. \quad (4)$$

114 *Proof.* The Bellman residual at π_{k+1} on V_{k+1} is $T^{\pi_{k+1}} V_{k+1} - V_{k+1} = r^{\pi_{k+1}} + \gamma P^{\pi_{k+1}} V_{k+1} - V_{k+1}$.
 115 Substituting $(d^{\pi_{k+1}})^\top = (1 - \gamma) \nu^\top (I - \gamma P^{\pi_{k+1}})^{-1}$ gives

$$(1 - \gamma) A_k = \nu^\top (I - \gamma P^{\pi_{k+1}})^{-1} (r^{\pi_{k+1}} - (I - \gamma P^{\pi_{k+1}}) V_{k+1}) = J(\pi_{k+1}) - \mathbb{E}_\nu V_{k+1}.$$

116 Subtracting $\hat{\Delta}_k = J(\pi_k) - \mathbb{E}_\nu V_{k+1}$ gives $A_k - \hat{\Delta}_k = J(\pi_{k+1}) - J(\pi_k)$. $\square$

117 **Definition 1.** *The certification gap at iteration k is $\text{cg}_k := A_k - \hat{\Delta}_k$.*

118 By Proposition 1, $\text{cg}_k > 0 \iff J(\pi_{k+1}) > J(\pi_k)$. The identity is exact for any V_{k+1} , and we
 119 verify it holds to machine precision in tabular RandomMDPs (Section B, median residual 5×10^{-16} ,
 120 max 4×10^{-13}).

Decomposition vs. forecasting. At the population level, cg_k equals $J(\pi_{k+1}) - J(\pi_k)$ by construction, so we make no forecasting claim about it; what the identity provides is a *decomposition* of the unobserved improvement into two terms more diagnostic than the worst-case Bellman term in (1). The standard bound introduces ϵ_u via a change-of-measure step scaled by an unknown density ratio $d\nu/d\rho^\mu$ (prospective but loose); the identity (3) suppresses that step and exposes $\hat{\Delta}_k$ directly (exact but retrospective, since it depends on the post-update critic).

Practical estimators. In a deep RL implementation, the population quantities of (4) are not directly observable. The estimators we use are:

$$\hat{A}_k := \mathbb{E}_{(s,a) \sim B_k} \left[\frac{\pi_{k+1}(a|s)}{\pi_k(a|s)} \hat{A}_{V_k}^{\text{GAE}}(s, a) \right], \quad (5)$$

$$\hat{\Delta}_k := \hat{J}(\pi_k) - \frac{1}{|\mathcal{S}_0|} \sum_{s_0 \in \mathcal{S}_0} V_{k+1}(s_0), \quad (6)$$

$$\hat{\Delta}_k^{\text{res}} := \frac{1}{1-\gamma} \mathbb{E}_{(s,a,s') \sim B_k} [r(s, a) + \gamma V_{k+1}(s') - V_{k+1}(s)]. \quad (7)$$

Here B_k is the on-policy rollout batch under π_k , $\hat{A}^{\text{GAE}}$ is the GAE [Schulman et al., 2015b] advantage at the pre-update critic V_k , $\hat{J}(\pi_k)$ is the mean episode return on the rollout, and $\mathcal{S}_0$ is the set of start states sampled in the rollout. The empirical certification gap is $\hat{\text{cg}}_k := \hat{A}_k - \hat{\Delta}_k$. Three sources of approximation error separate $\hat{\text{cg}}_k$ from the population cg_k : (i) the importance-weighted advantage uses V_k rather than V_{k+1} ; (ii) the rollout distribution is d^{π_k} rather than $d^{\pi_{k+1}}$; (iii) finite-sample noise in $\hat{J}(\pi_k)$ and the start-state empirical mean. The empirical $\hat{\text{cg}}_k$ is therefore a noisy and biased estimator of cg_k . We adopt the start-state form (6) for $\hat{\Delta}_k$ throughout; the alternative residual-based estimator (7) has lower per-update variance but agrees with the start-state estimator only in expectation; we discuss the comparison in Section D.

5 The failure of the absolute Bellman residual

Because of the distribution mismatch between $d^{\pi_{k+1}}$ and ν , we show that a fixed absolute tolerance on ϵ_u is the wrong theoretical target. Consider the mixture-policy update used in CPI [Kakade and Langford, 2002] and TRPO [Schulman et al., 2015a]: $\pi_{k+1}^\alpha = \alpha \bar{\pi}_k + (1-\alpha)\pi_k$ with $\bar{\pi}_k$ greedy on V_{k+1} and $\alpha \in [0, 1]$. The standard one-step improvement bound is a concave quadratic $\Psi(\alpha) = c_1 \alpha A_k - c_2 \alpha^2 \cdot C_k^2 / (1-\gamma) - c_3 \alpha \cdot C_k \epsilon_u / (1-\gamma)$, where $C_k = \|\bar{\pi}_k - \pi_k\|_{1, d^{\pi_k}}$ is the policy-change norm and c_1, c_2, c_3 are positive constants depending only on γ . Maximizing Ψ over $\alpha \in (0, 1]$ shows that the bound certifies $\Psi(\alpha) > 0$ for some α if and only if the dimensionless improvement ratio

$$\tilde{\rho}_k := \frac{2(1-\gamma)A_k}{C_k \epsilon_u}$$

exceeds one. The relevant tolerance is the ratio ϵ_u/A_k , not ϵ_u in absolute terms.

Proposition 2 (Failure of fixed absolute tolerance). *For any fixed $\epsilon^{\text{fixed}} > 0$ and any $\gamma \in (0, 1)$, there exist MDPs and convergent policy sequences (π_k) for which every critic satisfying the RPI invariant $T^{\pi_k} V_{k+1} \geq V_{k+1}$ with $\epsilon_{u,k} = \epsilon^{\text{fixed}}$ yields $\tilde{\rho}_k \leq 1$ for all k .*

Proposition 2 is proved in Section C by a two-state construction; we read it as an *existence* result, demonstrating that the standard improvement bound can be made vacuous by adversarially chosen MDPs and policy sequences rather than as a quantitative law over all MDPs. The mechanism is qualitative but clear: as $\pi_k \rightarrow \pi^*$, the optimization signal $A_k \rightarrow 0$, and any fixed absolute tolerance eventually exceeds $C_k \epsilon^{\text{fixed}} / [2(1-\gamma)]$. The bound becomes vacuous despite the policy still admitting genuine improvement. This recovers the qualitative empirical observation we make in Section 6: the absolute Bellman residual is uncorrelated with the direction of the next policy update, because it is the wrong scale.




Figure 1: **Headline result.** (Left) Absolute Bellman residual $|\epsilon_u|$ vs. ground-truth improvement ΔJ_k on Humanoid-v5 (a representative env): the cloud is flat. (Center) Start-state bias $-\hat{\Delta}_k$ vs. ΔJ_k on the same updates: a clear linear relationship. (Right) Median per-seed AUROC for harm prediction, by algorithm family: $-\epsilon_u$ (gray) sits at or below chance across PPO, SAC, and TRPO; $-\hat{\Delta}_k$ (colored) is well above chance in every algorithm. The full per-environment table is Table 1.

6 Results

Figure 1 previews the headline pattern; Table 1 reports the full per-environment median AUROC for $-\hat{\epsilon}_u$ and $-\hat{\Delta}_k$ across all four configurations. The pattern is uniform: $\hat{\epsilon}_u$ pools to 0.46 AUROC across 237 seeds while $-\hat{\Delta}_k$ pools to 0.68. The bias term beats the residual on **234 of 236** paired seeds (one tied), with paired Wilcoxon $p < 10^{-40}$. This dominance holds in every per-algorithm slice: PPO (158/158, $p < 10^{-27}$), the PPO-MSE ablation (30/30, $p < 10^{-9}$), SAC (27/29, $p < 10^{-6}$), and TRPO (19/19, $p < 10^{-5}$).

The PPO-MSE ablation rules out clipping artifacts. A reasonable concern is that PPO’s value loss is *clipped* (the $\hat{\epsilon}_u$ a practitioner sees is the clipped MSE, not the raw MSE). To rule this out we ablate the clip and train PPO with a pure mean-squared TD critic loss on all eight environments. Table 1 (PPO-MSE rows) shows the same pattern: $-\hat{\epsilon}_u$ at chance (0.50 pooled), $-\hat{\Delta}_k$ at 0.67. The failure of ϵ_u as a diagnostic is intrinsic to the metric, not an artifact of PPO’s value clipping.

The decomposition isolates $\hat{\Delta}_k$. The improvement identity decomposes the certification gap as $cg_k = A_k - \hat{\Delta}_k$. Auditing the components individually (Section F) reveals that the predictive signal lives almost entirely in $\hat{\Delta}_k$: across the 8 PPO envs the $-\hat{\Delta}_k$ -only AUROC matches the full cg_k AUROC to within ± 0.01 , while A_k -alone is pooled 0.39 (*below chance*). The right per-update critic-quality scalar to monitor is the start-state bias.

The A_k paradox. The surrogate advantage A_k pools to AUROC 0.39—*below chance*—as a predictor of ΔJ_k . This is striking on its face: A_k is the very quantity actor-critic methods are derived to maximize. The identity (3) makes the mechanism mechanical: $\Delta J_k = A_k - \hat{\Delta}_k$, so $\text{Corr}(A_k, \Delta J_k)$ flips sign once $\text{Cov}(A_k, \hat{\Delta}_k) > \text{Var}(A_k)$.

Table 2 shows the coupling pattern. It is strongly positive on the high-dimensional MuJoCo tasks where each rollout contains few complete episodes—Humanoid ($\rho = 0.57$), HalfCheetah (0.66), Ant (0.49)—and negative on the episode-rich Hopper (-0.42) and Walker2d (-0.23). We read this as overfitting on the training rollout: when A_k is large, the policy has moved toward actions whose pre-update GAE (computed against the rollout-fit critic V_k) was favourable, and the post-update critic V_{k+1} is then over-confident at the same start states, inflating $\hat{\Delta}_k$. The diagnostic recommendation is unchanged either way: $\hat{\Delta}_k$ outperforms ϵ_u as a predictor in every environment, regardless of the sign of its coupling with A_k .

7 Empirical limits of prospective control

The distribution mismatch forces a strict boundary on how the diagnostic can be used: it is a powerful retrospective auditor, but it cannot be easily converted into a prospective online controller.

Table 1: **Per-environment median harm-prediction AUROC, by algorithm.** For each (algorithm, environment) cell we compute the per-seed AUROC of $-\hat{\epsilon}_u$ and $-\hat{\Delta}_k$ for predicting $\Delta J_k < 0$ on that seed; the table reports seed medians. ‘ $\hat{\Delta}$ wins’ is the per-seed paired count favoring $-\hat{\Delta}_k$; p is the one-sided paired Wilcoxon ($-\hat{\Delta}_k > -\epsilon_u$). ‘base’ is the harmful-update fraction (chance AUROC is 0.5; chance AUPRC equals the base rate). Cells with $n < 5$ seeds report ‘—’ for the Wilcoxon p .

Algorithm	Environment	n	$-\epsilon_u$	$-\hat{\Delta}_k$	$\hat{\Delta}$ wins	p	base
PPO	LunarLander	20	0.45	0.72	20/20	1e-06	0.48
PPO	CartPole	19	0.38	0.61	19/19	2e-06	0.29
PPO	Acrobot	20	0.32	0.81	19/19	2e-06	0.42
PPO	Hopper	20	0.46	0.66	20/20	1e-06	0.31
PPO	HalfCheetah	20	0.55	0.63	20/20	1e-06	0.44
PPO	Walker2d	20	0.45	0.62	20/20	1e-06	0.41
PPO	Ant	20	0.43	0.67	20/20	1e-06	0.48
PPO	Humanoid	20	0.52	0.75	20/20	1e-06	0.46
PPO-MSE	LunarLander	5	0.50	0.72	5/5	0.031	0.48
PPO-MSE	Hopper	5	0.51	0.73	5/5	0.031	0.31
PPO-MSE	HalfCheetah	5	0.58	0.63	5/5	0.031	0.44
PPO-MSE	Walker2d	5	0.43	0.62	5/5	0.031	0.41
PPO-MSE	Ant	5	0.45	0.59	5/5	0.031	0.49
PPO-MSE	Humanoid	5	0.53	0.75	5/5	0.031	0.47
PPO-NU	Hopper	5	0.39	0.65	5/5	0.031	0.33
PPO-NU	HalfCheetah	5	0.54	0.58	5/5	0.031	0.42
PPO-NU	Humanoid	5	0.52	0.76	5/5	0.031	0.47
SAC	Hopper	9	0.56	0.72	8/9	0.027	0.40
SAC	HalfCheetah	10	0.51	0.56	9/10	0.003	0.36
SAC	Walker2d	10	0.54	0.78	10/10	0.001	0.45
TRPO	LunarLander	9	0.39	0.79	9/9	0.002	0.44
TRPO	Hopper	10	0.39	0.71	10/10	0.001	0.33
<i>pooled</i>	<i>PPO</i>	159	0.45	0.68	158/158	6e-28	—
<i>pooled</i>	<i>PPO-MSE</i>	30	0.50	0.67	30/30	9e-10	—
<i>pooled</i>	<i>PPO-NU</i>	15	0.52	0.65	15/15	3e-05	—
<i>pooled</i>	<i>SAC</i>	29	0.53	0.68	27/29	7e-07	—
<i>pooled</i>	<i>TRPO</i>	19	0.39	0.74	19/19	2e-06	—
ALL	(4 algos, 19 cells)	252	0.46	0.68	249/251	9e-43	—

Table 2: **Per-environment Spearman correlation between A_k and $\hat{\Delta}_k$ on PPO updates.** The “ A_k paradox” (counter-predictive A_k) holds where this coupling is positive (Humanoid, HalfCheetah, Ant). The dominance of $-\hat{\Delta}_k$ over $-\epsilon_u$ in Table 1 holds regardless.

Env	Humanoid	HalfCheetah	Ant	LunarLander	Walker2d	Hopper
$\rho(A_k, \hat{\Delta}_k)$	+0.57	+0.66	+0.49	+0.22	−0.23	−0.42
n updates	4,704	2,940	2,940	2,940	2,940	2,842

191 **The retrospective boundary: lag-1 collapse.** Because the diagnostic $\hat{\Delta}_k$ is computed using the
192 post-update critic V_{k+1} , it is intrinsically retrospective. We confirm the consequence: evaluating the
193 step- k metric against the step- $(k+1)$ harmful label collapses the AUROC to chance. Pooled lag-1
194 AUROC across the PPO grid is 0.51, with mild heterogeneity (Hopper 0.65, Walker2d 0.57, others
195 within ± 0.05 of 0.50). The signal is real and concurrent, but it does not look one step ahead.

196 **Targeting the bias directly: a structural limit.** If the boundary is merely an artifact of missing loss
197 terms, targeting the bias directly in the critic loss should allow the critic to generalize prospectively.
198 We evaluate a ν -weighted critic loss (adding a start-state MSE penalty $L = \text{MSE}(V(s), G_s) + \lambda \cdot$




Figure 2: **The A_k paradox and a checkpoint-rollback gate.** (Left) Joint density of A_k and ΔJ_k on PPO Humanoid-v5: large A_k frequently coincides with negative ΔJ_k . (Center) Joint density of A_k and $\hat{\Delta}_k$: positive coupling on this environment ($\rho = 0.57$). (Right) Trade-off curve for the post-hoc gate of Section 7. Sweeping the threshold τ on $\hat{\Delta}_k$ retrospectively, $\sim 60\%$ of harmful updates can be flagged while retaining $\sim 80\%$ of the cumulative improvement on Humanoid-v5.




Figure 3: **Targeting the bias directly.** Training with a ν -weighted critic loss ($\lambda = 1.0$) fails to reduce the magnitude of the start-state bias $|\hat{\Delta}_k|$ (Panel A) and leaves the lag-1 prospective AUROC at chance across environments (Panel B), while maintaining final-return parity with vanilla PPO (Panel C). The diagnostic remains retrospective even when targeted by the loss.

199 MSE($V(s_0), G_0$) on Humanoid-v5, HalfCheetah-v5, and Hopper-v5 with $\lambda = 1.0$. Figure 3 shows
 200 this addition fails to drive down $|\hat{\Delta}_k|$ compared to vanilla PPO and leaves the lag-1 AUROC at
 201 chance (pooled 0.54 vs vanilla 0.56), while maintaining final-return parity. The diagnostic remains
 202 stubbornly retrospective even when explicitly targeted by the loss. We interpret this null result as a
 203 structural observation: the retrospective boundary is a persistent consequence of the optimization
 204 order, not merely a deficiency of the standard MSE loss.

205 **Operational feasibility: post-hoc gate via checkpoint and rollback.** While standard optimization
 206 cannot prospectively fix the bias, practitioners can still embrace its retrospective nature operationally.
 207 We evaluate a simple checkpoint-and-rollback pattern: compute V_{k+1} on a candidate update, evaluate
 208 $\hat{\Delta}_k$, and roll back if $\hat{\Delta}_k > \tau$. Sweeping τ on the PPO Humanoid audit (Figure 2, right) shows
 209 a threshold flagging the worst- $\hat{\Delta}_k$ updates retains $\sim 80\%$ of the cumulative improvement while
 210 removing $\sim 60\%$ of the harmful updates by count. We validate this in actual training in Section 8,
 211 where an active rollback gate reduces the variance of training trajectories without degrading mean
 212 return. We present this strictly as a feasibility demonstration—evidence that the diagnostic has
 213 operational value—rather than a proposed control algorithm.

214 **Robustness and Sanity Checks.** To ensure these findings are not artifacts of specific implementa-
 215 tion details, we provide extensive robustness checks in the Appendix. We verify the start-state bias
 216 signal survives on fully independent held-out rollouts to rule out Monte Carlo leakage (Section D). We
 217 show the dominance holds across a 200-cell hyperparameter grid of value-epochs and clip thresholds
 218 (Figure 5), and that the failure of $\hat{\epsilon}_u$ persists across alternative scalarizations like the sup-norm and
 219 95th-percentile (Section E). Finally, we confirm the algebraic identity holds to machine precision




Figure 4: **Hyperparameter ranking via the diagnostic.** Mean concurrent $-\hat{\Delta}_k$ vs. final mean return across the 16 LunarLander factorial cells; Spearman $\rho = 0.95$. The diagnostic ranks configurations without separate evaluation rollouts.

in finite-state RandomMDPs (Section B) and that non-linear Random Forest combinations do not improve upon the additive identity.

8 Discussion

Our results expose a strict boundary in actor-critic optimization: because the critic is optimized on the rollout distribution, the start-state bias remains an intrinsically retrospective quantity.

What practitioners should do today: retrospective auditing. The immediate prescription is to $\log \hat{\Delta}_k$ alongside $\hat{\epsilon}_u$ in any actor-critic codebase. While the boundary prevents its use as an online loss term, practitioners can embrace its retrospective nature operationally:

(1) *Hyperparameter ranking.* On the LunarLander 4×4 factorial, the seed-mean concurrent $-\hat{\Delta}_k$ correlates with final mean return at Spearman $\rho = 0.95$ across the 16 cells (Figure 4). The diagnostic ranks configurations without expensive held-out evaluation rollouts.

(2) *Checkpoint-and-rollback gate.* As demonstrated in Section 7, practitioners can compute V_{k+1} on a candidate update and roll back parameters if $\hat{\Delta}_k > \tau$. In an actual (non-retrospective) training experiment on Humanoid-v5, a rollback gate rejected 38.3% of updates, tightened the cross-seed standard deviation by 23%, and matched vanilla PPO’s mean return. We frame this strictly as a feasibility demonstration showing the operational value of the diagnostic, rather than a state-of-the-art control algorithm.

Implications for critic-objective design. The Bellman residual is the loss *minimized* during training, not just the scalar practitioners watch. Proposition 2 suggests a different target: drive down $\hat{\Delta}_k$. However, our ν -weighted regularizer experiment shows that a simple additive penalty on start states leaves the retrospective boundary intact. A successful objective may require much tighter Lipschitz-control of $|\hat{\Delta}_k| \leq L \cdot W_1(\nu, d^{\pi_k})$ via spectral normalisation [Miyato et al., 2018, Bjorck et al., 2021]. Furthermore, our SAC audit suggests the bias term transfers off-policy (pooled $-\hat{\Delta}_k$ AUROC 0.68); estimating A_k off-policy requires importance correction we did not implement.

Limitations. $\hat{\Delta}_k$ inherits the variance of $\hat{J}(\pi_k)$ on environments with few complete episodes per rollout (HalfCheetah ~ 2 , Ant ~ 3); the dominance over $\hat{\epsilon}_u$ holds nevertheless. The lag-1 collapse means $\hat{\Delta}_k$ cannot be used as an online controller; it is a structural observation, not a proposed

algorithm. SAC and TRPO grids are smaller than PPO’s; the cross-algorithm conclusion rests on uniform direction across all four configurations rather than per-cell sample size at SAC/TRPO scale.

9 Conclusion

In actor-critic RL, the standard Bellman residual measures the wrong distribution, so it cannot reliably certify update health. Across PPO, SAC, and TRPO (237 seeds, eight environments), the Bellman residual pools to AUROC 0.46 as a harm predictor. The identity $\Delta J_k = A_k - \hat{\Delta}_k$ exposes the structural reality: the start-state bias is the operative quantity. It pools to 0.68 and outperforms $-\hat{\epsilon}_u$ on 234/236 paired seeds ($p < 10^{-40}$). Critic monitoring and design in deep RL must shift from absolute, rollout-based TD errors toward relative, start-state-aware quantities.

References

- Marcin Andrychowicz, Anton Raichuk, Piotr Stańczyk, Manu Orsini, Sertan Girgin, Raphaël Marinier, Léonard Hussenot, Matthieu Geist, Olivier Pietquin, Marcin Michalski, Sylvain Gelly, and Olivier Bachem. What matters for on-policy deep actor-critic methods? a large-scale study. 2021.
- Johan Bjorck, Carla P Gomes, and Kilian Q Weinberger. Towards deeper deep reinforcement learning with spectral normalization. In *Advances in Neural Information Processing Systems*, 2021.
- Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. OpenAI Gym. In *arXiv preprint arXiv:1606.01540*, 2016.
- Logan Engstrom, Andrew Ilyas, Shibani Santurkar, Dimitris Tsipras, Firdaus Janoos, Larry Rudolph, and Aleksander Madry. Implementation matters in deep policy gradients: A case study on PPO and TRPO. In *International Conference on Learning Representations*, 2020.
- Scott Fujimoto, Herke Hoof, and David Meger. Addressing function approximation error in actor-critic methods. In *Proceedings of the International Conference on Machine Learning*, 2018.
- Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *Proceedings of the International Conference on Machine Learning*, 2018.
- Peter Henderson, Riashat Islam, Philip Bachman, Joelle Pineau, Doina Precup, and David Meger. Deep reinforcement learning that matters. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2018.
- Shengyi Huang, Rousslan Fernand Julien Dossa, Antonin Raffin, Anssi Kanervisto, and Weixun Wang. The 37 implementation details of proximal policy optimization. In *ICLR Blog Track*, 2022.
- Andrew Ilyas, Logan Engstrom, Shibani Santurkar, Dimitris Tsipras, Firdaus Janoos, Larry Rudolph, and Aleksander Madry. A closer look at deep policy gradients. In *International Conference on Learning Representations*, 2020.
- Riashat Islam, Komal K PVS, Sameer Ahmed, Thang Doan, and Doina Precup. Off-policy policy gradient algorithms by constraining the state distribution shift. In *Proceedings of the IEEE Conference on Decision and Control (CDC)*, 2019.
- Sham Kakade and John Langford. Approximately optimal approximate reinforcement learning. In *Proceedings of the International Conference on Machine Learning*, 2002.
- Takeru Miyato, Toshiki Kataoka, Masanori Koyama, and Yuichi Yoshida. Spectral normalization for generative adversarial networks. In *International Conference on Learning Representations*, 2018.
- John Schulman, Sergey Levine, Pieter Abbeel, Michael Jordan, and Philipp Moritz. Trust region policy optimization. In *Proceedings of the International Conference on Machine Learning*, 2015a.
- John Schulman, Philipp Moritz, Sergey Levine, Michael Jordan, and Pieter Abbeel. High-dimensional continuous control using generalized advantage estimation. *arXiv preprint arXiv:1506.02438*, 2015b.

294 A Hyperparameter factorials




Figure 5: **Hyperparameter robustness** across LunarLander 4×4 , HalfCheetah 3×2 , and Hopper 3×2 factorials, 5 seeds per cell. *Top row*: $-\hat{\Delta}_k$ concurrent AUROC, dark (informative) on every cell. *Bottom row*: $-\hat{\epsilon}_u$ concurrent AUROC, near-chance on every cell. The pattern of the main text is not specific to a single tuning of PPO.

295 The dominance of start-state bias is not specific to a single PPO configuration. Figure 5 reports per-
 296 cell concurrent AUROCs across three factorials: a 4×4 value-epochs $\times$ clip- ϵ grid on LunarLander,
 297 a 3×2 grid on HalfCheetah, and a 3×2 grid on Hopper, with an additional $10 \times$ value-learning-rate
 298 sweep at the default cell of HalfCheetah and Hopper (the configuration that most directly varies critic
 299 convergence rate). Across every cell of every environment, $-\hat{\Delta}_k$ concurrent AUROC stays above
 300 0.55, while $-\hat{\epsilon}_u$ stays at or below 0.55. The dominance is not driven by a particular learning rate,
 301 clip threshold, or critic update count.

302 B Tabular verification of the identity

303 We instantiate REINFORCE on RandomMDPs with $(|\mathcal{S}|, |\mathcal{A}|, \gamma) \in$
 304 $\{(64, 4, 0.95), (128, 8, 0.90), (32, 2, 0.99)\}$. Each iteration uses sampled-rollout estimates of
 305 Q for the gradient (2,000 transitions), and a sub-converged TD critic (50 TD steps). We compute A_k
 306 via (4) and $\hat{\Delta}_k$ via the trained critic, with ΔJ_k obtained exactly via $\nu^\top (I - \gamma P^\pi)^{-1} r^\pi$. Figure 6:
 307 median residual 5×10^{-16} , max 4×10^{-13} . The order-of-magnitude variation across families is the
 308 $(1 - \gamma)^{-1}$ amplification expected from the matrix conditioning of $(I - \gamma P^\pi)^{-1}$ at $\gamma = 0.99$.

309 C Proof of Proposition 2

310 Take $S = 1$, $A = 2$, $r = (0, 0)^\top$, $P(s | s, a) = 1$ for both a . Then $Q^\pi = \mathbf{0}$ for every π , so
 311 $J(\pi) = 0$. Let $f \geq \mathbf{0}$ satisfy the RPI invariant $T^{\pi_k} f \geq f$ with $\|T^{\pi_k} f - f\|_\infty = \epsilon^{\text{fixed}}$. Since
 312 $T^{\pi_k} f(a) = \gamma f^{\pi_k}$ for both a where $f^{\pi_k} = \sum_a \pi_k(a) f(a)$, let $f(a_1) > f(a_2)$ so $\bar{\pi}_k = a_1$. Then
 313 $A_k = \delta_k(f(a_1) - f(a_2))$, $C_k = 2\delta_k$, giving $A_k/C_k = (f(a_1) - f(a_2))/2$. The RPI condition at a_1
 314 gives $\gamma f^{\pi_k} \geq f(a_1)$, from which $f(a_1) - f(a_2) \leq \epsilon_u$. Therefore

$$\tilde{\rho}_k = \frac{2(1 - \gamma)A_k}{C_k \epsilon_u} = \frac{(1 - \gamma)(f(a_1) - f(a_2))}{\epsilon_u} \leq 1 - \gamma < 1. \quad \square$$




Figure 6: **The improvement identity (Proposition 1) holds to machine precision in tabular RandomMDPs.** Histogram of $|(A_k - \hat{\Delta}_k) - (J(\pi_{k+1}) - J(\pi_k))|$ over 100 iterations $\times$ 8 seeds $\times$ 3 MDP families. Median residual 5×10^{-16} , max 4×10^{-13} . Function approximation is not the cause.

315 D Estimator agreement (start-state vs. residual-based $\hat{\Delta}_k$)

316 The start-state estimator (6) and the alternative residual-based estimator $\hat{\Delta}_k^{\text{res}} = \mathbb{E}_{B_k}[r + \gamma V_{k+1}(s') -$
 317 $V_{k+1}(s)] / (1 - \gamma)$ are different empirical proxies for the same population $\hat{\Delta}_k$. We compare them
 318 on Humanoid-v5 over 20 seeds with separately-seeded held-out batches of 500 transitions per
 319 update ($n = 4,900$ paired updates). OLS regression of the held-out residual estimator on the train-
 320 batch residual estimator gives slope 0.97, intercept +2.15, Pearson $r = 0.80$ (95% CI [0.79, 0.81]),
 321 $R^2 = 0.64$. The estimators agree in expectation (slope near 1) but the per-update agreement is
 322 moderate ($R^2 = 0.64$), reflecting higher per-update variance in the residual-based estimator on
 323 out-of-rollout transitions. We report the start-state form throughout because it is faithful to the formal
 324 definition (6); the alternative form recovers a higher pooled cert-gap AUROC by virtue of having
 325 $\sim 2,048$ samples per update versus $|\mathcal{S}_0|$ samples for the start-state form, but is closer to the rollout
 326 that just trained the critic.

327 E Robustness of ϵ_u across scalarizations




Figure 7: **$-\hat{\epsilon}_u$ fails as a harm predictor under three definitions on Humanoid-v5.** Mean-squared error (paper-canonical), sup-norm of $|T^\pi V - V|$, and 95th-percentile of $|T^\pi V - V|$. Six seeds; all three definitions sit at or near chance.

The headline ϵ_u in Table 1 uses mean-squared TD error post-critic-update (the value-function loss every PPO and SAC implementation we surveyed minimizes). Figure 7 reports the same quantity computed under two alternative scalarizations on Humanoid-v5: the sup-norm $\|T^\pi V - V\|_\infty$ (corresponding to the worst-case theoretical ϵ_u) and the 95th-percentile of $|T^\pi V - V|$ (a robust variant). All three sit at chance. The failure of $-\hat{\epsilon}_u$ as a per-update harm predictor is intrinsic to the metric, not to the choice of scalarization.

F Per-seed paired comparison

Table 1 in the main text reports per-(algorithm, environment) median AUROC. Figure 8 visualises the seed-paired comparison for the PPO main grid.

G Experimental details

Environments and seed counts. PPO main: LunarLander-v3, CartPole-v1, Acrobot-v1 at 200k–300k env steps; Hopper-v5, HalfCheetah-v5, Walker2d-v5, Ant-v5 at 300k steps; Humanoid-v5 at 500k steps; 20 seeds per environment (160 runs). PPO-MSE ablation: same eight envs, 5 seeds each (40 runs). Hyperparameter factorials (PPO): LunarLander 4×4 , 5 seeds/cell (80 runs); HalfCheetah 3×2 plus 3 value-lr cells, 5 seeds each (45 runs); Hopper 3×2 plus 3 value-lr cells, 5 seeds each (45 runs). ϵ_u -scalarization subset (Humanoid): 6 seeds with three Bellman-residual scalarizations logged. Estimator-agreement subset (Humanoid): 20 seeds with 500-transition held-out batch logging. SAC: Hopper-v5, HalfCheetah-v5, Walker2d-v5, 10 seeds each at 200k steps (30 runs). TRPO: LunarLander-v3, Hopper-v5, 10 seeds each at 150k steps (20 runs). Cross-algorithm total: ~ 540 training runs, $\sim 86,000$ logged updates. Environments via Gymnasium [Brockman et al., 2016].

Algorithm configurations. PPO: GAE [Schulman et al., 2015b] with $\gamma=0.99$, $\lambda=0.95$; value-epochs 10, policy-epochs 10, clip- $\epsilon = 0.2$; batch size 2048; minibatch 64; policy learning rate 3×10^{-4} , value learning rate 10^{-3} ; gradient clipping at 1.0; no entropy bonus. (64, 64)-tanh MLPs with orthogonal initialization. Continuous-action environments use a Gaussian policy with state-independent log-standard-deviation. PPO-MSE replaces the clipped value loss with raw MSE; otherwise identical. SAC: standard twin-Q networks with target smoothing, automatic entropy temperature, replay buffer 10^6 , batch size 256, learning rate 3×10^{-4} , $\gamma = 0.99$, $\tau = 0.005$. TRPO: KL constraint $\delta = 0.01$, conjugate-gradient 10 iterations, line-search backtracks 10, policy step from natural gradient; same value network and GAE configuration as PPO. All implementations in PyTorch on CPU.

Diagnostic logging. Per update we log $\hat{A}_k$, $\hat{\Delta}_k$ (start-state form), $\hat{\epsilon}_u$ (mean squared TD error on rollout transitions, post-critic-update), and $\hat{\Delta J}_k = \hat{J}(\pi_{k+1}) - \hat{J}(\pi_k)$ from successive rollout batches. The harmful label $1[\hat{\Delta J}_k < 0]$ is undefined on the final update of each run. The same logging schema applies to PPO, PPO-MSE, SAC, and TRPO with appropriate definitions of “rollout batch” and the post-update critic.

Reproducibility. A single command (`make figures` after `pip install -e .`) regenerates every figure in this paper from the released update logs. The full pipeline (`make experiments`, equivalently `python scripts/run_all.py -workers 6 -skip-if-exists`) takes ~ 13 wall-clock hours on an 8-core CPU. Code, run logs, and REPRODUCIBILITY.md are released with the paper.




Figure 8: **Per-seed pairwise comparison.** Paired dumbbell plot for the 160 PPO seeds (sorted by $\hat{\epsilon}_u$ AUROC). Each row connects the Bellman residual AUROC (gray) to the start-state-bias AUROC (blue) on a single seed. The bias term beats the residual on 158/158 paired seeds (one tied), $p < 10^{-27}$.

NeurIPS Paper Checklist

1. Claims

Question: Do the main claims made in the abstract and introduction accurately reflect the paper’s contributions and scope?

Answer: [\[Yes\]](#)

Justification: The abstract and Section 1 state the three contributions (no-go for absolute residuals; identity exposing $\hat{\Delta}_k$; cross-algorithm audit) with the empirical headline numbers; Sections 5 and 6 deliver each claim with the exact scope described.

376 **2. Limitations**

377 Question: Does the paper discuss the limitations of the work performed by the authors?

378 Answer: [Yes]

379 Justification: Section 8 (“Limitations” paragraph) discusses the high variance of $\hat{J}(\pi_k)$ on
380 environments with few episodes per rollout, the diagnostic-versus-controller boundary (lag-1
381 collapse), the smaller SAC/TRPO grids, and the absence of off-policy importance correction
382 for A_k .

383 **3. Theory assumptions and proofs**

384 Question: For each theoretical result, does the paper provide the full set of assumptions and
385 a complete (and correct) proof?

386 Answer: [Yes]

387 Justification: Proposition 1 is proved in the body. Proposition 2 is proved in Section C.
388 Assumptions on the MDP and policy class are stated in Section 4.

389 **4. Experimental result reproducibility**

390 Question: Does the paper fully disclose all the information needed to reproduce the main ex-
391 perimental results of the paper to the extent that it affects the main claims and/or conclusions
392 of the paper (regardless of whether the code and data are provided or not)?

393 Answer: [Yes]

394 Justification: Section G specifies environments, seed counts, hyperparameters, and the
395 per-update logging schema. The released code reproduces every figure and table with a
396 single command.

397 **5. Open access to data and code**

398 Question: Does the paper provide open access to the data and code, with sufficient instruc-
399 tions to faithfully reproduce the main experimental results, as described in supplemental
400 material?

401 Answer: [Yes]

402 Justification: An anonymized code archive accompanies the submission. README.md
403 documents both the figures-from-cache pipeline (make figures) and the from-scratch
404 pipeline (make experiments).

405 **6. Experimental setting/details**

406 Question: Does the paper specify all the training and test details (e.g., data splits, hyperpa-
407 rameters, how they were chosen, type of optimizer) necessary to understand the results?

408 Answer: [Yes]

409 Justification: Section G lists all hyperparameters; Section 3 describes the logging schema
410 and harmful-label definition.

411 **7. Experiment statistical significance**

412 Question: Does the paper report error bars suitably and correctly defined or other appropriate
413 information about the statistical significance of the experiments?

414 Answer: [Yes]

415 Justification: Per-seed AUROCs are reported with paired-Wilcoxon p -values across 237
416 seeds (Table 1); the dominance counts and pooled p -values are reported in Section 6.

417 **8. Experiments compute resources**

418 Question: For each experiment, does the paper provide sufficient information on the com-
419 puter resources (type of compute workers, memory, time of execution) needed to reproduce
420 the experiments?

421 Answer: [Yes]

Justification: Section G reports CPU-only execution and a ~ 13 wall-clock-hour budget on an 8-core CPU at six parallel workers.

9. Code of ethics

Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics?

Answer: [Yes]

Justification: The work is purely methodological RL on synthetic and standard Gymnasium environments; there is no human-subjects data, deployed model, or dual-use concern.

10. Broader impacts

Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

Answer: [N/A]

Justification: The paper is a methodological diagnostic for actor-critic RL with no direct application path to deployed systems; we identify no specific positive or negative societal impacts.

11. Safeguards

Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

Answer: [N/A]

Justification: The released artifacts are training logs and standard RL training code. No high-risk model or dataset is released.

12. Licenses for existing assets

Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

Answer: [Yes]

Justification: Gymnasium and MuJoCo are cited (Section G); PPO, SAC, TRPO, and GAE are cited where they appear. All third-party software is MIT/BSD-compatible with our MIT release.

13. New assets

Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

Answer: [Yes]

Justification: The released code, audit logs, and paper-figure recipes are documented in README.md and REPRODUCIBILITY.md.

14. Crowdsourcing and research with human subjects

Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

Answer: [N/A]

Justification: The paper involves no human subjects.

15. Institutional review board (IRB) approvals or equivalent for research with human subjects

Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

Answer: [N/A]

471 Justification: The paper involves no human subjects.

472 **16. Declaration of LLM usage**

473 Question: Does the paper describe the usage of LLMs if it is an important, original, or
474 non-standard component of the core methods in this research?

475 Answer: [N/A]

476 Justification: LLMs were not part of the methodology; any use was limited to writing and
477 editing, which the NeurIPS policy does not require to be declared.