

# Rank Modulation in Flash Memories

Course Project, EE 605

Saketika Chekuri<sup>1</sup>   Suraj Samaga<sup>2</sup>

<sup>1</sup>190070054

Electrical Engineering, IIT Bombay

<sup>2</sup>190020114

Electrical Engineering, IIT Bombay

Error Correcting Codes, Autumn 2021

# Table of Contents

- 1 Setup
- 2 Basic Construction
  - Notation
  - Definitions
  - Construction
- 3 Balanced  $n$ -RMGC
  - Definition and Construction
  - Ranking Permutations
- 4 Conclusion
- 5 References

# Introduction

Flash memory is a non-volatile memory that is both electrically programmable and erasable.

# Introduction

Flash memory is a non-volatile memory that is both electrically programmable and erasable. Historically, it comprises of blocks of cells, where each cell is in one of two states. However, multi-level cells, where each cell stores one of  $q$  levels are being actively developed.

# Introduction

Flash memory is a non-volatile memory that is both electrically programmable and erasable. Historically, it comprises of blocks of cells, where each cell is in one of two states. However, multi-level cells, where each cell stores one of  $q$  levels are being actively developed.

Device electronics tells us that while adding charge to a single cell is a fast and simple operation, removing charge from a single cell is very difficult.

# Introduction

Flash memory is a non-volatile memory that is both electrically programmable and erasable. Historically, it comprises of blocks of cells, where each cell is in one of two states. However, multi-level cells, where each cell stores one of  $q$  levels are being actively developed.

Device electronics tells us that while adding charge to a single cell is a fast and simple operation, removing charge from a single cell is very difficult. This calls for accurate programming schemes that cautiously approach target charge levels from below.

# Introduction

Additionally, the move to multi-level flash cells aggravates device reliability.

# Introduction

Additionally, the move to multi-level flash cells aggravates device reliability. For example, sufficient drift in device threshold levels may cause programming and reading errors.



# Introduction

Additionally, the move to multi-level flash cells aggravates device reliability. For example, sufficient drift in device threshold levels may cause programming and reading errors.

## Problem

Designing codes where  $k$  bits are stored using a block of  $n$  cells with  $q$  levels each, with the additional requirement of addressing the challenges above.

# Introduction

Additionally, the move to multi-level flash cells aggravates device reliability. For example, sufficient drift in device threshold levels may cause programming and reading errors.

## Problem

Designing codes where  $k$  bits are stored using a block of  $n$  cells with  $q$  levels each, with the additional requirement of addressing the challenges above.

One such scheme is Rank Modulation.

# Rank Modulation

- An ordered set of  $n$  cells stores the information in the permutation induced by the charge levels of the cells

# Rank Modulation

- An ordered set of  $n$  cells stores the information in the permutation induced by the charge levels of the cells
- The only allowed programming operation is a 'push-to-the-top' operation, raising the charge level of one of the cells to above the current highest one

# Rank Modulation

- An ordered set of  $n$  cells stores the information in the permutation induced by the charge levels of the cells
- The only allowed programming operation is a 'push-to-the-top' operation, raising the charge level of one of the cells to above the current highest one
- Additionally, 'block-deflation', decrease of all the charge levels in a block by a constant amount smaller than the lowest, maintaining relative values is allowed

# Rank Modulation - Gray Codes

We use Gray Codes to implement Rank Modulation.

# Rank Modulation - Gray Codes

We use Gray Codes to implement Rank Modulation.

## Definition 1 (Gray Codes)

Ordered set of distinct states for which every state  $s_i$  is followed by a state  $s_{i+1}$  such that  $s_{i+1} = t(s_i)$

# Rank Modulation - Gray Codes

We use Gray Codes to implement Rank Modulation.

## Definition 1 (Gray Codes)

Ordered set of distinct states for which every state  $s_i$  is followed by a state  $s_{i+1}$  such that  $s_{i+1} = t(s_i)$  where  $t \in \mathcal{T}$  is a transition function from a predetermined set  $\mathcal{T}$  defining the Gray Code



# Rank Modulation - Gray Codes

We use Gray Codes to implement Rank Modulation.

## Definition 1 (Gray Codes)

Ordered set of distinct states for which every state  $s_i$  is followed by a state  $s_{i+1}$  such that  $s_{i+1} = t(s_i)$  where  $t \in T$  is a transition function from a predetermined set  $T$  defining the Gray Code

The traversal of states by the Gray Code is mapped to the increase of cell level in the multi-level flash cell.

# Table of Contents

- 1 Setup
- 2 Basic Construction
  - Notation
  - Definitions
  - Construction
- 3 Balanced  $n$ -RMGC
  - Definition and Construction
  - Ranking Permutations
- 4 Conclusion
- 5 References

# Notation

- We consider each relative ordering of the  $n$  cells as a state, belonging to state space  $S$ .

# Notation

- We consider each relative ordering of the  $n$  cells as a state, belonging to state space  $S$ .
- Let  $[n]$  denote the set  $\{1, 2, \dots, n\}$ . An ordered set of  $n$  memory cells labelled  $1, 2, \dots, n$  which distinct charge levels induce permutations of  $[n]$  by representing the cell names as vectors  $[a_1, a_2, \dots, a_n]$  in descending order of charge levels.
- State space would be all possible permutations on  $[n]$ .

# Notation

- For the rank modulation scheme, we only consider push-to-the-top operations.

# Notation

- For the rank modulation scheme, we only consider push-to-the-top operations.
- Let  $t_i$  represent the transition that pushes the  $i$ th highest cell to the highest charge level.

$$t_i([a_1, a_2, \dots, \mathbf{a_i}, a_{i+1}, \dots a_n]) = [\mathbf{a_i}, a_1, a_2, \dots, a_{i-1}, a_{i+1}, \dots a_n]$$

# Notation

- For the rank modulation scheme, we only consider push-to-the-top operations.
- Let  $t_i$  represent the transition that pushes the  $i$ th highest cell to the highest charge level.

$$t_i([a_1, a_2, \dots, \mathbf{a_i}, a_{i+1}, \dots a_n]) = [\mathbf{a_i}, a_1, a_2, \dots, a_{i-1}, a_{i+1}, \dots a_n]$$

- Let  $T$  be the set of all push-to-the-top transitions. That is,  $s_{i+1} = t(s_i)$  for some  $t \in T, s_i, s_{i+1} \in S$ .

# Definitions

- The code we consider, in which state space is all permutations on  $[n]$  and the set of our transitions is all possible push-to-the-top functions is called a "length- $n$  rank modulation Gray code" (**n-RMGC**).



# Definitions

- The code we consider, in which state space is all permutations on  $[n]$  and the set of our transitions is all possible push-to-the-top functions is called a "length- $n$  rank modulation Gray code" (**n-RMGC**).
- If the code is such that  $s_1 = t(s_m)$  for some  $t \in T$ , the code is **cyclic**.
- If the code spans all of  $S$ , it is considered **complete**.

# Example

## Example 2

A 3-RMGC is given below:

1	2	3	1	3	2
2	1	2	3	1	3
3	3	1	2	2	1

Here, the permutations are the different columns.

# Example

## Example 2

A 3-RMGC is given below:

1	2	3	1	3	2
2	1	2	3	1	3
3	3	1	2	2	1

Here, the permutations are the different columns. This code is defined by the transitions  $t_2, t_3, t_3, t_2, t_3, t_3$ . Note that the last  $t_3$  transition gives back 1, 2, 3, making the code cyclic.

# Construction of n-RMGC

- Construct cyclic and complete RMGCs via recursion.
- Recursion basis is 2-RMGC:  $[1, 2], [2, 1]$

# Construction of n-RMGC

- Construct cyclic and complete RMGCs via recursion.
- Recursion basis is 2-RMGC:  $[1, 2], [2, 1]$
- Assume cyclic and complete  $(n - 1)$ -RMGC already available called  $C_{n-1}$  defined by transitions  $t_{i_1}, t_{i_2}, \dots, t_{i_{(n-1)!}}$  with  $t_{i_{(n-1)!}} = t_2$

# Construction of n-RMGC

- Construct cyclic and complete RMGCs via recursion.
- Recursion basis is 2-RMGC:  $[1, 2], [2, 1]$
- Assume cyclic and complete  $(n - 1)$ -RMGC already available called  $C_{n-1}$  defined by transitions  $t_{i_1}, t_{i_2}, \dots, t_{i_{(n-1)!}}$  with  $t_{i_{(n-1)!}} = t_2$
- The  $t_{i_{(n-1)!}} = t_2$  condition is not very restrictive, since it only necessitates a  $t_2$  transition somewhere in the transition sequence, and we can always rotate the sequence to make  $t_2$  the last one.

# Construction of $n$ -RMGC

- Construct cyclic and complete RMGCs via recursion.
- Recursion basis is 2-RMGC:  $[1, 2], [2, 1]$
- Assume cyclic and complete  $(n - 1)$ -RMGC already available called  $C_{n-1}$  defined by transitions  $t_{i_1}, t_{i_2}, \dots, t_{i_{(n-1)!}}$  with  $t_{i_{(n-1)!}} = t_2$
- The  $t_{i_{(n-1)!}} = t_2$  condition is not very restrictive, since it only necessitates a  $t_2$  transition somewhere in the transition sequence, and we can always rotate the sequence to make  $t_2$  the last one.
- We further assume  $t_2$  appears at least twice.

# Construction

- Without loss of generality, assume the first permutation is  $[1, 2, \dots, n]$ .
- Using  $t_{i_1}, t_{i_2}, \dots, t_{i_{(n-1)!-1}}$  from  $C_{n-1}$  (and thus effectively keeping the last element fixed), we get the first *block* of  $(n-1)!$  elements of our construction.



# Construction

- Without loss of generality, assume the first permutation is  $[1, 2, \dots, n]$ .
- Using  $t_{i_1}, t_{i_2}, \dots, t_{i_{(n-1)!-1}}$  from  $C_{n-1}$  (and thus effectively keeping the last element fixed), we get the first *block* of  $(n-1)!$  elements of our construction.
- Since  $t_{i_{(n-1)!}} = t_2$ , the last element of the first block is  $[2, 1, 3, 4, \dots, n-1, n]$

# Construction

- Without loss of generality, assume the first permutation is  $[1, 2, \dots, n]$ .
- Using  $t_{i_1}, t_{i_2}, \dots, t_{i_{(n-1)!-1}}$  from  $C_{n-1}$  (and thus effectively keeping the last element fixed), we get the first *block* of  $(n-1)!$  elements of our construction.
- Since  $t_{i_{(n-1)!}} = t_2$ , the last element of the first block is  $[2, 1, 3, 4, \dots, n-1, n]$
- For the first element of the second block, we first use  $t_n$ , and use  $t_{i_1}, t_{i_2}, \dots, t_{i_{(n-1)!-1}}$  again.

# Construction

- Without loss of generality, assume the first permutation is  $[1, 2, \dots, n]$ .
- Using  $t_{i_1}, t_{i_2}, \dots, t_{i_{(n-1)!-1}}$  from  $C_{n-1}$  (and thus effectively keeping the last element fixed), we get the first *block* of  $(n-1)!$  elements of our construction.
- Since  $t_{i_{(n-1)!}} = t_2$ , the last element of the first block is  $[2, 1, 3, 4, \dots, n-1, n]$
- For the first element of the second block, we first use  $t_n$ , and use  $t_{i_1}, t_{i_2}, \dots, t_{i_{(n-1)!-1}}$  again.
- This time,  $(n-1)$  would be the fixed last element while all the other elements create  $(n-1)!$  more permutations.

# Construction

- Without loss of generality, assume the first permutation is  $[1, 2, \dots, n]$ .
- Using  $t_{i_1}, t_{i_2}, \dots, t_{i_{(n-1)!-1}}$  from  $C_{n-1}$  (and thus effectively keeping the last element fixed), we get the first *block* of  $(n-1)!$  elements of our construction.
- Since  $t_{i_{(n-1)!}} = t_2$ , the last element of the first block is  $[2, 1, 3, 4, \dots, n-1, n]$
- For the first element of the second block, we first use  $t_n$ , and use  $t_{i_1}, t_{i_2}, \dots, t_{i_{(n-1)!-1}}$  again.
- This time,  $(n-1)$  would be the fixed last element while all the other elements create  $(n-1)!$  more permutations.
- Repeat this process  $(n-1)$  times to get  $(n-1)!$  permutations each time.

# Construction

## Lemma 3

*Second element in first permutation to every block is 2. It follows that first element of last permutation in every block is also 2.*

## Proof.

We use the transitions  $t_{i_1}, t_{i_2}, \dots, t_{i_{(n-1)!-1}}$  in this particular order. If we use  $t_{i_{(n-1)!}} = t_2$ , we get the first permutation of the block back, which has 2 in the second position. Therefore, after  $t_{i_{(n-1)!-1}}$ , we get the last permutation of the block in which 2 must have been the first element.  $\square$

# Construction

## Lemma 4

*In any block, last element of all permutations is always constant, and the sequence of last elements starting from  $[1, 2, \dots, n]$  is always  $n, n-1, \dots, 4, 3, 1$ . 2 is never the last element.*

## Proof.

- The first claim is justified since we use transitions that define  $C_{n-1}$  which only operate on the first  $(n-1)$  elements.
- 2 is the first element for the last permutation of each block from Lemma 3, so it can't simultaneously be the last element as well.



# Construction

- Let the set of  $(n - 1)$  blocks we constructed be  $C'$ .
- From the lemmas above, we can see that  $C'$  is not complete yet since it doesn't have any permutations ending in 2.

# Construction

- Let the set of  $(n - 1)$  blocks we constructed be  $C'$ .
- From the lemmas above, we can see that  $C'$  is not complete yet since it doesn't have any permutations ending in 2.
- We provide an alternate construction to build  $C''$ , the set of all permutations with 2 as last element.



# Construction of $C''$

- Start by rotating  $t_{i_1}, t_{i_2}, \dots, t_{i_{(n-1)!}}$  so that the last transition is  $t_{n-1}$ .

# Construction of $C''$

- Start by rotating  $t_{i_1}, t_{i_2}, \dots, t_{i_{(n-1)!}}$  so that the last transition is  $t_{n-1}$ .  
Let this rotated sequence be  $\tau_{i_1}, \tau_{i_2}, \dots, \tau_{i_{(n-1)!}}$  such that  
 $\tau_{i_{(n-1)!}} = t_{n-1}$

# Construction of $C''$

- Start by rotating  $t_{i_1}, t_{i_2}, \dots, t_{i_{(n-1)!}}$  so that the last transition is  $t_{n-1}$ . Let this rotated sequence be  $\tau_{i_1}, \tau_{i_2}, \dots, \tau_{i_{(n-1)!}}$  such that  $\tau_{i_{(n-1)!}} = t_{n-1}$
- We start with the first permutation in the block as  $[a_1, a_2, \dots, a_{n-1}, 2]$ . Set the permutations of  $C''$  as those formed by  $\tau_{i_1}, \tau_{i_2}, \dots, \tau_{i_{(n-1)!-1}}$  starting from this first permutation.

# Construction of $C''$

- Start by rotating  $t_{i_1}, t_{i_2}, \dots, t_{i_{(n-1)!}}$  so that the last transition is  $t_{n-1}$ . Let this rotated sequence be  $\tau_{i_1}, \tau_{i_2}, \dots, \tau_{i_{(n-1)!}}$  such that  $\tau_{i_{(n-1)!}} = t_{n-1}$
- We start with the first permutation in the block as  $[a_1, a_2, \dots, a_{n-1}, 2]$ . Set the permutations of  $C''$  as those formed by  $\tau_{i_1}, \tau_{i_2}, \dots, \tau_{i_{(n-1)!-1}}$  starting from this first permutation.
- The last permutation of  $C''$  will therefore be  $[a_2, a_3, \dots, a_{n-1}, a_1, 2]$

# Construction


- In  $C'$ , we look for a transition of the form  
 $[a_2, a_3, \dots, a_{n-1}, 2, a_1] \rightarrow [2, a_2, \dots, n-1, a_1]$

# Construction

- In  $C'$ , we look for a transition of the form  $[a_2, a_3, \dots, a_{n-1}, 2, a_1] \rightarrow [2, a_2, \dots, n-1, a_1]$
- Such a transition would surely exist; while  $C'$  doesn't have any permutations in which 2 is the last element, it does have permutations in which 2 is the penultimate element and others in which 2 is the first element. Since  $C'$  is cyclic, such a transition would surely exist.

# Construction

- In  $C'$ , we look for a transition of the form  $[a_2, a_3, \dots, a_{n-1}, 2, a_1] \rightarrow [2, a_2, \dots, n-1, a_1]$
- Such a transition would surely exist; while  $C'$  doesn't have any permutations in which 2 is the last element, it does have permutations in which 2 is the penultimate element and others in which 2 is the first element. Since  $C'$  is cyclic, such a transition would surely exist.
- Whenever such a transition occurs (note that there can be multiple such occurrences, so we can choose any one), we split  $C'$  and insert  $C''$  to create a complete RMGC as follows:



# Summary

## Theorem 5

*For every integer  $n \geq 2$ , there exists a cyclic and complete  $n$ -RMGC.*



# Example

## Example 6

As considered in Example 2, we start the 3-RMGC we obtained. However, this had the transition sequence  $t_2, t_3, t_3, t_2, t_3, t_3$ , but we want it to end in  $t_2$

# Example

## Example 6

As considered in Example 2, we start the 3-RMGC we obtained. However, this had the transition sequence  $t_2, t_3, t_3, t_2, t_3, t_3$ , but we want it to end in  $t_2$ . So, we rotate the sequence to  $t_3, t_3, t_2, t_3, t_3, t_2$  and obtain the following  $C'$  starting with  $[1, 2, 3, 4]$ :

1 3 2 3 1 2	4 1 2 1 4 2	3 4 2 4 3 2
2 1 3 2 3 1	2 4 1 2 1 4	2 3 4 2 4 3
3 2 1 1 2 3	1 2 4 4 2 1	4 2 3 3 2 4
4 4 4 4 4 4	3 3 3 3 3 3	1 1 1 1 1 1

# Example

To construct  $C''$ , we look for a transition in which 2 goes from the penultimate position to the top. Multiple such transitions exist, so we choose  $[1, 3, 2, 4] \rightarrow [2, 1, 3, 4]$ . Inserting  $C''$  between  $C'$ , we get:

1	3	2	3	1	4	1	3	4	3	1	2	4	1	2	1	4	2	3	4	2	4	3	2
2	1	3	2	3	1	4	1	3	4	3	1	2	4	1	2	1	4	2	3	4	2	4	3
3	2	1	1	2	3	3	4	1	1	4	3	1	2	4	4	2	1	4	2	3	3	2	4
4	4	4	4	4	2	2	2	2	2	2	4	3	3	3	3	3	3	1	1	1	1	1	1

# Table of Contents

- 1 Setup
- 2 Basic Construction
  - Notation
  - Definitions
  - Construction
- 3 **Balanced n-RMGC**
  - **Definition and Construction**
  - **Ranking Permutations**
- 4 Conclusion
- 5 References

# Definitions

While the construction seen in the previous section is straightforward and intuitive, it suffers from a serious drawback.

# Definitions

While the construction seen in the previous section is straightforward and intuitive, it suffers from a serious drawback. While the top-charged cells are changed regularly while permuting within a block, the bottom cell remains unchanged and is only activated at the end of each block.

# Definitions

While the construction seen in the previous section is straightforward and intuitive, it suffers from a serious drawback. While the top-charged cells are changed regularly while permuting within a block, the bottom cell remains unchanged and is only activated at the end of each block. This leads to a large gap between the least charged and most charged cells, which is undesirable.

# Definitions

## Definition 7

We define  $c_i : \mathbb{N} \mapsto \mathbb{N}$  where  $c_i(p)$  is the charge level of the  $i^{th}$  cell after the  $p^{th}$  programming cycle.



# Definitions

## Definition 7

We define  $c_i : \mathbb{N} \mapsto \mathbb{N}$  where  $c_i(p)$  is the charge level of the  $i^{th}$  cell after the  $p^{th}$  programming cycle.

- Suppose we use transition  $t_j$  in the  $p^{th}$  programming cycle, and the  $i^{th}$  cell is at that time,  $j^{th}$  from the top

# Definitions

## Definition 7

We define  $c_i : \mathbb{N} \mapsto \mathbb{N}$  where  $c_i(p)$  is the charge level of the  $i^{th}$  cell after the  $p^{th}$  programming cycle.

- Suppose we use transition  $t_j$  in the  $p^{th}$  programming cycle, and the  $i^{th}$  cell is at that time,  $j^{th}$  from the top
- $c_i(p) > \max_k c_k(p-1)$

# Definitions

## Definition 7

We define  $c_i : \mathbb{N} \mapsto \mathbb{N}$  where  $c_i(p)$  is the charge level of the  $i^{th}$  cell after the  $p^{th}$  programming cycle.

- Suppose we use transition  $t_j$  in the  $p^{th}$  programming cycle, and the  $i^{th}$  cell is at that time,  $j^{th}$  from the top
- $c_i(p) > \max_k c_k(p-1)$
- for  $k \neq i$ ,  $c_k(p) = c_k(p-1)$

# Definitions

## Definition 7

We define  $c_i : \mathbb{N} \mapsto \mathbb{N}$  where  $c_i(p)$  is the charge level of the  $i^{th}$  cell after the  $p^{th}$  programming cycle.

- Suppose we use transition  $t_j$  in the  $p^{th}$  programming cycle, and the  $i^{th}$  cell is at that time,  $j^{th}$  from the top
- $c_i(p) > \max_k c_k(p-1)$
- for  $k \neq i$ ,  $c_k(p) = c_k(p-1)$
- In an optimal setting with no overshoots, or 'gaps',  
 $c_i(p) = \max_k c_k(p-1) + 1$

# Definitions

- Assuming the  $i^{th}$  cell was affected (moved) in the  $p^{th}$  transition, 'jump' is defined as  $c_i(p) - c_i(p - 1)$

# Definitions

- Assuming the  $i^{th}$  cell was affected (moved) in the  $p^{th}$  transition, 'jump' is defined as  $c_i(p) - c_i(p - 1)$
- **Jump Cost** of an  $n$ -RMGC is defined as the maximum jump over all transitions of the code

# Definitions

- Assuming the  $i^{th}$  cell was affected (moved) in the  $p^{th}$  transition, 'jump' is defined as  $c_i(p) - c_i(p - 1)$
- **Jump Cost** of an  $n$ -RMGC is defined as the maximum jump over all transitions of the code
- An  $n$ -RMGC is said to be optimal if its jump cost is not larger than any other  $n$ -RMGC

# Definitions

- Assuming the  $i^{th}$  cell was affected (moved) in the  $p^{th}$  transition, 'jump' is defined as  $c_i(p) - c_i(p - 1)$
- **Jump Cost** of an  $n$ -RMGC is defined as the maximum jump over all transitions of the code
- An  $n$ -RMGC is said to be optimal if its jump cost is not larger than any other  $n$ -RMGC
- In the above definition we assume that there are no degenerate cells, i.e. every cell level is raised at-least once



# Definitions

## Lemma 8

*For any optimal  $n$ -RMGC,  $n \geq 3$  without any degenerate cells, the jump cost is at least  $n + 1$*

# Definitions

## Lemma 8

*For any optimal  $n$ -RMGC,  $n \geq 3$  without any degenerate cells, the jump cost is at least  $n + 1$*

## Proof.

- The transition  $t_n$  would be the worst-case one to consider while evaluating jump cost

# Definitions

## Lemma 8

*For any optimal  $n$ -RMGC,  $n \geq 3$  without any degenerate cells, the jump cost is at least  $n + 1$*

## Proof.

- The transition  $t_n$  would be the worst-case one to consider while evaluating jump cost
- Such a jump has magnitude of at-least  $n$  (when all charge levels are consecutive) and we must use it at-least  $n$  times to cover all states

# Definitions

## Lemma 8

*For any optimal  $n$ -RMGC,  $n \geq 3$  without any degenerate cells, the jump cost is at least  $n + 1$*

### Proof.

- The transition  $t_n$  would be the worst-case one to consider while evaluating jump cost
- Such a jump has magnitude of at-least  $n$  (when all charge levels are consecutive) and we must use it at-least  $n$  times to cover all states
- However we cannot apply  $t_n$   $n$  times consecutively, as that would lead us to the first permutation after just  $n$  steps

# Definitions

## Lemma 8

*For any optimal  $n$ -RMGC,  $n \geq 3$  without any degenerate cells, the jump cost is at least  $n + 1$*

### Proof.

- The transition  $t_n$  would be the worst-case one to consider while evaluating jump cost
- Such a jump has magnitude of at-least  $n$  (when all charge levels are consecutive) and we must use it at-least  $n$  times to cover all states
- However we cannot apply  $t_n$   $n$  times consecutively, as that would lead us to the first permutation after just  $n$  steps
- Hence our set of transitions must at-least one other transition  $t_i, i \neq n$

# Definitions

## Lemma 8

*For any optimal  $n$ -RMGC,  $n \geq 3$  without any degenerate cells, the jump cost is at least  $n + 1$*

### Proof.

- The transition  $t_n$  would be the worst-case one to consider while evaluating jump cost
- Such a jump has magnitude of at-least  $n$  (when all charge levels are consecutive) and we must use it at-least  $n$  times to cover all states
- However we cannot apply  $t_n$   $n$  times consecutively, as that would lead us to the first permutation after just  $n$  steps
- Hence our set of transitions must at-least one other transition  $t_i, i \neq n$
- This would cause a 'gap' in the charge levels, and the first  $t_n$  to be used after it will have a jump of magnitude at-least  $n + 1$



# Balanced $n$ -RMGC

- An  $n$ -RMGC that achieves the optimal jump cost of  $n + 1$  is called a *Balanced  $n$ -RMGC*

# Balanced $n$ -RMGC

- An  $n$ -RMGC that achieves the optimal jump cost of  $n + 1$  is called a *Balanced  $n$ -RMGC*
- We now try to come up with a construction that converts any  $(n - 1)$ -RMGC that is cyclic(complete) into a balanced  $n$ -RMGC that is cyclic(complete)



# Balanced $n$ -RMGC

- An  $n$ -RMGC that achieves the optimal jump cost of  $n + 1$  is called a *Balanced  $n$ -RMGC*
- We now try to come up with a construction that converts any  $(n - 1)$ -RMGC that is cyclic(complete) into a balanced  $n$ -RMGC that is cyclic(complete)
- We observe that the transition  $t_n$  is the only one that does not introduce gaps between charge levels.

# Balanced $n$ -RMGC

- An  $n$ -RMGC that achieves the optimal jump cost of  $n + 1$  is called a *Balanced  $n$ -RMGC*
- We now try to come up with a construction that converts any  $(n - 1)$ -RMGC that is cyclic(complete) into a balanced  $n$ -RMGC that is cyclic(complete)
- We observe that the transition  $t_n$  is the only one that does not introduce gaps between charge levels.
- Hence we base our construction around  $t_n$  and try to use it as often as possible

# Balanced n-RMGC Construction

## Theorem 9

*Given a cyclic and complete  $(n-1)$ -RMGC  $C_{n-1}$  defined by the transitions  $t_{i_1}, \dots, t_{i_{(n-1)!}}$ , the following transitions define an  $n$ -RMGC that is cyclic, complete and balanced*

$$t_{j_k} = \begin{cases} t_{n-i_{\lceil k/n \rceil}+1} & k \equiv 1(\text{mod } n) \\ t_n & \text{otherwise} \end{cases}$$

*for all  $k \in \{1, \dots, n\}$*

# Balanced n-RMGC Construction

## Proof.

- Consider the abstract transition  $\bar{t}_i, 2 \leq i \leq n$  that pushes the  $i^{th}$  element from the bottom to the bottom of a permutation

# Balanced n-RMGC Construction

## Proof.

- Consider the abstract transition  $\bar{t}_i, 2 \leq i \leq n$  that pushes the  $i^{th}$  element from the bottom to the bottom of a permutation
- $\bar{t}_i([a_1, a_2, \dots, \mathbf{a}_{n-i+1}, a_{i+1}, \dots, a_n]) = [a_1, a_2, \dots, a_{i-1}, a_{i+1}, \dots, a_n, \mathbf{a}_{n-i+1}]$

# Balanced n-RMGC Construction

## Proof.

- Consider the abstract transition  $\bar{t}_i, 2 \leq i \leq n$  that pushes the  $i^{th}$  element from the bottom to the bottom of a permutation
- $\bar{t}_i([a_1, a_2, \dots, \mathbf{a_{n-i+1}}, a_{i+1}, \dots a_n]) = [a_1, a_2, \dots, a_{i-1}, a_{i+1}, \dots a_n, \mathbf{a_{n-i+1}}]$
- Since  $C_{n-1}$  is cyclic and complete, using  $\{\bar{t}_i\}_{(n-1)!}$  we can traverse all permutations of  $[n-1]$



# Balanced n-RMGC Construction

## Proof.

- Consider the abstract transition  $\bar{t}_i, 2 \leq i \leq n$  that pushes the  $i^{th}$  element from the bottom to the bottom of a permutation
- $\bar{t}_i([a_1, a_2, \dots, \mathbf{a_{n-i+1}}, a_{i+1}, \dots, a_n]) = [a_1, a_2, \dots, a_{i-1}, a_{i+1}, \dots, a_n, \mathbf{a_{n-i+1}}]$
- Since  $C_{n-1}$  is cyclic and complete, using  $\{\bar{t}_i\}_{(n-1)!}$  we can traverse all permutations of  $[n-1]$
- Using the above with  $[n]$  will thus generate all  $(n-1)!$  permutations of  $[n]$  with first element fixed



# Balanced n-RMGC Construction

## Proof.

- Consider the abstract transition  $\bar{t}_i, 2 \leq i \leq n$  that pushes the  $i^{th}$  element from the bottom to the bottom of a permutation
- $\bar{t}_i([a_1, a_2, \dots, \mathbf{a_{n-i+1}}, a_{i+1}, \dots a_n]) = [a_1, a_2, \dots, a_{i-1}, a_{i+1}, \dots a_n, \mathbf{a_{n-i+1}}]$
- Since  $C_{n-1}$  is cyclic and complete, using  $\{\bar{t}_i\}_{(n-1)!}$  we can traverse all permutations of  $[n-1]$
- Using the above with  $[n]$  will thus generate all  $(n-1)!$  permutations of  $[n]$  with first element fixed
- It is not hard to see that

$$\bar{t}_i(\sigma) = (t_n \circ \dots (n-1 \text{ times}) \circ t_n \circ t_{n-i+1})(\sigma), \forall \sigma \in S_n$$



# Balanced n-RMGC Construction

contd.

$$\underbrace{t_{n-i_1+1}, \overbrace{t_n, \dots, t_n}^{n-1 \text{ times}}}_{\overrightarrow{t_{i_1}}} \dots \underbrace{t_{n-i_{(n-1)!}+1}, \overbrace{t_n, \dots, t_n}^{n-1 \text{ times}}}_{\overrightarrow{t_{i_{(n-1)!}}}}.$$

Figure: Transition sequence

- From the above two points, the sequence of transitions to be applied to  $[n]$  to generate a balanced n-RMGC is as shown in 1

# Balanced n-RMGC Construction

contd.

$$\underbrace{t_{n-i_1+1}, \overbrace{t_n, \dots, t_n}^{n-1 \text{ times}}}_{\overrightarrow{t_{i_1}}}, \dots, \underbrace{t_{n-i_{(n-1)!}+1}, \overbrace{t_n, \dots, t_n}^{n-1 \text{ times}}}_{\overrightarrow{t_{i_{(n-1)!}}}}.$$

Figure: Transition sequence

- From the above two points, the sequence of transitions to be applied to  $[n]$  to generate a balanced n-RMGC is as shown in 1
- Note that in every block of  $n$  transitions starting with a  $t_{n-i+1}$ , for  $2 \leq i \leq n-1$  we have:

# Balanced n-RMGC Construction

contd.

$$\underbrace{t_{n-i_1+1}, \overbrace{t_n, \dots, t_n}^{n-1 \text{ times}}}_{\vec{t_{i_1}}}, \dots, \underbrace{t_{n-i_{(n-1)!}+1}, \overbrace{t_n, \dots, t_n}^{n-1 \text{ times}}}_{\vec{t_{i_{(n-1)!}}}}.$$

Figure: Transition sequence

- From the above two points, the sequence of transitions to be applied to  $[n]$  to generate a balanced n-RMGC is as shown in 1
- Note that in every block of  $n$  transitions starting with a  $t_{n-i+1}$ , for  $2 \leq i \leq n-1$  we have:
- the transition  $t_{n-i+1}$  with a jump of  $n-i+1$

# Balanced n-RMGC Construction

contd.

$$\underbrace{t_{n-i_1+1}, \overbrace{t_n, \dots, t_n}^{n-1 \text{ times}}}_{\vec{t}_{i_1}}, \dots, \underbrace{t_{n-i_{(n-1)}!+1}, \overbrace{t_n, \dots, t_n}^{n-1 \text{ times}}}_{\vec{t}_{i_{(n-1)}!}}.$$

Figure: Transition sequence

- From the above two points, the sequence of transitions to be applied to  $[n]$  to generate a balanced n-RMGC is as shown in 1
- Note that in every block of  $n$  transitions starting with a  $t_{n-i+1}$ , for  $2 \leq i \leq n-1$  we have:
  - the transition  $t_{n-i+1}$  with a jump of  $n-i+1$
  - $i-1$  transitions of type  $t_n$  with a jump of  $n+1$

# Balanced n-RMGC Construction

contd.


$$\underbrace{t_{n-i_1+1}, \overbrace{t_n, \dots, t_n}^{n-1 \text{ times}}}_{\vec{t}_{i_1}}, \dots, \underbrace{t_{n-i_{(n-1)}!+1}, \overbrace{t_n, \dots, t_n}^{n-1 \text{ times}}}_{\vec{t}_{i_{(n-1)}!}}.$$

Figure: Transition sequence


- From the above two points, the sequence of transitions to be applied to  $[n]$  to generate a balanced n-RMGC is as shown in 1
- Note that in every block of  $n$  transitions starting with a  $t_{n-i+1}$ , for  $2 \leq i \leq n-1$  we have:
  - the transition  $t_{n-i+1}$  with a jump of  $n-i+1$
  - $i-1$  transitions of type  $t_n$  with a jump of  $n+1$
  - $n-i$  transitions of type  $t_n$  with a jump of  $n$

# Balanced n-RMGC - Example

We now demonstrate the above theorem by ways of an example.



# Balanced n-RMGC - Example



# Ranking Permutations

For completing the design of a multi-level flash cell, we must define the correspondence between a permutation and its rank in the balanced  $n$ -RMGC.



# Ranking Permutations

For completing the design of a multi-level flash cell, we must define the correspondence between a permutation and its rank in the balanced  $n$ -RMGC. We use the B-Factoradic Number System for representation.

## B-Factoradic Number System

A number  $m \in \{0, \dots, n! - 1\}$  can be uniquely represented by the digits  $b_{n-1}b_{n-2} \dots b_1b_0$  where  $b_i \in \{0, \dots, n - i - 1\}$  and the weight of  $b_i$  is  $\frac{n!}{(n-i)!}$ .

# Ranking Permutations - Construction

We now describe an algorithm by way of an example to ascertain the rank of a permutation in the B-Factoradic Number System.

## Example 10

- Let  $n = 4$  and the current permutation be  $\sigma = [1, 4, 3, 2]$ , let  $pos(k), k \in \{1, \dots, n\}$  be the position of  $k$  in  $\sigma$  from the left. For example,  $pos(4) = 2$

# Ranking Permutations - Construction

We now describe an algorithm by way of an example to ascertain the rank of a permutation in the B-Factoradic Number System.

## Example 10

- Let  $n = 4$  and the current permutation be  $\sigma = [1, 4, 3, 2]$ , let  $pos(k), k \in \{1, \dots, n\}$  be the position of  $k$  in  $\sigma$  from the left. For example,  $pos(4) = 2$
- We find it's B-Factoradic representation  $b_3b_2b_1b_0$  as follows

# Ranking Permutations - Construction

We now describe an algorithm by way of an example to ascertain the rank of a permutation in the B-Factoradic Number System.

## Example 10

- Let  $n = 4$  and the current permutation be  $\sigma = [1, 4, 3, 2]$ , let  $pos(k), k \in \{1, \dots, n\}$  be the position of  $k$  in  $\sigma$  from the left. For example,  $pos(4) = 2$
- We find it's B-Factoradic representation  $b_3b_2b_1b_0$  as follows
- With  $i \in \{0, \dots, n-1\}$ , for the  $i^{th}$  digit from the right,  $b_i =$  the position of the largest element still in the permutation minus 2 (modulo  $(n-i)$ )

# Ranking Permutations - Construction

We now describe an algorithm by way of an example to ascertain the rank of a permutation in the B-Factoradic Number System.

## Example 10

- Let  $n = 4$  and the current permutation be  $\sigma = [1, 4, 3, 2]$ , let  $pos(k), k \in \{1, \dots, n\}$  be the position of  $k$  in  $\sigma$  from the left. For example,  $pos(4) = 2$
- We find it's B-Factoradic representation  $b_3b_2b_1b_0$  as follows
- With  $i \in \{0, \dots, n-1\}$ , for the  $i^{th}$  digit from the right,  $b_i$  = the position of the largest element still in the permutation minus 2 (modulo  $(n-i)$ )
- $b_0 = \{pos(4) - 2\}(mod 4) = 0$

# Ranking Permutations - Construction

- Now we remove the largest number from the permutation and read the permutation from the point of removal leftwards, arriving at the residual permutation

# Ranking Permutations - Construction

- Now we remove the largest number from the permutation and read the permutation from the point of removal leftwards, arriving at the residual permutation
- $\sigma = \{1, 4, 3, 2\}, \sigma_1 = \{1, 2, 3\}$

# Ranking Permutations - Construction

- Now we remove the largest number from the permutation and read the permutation from the point of removal leftwards, arriving at the residual permutation
- $\sigma = \{1, 4, 3, 2\}, \sigma_1 = \{1, 2, 3\}$
- We now recurse on the residual permutation using the steps described above



# Ranking Permutations - Construction

- Now we remove the largest number from the permutation and read the permutation from the point of removal leftwards, arriving at the residual permutation
- $\sigma = \{1, 4, 3, 2\}, \sigma_1 = \{1, 2, 3\}$
- We now recurse on the residual permutation using the steps described above
- $b_1 = \{pos(3) - 2\}(mod 3) = 1$

# Ranking Permutations - Construction

- Now we remove the largest number from the permutation and read the permutation from the point of removal leftwards, arriving at the residual permutation
- $\sigma = \{1, 4, 3, 2\}, \sigma_1 = \{1, 2, 3\}$
- We now recurse on the residual permutation using the steps described above
- $b_1 = \{pos(3) - 2\}(mod 3) = 1$
- $\sigma_2 = \{2, 1\}$  and  $b_2 = \{pos(2) - 2\}(mod 2) = 1$

# Ranking Permutations - Construction

- Now we remove the largest number from the permutation and read the permutation from the point of removal leftwards, arriving at the residual permutation
- $\sigma = \{1, 4, 3, 2\}, \sigma_1 = \{1, 2, 3\}$
- We now recurse on the residual permutation using the steps described above
- $b_1 = \{pos(3) - 2\}(mod 3) = 1$
- $\sigma_2 = \{2, 1\}$  and  $b_2 = \{pos(2) - 2\}(mod 2) = 1$
- $\sigma_3 = \{1\}$  and  $b_3 = \{pos(1) - 2\}(mod 1) = 0$

# Ranking Permutations - Construction

- Now we remove the largest number from the permutation and read the permutation from the point of removal leftwards, arriving at the residual permutation
- $\sigma = \{1, 4, 3, 2\}, \sigma_1 = \{1, 2, 3\}$
- We now recurse on the residual permutation using the steps described above
- $b_1 = \{pos(3) - 2\}(mod 3) = 1$
- $\sigma_2 = \{2, 1\}$  and  $b_2 = \{pos(2) - 2\}(mod 2) = 1$
- $\sigma_3 = \{1\}$  and  $b_3 = \{pos(1) - 2\}(mod 1) = 0$
- The B-Factoradic representation is therefore  $0_3 1_2 1_1 0_0$

# Table of Contents

- 1 Setup
- 2 Basic Construction
  - Notation
  - Definitions
  - Construction
- 3 Balanced  $n$ -RMGC
  - Definition and Construction
  - Ranking Permutations
- 4 Conclusion
- 5 References

# Conclusion

- We started by looking at what rank modulation is, and why it is needed
- We have looked at a simple construction of cyclic and complete  $n$ -RMGC codes
- We then moved to a more efficient balanced  $n$ -RMGC construction
- The final mapping from the permutations to the symbols is done by using the B-Factoradic number system

# Table of Contents

- 1 Setup
- 2 Basic Construction
  - Notation
  - Definitions
  - Construction
- 3 Balanced  $n$ -RMGC
  - Definition and Construction
  - Ranking Permutations
- 4 Conclusion
- 5 References

# References

- Anxiao Jiang, R. Mateescu, M. Schwartz and J. Bruck, "Rank modulation for flash memories," 2008 IEEE International Symposium on Information Theory, 2008, pp. 1731-1735, doi: 10.1109/ISIT.2008.4595284.