

CS 838 (Spring 2017): Data Science

Project Report - Stage 4 (Group 12)

Deepanker Aggarwal Saket Saurabh
deepanker@cs.wisc.edu ssaurabh@cs.wisc.edu

Vishnu Lokhande
lokhande@cs.wisc.edu

1 Objective

In the previous stage, a matcher was built which can determine whether two tuples, one from table A and the other from table B , denote the same entity or not. The matcher was trained on small sample datasets from table A and table B .

In this stage, we apply the trained matcher on tables A and B to determine the set of all matching tuple pairs and then later merge these tuple pairs to form a single table.

2 Choice of the matcher

- From the previous stage, upon training and testing several matchers on a sample of dataset, we found that Naive Bayes performed better than other matchers. This is based on the test-set accuracies.
- Next, we train the selected matcher on the combined set of training and testing data. This is to improve the performance of the matcher before taking it to the production stage.

3 Deploying the matcher and creating Table E

- We first generate the set of all tuple pairs of tables A and B . We do blocking on 'zip-code'.
- The table A is the restaurants data from Yelp and it has following schema (name, address, zipcode, cuisine, price). Table B is the NYC Restaurant Inspection dataset and it has the following schema (name, address, zipcode, cuisine, violation_code, critical_flag, grade).




Figure 1: Schema Merging

- We apply the matcher chosen in the previous section to generate the set of all matching tuple pairs. The matcher works on the common schema between the two tables A and B which is (name, address, zipcode, cuisine)
- The positively matched tuple pairs are merged into a single tuple. Merging is done using some rules which is explained in the next section.
- At this point, we join the output of the merger with a Table D which is NYC demographic dataset. Please refer to stage 1 for an elaborate description of this table. The join is done over the "zip-code" attribute.
- The figure(3) describes this entire process as a flow-chart.

4 Merging the Tables

We do not have any missing values in our data, hence, the case is not handled. The common attributes between the tables A and tables B are (name, address, zipcode, cuisine). Rules for each of these attributes is described below.

- **Name**
Among the two names, we choose the longer name. Upon observation of the dataset we came to know that longer names are more informative than shorter ones.
- **Address**
We choose the address from the Yelp dataset over the Inspection dataset.

This is because the former is provided by the restaurant itself unlike the later which is provided by the personnel inspecting the restaurant, hence, making the one from Yelp dataset more reliable.

- Zipcode
- Cuisine

5 Statistics of Table E

6 Code

```
#####
#--- data_merger.py ---#
#####
# The main python file that does data merging for matches between
# tables A and B. The file expects two command-line arguments
# and can be run as:
# 'python3 data_merger.py <input_file> <output_file>'
# It uses two helper files merge_rules.py and nyc_demographics.py
# that are described later in the document.

import csv
import sys

# Import our python classes that we wrote for merging. (Included below)
import merge_rules
import nyc_demographics

nyc_demographics_dataset = nyc_demographics.NYCDemographicsDataset()

def merge_attributes(row):
    merge_rules_dict = {
        'NameMergeRule': merge_rules.NameMergeRule(),
        'AddressMergeRule': merge_rules.AddressMergeRule(),
        'ZipcodeMergeRule': merge_rules.ZipcodeMergeRule(),
        'CuisineMergeRule': merge_rules.CuisineMergeRule()
    }
    merged_name =
        merge_rules_dict['NameMergeRule'].process(row["ltable_name"],
            row["rtable_name"])
    merged_address =
        merge_rules_dict['AddressMergeRule'].process(row["ltable_address"],
            row["rtable_address"])
    merged_zipcode =
        merge_rules_dict['ZipcodeMergeRule'].process(row["ltable_zipcode"],
            row["rtable_zipcode"])
```

```

merged_cuisine =
    merge_rules_dict['CuisineMergeRule'].process(row["ltable_cuisine"],
        row["rtable_cuisine"])
extracted_price = row["ltable_price"]
extracted_violation_code = row["rtable_violation_code"]
extracted_critical_flag = row["rtable_critical_flag"]
extracted_grade = row["rtable_grade"]
merged_row = [merged_name, merged_address, merged_zipcode,
    merged_cuisine,
        extracted_price, extracted_violation_code,
        extracted_critical_flag, extracted_grade]

# Add the attributes from Table D: NYC Demographics Dataset
merged_row.extend(nyc_demographics_dataset.find(merged_zipcode))
return merged_row

def write_header(f):
    # Write CSV Header
    f.writerow(["name", "address", "zipcode", "cuisine", "price",
        "violation_code", "critical_flag", "grade",
        "median_household_income", "median_real_estate_value",
        "population_density", "cost_of_living", "population"])

def write_row(f, merged_row):
    f.writerow(merged_row)

def main(argv):
    if len(argv) < 2:
        sys.stderr.write("Incorrect arguments. Expecting two arguments:
            <input_file> <output_file>\n")
        sys.exit(-1)

    input_file = csv.DictReader(open(argv[0]))
    output_file = csv.writer(open(argv[1], "w"))
    write_header(output_file)

    for row in input_file:
        merged_row = merge_attributes(row)
        write_row(output_file, merged_row)

if __name__ == "__main__":
    main(sys.argv[1:])

#####
#--- merge_rules.py ---#
#####
# This is a helper python file that contains classes that define
# rules for merging columns of A and B.
# Specifically, it defines following classes:

```

```

# class NameMergeRule- to merge restaurant names,
# class AddressMergeRule- to merge restaurant addresses,
# class ZipcodeMergeRule- to merge restaurant zipcodes,
# class CuisineMergeRule- to merge restaurant cuisines.

import json
import re

class NameMergeRule:
    @staticmethod
    def process(value_l, value_r):
        # After inspection of the dataset, we find that the longer names
        # are more descriptive and hence better.
        if len(value_l) > len(value_r):
            return value_l
        else:
            return value_r

class AddressMergeRule:
    @staticmethod
    def process(value_l, value_r):
        if value_l:
            # Trust address from Yelp(value_l) over
            # Inspection dataset(value_r) because it is more reliable,
            # given that it is provided by the restaurant itself
            # and used by customers to navigate to the place.
            return value_l
        else:
            return value_r

class ZipcodeMergeRule:
    @staticmethod
    def process(value_l, value_r):
        if value_l:
            # Trust zipcode from Yelp(value_l) over
            # Inspection dataset(value_r) because
            # it is coming from a relational database backend of Yelp,
            # extracted using Yelp API.
            return value_l
        else:
            return value_r

class CuisineMergeRule:
    valid_cuisine_map = {}

    def __init__(self):

```

```

with open('cuisines_dictionary.json') as json_data:
    self.valid_cuisine_map = json.load(json_data)

def process(self, value_l, value_r):
    # For cuisines, we merge all the cuisine names mentioned in
    # both value_l and value_r. However, we pick only those names
    # that exist in the valid dictionary of cuisines,
    # which we have created.
    merged_cuisine = set()
    cuisines = re.split('\W', value_l + " " + value_r)
    for cuisine in cuisines:
        if cuisine in self.valid_cuisine_map:
            # add the cuisine associated with this key to the set
            merged_cuisine.add(self.valid_cuisine_map[cuisine])

    return " ".join(merged_cuisine)

#####
#--- nyc_demographics.py ---#
#####
# This is a helper python file that loads
# the NYC Demographics dataset (Table D).

# Given a zipcode, the find() function of
# the class NYCDemographicsDataset
# returns the corresponding demographic data for that zipcode.

import csv

class NYCDemographicsDataset:
    zipcode_data_map = {}

    def __init__(self):
        input_file = csv.DictReader(open("../data/Table_D.csv"))
        for row in input_file:
            data = [
                row["median_household_income"],
                row["median_real_estate_value"],
                row["population_density"],
                row["cost_of_living"],
                row["population"]
            ]
            self.zipcode_data_map[row["zipcode"]] = data

    def find(self, zipcode):
        if zipcode in self.zipcode_data_map:
            return self.zipcode_data_map[zipcode]
        else:

```

```

        return []

#####
#--- cuisines_dictionary.json ---#
#####
# This is the dictionary of well-known cuisines that we use
# when merging cuisines from Table A and Table B.
# The key describes the possible derivatives/variations associated
# with a cuisine value.

{
    "bars": "bars",
    "cocktail": "bars",
    "beer": "bars",
    "wine": "bars",
    "pubs": "bars",
    "gastropubs": "bars",
    "american": "american",
    "burgers": "burgers",
    "burger": "american",
    "hot": "american",
    "dogs": "american",
    "hamburgers": "american",
    "steak": "american",
    "pancakes": "american",
    "waffles": "american",
    "japanese": "japanese",
    "sushi": "japanese",
    "korean": "korean",
    "mexican": "mexican",
    "tacos": "mexican",
    "barbeque": "barbeque",
    "barbecue": "barbeque",
    "french": "french",
    "brasseries": "french",
    "creperies": "french",
    "greek": "greek",
    "desserts": "desserts",
    "ice": "desserts",
    "cream": "desserts",
    "yogurt": "desserts",
    "gelato": "desserts",
    "italian": "italian",
    "pizza": "italian",
    "latin": "latin",
    "cuban": "cuban",
    "dominican": "dominican",
    "puerto rican": "puerto rican",
    "puerto": "puerto rican",

```

```

"rican": "puerto rican",
"chinese": "chinese",
"noodles": "chinese",
"ramen": "chinese",
"asian": "asian",
"jewish": "jewish",
"kosher": "jewish",
" cambodian": "cambodian",
"thai": "thai",
"german": "german",
"taiwanese": "taiwanese",
"vietnamese": "vietnamese",
"cafe": "cafe",
"donuts": "cafe",
"coffee": "cafe",
"tea": "cafe",
"juice": "cafe",
"smoothies": "cafe",
"cafe": "cafe",
"bagels": "cafe",
"pretzels": "cafe",
"cafeteria": "cafe",
"vegan": "vegan",
"vegetarian": "vegan",
"filipino": "filipino",
"mediterranean": "mediterranean",
"indian": "indian",
"hawaiian": "hawaiian",
"caribbean": "caribbean",
"turkish": "turkish",
"middle eastern": "middle eastern",
"middle": "middle eastern",
"eastern": "middle eastern",
"falafel": "middle eastern",
"seafood": "seafood",
"venezuelan": "venezuelan",
"spanish": "spanish",
"malaysian": "malaysian",
"bakery": "bakery",
"bakeries": "bakery",
"british": "british",
"european": "european",
"irish": "irish",
"pakistani": "pakistani",
"halal": "pakistani",
"scandinavian": "scandinavian",
"brazilian": "brazilian",
"senegalese": "senegalese",
"african": "african",
"cantonese": "cantonese",

```



```
"portuguese": "portuguese",  
"malaysia": "malaysia",  
"peruvian": "peruvian",  
"colombian": "colombian",  
"bangladeshi": "bangladeshi",  
"hookah": "bangladeshi",  
"salvadoran": "salvadoran",  
"chilean": "chilean",  
"australian": "australian",  
"russian": "russian",  
"ukrainian": "ukrainian",  
"uzbek": "uzbek",  
"armenian": "armenian",  
"mongolian": "mongolian",  
"afghan": "afghan",  
"haitian": "haitian",  
"trinidadian": "trinidadian"  
}
```
