INDEX

	Contents.	Page No.
A	*Overview*	2
B	*How the Apps Work Together*	3
C	*Road to Industry Standards & Future Scaling*	4
D	*DB Schema & Relations*	5
E	*API Endpoints*	8
F	*Video & User Data Analytics*	9
G	*Analytics Visualization & Calculations*	10
H	*Caching Strategy*	11
I	*System Architecture*	12
J	*Settings Configurations & keys*	13
K	*Testing*	14
L	*Infrastructure Cost Breakdown*	15
M	*Terminal Commands*	16
N	*GitHub WorkFlow*	17
O	*Functionalities Explanation*	18

A). **Overview:**

What sets the platform apart :-

For Creators:	For Viewers:
• Complete viewer behavior analysis showing exactly when and why viewers engage or disengage • Advanced pattern recognition revealing which content elements drive the strongest audience response • Predictive analytics forecasting content performance based on historical data patterns • Detailed demographic insights correlated with content preferences • Viewer journey mapping from discovery to long-term engagement • Content impact scoring based on audience retention and growth metrics • Community interaction patterns and engagement hotspots • Comparative analysis across different content formats and styles • Continuous analytics notifications via email/msg	• Personal engagement patterns and content preference insights • Community trend participation metrics • Content discovery patterns • Watch time analysis and content type preferences • Interactive community engagement stats

To-do list : (4th Dec)

- ☑ ~~**Messages**~~
- ☑ ~~**Email & Password Management thru Email**~~
- ☑ ~~**Fun Corner - Analytics & ML**~~
- ☑ ~~**Follower / Following Page for the User**~~
- ☑ ~~**Caching Strategy**~~
- ☑ ~~**Add Pagination & Filters on FE, BE on Viewer Hist.**~~
- ☑ ~~**Search (and maybe Pagination) on User Videos**~~
- ☑ ~~**Managing Passwords on Settings Page**~~
- ☑ ~~**Video Playlisting System**~~
- ☑ ~~**Public/Private listing for videos & playlists**~~
- ☑ ~~**Task Queues Implementation**~~
- ☑ ~~**API Development**~~
- ☑ ~~**Analytics Enhancement**~~
  - ☑ ~~**Stores & visualizes user-session related data**~~
  - ☑ ~~**Denormalise UserSession tbl & connect to FE**~~
  - ☑ ~~**Stores & vis. followers/following related data**~~
  - ☑ ~~**Store & visualize content performance related data**~~
  - ☑ ~~**Denormalise visual content performance data**~~
- ☑ ~~**Plan to Handle Stray UserSessions in DB that are opened but not closed**~~
- ☑ ~~**AI generated reports on user & video data analytics**~~
- ☑ ~~**Beautification of FE**~~
- ☑ ~~**Analytics optimization**~~
- ☑ ~~**Correct the prompts to Gemini for reports generation**~~
- ☑ ~~**Optimise Queries on Other Pages**~~
- ☑ ~~**Take out the thumbnail play preview functionality**~~
- ☑ ~~**Fix the Video Playback Page styling (Comments,bio)**~~
- ☑ ~~**Write tests for user and project apps.**~~
- ☑ ~~**Road to Industry Standards**~~
- ☑ ~~**Connect to D.O Database service**~~
- ☑ ~~**Connect to D.O spaces**~~
- ☐ **Re-up fun corner data (optional)**
- ☐ **Deployment Steps**
  - ☑ ~~**Dockerization**~~
  - ☐ **Connect to D.O App platform**

B). **How the Apps Work Together:**

1."users" App (User Management) (***Models-User, Profile, Follow, Message, UserSession, UserActivitySummary, Report***)	
Core Purpose -	Advanced Purpose -
1.Handles user accounts (signup/login) ✔️ 2.Manages user profiles ✔️ 3.Stores user information ✔️ 4.User to User Following feature ✔️ 5.Handles Authentication & Authorization✔️ 6.User to User Messages feature ✔️ 7.Email & Password Management ✔️ 8.Stores all User App related metadata for Analysis✔️ 9.Caching strategy for users related data ✔️ 10.Instant AI data analysis report generation + TTS gen. ✔️	1. Continuous analytics notifs via email/msg ❓ ❓ 2. Monetization ⁉️⁉️


2."projects" App (Core Features) (***Models-Video, Tag, Like, Review, Playlist, ViewHistory, VideoAnalytics, PlaylistItem)***	
Core Purpose -	Advanced Purpose -
1.Handles video uploads ✔️ 2.Manages video playback ✔️ 3.Stores all relevant video metadata for Analysis✔️ 4.Manages video & playlists listings (public / private)✔️ 5.Handles video reviews/ratings ✔️ 6.Manages video tagging system ✔️ 7.Fitting the thumbnails with Bars ✔️ 8.Managing user's viewing history ✔️ 9.Video Compression and Encoding ✔️ 10. Video analytics page ✔️ 11.Task queues for video processing ✔️ 12.Caching strategy for projects Related Data✔️ 13.Dynamic Comment Section ✔️ 14.Search Bar and Pagination ✔️ 15.Fun Corner - Analytics and ML ✔️ 16.Handles video playlisting system✔️	1.Unique Video Recs for User wrt vid listing & user history ❓ ❓ 2.Third Party CDN integration if needed ❓ ❓ 3.Thumbnail Generation ⁉️ 4.Ability to Handle Live Streaming ⁉️⁉️ 5.Security and Compliance (Copyrite) ⁉️⁉️ 6.Creator Tools Page ⁉️⁉️

C). **Road to Industry Standards & Future Scaling:**

1	**Separate concerns (HTML, CSS, JS)** - Bundling the CSS & JS code away from HTML template	✔️
2	**Clean-up URLs & route them properl**y - which pages **need pk to access** user profile, **and/or** which **need "profile = user.request.profile' to access the user** profile in views.	✔️
3	Make sure only authenticated users are allowed to access particular views in every app.	✔️
4	**Clean and debugged** code	
5	Adopt modern JavaScript features like fetch, async/await, and template literals.	⏳
6	Error handling: **Make sure every interaction has proper success/failure feedback.**	✔️
7	Security: **Validate and sanitize inputs.** (MVP Level)	✔️
8	Responsive design: Mostly use CSS classes to control UI behavior instead of inline styles.	⏳
9	**Document everything important** in the codebase	✔️
10	Look for the best place to host - AWS free tier, **DigitalOcean**	✔️
11	**When to transfer regular views to API views**: **If the view**: Only handles data operations (CRUD) ,Doesn't render HTML ,Needs to support multiple clients Gets called by JavaScript/AJAX **Don't transfer i**f: View renders HTML templates, Handles file uploads with forms, Manages user sessions directly, does page redirects	✔️
12	**Cache Data When :** Data is static/semi-static, Operations are expensive, Access frequency is high, slight staleness is acceptable **Don't Cache When**: User-specific data, Sensitive information, Constantly changing data **Clear Cache When**: Data is updated, TTL expires, Manual admin clear, Logout	✔️
13	**Optimize Analytics** Hub: Indexing (/Composite), Denormalization, Query Caching, Precalculated Graphs, Batch Processing, Aggregation, Data limiting (selecting exact columns instead of *)	✔️
14	Make the Web app **look as uniform as possible** - equal header padding for each page, colour scheme, etc	✔️
15	Add locking mech to important signals to avoid race conditions on Denormalized tables. **Look for race conditions in general.** (MVP Level)	✔️
16	**Set Up Environment Variables** for sensitive data in the codebase	
17	**Only** Write tests for **critical functionalities** (MVP Level)	✔️

Future Scaling - *When using multiple servers/instances, high traffic needs, high availability requirements,V2 release requirements*	
1. Stores & visualize - videos & user related advanced data 2. A/B testing & Predictive Analysis for creators and admin. 3. Load balancing 4. Database Sharding	5. Implement a Home Page Caching Strategy 6. Optimising the Overall Caching Strategy 7. Shifting to Microservices from Monolithic 8. May be Implement Batch Processing in UserSessionCache

D). **DB Schema & Relations:** (https://tinyurl.com/dbcshema1)



1) User - Profile Relationship Practical: Each user has exactly one profile, and each profile belongs to exactly one user Technical: One-to-One relationship with Profile.user_id referencing User.id Example: Like a YouTube account (User) having one channel profile (Profile) Access: user.profile or profile.user	2) User - Video Relationship Practical: One user can upload many videos, but each video has one uploader Technical: One-to-Many relationship with Video.uploader_id referencing User.id Example: A YouTuber uploading multiple videos to their channel Access: user.videos.all() or video.uploader	3) User - Review Relationship Practical: One user can write many reviews, each review has one author Technical: One-to-Many relationship with Review.user_id referencing User.id Example: A user commenting on multiple different videos Access: user.reviews.all() or review.user
4) User - Like Relationship Practical: One user can like many videos, each like comes from one user Technical: One-to-Many with Like.user_id referencing User.id Example: A user liking multiple different videos Access: user.video_likes.all() or like.user	5) User - Playlist Relationship Practical: One user can create many playlists, each playlist has one owner Technical: One-to-Many with Playlist.user_id referencing User.id Example: A user creating multiple playlists for different video categories Access: user.playlists.all() or playlist.user	6) Video - Tag Relationship Practical: One video can have many tags, one tag can be on many videos Technical: Many-to-Many relationship using an automatic junction table Example: A video having multiple tags (#funny, #music, #tutorial) Access: video.tags.all() or tag.video_set.all()

7) Playlist - PlaylistItem Relationship Practical: A playlist can contain multiple videos, but a PlaylistItem uniquely identifies a video within the playlist. Technical: One-to-Many with PlaylistItem. playlist_id referencing Playlist.id. Each PlaylistItem corresponds to one playlist. Access: playlist.playlist_items.all() for all PlaylistItems in a playlist.	8) User - Follow Relationship Practical: Users can follow many users and be followed by many users Technical: Many-to-Many through explicit Follow model with additional data Example: Like following multiple YouTube channels Access: user.following_set.all() or user.followers_set.all()	9) Video - Like Relationship Practical: One video can have many likes, each like belongs to one video Technical: One-to-Many with Like.video_id referencing Video.id Example: Multiple users liking or disliking a single video Access: video.likes.all() or like.video
10) Video - Review Relationship Practical: One video can have many comments, each comment belongs to one video Technical: One-to-Many with Review.video_id referencing Video.id Example: Like YouTube comments where multiple users can comment on a single video	11) Video - ViewHistory Relationship Practical: One video can have many view records Technical: One-to-Many with ViewHistory.video_id referencing Video.id Example: Tracking individual views of a video Access: video.views_history.all() Features: Tracks timestamp and IP for anonymous views	12) User - ViewHistory Relationship Practical: Users can have viewing history for multiple videos (nullable) Technical: One-to-Many with ViewHistory.user_id referencing User.id (null=True) Example: Tracking what videos a user has watched Access: user.view_history.all()
13) Video - VideoAnalytics Relationship Practical: Each video has exactly one analytics dashboard tracking engagement metrics Technical: One-to-One relationship with VideoAnalytics.video_id referencing Video.id Example: Like a YouTube Studio analytics panel showing comprehensive video statistics	14) User - VideoAnalytics Relationship Practical: A user can see analytics for all their uploaded videos Technical: One-to-Many with VideoAnalytics.uploader_id referencing User.id Example: A creator viewing analytics across their entire video catalog	15) Message - Profile (Sender) Relationship Practical: One profile can send many messages, each message has one sender (nullable) Technical: One-to-Many relationship with Message.sender_id referencing Profile.id (null=True) Example: Like YouTube's direct messaging where a user can send multiple messages Access: profile.message_set.all() or message.sender

16) Message - Profile (Recipient) Relationship Practical: One profile can receive many messages, each message has one recipient (nullable) Technical: One-to-Many relationship with Message.recipient_id referencing Profile.id (null=True) Example: Like receiving multiple direct messages in your YouTube inbox Access: profile.messages.all() (using related_name='messages') or message.recipient	17) Video - PlaylistItem Relationship Practical: A video can appear in multiple playlists, but a PlaylistItem uniquely identifies the video in a specific playlist. Technical: One-to-Many with PlaylistItem.video_id referencing Video.id.. Access: video.playlist_items.all() for all PlaylistItems referencing a video. playlist_item.video for the video of a PlaylistItem.	18) User - UserSession Relationship Practical:A user can have multiple sessions (one per login/activity period), Each session belongs to exactly one user. Technical:One-to-Many with UserSession.user_id referencing User.id Access: user.usersession_set.all() // All sessions for a user session.user // The user who owns this session
19) User - UserActivitySummary Relationship Technical: One-to-One relationship with UserActivitySummary.user referencing User.id. Example: Similar to viewing total watch time on YouTube. Access: Use user.activity_summary to access the summary or activity_summary.user to access the user.	20) Report - User Relationship Practical: Each user has exactly one report table record, and each report belongs to one user. Technical: One-to-One relationship with Report.user referencing User.id (on_delete=CASCADE) Access: user.report or report.user	

E). **API Endpoints** (with CORS):

API URL	METHODS	What does it do ?	Linked to FE
/api/	GET	Returns list of all available API URLs	❌
/api/users/token/	POST	Get JWT tokens	✅ login form
/api/users/token/refresh/	POST	Refresh JWT token	✅ auth.js
/api/users/token-from-session/	GET	Convert session to JWT	✅ auth.js
/api/projects/	GET	Gets all videos/projects	❌
/api/projects/<id>/	GET	Gets single video/project	❌
/api/debug-videos/	GET	Debug information about all videos	❌
/api/projects/<id>/stream/	GET	Streams video content in chunks	✅ video-player.html
/api/projects/<id>/like/	GET POST	Gets like status and counts, Toggles like/dislike	✅ api_like_dislike.js ✅ api_like_dislike.js
/api/projects/<id>/reviews/	GET POST	Gets all comments for a video Creates new comment	✅ api_comments.js ✅ api_comments.js
/api/projects/<id>/reviews/<review_id>/	PUT DELETE	Updates a comment Deletes a comment	✅ api_comments.js ✅ api_comments.js
/api/projects/<id>/reviews/stream/	GET	Streams comments (real-time)	✅ api_comments.js
/api/users/<id>/follow/	POST	Toggle follow/unfollow & return stats	✅ api_follow.js ✅ api_profile_follow.js
/api/video-stats/	POST	Sending Video Stats to BE at logout	✅ video_player.js
/api/generate-report/	POST	Generate reports (user,video) using Gemini AI	✅ analytics.html(for now)
/api/generate-speech/	POST	Generate audio reports using VITS (AI)	✅ tts-utils.js
/api/audio/<profile_is>/<report_type>	GET	Serves audio from BE to FE	✅report.html
/api/check–tts-status/<username>	GET	Checks tts generation status from FE to BE	✅ tts-utils.js

F). **Video & User Data Analytics:**

ANALYTICS HUB	
USER DATA ANALYSIS	**VIDEO DATA ANALYSIS**
User Behaviour Pattern Follower Based for Creators (A & D)	Views Based for Creators Follower Based for Creators (B) Content Performance Metrics Engagement Based for Creators Demographic Based for Creators


ANALYTICS & VISUALIZATION TYPES		
i. Views Based for Creators	**ii. Follower Based for Creators**	**iii. User Behaviour Pattern**
A. Total Views of all vids ✔️ B. Daily Views for each vid ✔️ C. Hourly Views for each vid ✔️ D.Peak Viewing Time ✔️ E.Peak Viewing Day ✔️	A. Follower growth over time ✔️ B. Follower engagement metrics ✔️ C. Follower retention statistics ❓ D Follower/Following basic stats ✔️	A. Heat map: DAYS vs HOURS ✔️ B. Visits to the Users Profile ✔️ C. Navigation patterns 🔒⌛ D. Word cloud: Popular Search terms ❓ E.Avg vs User's Time spent on platform ✔️ F. Users Average Session Length ✔️
iv. Engagement Based for Creators	**v. Content Performance Metrics for Creators**	**vi. Demographic Based for Creators**
A. Total like-dislike for all videos ✔️ B.Total Comments for all videos ✔️ C. Total shares for all videos ❓ D. Watch time patterns ❓ E. Viewer retention rates ❓ F. Engagement/drop-off points ❓	A. Avg. Video completion rates ✔️ B. Average watch duration ✔️ C.Audience retention graphs ❓ D.Avg. Watch Time for all videos ✔️ E.Avg. completion rate for all videos ✔️	A. Age Distribution-all Viewers/followers ❓ B. Gender Distri.- all Viewers/followers ❓ C. Location Distri. - all Viewers/followers ❓

POSSIBLE FUTURE IMPLEMENTATIONS	
FRONTEND TRACKING 🖥️	**BACKEND IMPLEMENTATION 🔚**
□ Add JavaScript tracking code □ Set up event listeners for: - Page load/unload - User interactions - Scroll tracking	□ Add Sentiment Analysis for comments □ Add Predictive Analysis

G). **Analytics Visualization & Calculations:**

Data Type	Visualization Name	No. of Queries	Visualization Type	Source Table (DB)	Calculating Technique	Index
User	Your Activity for the Past 30 Days	1 Q/User	Heat Map	UserSession	Real - Time	✅
User	Your Total Activity, Visits to Your Profile, Your Average Session Length, Total Following, Total Followers	1 Q/User	Numbers	UserActivitySummary	Denormalization	✅
User	Average User Activity	1 Q/User	Numbers	UserActivitySummary	Denormalization	✅
User	Follower Growth (Number), Follower Growth (Graph),	1 Q/User	Number, Line Graph	Follow	Real - Time	✅
Video	Follower/Non-follower - Likes, Follower/Non-follower - Comments, Follower/Non-follower - Dislikes, Follower/Non-follower - Views	4 Q/User	Pie Charts	Follow, Like, View, Review	Real - Time	✅
Video	Total Views, Likes & Dislikes, Comments, Watch Time, Completion Rate	1 Q/User 0 Q/Use	Line Graph, Bar Graphs	VideoAnalytics	Denormalization	✅
Video	Daily Views, Hourly Distribution,	1 Q/User 1 Q/User	Line Graphs	ViewHistory	Real - Time	✅
Video	Peak Viewing Time, Peak Viewing Day	1 Q/User 1 Q/User	Numbers	ViewHistory	Real - Time	✅
Video	Avg. Watch time of all videos, Avg. Completion Rate of all videos	0 Q	Numbers	VideoAnalytics	Denormalization	✅

H). **Caching Strategy:**




Server Side Global Redis Caching -

1. Multiple users hitting Django server
2. Server checks **Redis Global Cache** first (DB1)
3. Cache hit → return data
4. Cache miss → get from Django DB
5. Store fresh data in cache
6. Return to user

Rules for the Uncached Views in Users App				
🟢 Cache Duration: (Data Type and Duration)	🟢 Monitor: (Cache & DB)	🟡 Cache only after Monitoring (future)	🔴 Don't Cache: (Sensitive Data, Too User-Specific)	
Real-Time Data: 1-5 minutes Regular Data: 1 hour - 10 mins Static Data: 24 hours or NONE	Cache hits/misses Cache Memory usage Cache Error Rates DB Queries DB “Read/Write” ratio	inbox view:	login, logout_user Register_user clear_temp_tokens user_videos viewer history	Update_profile , Create_message, View_message Creator_studio: analytics:, settings:

Type of Data being Cached in Redis (DB1)	**Cache Function**	**Policy**	**TTL**
Major Studio Box Office Data (/fun_corner)(Static)	get_studio_data	Cache-Aside	24 hrs
Current Movies Playing Data (/fun_corner)(Static)	get_current_movies	Cache-Aside	24 hrs
Movie Recs Trained Model (/fun_corner)(Static)	get_movie_recs_model	Cache-Aside	24 hrs
Tracking & Recording Views of vid (/project)(Real-Time)	can_record_view	Time-Based	5 mins
Context of a Vid (title,tags,desc.,etc)(/project)(Regular)	set_context	• Read-Through • Cache Invalidation on Write	15 mins
Form key to stop multiple submit (All form submit views)(Real-Time)	set_submission	Time-Based	1 min
Profile Info of User(name,socials,etc,)(/profile)(Regular)	set_profile_cache	• Read-Through • Cache Invalidation on Write	10 mins
User Session Activity - Log (users/middleware)(Static)	add_page_visit	• Write-Behind • Cache flush & Invalidation on Logout	24 hrs
Video Stats (watch duration,is_completed)(users/middleware)(Static)	set_video_stats	• Write-Behind •Cache flush & Invalidation on Logout	24 hs
Session Lock (users/middleware)(Real-Time)	acquire_lock	Time-Based	1 min

I). **System Architecture:** (https://tinyurl.com/sys-archew)



This architecture represents a classic monolithic design where all components are tightly integrated within a single Django application. Here's why it's monolithic:

1. Single Application Integration: All components (Web Layer, Core Apps, Services) exist within one Django project, Services directly communicate with each other within the same application space, Shared database and storage resources, Single deployment unit.

2. Vertical Structure: The architecture flows from top (Client) to bottom (Storage), Each layer directly depends on the layers below it, Tightly coupled components where Services can directly access the database

3. Shared Resources: Single database (SQLite) serving all services, Shared media storage for all file operations , Common Redis instance for caching and message brokering, Unified authentication system (JWT and Session)

SWITCH FROM MONOLITH TO MICROSERVICES ONLY WHEN THE TEAM GROWS IN SIZE AND DEVELOPERS START STEPPING ON EACH OTHER'S TOES. IT'S FINE TO START AS A MONOLITH AND THEN SWITCH EVENTUALLY.

This monolithic approach has advantages for this application:

- Simpler development and deployment, Easier debugging as all code is in one place
- Direct database access without network overhead
- Simpler transaction management
- Suitable for the application size and complexity
- The architecture is well-organized within its monolithic constraints, using clear separation of concerns (Web, Services, Storage) while maintaining the benefits of a unified system.

J). **Settings Configurations & Keys:**

<table>
<tr><td>SMTP</td><td>Google SMTP</td><td>Mailtrap SMTP</td></tr>
<tr><td></td><td>EMAIL_HOST = 'smtp.gmail.com'
EMAIL_PORT = 587
EMAIL_USE_TLS = True
EMAIL_HOST_USER = 'filmsnation99@gmail.com'
EMAIL_HOST_PASSWORD = 'iipo pjsw mhjv aumx'</td><td>EMAIL_HOST = 'sandbox.smtp.mailtrap.io'
EMAIL_PORT = 2525
EMAIL_USE_TLS = True
EMAIL_HOST_USER = '325d9889579e2a'
EMAIL_HOST_PASSWORD = '51ca0096774d01'</td></tr>
<tr><td>DATABASE</td><td>Local - SQLite3</td><td>Local - PostgreSQL</td><td>D.O - PostgreSQL</td></tr>
<tr><td></td><td>DATABASES = {
"default": {
"ENGINE": "django.db.backends.sqlite3",
"NAME": BASE_DIR / "db.sqlite3",
}
}</td><td>DATABASES = {
"default": {
"ENGINE": "django.db.backends.postgresql",
"NAME": "testrun",
"USER": "saketmanolkar",
"PASSWORD": "Clarion67@123",
"HOST": "localhost",
"PORT": "5432",
}
}</td><td>DATABASES = {
"default": {
"ENGINE": "django.db.backends.postgresql",
"NAME": "defaultdb", # DigitalOcean default database name
"USER": "doadmin", # DigitalOcean default admin user
"PASSWORD": "AVNS_BXYkKwtVzCb-jcasNTY", # Use your actual password
"HOST": "db-postgresql-testrun-do-user-18917001-0.l.db.ondigitalocean.com",
"PORT": "25060",
"OPTIONS": {
"sslmode": "require",
"sslrootcert": os.path.join(BASE_DIR, "cert", "ca-certificate.crt"),
}
}
}</td></tr>
<tr><td>REDIS</td><td>Local</td><td>D.O - Redis</td></tr>
<tr><td></td><td>REDIS_URL = os.environ.get('REDIS_URL', 'redis://127.0.0.1:6379')</td><td>REDIS_URL = os.environ.get('REDIS_URL', 'rediss://default:AVNS_VfAUOUeuEylqQuNwZJK@db-caching-nyc3-18707-do-user-18917001-0.k.db.ondigitalocean.com:25061')</td></tr>
<tr><td>STATIC & MEDIA DEILIVERY</td><td>Local</td><td>D.O - Spaces</td></tr>
<tr><td></td><td># Use local storage for testing
MEDIA_URL = '/media/'
MEDIA_ROOT = os.path.join(BASE_DIR, 'media')
DEFAULT_FILE_STORAGE = 'django.core.files.storage.FileSystemStorage'
Define video upload path
VIDEO_UPLOAD_PATH = os.path.join(MEDIA_ROOT, 'videos')
Create necessary media directories if they don't exist
MEDIA_DIRS = [
os.path.join(BASE_DIR, 'media'),
os.path.join(BASE_DIR, 'media', 'videos'),
os.path.join(BASE_DIR, 'media', 'thumbnails'),
os.path.join(BASE_DIR, 'media', 'reports'),
os.path.join(BASE_DIR, 'media', 'profiles'),
]
for dir_path in MEDIA_DIRS:
os.makedirs(dir_path, exist_ok=True)
Create video upload path
os.makedirs(VIDEO_UPLOAD_PATH, exist_ok=True)</td><td># DigitalOcean Spaces configuration
AWS_DEFAULT_ACL = 'public-read'
AWS_QUERYSTRING_AUTH = False
AWS_FILE_OVERWRITE = False
AWS_ACCESS_KEY_ID = 'DO801ZRMXFKTEYBYXUQK'
AWS_SECRET_ACCESS_KEY = 'p9hW6mweseMZLNpFTdCqjWo1324WVXvCIKLMogKK3Q0'
AWS_STORAGE_BUCKET_NAME = 'bucket-devserach'
AWS_S3_REGION_NAME = 'nyc3'
AWS_S3_CUSTOM_DOMAIN = 'bucket-devserach.nyc3.cdn.digitaloceanspaces.com'

Fixed endpoint URL - this was incorrect before
AWS_S3_ENDPOINT_URL = 'https://nyc3.digitaloceanspaces.com'

Use DigitalOcean Spaces in production
DEFAULT_FILE_STORAGE = 'storages.backends.s3boto3.S3Boto3Storage'
MEDIA_URL = f'https://{AWS_S3_CUSTOM_DOMAIN}/'</td></tr>
<tr><td>GEMINI API</td><td colspan="2">AIzaSyBOB5FpLu0hsHrfZuML-6VfrKVck1W8xP4</td></tr>
</table>

K). **Testing:**

MAJOR FUNCTIONALITIES TO TEST			
Video Managemen:	**User Authentication:**	**Analytics;**	**API Endpoints:**
Video upload functionality Video processing functionality Video playback functionality Video CRUD operations Permissions on video access	User registration Login functionality Logout functionality Password reset processes User permission checks	View count calculation Watch time tracking Analytics data aggregation AI Report generation	Request validation Response formatting Authentication for API requests Rate limiting functionality
Social Features:	**Search & Discovery:**	**Caching Logic:**	**Playlists:**
Following/follower functionality Like/dislike mechanics Comment systems Messaging systems	Search functionality Recommendation algorithms Filtering and sorting	Cache invalidation Cache hit/miss behavior Cache data consistency	Creating playlists modifying playlists Adding/removing videos

TESTING TYPES					
Integration test	**View tests**	**Form tests**	**Unit tests**	**Model tests**	**Template tests**
Testing how components work together	Testing HTTP responses	Testing form validation	Testing individual functions or methods	Testing model behavior	Testing rendered HTML

FUNCTIONALITY		TEST TYPE
User Authentication	Login functionality Logout functionality User registration	Integration Test
Video Management	Video upload functionality	Integration Test
Video Management	Video processing functionality	Integration Test
Video Management	Video playback functionality Permissions on video access	Integration Test
Social Features	Following/follower functionality Like/dislike mechanics Comment systems	Integration Test

L). **Infrastructure Cost Breakdown:**

HIGH LEVEL - CLOUD TESTING COST			
SERVICE	**COMPANY**	**COST & DURATION**	**ACQUIRED**
Domain	Namecheap	Free ".me" domain for a year	✔️
Cloud Infrastructure	Digital Ocean	Free 200 $ worth credits for a year	✔️
Hosting	Digital Ocean - Application Platform	25 $/month	❓
Redis (Caching)	Digital Ocean - Databases	15 $/month	✔️
PostgreSQL (Database)	Digital Ocean - Databases	15.15 $/month	✔️
Static & Media Files Delivery w/ CDN	Digital Ocean - Spaces	5 $/month	✔️

D.O - Databases (PostgreSQL)			
Start Date	End Date	Duration	Cost
March 5, 2025	April 5 , 2025	1 Month	$15.15

D.O - Databases (Redis)			
Start Date	End Date	Duration	Cost
March 13, 2025	April 13, 2025	1 Month	$15

D.O - Spaces			
Start Date	End Date	Duration	Cost
March 5, 2025	April 5 , 2025	1 Month	$5

D.O - App Platform			
Start Date	End Date	Duration	Cost

Domain - saketmanolkar.me			
Start Date	End Date	Duration	Cost
Jan 27, 2025	Jan 27, 2026	1 year	$0

M). **Terminal Commands:**

TERMINAL COMMANDS	FUNCTIONALITY	TERMINAL COMMANDS	FUNCTIONALITY
python manage.py runserver 0.0.0.0:8000	*Network Testing RunServer*	celery -A testrun flower	*Starts Flower Dashboard*
python manage.py flush	*This will delete all data but maintain your db structure*	pkill -f celery	*Stop all Celery workers and Flower*
python manage.py createsuperuser	*This will make a superuser*	pkill -f -9 celery	*Stop more forcefully*
redis-server	*Starting Redis - Local*	python manage.py test users.tests --keepdb python manage.py test projects.tests --keepdb	*Running tests without dropping DB*
redis-cli flushall	*Flush Redis - Local*	python manage.py validate_analytics	*Validate User Activity Table*
redis-cli shutdown	*Shutdown Redis - Local*	python manage.py validate_video_analytics	*Validate Video Analytics Table*
redis-commander	*Starts Redis Commander - Local*	python manage.py rebuild_analytics	*Rebuild Video Analytics Tab*
redis-cli info	*General Redis Information - Local*	python manage.py build_activity_summary	*Rebuild User Activity Tab*
redis-cli info memory	*Redis Memory Information - Local*	dockerfile-django generate	*Auto generation of Docker File*
redis-cli memory stats	*Shows Redis Memory Stats - Local*	docker stop $(docker ps -a -q)	*Stop all running containers*
redis-commander \ --redis-host db-caching-nyc3-18707-do-user-18917001-0.k.db.ondigitalocean.com \ --redis-port 25061 \ --redis-password AVNS_VfAUOUeuEylqQuNwZJK \ --redis-tls \ --redis-db 0	*Starts Redis Commander - Cloud Redis*	docker rm $(docker ps -a -q)	*Remove all containers*
redis-cli -h db-caching-nyc3-18707-do-user-18917001-0.k.db.ondigitalocean.com \ -p 25061 \ --tls \ --insecure \ -a AVNS_VfAUOUeuEylqQuNwZJK \ SHUTDOWN	*Shutdown Redis - Cloud*	docker rmi $(docker images -q)	*Remove all images*
redis-cli -h db-caching-nyc3-18707-do-user-18917001-0.k.db.ondigitalocean.com \ -p 25061 \ --tls \ --insecure \ -a AVNS_VfAUOUeuEylqQuNwZJK \ INFO	*General Redis Information - Cloud*	docker volume prune -f	*Remove unused volumes*
redis-cli -h db-caching-nyc3-18707-do-user-18917001-0.k.db.ondigitalocean.com \ -p 25061 \ --tls \ --insecure \ -a AVNS_VfAUOUeuEylqQuNwZJK \ MEMORY STATS	*Shows Redis Memory Stats - Cloud*	docker network prune -f	*Remove unused network*
redis-cli -h db-caching-nyc3-18707-do-user-18917001-0.k.db.ondigitalocean.com \ -p 25061 \ --tls \ --insecure \ -a AVNS_VfAUOUeuEylqQuNwZJK \ INFO MEMORY	*Redis Memory Information - Cloud*	docker builder prune -a -f	*Remove build cache*
redis-cli -h db-caching-nyc3-18707-do-user-18917001-0.k.db.ondigitalocean.com \ -p 25061 \ --tls \ --insecure \ -a AVNS_VfAUOUeuEylqQuNwZJK \ FLUSHALL	*Flush Redis - Cloud*	docker-compose build --no-cache	*Now rebuild your application*
celery -A testrun worker -l info	*Starts Celery Worker*	docker-compose up	*Start your application*

N). **GitHub WorkFlow:**

<table>
<tr>
<td rowspan="2">+ To get the exact repository state from remote to your local

Check current branches (*indicates current branch)
> git branch

First switch to remote branch (if not already there)
> git checkout branch-name

Fetch all changes from remote
> git fetch origin

Hard reset to the remote branch
> git reset --hard origin/branch-name

(if needed)

Remove the database
> rm db.sqlite3

Remove all migration files except __init__.py
> rm app-name/migrations/0*.py

Make new migrations and apply them
> python manage.py makemigrations
> python manage.py migrate

Create a superuser
> python manage.py createsuperuser</td>
<td>1.Initial Status and Feature Branch Work

Check current branches (*indicates current branch)
> git branch

Stage all changes
> git add .

Commit changes with message
> git commit -m "your message"

Push feature branch to remote
> git push origin feature/branch-name</td>
<td>2. Update Main Branch

Switch to main branch
> git checkout main

Pull changes from develop to main
> git pull origin develop

Push changes to main
> git push origin main

#If rejected:
sync with remote main
> git pull origin main

try pushing again
> git push origin main</td>
<td>3.Update Develop Branch

Switch to develop
> git checkout develop

Get latest changes
> git pull origin develop

Merge feature branch into develop
> git merge feature/branch-name

Push updated develop
> git push origin develop</td>
</tr>
<tr>
<td>4.Clean Up Feature Branch

Delete local feature branch
> git branch -d feature/branch-name

Delete remote feature branch
> git push origin --delete feature/branch-name</td>
<td>5.Start New Feature Branch

Create and switch to new feature branch from develop
> git checkout develop
> git checkout -b feature/new-branch-name

Push new branch to remote and set tracking
> git push -u origin feature/new-branch-name</td>
<td>6.Final Sync


Get all remote updates
> git fetch --all

Pull updates for all branches
> git pull --all


Verify branch structure
> git branch</td>
</tr>
</table>

O). **Functionalities Explanation:**

- **Video Upload Pipeline with task queue Implementation**
  (https://tinyurl.com/videoupload122)



- **Using Middleware to implement Session Activity Logging to DB**
(https://tinyurl.com/middlew-ple34)



- **Authentication using JWT & Session cookies**

The authentication system uses a hybrid approach combining both traditional Django sessions and JWT tokens. Here's how it works:

When a user logs in through the login_user view, two things happen simultaneously. First, Django's session authentication is initiated with login(request, user), which creates a session cookie for the user. At the same time, JWT tokens (both access and refresh) are generated using RefreshToken.for_user(user) and sent back to the client in a JSON response. These tokens are then stored in the browser's localStorage.

For ongoing authentication, your system is flexible. Traditional Django views can rely on the session cookie for authentication, while API endpoints can use the JWT tokens. This is why your API views have both JWTAuthentication and SessionAuthentication in their authentication classes. When making API requests, the frontend includes the JWT token in the Authorization header, but the session cookie is also present for traditional requests.
During logout, handled by logout_user, the system cleans up both authentication methods. The Django session is cleared using logout(request), and a special cookie is set that triggers JavaScript to clear the JWT tokens from localStorage. This ensures both authentication methods are properly terminated.

The registration process implements a hybrid authentication approach. When a user registers through register_user, it generates both a traditional Django session with login(request, user) and JWT tokens using RefreshToken.for_user(user). The tokens are temporarily stored in the session and then transferred to localStorage via a script in the profile update template. This ensures the user has immediate access to both regular web views (via session) and API features like likes, comments, and follows (via JWT) without needing to log in separately. The system seamlessly handles both web and API authentication from the moment of registration.

- **Video Streaming Implementation Process**

Our video streaming implementation follows a sophisticated process that efficiently delivers video content from server storage to end users. The process begins when a user requests a video through our web interface. Instead of loading the entire video file into memory, as was done in our previous implementation, we now utilize a chunked streaming approach.
When the video player initializes, it first requests only the video metadata. This metadata includes information about the video duration, dimensions, and available quality versions. The server, through our VideoService, determines the appropriate version of the video to serve, typically defaulting to 720p if available, with fallback options to other qualities or the original file if necessary.

As playback begins, the video player sends HTTP range requests to our server. These requests specify exactly which portions of the video file are needed at any given moment. Our stream_video view function processes these requests, using the file_iterator to read the video file in small, manageable chunks of 8KB (8192 bytes). This chunked approach means that only a small portion of the video is held in memory at any given time, significantly reducing server resource usage.

The file_iterator function is central to our streaming process. When it receives a range request, it opens the video file, seeks to the specified position, and yields data in controlled chunks. This streaming process continues throughout the video playback, with the player requesting new chunks as needed. For seeking operations, when a user jumps to a different part of the video, the player simply sends a new range request for that specific portion of the file.

Our implementation includes built-in support for quality management through encoded versions of each video. The ModelService handles the URL generation for these different quality versions, while the VideoService manages the overall video delivery process, including view counting and caching of video context data. This service-oriented architecture ensures clean separation of concerns and maintainable code.

The actual delivery of video content to the client is handled through Django's StreamingHttpResponse, which maintains an open connection to stream the video chunks. The response includes proper HTTP headers for content range and length, allowing the client's video player to properly handle the incoming stream. This streaming response is crucial for efficient memory usage and proper handling of large video files.

On the frontend, we utilize the Video.js player, which is configured to handle these chunked streams efficiently. The player maintains its own buffer of video data, requesting new chunks as needed based on the user's playback position and network conditions. Our custom CSS ensures proper video display regardless of the video's original dimensions, maintaining aspect ratios while providing a consistent user interface.

This entire process represents a significant improvement over traditional video serving methods. Where previously we would load entire video files into memory, potentially causing server strain with multiple concurrent users, we now handle video delivery in a memory-efficient, scalable manner. The chunked streaming approach, combined with quality management and proper range request handling, provides a smooth, efficient video playback experience while maintaining server stability under load.

The end result is a robust video streaming system that efficiently manages server resources while providing users with smooth, high-quality video playback. The system handles everything from initial video request through continuous playback and seeking operations, all while maintaining minimal memory footprint and optimal performance characteristics.

● Dynamic Comment Section

The dynamic comments system represents a sophisticated approach to real-time user interaction in our video platform. Unlike traditional comment systems that require page refreshes, our implementation provides a seamless, single-page application experience while maintaining data consistency and user engagement.

When a user first loads a video page, the system initializes by embedding existing comments directly into the page's HTML. This initial state is cleverly stored in a hidden input element as JSON data, allowing immediate access to comments without additional server requests. This approach significantly reduces initial load time and provides a smooth user experience from the moment the page loads.

The heart of our commenting system lies in its event handling architecture. Rather than attaching individual event listeners to each button or element, we implement a central event delegation system. This system captures all click events at the document level and determines the appropriate action based on the clicked element. This approach not only improves performance but also handles dynamically added content without requiring additional event binding.

Comment creation follows a sophisticated process. When a user clicks the "Add Comment" button, the system smoothly reveals a comment form. As the user types and submits their comment, our JavaScript handler intercepts the form submission, preventing the default page reload. Instead, it packages the form data and sends it to the server via an AJAX request. The server processes this request, stores the comment in the database, and returns the formatted comment data. The frontend then seamlessly inserts this new comment into the page's DOM, providing immediate visual feedback to the user.

The editing and deletion processes follow similarly sophisticated patterns. For comment owners, edit and delete buttons appear alongside their comments. Clicking edit transforms the comment text into an editable form, while delete triggers a confirmation modal. Both actions communicate with the server asynchronously, updating the UI only after successful server responses. This ensures data consistency while maintaining a responsive user interface.

Our backend architecture centers around the Review model, which stores essential comment data including the comment text, user reference, video reference, and timestamps. Each comment is assigned a unique UUID, ensuring reliable identification across the system. The model's structure supports efficient querying and maintains proper relationships between users, videos, and comments.

The server-side implementation includes robust view functions that handle comment creation, updates, and deletion. These views incorporate proper authentication checks, ensuring that users can only modify their own comments. They return JSON responses that the frontend can easily process and display. The system also includes protection against common issues like double submissions and race conditions.

The frontend JavaScript code is organized around clear responsibilities. The createCommentRow function handles the HTML generation for comments, ensuring consistent formatting. The handleSubmit function manages form submissions, including preventing double submissions and providing user feedback. The system also includes sophisticated error handling, displaying appropriate messages to users when issues occur.

This entire system works together to provide a modern, responsive commenting experience. Users can interact with comments instantly, seeing their changes reflected immediately while the system ensures all data is properly synchronized with the server. The implementation balances performance, user experience, and data integrity, creating a robust platform for user engagement through comments.

The result is a commenting system that feels natural and responsive, encouraging user interaction while maintaining data consistency and system reliability. Through careful architecture and modern web technologies, we've created a seamless experience that enhances the overall video platform functionality.