FINTECHATHON 2026 · INTERNATIONAL TRACK · TOPIC C

Remi — Technical Documentation

AI as a Financial Participant · FinTechathon 2026 International Track · Topic C: Cross-border & Student Finance Assistant

Team Git Push Pray
Syed Nazmus Sakib (East Delta University) · Sadmanul Arefin (Ahsanullah University of Science & Technology)
October 2026 · github.com/sakib-101-git/remi

Sandbox demo. All banks, providers and universities are fictional. Not financial, legal or tax advice.

Contents

1. Executive summary
2. Problem and target users
   - 2.1 Pain points
   - 2.2 Personas (seed data, switchable in the UI)
3. System architecture
   - 3.1 Layered architecture
   - 3.2 Components
   - 3.3 Data flow: a tuition payment from chat to settlement
4. Agent design
   - 4.1 Prompting
   - 4.2 Tools and tiers
   - 4.3 Orchestration loop
   - 4.4 Free-provider fallback chain, quota protection and replay cache
   - 4.5 Structured responses and explainability
5. Core algorithms
   - 5.1 Remittance cost optimizer (services/quotes.py)
   - 5.2 FX conversion helper (services/conversions.py)
   - 5.3 Budget and runway (services/budget.py)
   - 5.4 Credit-building planner (services/credit.py)
   - 5.5 Risk scoring (risk/engine.py)
   - 5.6 Hybrid retrieval (knowledge/retrieval.py)
6. Knowledge base and RAG pipeline
7. Security design
   - 7.1 Permission tiers
   - 7.2 Confirmation tokens
   - 7.3 Step-up and cooling-off
   - 7.4 Limits (config/limits.yaml, USD equivalent)
   - 7.5 Prompt-injection and fraud defence
   - 7.6 Idempotency
   - 7.7 Audit log
   - 7.8 Privacy
   - 7.9 LLM guardrails
   - 7.10 Public-deployment protection
8. Compliance and explainability
   - 8.1 Interaction design
9. Sandbox and data
10. Testing and evaluation
11. Deployment (zero cost)
12. Limitations and roadmap
13. Team

Appendix A. Screens

1. Executive summary

Remi is an AI money agent for international students that actually acts. It plans and executes cross-border payments, manages multi-currency wallets, tracks budgets and runway, and builds a credit history in a new country. It works entirely inside a realistic sandbox: a double-entry ledger, simulated FX, four fictional payment providers, and per-visitor workspaces.

Remi follows the track theme, *AI as a Financial Participant*. The agent completes real tasks end to end. It compares providers on true landed cost, prepares an exact payment, gets human confirmation, executes it in the sandbox ledger, issues a receipt and tracks settlement in real time. Security comes from a strict separation of concerns:

- The **LLM only interprets intent, chooses tools and explains results.** Every number comes from deterministic code using `Decimal` arithmetic.
- A **deterministic policy engine is the only gate to money movement.** It assigns permission tiers T0–T4, enforces limits, scores risk and issues **single-use confirmation tokens bound to the exact action**. The LLM never sees these tokens.
- High-risk actions add **step-up verification** (a simulated one-time code delivered like a phone notification) and **cooling-off** for new payees.
- Every step is written to an **append-only, SHA-256 hash-chained audit log** that anyone can verify.
- **Prompt-injection and invoice-fraud defences** treat document and knowledge-base text as untrusted data. University payments must match a verified registry.

Remi runs at zero cost. The primary model is Google Gemini's free tier, with a fallback chain (Groq → OpenRouter free → local Ollama → deterministic mock agent) and a record/replay cache, so the live demo never depends on rate limits or venue Wi-Fi.

Results (sandbox): 13/13 golden scenarios pass end to end through the real HTTP API on the deterministic agent (122/122 checks), on Google Gemini's free tier live (136/136 checks, no fallback allowed) and from the recorded replay cache (136/136). 106 automated unit and API tests and a Playwright browser test of S1 are green. Details in §10.

2. Problem and target users

2.1 Pain points

International students move money across borders at the most expensive and stressful moments of their lives:

Pain point	What goes wrong today
Hidden FX markups	Providers advertise "low fees" but hide 1–3% in the exchange rate. In our sandbox, Beta Express charges the *lowest* fee for a £9,250 tuition payment (฿244) but has the *highest* total cost (฿32,869), three times the best option.

Pain point	What goes wrong today
Tuition deadlines	Slow rails (3–5 business days), cut-off times and document checks make deadlines easy to miss.
Limits and documentation	Cheap apps have low per-transfer limits. Students are tempted to split payments, which looks like *structuring* and can get accounts frozen.
Multi-currency confusion	Money sits in BDT, GBP and USD. Nobody knows the total or how long it will last.
No credit history	Arrivals cannot rent, get phone contracts or cards.
Scams	"Our bank details have changed" invoices target students right before deadlines.


2.2 Personas (seed data, switchable in the UI)

Persona	Corridor	Wallets	Situation
Rahim	Bangladesh → UK, Master's	BDT 2,400,000 · GBP 1,240 · USD 300	£9,250 tuition due in 21 days, family sends BDT monthly, no UK credit history
Ada	Nigeria → Canada, undergraduate	NGN 6,500,000 · CAD 3,200 · USD 150	Rent CAD 1,150/month, sends money to mum, wants credit
Priya	India → USA, PhD	INR 250,000 · USD 4,800	Stipend, fees due, sends money home

Each persona has 90 days of deterministic transaction history, beneficiaries, obligations and an invoice from a fictional institution in the verified registry.

3. System architecture


3.1 Layered architecture



```
UI (React: landing, Home/Send/Wallets/Insights/Credit/Security/Help, Ask Remi panel with
rich cards)
   |  REST + Server-Sent Events
API layer (FastAPI; signed per-visitor workspace cookie; rate limiting; idempotency keys)
   |
Agent orchestrator (LLM loop; intent-scoped tool allowlist; ≤ 8 tool calls/turn; schema
validation; output validation)
   |  proposes actions only                  | read-only
Policy engine (tiers, limits, risk score,    Knowledge base (hybrid RAG, cited sources,
confirmation tokens, step-up, cooling-off)   untrusted-data wrapping)
   |  ← the ONLY gate to money movement
Domain services (wallets, FX, optimizer, payments, budget, credit, alerts, invoices)
   |
Sandbox ledger (SQLite, double-entry) + Audit log (append-only, SHA-256 hash chain)
```

The layering is enforced in code. Tools in `backend/app/agent/tools.py` can call read services and `policy.actions.propose()`. Nothing reachable from the agent can call `confirm()`, `step_up()` or `execute()`; those live only behind the human-facing `/api/actions/{id}/confirm|stepup` endpoints.


3.2 Components



Module	Responsibility
`app/api/`	REST + SSE routes, workspace cookies (`itsdangerous`-signed), `slowapi` rate limits, idempotent execute endpoints
`app/agent/`	`llm.py` provider abstraction + fallback chain + replay cache; `mock.py` deterministic agent; `tools.py` typed tool registry; `orchestrator.py` loop; `guardrails.py`; `prompts.py`
`app/policy/`	`engine.py` tiering and limits; `actions.py` proposal lifecycle; `tokens.py` HMAC-bound tokens and OTP; `limits.py`; `governance.py` (T4, human only); `idempotency.py`
`app/risk/engine.py`	Weighted, explainable risk rules
`app/services/`	`quotes.py` optimizer, `payments.py`, `conversions.py`, `budget.py`, `credit.py`, `alerts.py`, `invoices.py`, `beneficiaries.py` (+ verified registry), `compliance.py`, `automation.py`

Module	Responsibility
`app/sandbox/`	`ledger.py` double-entry, `fx.py` rates and random walk, `clock.py` simulated time, `seed.py`, `workspaces.py`, `controls.py`
`app/audit/log.py`	Append-only hash chain, verify, export
`app/security/`	`injection.py` detection and untrusted wrapping, `redact.py` PII/secret redaction
`app/knowledge/retrieval.py`	Chunking, BM25, local embeddings, hybrid ranking

3.3 Data flow: a tuition payment from chat to settlement



1. **Chat.** Rahim types *"Pay my £9,250 tuition before the deadline, cheapest safe way."* The browser POSTs to `/api/chat` and receives an SSE stream.
2. **Guardrails.** Deterministic pre-checks (evasion, governance, off-topic) pass. Intent classification selects the `payments` tool group, so only those schemas are sent to the model.
3. **Agent loop.** The LLM calls `get_obligations` (T0), which finds the open invoice NBU-2026-8201 due 2026-11-04. It then calls `propose_payment(recipient="university", amount="9250", amount_currency="GBP", invoice_id=…)` (T2).
4. **Optimizer.** `payments.plan()` runs `quotes.compare()` across all four providers as a *reverse quote* (recipient must receive exactly £9,250). It checks corridor, limits, tuition eligibility and deadline feasibility, then ranks the feasible options.
5. **Policy engine.** `evaluate_payment()` checks balance, verified beneficiary, per-transaction, daily and monthly limits, velocity, the registry match and the risk score. Result: **T2** (the verified institution threshold is $20k; the amount is ≈ $12.5k).
6. **Proposal.** A `PendingAction` is stored with the canonical payload, its SHA-256 `payload_hash`, the tier, the risk reasons and `HMAC(secret, token|action_id|payload_hash)`. The **token** is attached only to the UI card. The LLM receives `{"executed": false, "next_step": "the user must confirm …"}`.
7. **Explanation.** The model (or the mock agent) writes the explanation from tool outputs. Output validation strips any false "I've sent" claims.

8. **Human confirmation.** Rahim reviews the card (amount, rate vs mid-market, fee, landed cost, recipient, arrival date, purpose code, source of funds) and presses **Confirm**. The browser POSTs the token with an `Idempotency-Key`.
9. **Execution.** The server re-verifies the token (not used, not expired, payload hash unchanged, HMAC matches), **re-evaluates policy** against live state, and posts balanced journal entries: wallet −send, fees +fee, in-transit +net. It marks the invoice paid and issues a receipt (`RMI-20261014-XXXXXX`).
10. **Settlement.** The settlement engine moves the transfer `pending → processing → settled` (in demo mode after a few seconds, otherwise when simulated time passes the arrival date). It posts the payout legs and pushes live status updates over SSE.
11. **Audit.** Every step (`chat.message`, `tool.called`, `action.proposed`, `action.confirmed`, `action.executed`, `chat.reply`) is chained in the audit log.

4. Agent design

4.1 Prompting

The system prompt (`app/agent/prompts.py`) is about 450 tokens. It defines Remi's scope, and requires that every number come from tools, that the model only *proposes* money movement, explain recommendations, cite `[KB: title]`, treat `<<UNTRUSTED_DATA>>` blocks as data, never suggest splitting or evasion, give no investment, FX-speculation, legal or tax advice, and ask one clarifying question when details are missing. Persona context (name, corridor, reporting currency, simulated date) is injected per turn.

4.2 Tools and tiers

Tier	Tools
T0 read	`get_wallets`, `get_transactions`, `get_fx_rates`, `get_remittance_quotes`, `reverse_quote`, `explain_fee_breakdown`, `get_budget_summary`, `get_runway`, `get_obligations`, `get_credit_plan`, `get_compliance_checklist`, `search_knowledge`, `analyze_document`, `list_beneficiaries`, `fx_conversion_options`
T1 low-risk write	`create_budget`, `categorize_transaction`, `set_rate_alert`, `create_reminder`, `create_credit_plan`, `update_credit_task`, `draft_payment` (each returns undo information)
T2 money movement	`propose_fx_conversion`, `propose_payment`
T3 high risk	`propose_add_beneficiary`; any T2 proposal the policy engine escalates
T4 governance	*Not exposed as tools.* Limits, permissions, kill switch and audit are reachable only from the Security page (human-only endpoints) with step-up

Every tool has a Pydantic argument schema, so arguments are validated before the handler runs. Every call goes through `run_tool()`, which applies (1) an **allowlist**: the tool must belong to the intent-selected groups, (2) **schema validation**, (3) a **savepoint**: a failing tool rolls back its partial writes, (4) an **audit**

entry, and (5) **redaction** of the LLM-visible output (accounts masked, secrets removed).

4.3 Orchestration loop

```
run_turn(user_text, attachment):
    log user message
    pre = guardrails.precheck(text)            # evasion / governance / off-topic → deterministic refusal
    if pre: return refusal + KB sources
    groups = classify(text); tools = schemas_for(groups)       # quota protection: only relevant tools
    messages = system + running summary + last 10 turns + user (+ wrapped untrusted document)
    repeat up to 9 LLM calls:
        result = fallback_chain.chat(messages, tools)          # replay cache → gemini → groq → openrouter → ollama → mock
        if no tool calls: break
        if total calls > 8: stop with safety message
        for call in result.tool_calls:
            out = run_tool(call)                               # allowlist + schema + audit + redaction
            cards += out.cards                                 # UI-only (tokens live here)
            messages += tool result (JSON, ≤12k chars)
    text = validate_output(result.content)                     # no false "done" claims
    ensure citations → source chips; persist; stream cards + text over SSE
```

4.4 Free-provider fallback chain, quota protection and replay cache

All providers use **one OpenAI-compatible client** (`openai` SDK used generically) with configurable `base_url`, `model` and `api_key`:

`LLM_PROVIDER`	Endpoint	Default model (checked 2026-10-16)
`gemini` (primary)	`https://generativelanguage.googleapis.com/v1beta/openai/`	`gemini-3.5-flash-lite` (or `gemini-3.8-flash`)
`groq`	`https://api.groq.com/openai/v1`	`openai/gpt-oss-20b`
`openrouter`	`https://openrouter.ai/api/v1`	a `:free` model with tool support
`ollama`	`http://localhost:11434/v1`	`qwen3:4b`
`mock`	in-process	deterministic agent calling the same tools

- **Fallback.** On HTTP 429, timeout or tool-call error the chain retries once (0.8 s backoff), then falls through to the next provider. The provider and model that answered are shown as a badge in the UI.
- **Quota protection.** A compact prompt plus intent-scoped tool schemas (typically 6–12 tools rather than 25), a 10-turn history window with a deterministic running summary, a cap of 8 tool calls per turn, a process-wide daily LLM-call budget, and per-IP+workspace rate limits.
- **Record & replay.** `LLM_CACHE=record` stores `hash(conversation shape) → response` in `evals/replay_cache.json`. The hash covers user text and the tool-call sequence and masks IDs and dates, so a replay matches even though action IDs differ between runs. `LLM_CACHE=replay` serves cached responses first. The cache is committed, so the live deployment replays recorded demo scenarios with no network or quota.
- **Mock agent.** `app/agent/mock.py` speaks the same tool-calling protocol and composes replies from the same tool outputs. It keeps the app fully functional offline and makes tests deterministic.

4.5 Structured responses and explainability

Replies carry **cards** rendered by the UI: quote comparison, confirmation/action card, budget, runway, credit plan, alert, fraud warning, checklist, sources. Every recommendation carries an **explainability object**: inputs, formula, alternatives with the reason each was rejected, assumptions, data timestamp ("sandbox rates"), sources and disclaimer.

5. Core algorithms

5.1 Remittance cost optimizer (`services/quotes.py`)

For provider p with FX markup m_p, fixed fee F_p (published in USD, converted at mid) and percentage fee f_p:

- offered_rate = mid × (1 − m_p) (m_p = 0 for same-currency payouts)
- fee = F_p + f_p × send
- received = (send − fee) × offered_rate
- landed_cost = send − received ÷ mid (in the send currency)
- effective_cost_% = landed_cost ÷ send × 100

Reverse quote (recipient must receive exactly T):

send = (T ÷ offered_rate + F_p) ÷ (1 − f_p), **rounded up** to the minor unit so the target is never short.

Arrival. If the request comes after the provider's cut-off hour or on a weekend, processing starts the next business day at 09:00. Earliest and latest arrival are then that start + min/max business days.

Feasibility. The corridor must be supported; the USD equivalent must be within the provider's per-transfer limit (Remi **never splits** to fit); the provider must be tuition-eligible for tuition, and tuition-only rails require a registry-verified payee; and the worst-case arrival must fall on or before deadline − safety buffer (2 days).

Ranking. `cheapest`: by landed cost. `fastest`: by worst-case arrival. `balanced`: score = 0.7·cost_norm + 0.3·time_norm (min-max normalised over feasible options).

```
compare(send_ccy, recv_ccy, amount, mode, deadline, goal):
    mid = mid_rate(send_ccy, recv_ccy)
    for p in providers:
        q = quote(p, mid, amount, mode); check_feasibility(q, p)
    ranked = rank(feasible, goal)
    return best, alternatives(with why_not), rejected(with reasons), explanation
```

Worked example (S1/S2). Sandbox mid GBP/BDT = 164.4295 (1 BDT = 0.0060816327 GBP). Target: Northbridge University (demo) receives exactly £9,250; deadline 2026-11-04; request Wed 2026-10-14 10:00 UTC.

Provider	Markup	Fee (BDT)	Send (BDT)	FX markup cost	Landed cost	Eff. %	Worst-case arrival	Feasible
Campus Pay (sandbox)	0.60%	1,837.50	**1,531,991.57**	9,180.93	**11,018.43**	**0.72%**	2026-10-19	✅ recommended
Sandbox Bank Wire	1.20%	4,287.50	1,543,734.01	18,473.36	22,760.87	1.47%	2026-10-21	✅ (৳11,742 more)

Provider	Markup	Fee (BDT)	Send (BDT)	FX markup cost	Landed cost	Eff. %	Worst-case arrival	Feasible
Alpha Remit (sandbox)	0.40%	5,025.07	1,532,106.54	6,108.32	11,133.40	0.73%	2026-10-16	❌ $12.5k > $3k limit; not a tuition channel
Beta Express (sandbox)	2.10%	**243.78**	1,553,842.50	32,625.58	**32,869.36**	2.12%	2026-10-14	❌ $12.7k > $2k limit; not a tuition channel

Campus Pay check: offered = 0.0060816327 × 0.994 = 0.0060451429. Fixed fee = $15 × 122.5 = ৳1,837.50. send = 9,250 ÷ 0.0060451429 + 1,837.50 = 1,531,991.57 (rounded up). Landed cost = 1,531,991.57 − 9,250 ÷ 0.0060816327 = ৳11,018.43. The Beta Express row shows the hidden-markup trap: the lowest fee, but three times the true cost.

5.2 FX conversion helper (`services/conversions.py`)

No price prediction. For own-wallet conversions Remi applies a transparent 0.35% markup and shows the cost against mid-market. The helper offers three neutral options: **convert now** (lock the rate), **target-rate alert** (Remi proposes the conversion when it is hit, and the user still confirms), and **N equal weekly tranches** (an averaging effect, with a plain risk statement). Alerts are evaluated on every sandbox rate tick. When one fires, Remi creates a T2 proposal and pushes a live notification containing the confirmation card.

5.3 Budget and runway (`services/budget.py`)

- normalised_amount = amount × rate(txn_ccy → reporting_ccy, txn_date). The sandbox provides a deterministic daily rate history around the snapshot.
- Categorisation: merchant-keyword rules, user override via `categorize_transaction`, and an LLM fallback when a live model is available.
- daily_burn = Σ normalised spend (card spend + non-tuition transfers) over the trailing 60 days ÷ 60.
- **runway_days = (liquid balances − upcoming one-off obligations) ÷ daily_burn.** Future income is excluded (conservative).
- Insights: category change vs the previous 30 days, recurring subscriptions (same merchant and amount across ≥2 months), upcoming obligations. Up to **3 recommendations**, each with an estimated runway gain: days_gained = ⌊A ÷ (b − s/30)⌋ − ⌊A ÷ b⌋, where A is available funds, b is daily burn and s is monthly saving.

Rahim's example: liquid £16,059.42 − reserved £9,400.00 (tuition + visa fee) = £6,659.42 ÷ £38.75/day = **171 days (until 2027-04-03)**.

5.4 Credit-building planner (`services/credit.py`)

Rule-based per host-country configuration (`config/credit/{uk,ca,us}.yaml`): 7–8 tasks with months, points and dependencies. A task cannot be marked done before its dependencies. **Readiness = (Σ points(done) + ½ Σ points(in progress)) ÷ Σ points × 100**, labelled "Getting started / Building / Established". Everything is marked illustrative.

5.5 Risk scoring (`risk/engine.py`)

Rule	Points	Trigger
large_vs_history	20	amount > 3× largest past transfer
moderate_vs_history	10	amount > 1.5× largest past transfer
velocity	15	≥ 3 money movements in the last hour
new_beneficiary	25	first payment to the payee
registry_mismatch	60 + **hard block**	university payee name/account ≠ verified registry
structuring	35	≥ 2 payments within 85–100% of a threshold to the same payee in 24 h
restricted_jurisdiction	100 + **hard block**	destination on the (fictional) restricted list
unusual_time	10	00:00–04:59 in the user's host-country time zone
first_time_corridor	15	no prior transfer on this send→receive corridor
injection_in_source	40 + **hard block**	payment details came from a document with injected instructions

Score = min(100, Σ points). ≥ 50 escalates to T3 (step-up); ≥ 80 blocks. Every reason appears in plain English on the action card.

5.6 Hybrid retrieval (`knowledge/retrieval.py`)

score = α · cos_norm(q, c) + (1 − α) · bm25_norm(q, c), with α = 0.6, where cos_norm = clip((cos − 0.45)/0.40, 0, 1) for BGE-small embeddings and bm25_norm = s/(s + 6) (absolute saturation, so irrelevant queries stay low). Results below 0.35, or below 60% of the top score, are dropped. When nothing remains the agent says it doesn't know. Example: "What documents do I usually need to pay tuition from abroad?" → *Tuition payment documentation checklist* (0.705); "What is the capital of France?" → no result.

6. Knowledge base and RAG pipeline

- **Content.** 21 articles in `knowledge/*.md`, written in our own words: FX and fee glossary, how transfers work, landed cost, tuition document checklist (illustrative), paying tuition from abroad, purpose codes and source of funds (illustrative), credit-building basics UK/CA/US (illustrative), invoice-fraud red flags, scams targeting students, budgeting, runway, proof-of-funds basics

(illustrative), converting without speculating, Remi's safety tiers, limits and no-splitting, why transfers are monitored, KYC, rent safety, multi-currency wallets. Each article has front matter `title`, `region`, `last_reviewed`, `illustrative`.

- **Pipeline.** Paragraph-aware chunking (~400 tokens ≈ 1,600 characters, one-paragraph overlap) → local embeddings with `fastembed` `BAAI/bge-small-en-v1.5` (no API, cached as NumPy) + BM25 (`rank-bm25`, light stemming) → hybrid ranking → top-k with source IDs. `scripts/build_kb.py` builds the index; the app builds it at startup if it is missing.
- **Citations.** The agent cites `[KB: title]`. The orchestrator converts every citation into a clickable **source chip** that opens the article in a side panel.
- **Untrusted data.** Each chunk is scanned at index time. Instruction-like sentences in flagged chunks are replaced with `[removed: instruction-like text]`, and every retrieved chunk is wrapped in `<<UNTRUSTED_DATA source="kb:…">>`. A test plants a poisoned article and verifies it is sanitised and creates no action.

7. Security design

7.1 Permission tiers

Tier	Control	Implementation
T0 Read	automatic, logged	`run_tool` → `audit.append("tool.called")`
T1 Low-risk write	automatic, logged, undo info returned	handlers return `undo` objects
T2 Money movement	explicit human confirmation of an action card; single-use token bound to the payload hash; 5-minute expiry; the LLM never sees it	`policy/actions.py: propose/confirm`, `policy/tokens.py`
T3 High risk	confirmation + step-up OTP (phone-style notification) + cooling-off for new payees	`actions.step_up`, `_release` → `scheduled`, `run_scheduled`
T4 Governance	not exposed to the agent; human-only Security-page endpoints with OTP	`policy/governance.py`, deterministic guardrail refusal

7.2 Confirmation tokens

- token = 256-bit `secrets.token_urlsafe(32)`, delivered only inside the UI card.
- stored = HMAC-SHA256(SECRET_KEY, "confirm" | token | action_id | payload_hash), compared in constant time.
- **Bound:** changing any payload field changes `payload_hash` and the token no longer verifies. **Single-use:** `token_used` is set on first use. **Expiring:** 5 minutes, after which the action becomes `expired`.
- At confirmation the server **re-runs the policy engine** against live balances and limits (time-of-check/time-of-use protection).
- LLM-visible tool output (`actions.for_agent`) contains no token, masked accounts and an explicit `"executed": false`.

7.3 Step-up and cooling-off

A 6-digit OTP (HMAC-stored, 3-minute expiry, 3 attempts then cancel) is pushed over a separate SSE channel and shown as a phone-style notification, simulating an SMS. New payees (T3) become active only after `COOLING_OFF_SECONDS` (60 s in demo; hours in production). A confirmed payment to a payee still in cooling-off becomes `scheduled` and is released automatically when the period ends.

7.4 Limits (`config/limits.yaml`, USD equivalent)

Per-transaction maximum $30,000 (block) · step-up above $5,000 ($20,000 for registry-verified institutions) · daily soft limit $15,000 (step-up) · daily maximum $40,000 (block) · 30-day maximum $60,000 · velocity 5/hour (step-up) and 12/day (block). Limits can be changed only by the human on the Security page, with step-up, up to 5× the default in the sandbox.

Anti-structuring. The optimizer marks over-limit providers infeasible with the reason "Remi never splits a payment to get around a limit". If the user explicitly asks for a provider that cannot take the amount, Remi re-routes to a channel that can and explains why (S8). The structuring risk rule catches repeated near-threshold payments.

7.5 Prompt-injection and fraud defence

- **Deterministic document pre-review.** Every attachment goes through `invoices.analyze()` *before* the model sees it. The model cannot skip it, and the fraud card is always shown. If fraud is suspected, `propose_*` tools are removed from that turn's tool list, so not even a model that ignores the warning can create a payment from the document.
- `security/injection.py` detects instruction overrides, role hijacks, system-prompt probes, "bank details changed" claims, new-account requests, tool-call injection, auto-approve requests and urgency/secrecy language.
- Untrusted text (documents, KB chunks) is wrapped in delimiters; nested delimiters are neutralised.
- `services/invoices.py` extracts fields deterministically, compares the institution and account with the **verified registry**, and **blocks** on mismatch or injection, raising a red fraud card and notification and writing a `document.reviewed` audit entry.
- Payee details are **never** taken from documents. `draft_payment` always uses the registry account, and a payment to a university that does not match the registry is hard-blocked (`registry_mismatch`).
- Proposals sourced from a flagged document carry `source_flags`, which hard-block in the risk engine.

7.6 Idempotency

`/confirm` and `/stepup` require an `Idempotency-Key`. The first response is stored and an identical replay returns it (`idempotent_replay: true`); the same key with a different body returns 409. Combined with single-use tokens and status checks, a double-submit cannot double-pay (tested).

7.7 Audit log

Append-only `AuditEntry` rows per workspace: `seq`, `ts`, `actor` (user/agent/system), `action`, `tool`, `tier`, redacted `inputs`, `decision`, `result`, `prev_hash` and `hash = SHA-256(prev_hash ‖ canonical_json(entry))`. `GET /api/audit/verify` recomputes the chain and detects edited content, deleted rows and re-hashed rows (tests cover all three). `GET /api/audit/export` produces JSON evidence. Resetting a sandbox starts a new chain whose first entry records the previous head.

7.8 Privacy

Data minimisation (sandbox personas only); account numbers masked (`••••7890`) in the UI, logs and LLM inputs; recursive redaction of secrets, tokens, OTPs, emails and phone numbers before audit and LLM; consent screen on first use; no secrets in logs; `.env` never committed.

7.9 LLM guardrails

Deterministic pre-checks refuse evasion requests (S12) and governance requests (S10) before any model call. Off-topic requests are redirected. An intent-scoped tool allowlist, Pydantic schema validation, a cap of 8 tool calls per turn, timeouts and output validation (no false completion claims) complete the set. **All security decisions are made by code, not by the model.**

7.10 Public-deployment protection

Signed per-visitor workspaces (isolation is tested), per-IP+workspace rate limits (`slowapi`), a daily LLM-call budget that falls back to replay/mock with a visible "demo mode" badge, idle-workspace cleanup after 24 h, security headers (CSP, nosniff, frame-ancestors) and a one-click **kill switch** that blocks all agent money-movement proposals.

8. Compliance and explainability

- **Purpose of payment and source of funds.** Tuition payments carry an `EDU-TUITION` purpose code and a source-of-funds declaration on the confirmation card and the receipt.
- **Per-corridor document checklist** (`config/corridors.yaml`, illustrative) via `get_compliance_checklist`.
- **Simulated KYC status** per persona; **receipts** with reference numbers; a **persistent disclaimer**: *"Sandbox demo. Not financial, legal or tax advice."*
- **Explainability object** on every recommendation (inputs, formula, alternatives with reasons, assumptions, timestamp, sources, disclaimer). Risk reasons and policy escalations are listed on every action card.
- **No speculation.** The FX helper never forecasts; prediction requests get the neutral three-option helper.

8.1 Interaction design

Remi is designed for a stressed student reading English as a second language, and for judges who need to see the security story in seconds.

- **One question per screen.** Home ("Am I OK, and what needs my attention?"), Send ("send or pay cheaply and on time"), Wallets, Insights ("how long will my money last?"), Credit, Security ("what can Remi do on its own?") and Help. Secondary detail sits behind "Compare other options", "Fee breakdown", "Why this level of check" and "Technical details".
- **Ask Remi everywhere.** A chat panel opens from any screen. Replies are short and plain, and the agent's work appears as rich cards built from the same components as the pages: best option, approval card with a live expiry countdown, one-time-code entry, tracking timeline (Sent → On its way → Arrived) with a downloadable receipt, fraud warning, insight and cited-source chips.
- **Plain language, enforced.** Statuses, tool activity ("Comparing 4 providers…") and audit entries are translated into everyday sentences ("Remi prepared a payment of £9,250 to Northbridge University (demo) · waiting for your approval"). Tier codes appear only as small tags, and money and dates follow fixed rules (symbols, separators, "Thu 22 Oct").

- **Security made visible.** A permission ladder explains what Remi may do alone, what needs approval, what needs a code and waiting period, and what it can never do. The activity log is readable and shows a "Log verified" badge with a one-click re-check.
- **Design system.** Remi has its own brand: a lowercase wordmark whose i-dot is an orange coin, plus an `r.` app icon. The palette is warm cream, deep green and one orange accent; type is Bricolage Grotesque and Inter on an eight-style scale. Every colour, size, radius and shadow comes from one token file, every screen is assembled from one component kit, and a design lint fails the build on any hard-coded colour or font size. The interface is light-only, responsive from 390 px, keyboard-accessible and respects reduced motion. Lighthouse (mobile, throttled) scores the landing page 97 / 100 / 100 for performance, accessibility and best practices.
- **Judges' tools stay out of the student's way.** Sandbox controls (time travel, FX shocks, injected remittance or suspicious invoice, persona switch, AI provider status) live in a small "Demo" drawer.

9. Sandbox and data

- **Ledger.** Double-entry `JournalEntry` legs must net to zero per currency (enforced; trial balance tested). Balances are derived from entries. Settlement states: `pending → processing → settled / failed (reversal legs, fee refund)`.
- **FX.** A dated snapshot (USD base, labelled "sandbox rates") plus a deterministic per-workspace random walk (`tick`, seeded by workspace ID and tick count) and a "shock" control. Synthetic daily history is used for budget normalisation.
- **Providers (fictional).** Sandbox Bank Wire, Alpha Remit (sandbox), Beta Express (sandbox) and Campus Pay (sandbox) differ in markup, fees, speed, cut-offs, limits, corridors and tuition eligibility, so there are real trade-offs.
- **Verified registry (fictional).** Northbridge University (demo), Maplecrest College (demo), Lakeshore Institute of Technology (demo).
- **Sandbox control panel.** Advance simulated time, tick FX, apply a ±1% shock, inject an incoming family remittance, inject a suspicious invoice, reset the sandbox.
- **Per-visitor workspaces.** A signed cookie gives each browser its own seeded copy, and all tables are scoped by `workspace_id`.

10. Testing and evaluation

- **Unit/API tests.** 106 pytest tests: optimizer maths (forward, reverse, percentage fee, cut-off, ranking), Decimal rounding, ledger balance, limits, risk rules (structuring, history, corridor), tiering, confirmation-token binding/expiry/single-use/tamper, OTP attempts, cooling-off release, settlement lifecycle, audit-chain tamper detection (edit, delete, re-hash), redaction, injection detection, invoice fraud, workspace isolation, idempotency double-submit, governance step-up, kill switch, tool allowlist and schema validation, tool-call cap, RAG citations and poisoned-chunk sanitisation, replay-cache key stability, Gemini `thought_signature` passthrough, workspace-scoped invoice ids, `.env` parsing.
- **Golden scenarios.** `evals/run_evals.py` drives S1–S13 through the real HTTP API and checks tools, cards, policy tier, status transitions, final balances, trial balance and audit-chain validity.

Run	Scenarios	Checks
Deterministic agent (`mock`)	**13/13**	**122/122**
Gemini free tier, live (`gemini-3.5-flash-lite`)	**13/13**	**136/136**
Gemini recorded replay (fresh workspaces)	**13/13**	**136/136**

In real-model runs an extra check fails any turn that silently fell back to the mock agent, so the Gemini result is genuinely the model's. The first live run passed 9/13. Each failure led to a deterministic fix rather than prompt-only patching: a Gemini 3 `thought_signature` passthrough, a home-currency default for payee-less quotes, rejecting rate alerts that would fire immediately, a "never shrink or split to fit a limit" hint in quote output, and a deterministic illustrative-content disclaimer. The full history is in `evidence/eval_report.md`. Median live turn latency on the free tier was ≈ 18–25 s (several tool calls per turn), which is why the public demo serves recorded answers first and goes live only on a cache miss.

- **Browser end to end.** `frontend/e2e/s1_tuition.spec.ts` (Playwright) runs S1 through the real UI: consent → chat → quotes → confirmation card → executed → receipt → settled → audit chain verified. It runs locally against a fresh server and against the live deployment (`evidence/live_smoke_test.json`).
- **Audit evidence.** `scripts/export_audit.py` exports one session's hash-chained audit log, then edits a row and shows verification failing at that entry (`evidence/audit_export.json`).

Full per-scenario results: `evidence/eval_report.md`, `evidence/eval_results.json`, per-step logs in `evidence/sandbox_logs/`.

11. Deployment (zero cost)

Live demo: https://remi-pzqb.onrender.com (Render free web service, Docker). The S1 browser test passes against it (`evidence/live_smoke_test.json`). There, the demo prompts are answered from the recorded Gemini answers (≈ 0.2 s) and new questions go to live Gemini (≈ 20 s on the free tier).

Layer	Choice	Cost
LLM	Gemini free tier → Groq free → OpenRouter free → Ollama → mock; replay cache	$0
Embeddings	fastembed BGE-small, local CPU	$0
Backend	FastAPI + SQLite	$0
Frontend	React + Vite + Tailwind, served by FastAPI (one port)	$0
Hosting	Render free web service (Docker, `render.yaml`); backup Cloudflare quick tunnel. Hugging Face Docker Spaces now require PRO, so they were dropped	$0

A multi-stage Dockerfile (Node build → Python slim) reads `PORT`, exposes a health check, and builds the KB index and seed on startup. Free hosts may have ephemeral disks; per-visitor workspaces re-seed cleanly. See `docs/DEPLOYMENT.md`.

12. Limitations and roadmap

- **Sandbox only.** No real providers, KYC, sanctions screening or banking rails. Production would integrate licensed remittance partners, open-banking account information and payment initiation, real KYC/AML vendors and certified rate feeds.
- **Illustrative compliance.** Corridor rules, purpose codes and credit plans are simplified, need legal review per jurisdiction, and need regular content review (the `last_reviewed` field).
- **Free models.** Weaker reasoning and rate limits, mitigated by deterministic maths and security, the fallback chain and the replay cache. Production would use a no-retention enterprise tier or a self-hosted model.
- **SQLite and simulated OTP.** Production would use PostgreSQL with row-level security, a KMS-managed secret, WebAuthn/passkeys for step-up, and an external write-once log store anchoring audit-chain heads.
- **Roadmap.** Proof-of-funds monitor, deadline calendar, invoice OCR, multilingual replies, rent reporting partners, savings goals, and a family app for senders.

13. Team


Member	University	Role	Responsibilities
Syed Nazmus Sakib	East Delta University	Team leader	Agent (LLM orchestration, tools, free-provider fallback), backend (FastAPI, sandbox ledger, optimizer, policy engine), security (permission tiers, confirmation tokens, risk engine, audit chain)
Sadmanul Arefin	Ahsanullah University of Science & Technology	Member	Frontend (React UI, design system, chat cards), knowledge base (curated articles, RAG content), documentation (technical documentation, guides, deck)

Repository: https://github.com/sakib-101-git/remi · License: MIT · Third-party licenses: `THIRD_PARTY_LICENSES.md`.


Sandbox demo. Not financial, legal or tax advice. All company, bank, provider and university names are fictional.

Appendix A. Screens


All screenshots are captured automatically from the running app by `scripts/capture_screenshots.py` (`evidence/screenshots/`).




Landing page with a live sandbox quote




Home: balance, Ask Remi, what's next




Send: calculator, best option, other options




S1: Remi's plan and the T2 approval card




Executed: live tracking and receipt




Insights: how long the money lasts




S7: invoice fraud and prompt injection blocked



S8: T3 extra check with a one-time code



S13: cited help article



Security: permission ladder, limits, pause switch