TEXORA · SESSIONAL NOTES · STUDY SHEET

Front Part and Back Part

Finishing the trouser front and back as production pieces: allowances by edge, the back waist dart, grain and notch conventions, information blocks, and mirror-pair checking.

TE-3108 · APPAREL MANUFACTURING TECHNOLOGY-II SESSIONAL · STUDY 4 · LEVEL 3 TERM 1

1. Aim and place of the study

Aim: to convert the Study 3 draft into separate, finished front and back production pieces: net lines traced, allowances added, grain, notches, drill holes and the full information block applied to each piece.

2. Materials, machine settings and specimens

Materials: the Study 3 draft, pattern paper, tracing wheel/notcher, awl, shears. **Allowances for this course (TE-2207/2208 standard):** 1 cm general (inseam, fork, waist under the band), 1.5 cm at the side seams (adjustment), 2.5 cm at the hem. Waistband, fly and pocket pieces are finished in Study 5; this study completes the two leg pieces only.

Trouser measurement chart used throughout TE-3108 (men's basic trouser, garment values in cm): waist S 77 · **M 82** · L 87 · XL 92 (grade 5); hip 97 · **102** · 107 · 112 (grade 5); outseam (incl. waistband) 102 · **104** · 106 · 107; inseam 76 · **78** · 80 · 81; thigh 60 · **62** · 64 · 66 (grade 2); knee 44 · **46** · 48 · 50 (grade 2); hem (bottom) width 38 · **40** · 42 · 44 (grade 2); front rise 25 · **26** · 27 · 28. Size M is the working size unless the study states otherwise. Seam allowances, as in TE-2207/TE-2208: **1 cm** general, **1.5 cm** at side seams, waistband and other adjustment seams, **2.5 cm** at hems. The shirt values of TE-2207/2208 (size M chest 107, length 73, shoulder 46, sleeve 61.5, collar 40; grades 5/2/2/1.5/2 cm) are used unchanged wherever a shirt is the specimen.

3. Procedure

1. Trace the front net shape onto fresh paper. Add allowances edge by edge from the table: side seam 1.5, inseam 1.0, fork/fly curve 1.0, waist 1.0, hem 2.5. Square the hem allowance so the fold line is marked.
2. Trace the back likewise, marking the waist dart as a folded wedge in the pattern (the dart's sewing lines and its drill hole 1 cm before the point), the raised centre-back waist, side seam 1.5, hem 2.5.

3. Apply the markings: grain/crease line arrowed full length; notches — single at the front side seam knee point, double at the back (the TE-2207 convention), notch pairs matching inseam knee points front-to-back, hem fold notch.
4. Write the information block on each piece: style (basic trouser), piece name (front / back), size M, cut 2 (pair, mirrored), fabric (shell), and the chart reference (waist 82 · hip 102).
5. Separate the pieces and lay them as a pair: check the two fronts are true mirror images and the inseams of front and back walk equal (Study 3 check repeated on the net lines of the finished pieces).

4. What the examiner looks for

CHECK	STANDARD
Allowance widths	Measured at three points per edge; within ± 0.1 cm of the table.
Dart (back)	Intake 2 cm, length about 10 cm, drill hole placed; dart legs equal so the dart folds without a step at the waist.
Grain line	Coincides with the crease line; arrowheads both ends.
Mirroring	Left and right pieces are exact mirrors; a same-side pair is an automatic fail of the set (TE-2207 Topic 2 rule).

Precautions

- Add allowances only after the net shape is re-checked — allowances copy errors faithfully.
- Cut paper on the cutting line with long strokes; nicks become fabric nicks in every lay cut from the pattern.
- Label before separating: unlabelled separated pieces cannot be identified with certainty.

Practice (viva preparation)

Answer in your own words; brief model answers follow.

1. State the allowance at (a) the trouser side seam, (b) the inseam, (c) the hem, and the reason the side seam carries more.
2. Why are front notches single and back notches double?
3. A back piece is found with its dart legs unequal by 3 mm. What defect appears when the dart is sewn?

Answer key

1. (a) 1.5 cm — it is the adjustment seam, left wider so fit can be let out or taken in. (b) 1.0 cm general. (c) 2.5 cm hem allowance. Adjustment seams carry extra; enclosed/fixed seams carry the standard.
2. A standing identification convention: in the bundle and at the machine, single notch = front, double = back, so pieces are never paired wrongly in dim light or haste.
3. The waist edge steps by the same 3 mm at the dart: the waistband cannot sit smoothly over it and the dart point puckers. Equalise the legs by folding the dart as sewn and trimming the waistline across the fold.

5. Faults found in this study, and their corrections

FAULT	CAUSE AND CORRECTION
Side-seam allowance tapers from 1.5 to 1.1 cm	The allowance was added by eye from a single mark. Correct method: mark the allowance at several points along the edge and join the marks — never offset a long curve from one measurement.
Hem fold line not square to the crease	Hem allowance added without squaring from the crease line. Re-square: the fold line must be perpendicular to the crease so the hem hangs level.
Front and back inseam notches at different heights	Notches marked from the hem on one piece and from the crutch on the other. Mark both from the same datum (the knee line) and re-check by walking.
Grain arrow drawn freehand off the crease	The grain line is the crease line on a trouser leg; redraw it along the crease with the L-square, arrowheads at both ends.