TEXORA · SESSIONAL NOTES · STUDY SHEET

Trimming List of Shirts, Trouser and Jacket

Building the bill of materials for three garments: every trim specified and counted per garment, then converted through allowance and trading units into order quantities.

TE-3108 · APPAREL MANUFACTURING TECHNOLOGY-II SESSIONAL · STUDY 7 · LEVEL 3 TERM 1

1. Aim and place of the study

Aim: to compile the complete trimming (bill-of-materials) list for three garments — basic shirt, basic trouser and jacket — with per-garment quantities, specifications and the order quantities for a stated production run, using TE-3107 Topic 7's systems.

2. Materials, machine settings and specimens

Materials: the three garments' spec sheets (shirt values from TE-2207/2208; trouser chart of this course), trim card references, calculator. **Production run for the order calculation:** 10,000 pieces of the garment under study; process allowance 3% on all trims unless stated.

Trouser measurement chart used throughout TE-3108 (men's basic trouser, garment values in cm): waist S 77 · **M 82** · L 87 · XL 92 (grade 5); hip 97 · **102** · 107 · 112 (grade 5); outseam (incl. waistband) 102 · **104** · 106 · 107; inseam 76 · **78** · 80 · 81; thigh 60 · **62** · 64 · 66 (grade 2); knee 44 · **46** · 48 · 50 (grade 2); hem (bottom) width 38 · **40** · 42 · 44 (grade 2); front rise 25 · **26** · 27 · 28. Size M is the working size unless the study states otherwise. Seam allowances, as in TE-2207/TE-2208: **1 cm** general, **1.5 cm** at side seams, waistband and other adjustment seams, **2.5 cm** at hems. The shirt values of TE-2207/2208 (size M chest 107, length 73, shoulder 46, sleeve 61.5, collar 40; grades 5/2/2/1.5/2 cm) are used unchanged wherever a shirt is the specimen.

3. Trimming list — basic shirt (per garment)

TRIM	SPECIFICATION	QTY / GARMENT
Buttons	Polyester resin, 18L (11.4 mm), 4-hole, colour to fabric	10 (7 front, 2 cuff, 1 spare)

Fusible interlining	Light woven, PA dot coating	Collar band + fall, cuffs, placket (≈ 0.12 m²)
Sewing thread	Core-spun PES, tex 24	37.8 m incl. waste (TE-3107 Topic 3 worked figure)
Labels	Main woven label; size label; care label (printed)	1 + 1 + 1
Collar support pack	Butterfly + band insert, PVC	1 set (stand-up pack styles)
Packing	Tissue, folding board use, polybag with warning print, hang tag + kimble	1 set

4. Trimming list — basic trouser (per garment)

TRIM	SPECIFICATION	QTY / GARMENT
Zip	Metal or moulded, #4–#5, auto-lock slider, 18 cm (size M)	1
Waistband button + hook/bar	Button 24L (15.2 mm) or metal hook-and-bar set	1 set
Fusible interlining	Waistband weight, resin per Topic 7 test	Waistband length 89 cm × width (≈ 0.09 m²)
Pocketing fabric	Cotton/poly pocketing	2 bags (≈ 0.35 m length)
Sewing thread	Core-spun, tex 40 (needle), tex 24 serging	71.8 m incl. waste (Topic 3 worked figure, trouser)
Belt loops' stay / waistband curtain	As style	Per spec
Labels + packing	Main, size, care labels; polybag; hang tag	1 set each

5. Trimming list — jacket (per garment, summary)

TRIM	SPECIFICATION HIGHLIGHTS	QTY
Front fusible + canvas	Chest canvas (hair or fusible substitute), front interlining by zone	1 set

Shoulder pads	Layered foam/felt, size by garment size	1 pair
Sleeve head roll (sleeve wadding)	Supports the sleeve cap crown	1 pair
Buttons	Front 32L (20.3 mm) × 3; cuff 24L × 4 per sleeve; spares	11 + spares
Lining fabric	Viscose/polyester twill or satin, body + sleeve weights	Per marker (≈ 1.6 m)
Zip (if styled), labels, hanger + GOH bag	Hanger pack replaces folding set	1 set

6. Order calculation (worked, shirt buttons)

10,000 shirts × 10 buttons = 100,000; × 1.03 allowance = 103,000 buttons; ÷ 144 per gross = 715.3 → **716 gross**. The record for this study applies the identical chain to the trouser zips (10,000 × 1 × 1.03 = 10,300 zips = 103 bundles of 100) and states every trim of the three lists in its trading unit.

Precautions

- A trim list without specification (size, material, colour reference) is a shopping note, not a BOM — every line carries its spec.
- Quantities are per garment first; order quantities are derived, never estimated directly.
- Spare buttons sewn into the garment are consumption, and are counted in the per-garment figure.

Practice (viva preparation)

Answer in your own words; brief model answers follow.

1. Convert a 32L jacket button and a 24L trouser button to millimetres.
2. Calculate the order quantity, in bundles of 100, of trouser zips for 25,000 trousers at 3% allowance.
3. Why does the jacket list carry a hanger and GOH bag where the shirt list carries a folding set?
4. Which single trim on the trouser list is also a Topic 7 process item with temperature–pressure–time control?

Answer key

1. 32 × 0.635 = 20.3 mm; 24 × 0.635 = 15.2 mm.
2. 25,000 × 1.03 = 25,750 zips → 258 bundles (257.5 rounded up).

3. Jackets are packed garment-on-hanger to protect their moulded shape (Topic 9); folding would destroy the pressed form the finishing section built. The shirt's presentation is a flat fold.
4. The waistband fusible interlining: its fusing conditions (temperature, pressure, time) must be set and peel-tested per fabric pair.

Texora — course notes prepared from the official syllabus of B.Sc. in Textile Engineering · Made by Sakib