TEXORA · LECTURE SHEET

Recent Inventions and Value-Added Special Fabrics

A descriptive survey of the directions in which special fabrics are currently developing: fabrics that sense, respond, conduct, protect and clean themselves — and the manufacturing ideas (3D forming, digital finishing, single-polymer design) that cut across all of them.

FM-4103 · SPECIAL FABRIC PRODUCTION · TOPIC 4 · FABRIC MANUFACTURING SPECIALIZATION

1. How to read this topic

This sheet is a **survey of directions**, written deliberately without sales statistics or named-product claims: in a field where brochures outrun physics, the durable knowledge is the *mechanism* of each development and the *problem it answers*. The families below — responsive fabrics, electronic textiles, protective and medical fabrics, surface-engineered fabrics, and new forming methods — recur across the trade and research literature of the last two decades, and each connects back to a structure studied in this course or its neighbours.

2. Responsive ("smart") fabrics

- **Phase-change materials (PCM):** microcapsules of waxes that melt and solidify near skin temperature are coated or printed onto fabrics (or spun into fibres). Melting absorbs heat, solidifying releases it: the fabric buffers temperature swings in bedding, sportswear and protective clothing. The structure lesson: the effect lives in a *coating* (Topic 1) — durability is the engineering battle, since capsules must survive washing.
- **Chromic fabrics:** thermochromic (temperature) and photochromic (light) dyes in prints and coatings that change colour reversibly — used in novelty apparel, safety signalling and temperature indication.
- **Shape-memory textiles:** shape-memory polymer fibres and fabrics, and nickel–titanium (nitinol) wires woven or knitted in, recover a programmed shape on heating — ventilating structures that open pores when warm, crease-resistant garments, deployable structures.
- **Moisture- and temperature-responsive structures:** bilayer and specially spun yarns that swell or twist with humidity, opening and closing a knitted fabric's pores — ventilation controlled by the

fabric itself, no electronics.

3. Electronic textiles (e-textiles)

Conductivity is brought to fabric by **conductive yarns** (metal filaments, silver-coated nylon, stainless-steel staple blends, carbon yarns), by **conductive coatings and printed tracks** (silver and carbon inks), and increasingly by knitting or weaving the circuit as part of the structure — intarsia-knitted sensor zones, woven bus lines. On this base are built: textile electrodes for heart-rate and muscle monitoring in garments; resistive and capacitive pressure/strain sensors in knitted structures (the loop geometry of TE-3101 doubles as a sensor — stretch changes contact and resistance); heating fabrics (busbars plus resistive zones) for clothing, seats and medical wraps; and fabric antennas and RFID yarns for logistics and identity. The persistent engineering problems are the textile ones: wash durability of connections, contact reliability at crossovers, and joining soft circuits to hard electronics.



Figure 1 — E-textile principle (schematic): conductive yarns laid in chosen courses and wales form wiring and sensor zones inside an ordinary structure; the garment's patterning machinery becomes its circuit printer.

4. Protective and medical special fabrics

- **High-performance protective fabrics:** cut-resistant fabrics from high-tenacity and hard-yarn blends (para-aramid, UHMWPE, glass/steel-core yarns) engineered as knits whose loop structures resist blade draw; chainsaw-protection fabrics whose long fibres clog the sprocket; molten-metal and welding fabrics; chemical-protective laminates (Topic 1's barrier membranes with protective outers).
- **Medical fabrics:** compression bandages and stockings whose pressure is engineered through elastane content and fabric geometry (graduated compression is a designed pressure profile, calculable from fabric tension and limb radius by Laplace's law); hernia and support meshes of monofilament knits; antibacterial and odour-control finishes and fibres; spacer fabrics (Topic 2) in pressure-relief and orthopaedic roles; absorbent dressings built as nonwoven–film composites.
- **Antimicrobial and anti-odour systems:** silver, copper and zinc compounds, chitosan, and quaternary finishes — applied as fibre additives (durable) or coatings (cheaper, less durable), with the efficacy–durability–skin-safety triangle as the design problem.

5. Surface-engineered value addition

- **Self-cleaning and easy-care surfaces:** lotus-effect (superhydrophobic) finishes combining micro-roughness with low-surface-energy chemistry so water beads roll off carrying dirt; photocatalytic (TiO_2-based) coatings that break down organic soil in light.
- **Plasma and laser surface treatment:** plasma activation grafts wettability, adhesion or antimicrobial function onto a surface atomic layers deep, without wet chemistry; laser engraving and laser fading (the denim route of Topic 6) pattern surfaces without water or chemicals.
- **Digital finishing:** inkjet printing and digital coating place chemistry only where the design needs it — less water, less effluent, short runs — the finishing analogue of the jacquard principle.
- **Fragrance, cosmetic and wellness finishes:** microencapsulated scents and skin-care agents (aloe, vitamins) in binders on fabric — value added as a reservoir that releases in wear; durability through washes is again the honest limitation.

6. New forming and design directions

- **Single-polymer and mono-material design:** fabrics, membranes and adhesives all from one polymer family (e.g. all-polyester) so the product can be recycled whole — a direct answer to the laminate problem of Topic 1.
- **Bio-based and recycled inputs:** regenerated cellulosics from waste cotton, recycled polyester and nylon, and fibres from agricultural residues entering special fabrics first where specifications allow.
- **Auxetic fabrics:** structures (re-entrant honeycombs, rotating-unit knits and woven geometries) with negative Poisson's ratio that thicken when stretched — impact protection, conformable medical and composite uses.
- **3D printing on and as textiles:** polymer printed directly onto fabric for stiffening, grip and design; fully printed flexible meshes as fabric analogues — early, but a genuine new forming route to set beside weaving, knitting and nonwovens.
- **Computational design:** fabric structures simulated before manufacture (geometry of Topic 3/FM-4203 extended by software) so cover, permeability and drape are predicted from the design file — the direction in which the whole of this course's mathematics is heading.

Glossary

Phase-change material — substance storing/releasing latent heat at a transition temperature, microencapsulated onto fabric. **E-textile** — fabric carrying electrical function (sensing, heating, communication). **Auxetic** — negative Poisson's ratio: thickens under tension. **Mono-material design**

— product built from one polymer family for whole-product recycling. **Graduated compression** — designed pressure profile along a limb from fabric tension and radius.

Key points

• Judge every "invention" by mechanism and problem answered, not by brochure: capsules, conductive yarns, responsive polymers, engineered surfaces.
• The recurring engineering battles are durability (washing, abrasion) and joining — soft function to hard use.
• Value addition increasingly lives in coatings, finishes and structure-integrated function rather than in new base fibres.
• Sustainability is now a forming principle: mono-material design, recycled/bio inputs, digital (waterless) finishing.

Practice

1. Choose a mechanism from this sheet for a hospital mattress cover that must (a) buffer patient skin temperature and (b) resist bacterial growth, and state the durability question you would ask the supplier in each case.
2. Explain why a knitted strain sensor works at all, in terms of loop structure.
3. A brand wants a "self-cleaning" school uniform. Give two different technical meanings the claim could have, and one test question for each.
4. Why does mono-material design conflict with the classic membrane laminate of Topic 1, and how are manufacturers resolving the conflict?

Answer key

1. (a) **Phase-change microcapsules** in a coating, melting near skin temperature to buffer heat peaks; durability question: how many wash cycles before the PCM content (and hence the buffering) falls to a stated fraction — capsules rupture and wash out progressively. (b) **Antimicrobial system**, preferably fibre-integrated (silver/copper in the fibre) rather than a surface finish; durability question: efficacy after the hospital's actual laundering regime (temperature, chemistry, cycle count), plus skin-contact safety certification.
2. A knitted loop is a contact network: under strain the loops change shape, crossover contact areas and pressures change, and with a conductive yarn the pathway resistance changes with them. The structure is therefore a strain gauge whose sensing element and whose substrate are the same object — sensitivity comes from geometry, which is also why such sensors drift and show hysteresis that electronics must compensate.

3. (i) **Superhydrophobic lotus effect** — soil never wets in; test question: does the effect survive the school's washing (detergent attacks low-energy surfaces) and abrasion, measured by contact angle after stated cycles? (ii) **Photocatalytic coating** — soil is chemically decomposed in light; test question: decomposition rate under realistic indoor light (not just UV lamps), and does the catalyst also attack the fabric's own fibres and dyes over time?
4. The classic laminate joins unlike materials (fabric + membrane + adhesive) that cannot be separated for recycling. The resolution is to rebuild each layer from the **same polymer family** — polyester face, polyester membrane, polyester-compatible adhesive — so the whole product enters one recycling stream while keeping the laminate's division of labour.

Texora — course notes prepared from the official syllabus of B.Sc. in Textile Engineering · Made by Sakib