CUSTOMIZE BOOTSTRAP WITH SASS AND KOALA VARIABLES


- 1. Create a "bootstrap-mine" folder
- 2. Create a "css" folder inside the folder "bootstrap-mine"
- 3. Download the "source files" in the folder "bootstrap-mine" Link: https://github.com/twbs/bootstrap/archive/v4.3.1.zip
- 4. Unzip the .zip file and then delete the archive

 Note: all BS files must now be in a folder "Bootstrap-4.3.1".

 Please check, the rest of the operations are related to this folder!
- 5. Open VS Code and import/add the folder "bootstrap-mine"
- 6. Create a new file "bootstrap-custom.scss" in the "css/" folder

 Note the extension of this file: "scss"

 Current structure:



7. Find the file called "_variables.scss" and open it
The file is located in: bootstrap-4.3.1/scss/ variables.scss

8. Copy the target variables to your "bootstrap-custom.scss" file

Note: you have an example of variables to copy in the support file: "HTML-CSS/11.bootstrap/_customize_scss/custom-bootstrap.scss" You can use this .scss file as a starting point

9. DELETE the !default text everywhere ! Use Search and Replace

This text should not appear in your .scss file Exemple avec les variables couleurs après édition :

```
$blue: #007bff !default; became $blue: #007bff; $indigo: #6610f2 !default; became $red: #dc3545; etc.
```

10. Change the default values with your own values

```
In this example $blue: #007bff;

$blue => is the variable name

#007bff => the value to change
```

11. Link the Bootstrap files

```
At the end of your .scss file paste this line : @dimport "../bootstrap-4.3.1/scss/bootstrap"
```


An essential step before compilation. This line will bind all BS files and allow the recognition of variables.

Note: The red link above represents the path from your .scss file and the base BS file (bootstrap.scss).


Change it if your configuration is different.

12. Open "Koala" app and configure the basic settings

Click on the icon "gear" and then on "General". Uncheck everything and click OK.




Click on "Sass", uncheck everything and click OK.




13. Add your "css" folder to Koala

Click the icon + and add your css folder




14. Define the name and the path of the file to be exported

Right click on the bootstrap-custom.scss and "Set Output Path" file. The folder will be "css" and the name will be "bootstrap.min.css"



15. Compile / Export

Follow the steps in the image below to compile your file :



16. Test your work

Create a .html file at the root of the folder and import your "bootstrap.min.css" file:

<link rel="stylesheet" href="css/bootstrap.min.css">

Create a few divs / paragraphs and try the classes you have changed ...

With love from Granges.

Sincerely yours,

Sorin