# Docker Java Application Example

As, we have mentioned earlier that docker can execute any application.

Here, we are creating a Java application and running by using the docker. This example includes the following steps.

# 1. Create a directory

Directory is required to organize files. Create a director by using the following command.

```
$ mkdir java-docker-app
```

See, screen shot for the above command.

```
Irfan@irfan-GB-BXBT-2807: ~/Desktop
irfan@irfan-GB-BXBT-2807: ~/Desktop$ mkdir java-docker-app
```

# 2. Create a Java File

Now create a Java file. Save this file as Hello.java file.

## // Hello.java

```
class Hello{
public static void main(String[] args){
System.out.println("This is java app \n by using Docker");
}
}
```

Save it inside the directory java-docker-app as Hello.java.

# 3. Create a Dockerfile

After creating a Java file, we need to create a Dockerfile which contains instructions for the Docker. Dockerfile does not contain any file extension. So, save it simple with **Dockerfile** name.

#### // Dockerfile

```
FROM java:8

COPY . /var/www/java

WORKDIR /var/www/java

RUN javac Hello.java

CMD ["java", "Hello"]
```

Write all instructions in uppercase because it is convention. Put this file inside **java-docker-app** directory. Now we have Dockerfile parallel to Hello.java inside the **java-docker-app** directory.

See, your folder inside must look like the below.



# 4. Build Docker Image

After creating Dockerfile, we are changing working directory.

```
$ cd java-docker-app
```

See, the screen shot.

Now, create an image by following the below command. we must login as root in order to create an image. In this example, we have switched to as a root user. In the following command, **java-app** is name of the image. We can have any name for our docker image.

```
$ docker build -t java-app .
```

See, the screen shot of the above command.

```
🔊 🗇 🗊 root@irfan-GB-BXBT-2807: /home/irfan/Desktop/java-docker-app
oot@irfan-GB-BXBT-2807:/home/irfan/Desktop# cd java-docker-app/
oot@irfan-GB-BXBT-2807:/home/irfan/Desktop/java-docker-app# docker build -t java-app .
Sending build context to Docker daemon 3.072 kB
Step 1/5 : FROM java:8
---> a001fc27db5a
Step 2/5 : COPY . /var/www/html
 ---> Using cache
---> 8052cbc8ca31
Step 3/5 : WORKDIR /var/www/html
---> Using cache
---> 07977e913cb3
tep 4/5 : RUN javac Hello.java
  -> Using cache
  -> 0d6e2c3fbd77
tep 5/5 : CMD java Hello
 ---> Using cache
  -> 3f6fb4241c06
Successfully built 3f6fb4241c06
oot@irfan-GB-BXBT-2807:/home/irfan/Desktop/java-docker-app#
```

After successfully building the image. Now, we can run our docker image.

# 5. Run Docker Image

After creating image successfully. Now we can run docker by using run command. The following command is used to run java-app.

\$ docker run java-app

See, the screen shot of the above command.

```
© □ root@irfan-GB-BXBT-2807:/home/irfan/Desktop/java-docker-app
root@irfan-GB-BXBT-2807:/home/irfan/Desktop/java-docker-app# docker run java-app
This is java app
by using Docker
root@irfan-GB-BXBT-2807:/home/irfan/Desktop/java-docker-app#
```

Here, we can see that after running the java-app it produced an output.

Now, we have run docker image successfully on your system. Apart from all these you can also use other commands as well.