

400-779-6399

Material Safety Data Sheet

According to 1907/2006/EC 31

SECTION 1 CHEMICAL IDENTIFICATION

Product Details

Name: SA3000

Serial Number:36103000

Application:Assembly Adhesive Preparation

Supplier:Zhengzhou Dipute Chemical Co.,Ltd

Address: NO. 66 Tongtai Road ,New Eastern district,Zhengzhou ,Henan,China

Phone Number: +86 0371 63486729

Fax: +86 0371 63486729

SECTION 2 HAZARDS IDENTIFICATION

Hazard Symbol:



Classification Indications of danger : Toxic, Dangerous for the environment

R-phrases:

Irritating to eyes and skin.

May cause cancer.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Vapours may cause drowsiness and dizziness.

Possible risks of irreversible effects.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Characteristics

Adhesives based on: the chlorinated organic solvent neoprene

Hazardous components:

CAS:No Trichloroethylene 79-01-6 78.5%

Zhengzhou Dipute Chemical Co.,Ltd

Phone Number: +86 0371 63486729

CAS: chloroprene rubber 9010-98-4 11%

CAS:terpene resin 9003-74-1 10.5%

Product Name: SA3000

This manual risks listed in terms of additional information, refer to section 16.

SECTION 4 First aid measures

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

Take away from danger area and lay down affected person.

SECTION 5 Fire-fighting measures

Suitable extinguishing media

Foam, carbon dioxide (CO₂), dry chemical, water-spray.

Product does not burn, fire-extinguishing activities according to surrounding.

Extinguishing media which must not be used for safety reasons

Full water jet.

Special exposure hazards arising from substance or preparation itself, combustion products, resulting gases

Fire may produce:

Carbon monoxide and carbon dioxide.

Chlorine and traces of phosgene.

Hydrogen chloride gas.

Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Keep away from heat and sources of ignition.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with local regulations.

SECTION 6 Accidental release measures

Personal precautions:

In case of vapour formation use respirator.

Ensure adequate ventilation.

Use personal protective clothing.

Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

Methods for cleaning up/taking up:

Soak up with inert absorbent material(e.g. Sand,silica gel,acid binder,universal binder).

Shovel into suitable container for disposal.

Section 7 Handling and storage

Handling Advice on safe handling

Keep container tightly closed.

Vapours are heavier than air and spread along ground.

Care for thoroughly room ventilation, if necessary suck off at workplace. Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

Storage

Requirements for storage rooms and vessels

Keep containers tightly closed in a cool,well-ventilated place.

Advice on storage compatibility

Incompatible with:

Oxidizing agents.

Aluminium powder

Alkaline metals and earth alkaline metals.

Alkaline leaches

Further information on storage conditions

Keep away from food,drink and animal feeding stuffs.

SECTION 8 Exposure controls/personal protection

Exposure limit values

127-18-4 tetrachloroethylene

WEL: Short-term value: 689 mg/m³, 100 ppm

Long-term value: 345 mg/m³, 50 ppm

75-09-2 dichloromethane

WEL: Short-term value: 1060 mg/m³, 300 ppm

Long-term value: 350 mg/m³, 100 ppm

Sk

8050-09-7 rosin

WEL: Short-term value: 0.15 mg/m³

Long-term value: 0.05 mg/m³

Sen

Additional information: based on the effective during the period of editor list.

Protective and hygiene measures

Do not inhale vapours.

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using,do not eat,drink or smoke.

Take off immediately all contaminated clothing.

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment(gas filter type A).

Hand protection:

Protective gloves resistant to chemicals made off viton,Minimum coat thickness 0.7 mm,Permeation resistance(wear duration)approx,480 minutes,i.e.protective glove<Vitoject 890>.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use.Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Eye protection

Eye wash bottle with pure water.

Tightly fitting goggles.

Skin protection

Long sleeved clothing.

SECTION 9 Physical and chemical properties

General information

Physical state: Liquid

Color: Black

Odour: Sweetish

Changes in the physical state

Boiling point: 40°C approx.

Flash point: n.a. *)

Lower explosion limits: 13.0 vol%

Upper explosion limits: 22.0 vol%

self inflammability: This product is not flammable

Explosion hazard: This product is not explode.

Solubility in water/water mixed: not easy or difficult to mix

Viscosity: The dynamic viscosity at 20 °C : 3500-3500 mPa.s

Solvent content:

Organic solvent: 84-87%

Total solids: 13-16%

SECTION 10 Stability and reactivity

Conditions to avoid

Above 120°C, a thermic decomposition may take place.

Materials to avoid

Alkaline metals and alkaline earth metals.,Bases,Oxidizing agents.Aluminium powder

Hazardous decomposition products

Chlorine and traces of phosgene.

Hydrogen chloride gas

Carbon monoxide and carbon dioxide.

Additional information

No decomposition if stored and applied as directed.

SECTION 11 Toxicological information

Acute toxicity: Related to the classification of LD/LC50 value: The 75-09-2 Dichloromethane

Through the mouth: LD 50, 1410-1410 mg/kg (rat)

Through the skin: LD 50 > 2000 mg/kg (rat)

Through inhalation: LC50 (4 h) 88 mg/l (rat)

1314-13-2 zinc oxide

Through the mouth: LD 50 > 15000 mg/kg (rat)

Through inhalation: LC50 (4h) > 5.7 mg/l (rat)

Primary stimulation effect:

Skin contact: stimulates the skin and mucous membrane.

Eye contact: can irritate the eyes.

Sensitization: skin contact may cause irritation.

Additional toxicology information:

According to the latest release of the general classification of the preparation of the EU chemicals in the guide to calculation method, the product shows the following hazards:

harmful irritating

Sensitization: skin contact may cause irritation.

SECTION 12 Ecological information

Further information

Do not flush into surface water or sanitary sewer system.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Severe hazard to waters.

SECTION 13 Disposal considerations

Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

Don't disposal with other life garbage. Ban into the sewerage system. prohibit discharged into sewer system.

Waste disposal number of waste from residues/unused products.

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVE, SEALANTS AND PRINTING INKS;

wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances

Classified as hazardous waste.

Contaminated packaging:

Recommendation: disposal must be carried out in accordance with the official rules and regulations.

SECTION 14 Transport information

Land transport ADR/RID and GGVs/GGVE

ADR/RID-GGVs/E class: 6.1

Hazard-no.: 60

UN number: 2810

ADR/RID packing group: III

Hazard label: 6.1

Marine transport

UN number: 1710

IMDG: 6.1

IMDG label: III

EmS: F-A, S-A

Marine: Yes

Air transport

ICAO/IATA-DGR: 6.1

UN/ID number: 2810

Hazard label: 6.1

ICAO packing group: III

SECTION 15 Regulatory information

Labelling

Additional advice on labelling

According to EC-regulations the product is to be labelled as follows:

Danger symbols: T-Toxic;N-Dangerous for the environment



T - Toxic



N - Dangerous for the environment

Hazardous components which must be listed on the label

Dichloromethane

Tetrachloroethylene

Rosin

R phrases:

40 A few evidence shows may have carcinogenic effects.

43 Contact with skin may cause irritation.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S phrases:

3 Stored in shady and cool place.

23 Do not inhale the smoke.

25 Avoid contact with eyes.

36/37 Wear suitable protective clothing and gloves

57 Use appropriate container to avoid environmental pollution.

60 This material and its container must be as hazardous waste disposal.

Special labelling for certain preparations:

Contain lead.Should not be chewing and sucking food together with children.

National regulatory information

Employment restrictions: Observe employment restrictions for young people.Observe employment restrictions for child bearing mothers and nursing.

Water contaminating class(D):3-highly water contaminating

SECTION 16 Other information

This data is based on our current knowledge. However, they don't make a guarantee for any specific product features, but also not to establish a legally valid contract relationship.

The risk of related terms

20/22 Inhalation and swallow is harmful.

33 There is a risk of accumulation effect.

43 contact with skin may cause irritation.

50/53 to be toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

51/53 toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

61 May cause harm to the unborn baby.

62 May have the danger of fertility damage.