



OLIVER

RUBBER INDUSTRIES LLP

4F-15, 'OLIVER HOUSE', New Power House Road, JODHPUR - 342 001 (Raj.) INDIA
export@oliverrubber.in ; info@oliverrubber.in ; info@ombhansali.com ; www.oliverrubber.in
Cell # +91-95496-50303, 77268-66667, 94141-29472 ♦ Tel. : +91-291-2610472



Technical Data Sheet OM-2000

PRODUCT NAME & HSN NUMBER	:	Cold Vulcanizing Adhesive OM-2000 Cement 38123930
PACKING DETAIL	:	Tin Pack in 1 Kg Weight
APPLICATION	:	OM-2000 Cement is applicable for rubber-to-rubber, rubber-to-metal, rubber-to-fabric and fabric-to-fabric bonding applications for conveyor belts vulcanizing & maintenance work and in fields of wear & corrosion protection
BASE SOLVENT	:	Trichloroethylene (CAS# 79-01-6)
SHELF LIFE	:	4 Years
ADVANTAGES	:	Non-Flammable Long Shelf Life more than 4 years Excellent Bonding Adhesion Available in two colors – Green Easy to use process
PHYSICAL PROPERTIES	:	Flash Point = > NA Boiling Point = Approximately 90°C Density = 1.45 g/cm³ Relative Vapor Density = 4.54 Viscosity = 3000 mPa s Solvent Content = <90%
SAFETY INSTRUCTIONS	:	Skin and eye irritant. May cause cancer. May cause damage to Central Nervous System, Liver, and Kidneys May cause damage to organs with prolonged or repeated exposure Use only in a well-ventilated area. See MSDS for more detailed hazards prevention Measures.
STORAGE RECOMMENDATION	:	Store in a cool, well-ventilated, dry environment. Keep away from open flames, ignition sources, and incompatible materials (See Safety Data Sheet for details). Keep container tightly closed. Keep away from food, drink, and animal foodstuffs.