


Automatic Classification of C-Elegans Mitochondria

A Machine Learning project by Saksham Gautam and Daniel Hein
at the chair for Robotics and Embedded Systems at the Technische Universität München.

Introduction

Worms with fluorescent mitochondria are put under a fluorescence microscope and 10 to 20 pictures of it are generated. As the worm is transparent, photographing it with different focuses yields to photographs of different levels of the worm. After that, each “slice” of the worm is scrutinized on the computer screen to find just one picture where cells are clearly visible. Using computer imaging software, the photographs are discretized until mitochondria can be separated from background fluorescence. Afterwards, another routine of this pro-



Worms with fluorescent mitochondria are put under a fluorescence microscope and 10 to 20 pictures of it are generated. As the worm is transparent, photographing it with different focuses yields to photographs of different levels of the worm. After that, each “slice” of the worm is scrutinized on the computer screen to find just one picture where cells are clearly visible. Using computer imaging software, the photographs are discretized until mitochondria can be separated from background fluorescence. Afterwards, another routine of this pro-



Feature Extraction

Worms with fluorescent mitochondria are put under a fluorescence microscope and 10 to 20 pictures of it are generated. As the worm is transparent, photographing it with different focuses yields to photographs of different levels of the worm. After that, each “slice” of the worm is scrutinized on the computer screen to find just one picture where cells are clearly visible. Using computer imaging software, the photographs are discretized until mitochondria can be separated from background fluorescence. Afterwards, another routine of this pro-

Worms with fluorescent mitochondria are put under a fluorescence microscope and 10 to 20 pictures of it are generated. As the worm is transparent, photographing it with different focuses yields to photographs of different levels of the worm. After that, each “slice” of the worm is scrutinized on the computer screen to find just one picture where cells are clearly visible. Using computer imaging software, the photographs are discretized until mitochondria can be separated from background fluorescence. Afterwards, another routine of this pro-




Worms with fluorescent mitochondria are put under a fluorescence microscope and 10 to 20 pictures of it are generated. As the worm is transparent, photographing it with different focuses yields to photographs of different levels of the

Worms with fluorescent mitochondria are put under a fluorescence microscope and 10 to 20 pictures of it are generated. As the worm is transparent, photographing it with different focuses yields to photographs of different levels of the worm. After that, each “slice” of the worm is scrutinized on the computer screen to find just one picture where cells are clearly visible. Using computer imaging software, the photographs are discretized until mitochondria can be separated from background fluorescence. Afterwards, another routine of this program computes different attributes of the shape of the areas refined during the previous step. These are

Neural Network


Worms with fluorescent mitochondria are put under a fluorescence microscope and 10 to 20 pictures of it are generated. As the worm is transparent, photographing it with different focuses yields to photographs of different levels of the worm. After that, each “slice” of the worm is scrutinized on the computer screen to find just one picture where cells are clearly visible. Using computer imaging software, the photographs are discretized until mitochondria can be separated from background fluorescence. Afterwards, another routine of this pro-



Worms with fluorescent mitochondria are put under a fluorescence microscope and 10 to 20 pictures of it are generated. As the worm is transparent, photographing it with different focuses yields to photographs of different levels of the



Decision Boundary

Worms with fluorescent mitochondria are put under a fluorescence microscope and 10 to 20 pictures of it are generated. As the worm is transparent, photographing it with different focuses yields to photographs of different levels of the worm. After that, each “slice” of the worm is scrutinized on the computer screen to find just one picture where cells are clearly visible. Using computer imaging software, the photographs are discretized until mitochondria can be separated from background fluorescence. Afterwards, another routine of this pro-



Worms with fluorescent mitochondria are put under a fluorescence microscope and 10 to 20 pictures of it are generated. As the worm is transparent, photographing it with different focuses yields to photographs of different levels of the worm. After that, each “slice” of the

Worms with fluorescent mitochondria are put under a fluorescence microscope and 10 to 20 pictures of it are generated. As the worm is transparent, photographing it with different focuses yields to photographs of different levels of the worm. After that, each “slice” of the worm is scrutinized on the computer screen to find just one picture where cells are clearly visible. Using computer imaging software, the photo-



Worms with fluorescent mitochondria are put under a fluorescence microscope and 10 to 20 pictures of

Worms with fluorescent mitochondria are put under a fluorescence microscope and 10 to 20 pictures of it are generated. As the worm is transparent, photographing it with different focuses yields to photographs of different levels of the worm. After that, each “slice” of the worm is scrutinized on the computer screen to find just one picture where cells are clearly visible. Using computer imaging software, the photographs are discretized until mitochondria can be separated from background fluorescence. Afterwards, another routine of this program computes different attributes of the shape of the areas refined during the previous step. These are attributes like “circularity” (shape compared to a perfect circle), length of one mitochondria, kind of clustering, etc. These data are used to classify the morphology of the mitochondria into three classes: fragmented, tubular and in between. As this process involves human based classification, it is prone to biases
