





DETAIL A — PANEL HEAD

FOOT OF PANEL IS THE MIRROR



KEY

PARTS OF THE LEAF

- 1 Stile
- 2 Top rail
- 3 Upper panel — shaped bead, 4 roundels
- 4 Lock rail
- 5 Lower panel — same pattern
- 6 Bottom rail
- 7 Knob Ø2¹/₈"
- 8 Keyhole escutcheon
- 9 Meeting bead (pair only)
- 0³/₈" Architrave — to design

NOTES

READ BEFORE MAKING

Dimensions in feet and inches. Do not scale.

Proportions taken from a film-still reference;

leaf size, opening and thickness are ASSUMED.

Knob centre lands 3'-1 $\frac{3}{4}$ " above the floor — normal height.

D2 · D3 — DRESSING · BATHROOM, 7 ft 7 in × 2 ft 6 in.

Set out on the panel square. The 2 ft 6 leaf gives a

1'-10 $\frac{1}{8}$ " panel; the upper panel is two of those squares

(3'-8 $\frac{1}{4}$ "), the lower is one (1'-10 $\frac{1}{8}$ "). Rails follow: top 3 $\frac{7}{8}$ " ,

lock 9" , bottom 11 $\frac{5}{8}$ " . Knob centre 3'-2 $\frac{1}{4}$ " above the floor.

Both widths take the identical rails and mouldings, so

only the panel width changes — here 1'-10 $\frac{1}{8}$ " per panel.

Solid teak frame. Veneer and polish per

Materials; polish to match the teak desk.


Casing: 2 in lining plus 4 in moulding over it, so the

moulding head sits 6" above the leaf.

See AST-DR-011 (option A) and AST-DR-012 (option B).

SECTION B–B

HORIZONTAL THROUGH UPPER PANELS



RELIEF

Hinges and lock not yet designed.

FACE OF THE STILES AND RAILS = DATUM 0

Stiles and rails, 1¾" thick	DATUM 0
Ovolo sticking, 0¾" wide	WORKED ON THE FRAME EDGE
Panel, 0¾" thick, loose in a 0½" groove	—
Panel field	0½" IN
Shaped bead line round the field	2.5 IN
Roundel boss Ø1", four per panel	0⅛" OUT
Mitres at the sticking corners	CUT, NOT SCRIBED
Knob Ø2⅛" and escutcheon Ø1⅜"	SURFACE

DETAIL C — LOCK RAIL

ACTIVE LEAF

