

# Peer to Peer Applications: Overview

Kameswari Chebrolu

All the figures used as part of the slides are either self created or from the public domain with either 'creative commons' or 'public domain dedication' licensing. The public sites from which some of the figures have been picked include:

<http://commons.wikimedia.org> (Wikipedia, Wikimedia and workbooks); <http://www.sxc.hu> and <http://www.pixabay.com>

# Peer to Peer (P2P)

- Peer: Desktop/Laptops/Smart-phones managed by users
  - Contribute resources in the form of processing power, bandwidth, disk storage.
- Peer to Peer Architecture: Architecture that distributes application functionality across peers
  - Peers often equal; act as both client (consumer) and server (supplier)

# Usage Scenarios


- File Sharing: movies, songs, software such as Linux distributions, software updates, games etc
- Multimedia: Voice calls (E.g. Skype)
- Miscellaneous: currency (Bitcoin), web caches, distributed databases

# Why P2P?

- Consider distribution of large files: If client-server architecture is used to serve a large client population
  - Server needs to be always-on
  - Server needs to be powerful → Processing ✓
  - Server needs to have high bandwidth ✓
  - Above imply high cost; difficult to scale
- P2P leverages peer resources → low cost, highly scalable
  - Challenge: Intermittent connectivity

# Problem Statement

- Help users share files among themselves



**Need to put Geeta or Ravi in touch with Seeta; Raka in touch with Geeta**

Geeta: Acts as server when uploading "Another brick in the wall" to Seeta and as client when downloading "Hotel California" from Raka



# Application Functionality

- Join : how does a user join the peer-to-peer overlay network?
- Publish : how does a user advertise files willing to share?
- Search : how does a user find a file?
- Fetch : how does a user download a file?
- Challenge: Peers come and go (churn); Peer's IP address can change over time

# Types of Overlays

- Unstructured overlays:

- Edges between nodes are randomly formed (E.g. a new node randomly chooses three existing nodes in overlay as neighbors)
- Easy to build, robust against churn; search however is inefficient

- Structured overlays

- Edges arranged carefully to speed up search; rare files can also be found
- Based on Distributed Hash Tables (DHT)
- Complex, less robust against churn