Indian Institute of Technology Bombay
Department of Computer Science and Engineering

# Structured LLM Optimization

*Systems for LLMs*




**Saksham Rathi**

Under the guidance of

**Prof. Mythili Vutukuru**

Bachelor's Thesis Project

Academic Year: 2025–26

# Contents

**List of Figures** 3

**List of Tables** 4

**1 Background** 5
- 1.1 Stages in the Model Creation Pipeline . . . 5
- 1.2 Transformer Architecture . . . 7
  - 1.2.1 Tokenization . . . 7
  - 1.2.2 Embedding and Attention . . . 7
  - 1.2.3 Multi-Head Masked Attention . . . 7
- 1.3 Inferencing . . . 7
- 1.4 LLM Inferencing . . . 7
  - 1.4.1 Forward Pass . . . 8
  - 1.4.2 Token Probability Distribution . . . 8
  - 1.4.3 Generation Loop . . . 8
  - 1.4.4 Modes of Inference . . . 9
- 1.5 Inference Engines . . . 9
  - 1.5.1 Optimizations in Inference Engines . . . 10
- 1.6 Prefill vs Decode . . . 10
- 1.7 Metrics . . . 11
  - 1.7.1 Throughput . . . 11
  - 1.7.2 Latency . . . 11
- 1.8 KV Caching . . . 11

**2 Flash Attention** 12

**3 vLLM** 13
- 3.1 Automatic Prefix Caching in vLLM . . . 13

**4 SwiftLLM** 14

**5 SGLang** 15

**6 Experiments** 16
- 6.1 System Prompt in Cache Experiment . . . 16
  - 6.1.1 Example 1 . . . 16
  - 6.1.2 Example 2 . . . 17
  - 6.1.3 Observations . . . 18
  - 6.1.4 Analysis over different steps and using different metrics 19

6.1.5 Profiling across pipeline stages . . . 19
6.2 Batch of Requests . . . 20
6.3 Throughput and Latency Measurements across different techniques . . . 20
6.4 LLM Request Timelines . . . 23
6.4.1 Chunked Prefill Enabled . . . 23
6.5 Maximum Throughput with vLLM . . . 25
6.6 Nsight Systems GPU Metrics . . . 25
6.7 Throughput vs Load Comparison For vLLM . . . 27
6.8 Families of Requests . . . 27
6.9 Compute Utilization across various max batch sizes . . . 28
6.10 GPU Memory Breakdown . . . 28

**7 Maths behind LLMs** **30**
7.1 Transformer FLOPs . . . 30
7.1.1 FLOPs Calculation . . . 30
7.1.2 Model parameters (TinyLlama-1.1B-Chat) . . . 31
7.1.3 FLOPs Calculation for TinyLlama-1.1B-Chat . . . 31
7.1.4 Efficiency Calculation . . . 31
7.1.5 Efficiency Calculation . . . 31
7.1.6 Summary of the nomenclature used . . . 32

**8 QLora** **33**

**Bibliography** **34**

# List of Figures


1.1 Adopted from llm . . . . . 5
1.2 Adopted from USE . . . . . 6
1.3 Architecture of a Large Language Model (3) . . . . . 8
1.4 Architecture of a Large Language Model (3) . . . . . 9
1.5 Prefill vs Decode . . . . . 10

6.1 Throughput . . . . . 22
6.2 Average Latency . . . . . 22
6.3 P95 Latency . . . . . 22
6.4 20 Requests per second . . . . . 23
6.5 25 Requests per second . . . . . 23
6.6 All requests at once . . . . . 23
6.7 Request Timeline with GPU Metrics . . . . . 24
6.8 Chunked Prefill Enabled - 100 Requests per second . . . . . 24
6.9 Chunked Prefill Enabled - All requests at once . . . . . 24
6.10 Number of batch outputs - chunked prefill enabled . . . . . 25
6.11 Number of batch outputs - chunked prefill disabled . . . . . 25
6.12 Throughput vs Load . . . . . 27
6.13 Throughput vs Load for different models for heavy workloads . 27
6.14 SM Active and SM Occupancy across different max batch sizes 28

7.1 FLOPs Calculation Breakdown (from Casson (2023)) . . . . . 31

# List of Tables

6.1 Profiler Output . . . . . 19
6.2 Profiling results for various pipeline stages . . . . . 19
6.3 Measuring the time taken to process a batch of requests using different techniques . . . . . 20
6.4 Nsight Systems GPU Metrics . . . . . 26
6.5 GPU Memory Breakdown and KV Cache Usage . . . . . 29

7.1 Variables used in FLOPs . . . . . 32

# Chapter 1

# Background

Language models (LMs) are statistical models that predict the next word in a sequence given the previous words. They basically give us a probability distribution over words based on the context provided by the preceeding words. They enable machines to understand and generate human language. They can be used for a lot of tasks like answering questions, text summarization, translation, code generation and more.





Figure 1.1: Adopted from llm

## 1.1 Stages in the Model Creation Pipeline

- **Data Preparation:** The initial stage involves gathering and preprocessing the training data, which can be categorized into two parts: (1) pretraining data, consisting of extensive unlabeled corpora obtained from public or private sources and curated through processes like detoxification and deduplication; (2) alignment data, comprising a smaller set of high-quality labeled corpora used to align the model with specific





Figure 1.2: Adopted from USE

tasks. This data is typically acquired through expensive human annotation or labeling. Besides, all the data must be tokenized to ensure compatibility with the model's input.

- **Pretraining:** It involves self-supervised training on large-scale curated data, demanding a majority of resources within the overall development workflow. Training LLMs efficiently at scale necessitates various system innovations, such as state-sharding optimizers, meticulous model placement using data, pipeline, and tensor parallelisms.

- **Alignment:** This stage aims to adapt LLMs with user intent on a wide range of downstream tasks. Two primary aligning paradigms are commonly used: (1) prompt engineering, specifying prompts (i.e., inputs) without modifying model parameters. For example, in text summarization, appending a prompt "TL; DR" to the input article can improve model performance; (2) fine-tuning, updating model parameters on a task-specific dataset to improve performance in a particular domain.

- **Evaluation:** Given the vast application scenarios of LLM, it may be inaccurate to assess model quality solely based on a single metric like training loss. There are numerous factors to consider, such as accuracy, fairness, and toxicity. Consequently, it is crucial to account for a diverse set of criteria and measure performance across multiple tasks. Furthermore, regular evaluation is essential during the pretraining stage to provide timely feedback on model quality.

- **Deployment:** To meet the strict cost and latency constraints of LLM applications, several advanced techniques have been developed to achieve efficient model serving, including quantization, distillation, CUDA kernel optimization, model parallelism and memory management.

## 1.2 Transformer Architecture

### 1.2.1 Tokenization

Tokenization is the process of converting raw text into a sequence of tokens that the model can process. Instead of working directly with characters or words, modern language models often rely on subword tokenization methods such as Byte Pair Encoding (BPE), WordPiece, or SentencePiece. These approaches break words into smaller, more frequent units, balancing vocabulary size and representation power. For example, the word "unhappiness" may be split into "un", "happiness", while rare words are decomposed into character-level units. Tokenization ensures consistent representation of unseen or rare words and significantly reduces out-of-vocabulary issues.

### 1.2.2 Embedding and Attention

Once tokenized, tokens are mapped into continuous vector representations called embeddings. These embeddings capture semantic and syntactic relationships among words, such that similar words are close in the embedding space. Positional encodings are added to embeddings to preserve word order information, since attention mechanisms are permutation invariant by default.

Attention is the core mechanism of transformer models. It allows the model to selectively focus on different parts of the input sequence when generating or predicting tokens. Given a query, attention computes weighted similarities with key-value pairs, enabling contextualized representations that consider both local and long-range dependencies.

### 1.2.3 Multi-Head Masked Attention

Masked attention is used in autoregressive language models to prevent the model from "looking ahead" at future tokens during training. This masking enforces causality by ensuring that each token can only attend to itself and preceding tokens. Multi-head attention extends this concept by computing multiple attention functions in parallel. Each head captures different aspects of relationships—such as syntactic dependencies, semantic similarity, or positional cues. The outputs of all heads are concatenated and linearly transformed, providing a richer, more expressive representation of the input.

## 1.3 Inferencing

## 1.4 LLM Inferencing

Large Language Model (LLM) inferencing refers to the process of using a trained model to generate predictions (such as text completions, answers, translations, etc.) given some input. Unlike training, where parameters are updated, inferencing only runs the trained model forward to produce outputs.





Figure 1.3: Architecture of a Large Language Model (3)

### 1.4.1 Forward Pass

- The forward pass is the core computation step in inferencing.
- Input tokens (converted to embeddings) are passed layer by layer through the transformer blocks:
  - Embedding → Attention → Feedforward → Normalization (repeated across layers).
- Each forward pass produces *logits*: a vector of unnormalized scores for the next token in the vocabulary.

### 1.4.2 Token Probability Distribution

- The logits are passed through a softmax to get probabilities.
- These probabilities define the model's belief about which token should come next.
- Different decoding strategies may be applied:
  - **Greedy decoding**: pick the token with maximum probability.
  - **Sampling**: sample a token according to the probability distribution.
  - **Top-k / Top-p sampling**: restrict sampling to the most probable tokens.
  - **Beam search**: keep multiple hypotheses alive and expand them.

### 1.4.3 Generation Loop

- Inferencing is auto-regressive:
  1. Generate one token.
  2. Append it to the context.
  3. Feed back into the model.

- Repeat until a stopping criterion (e.g., end-of-sequence token or maximum length) is reached.

### 1.4.4 Modes of Inference

- **Forward only** (logits for a given input): used in classification, scoring, and embeddings.
- **Generate** (auto-regressive token loop): used in chatbots, summarization, and translation.
- **Hybrid tasks**: e.g., retrieval-augmented generation (RAG), where inference integrates external knowledge.

## 1.5 Inference Engines





Figure 1.4: Architecture of a Large Language Model (3)

An **inference engine** is the software and systems layer that manages the execution of large language model (LLM) inference on hardware resources. While the model architecture and parameters define the computation, inference engines ensure that requests are executed efficiently, reliably, and at scale.

- **Batching:** Multiple user requests are grouped into a single batch to maximize GPU utilization and reduce per-request overhead. Efficient batching is crucial for achieving high throughput in production environments.
- **Streaming:** Outputs are generated token-by-token and streamed back to the user as they are produced, reducing latency for interactive applications such as chatbots.
- **Fault Management:** Inference engines must be resilient to hardware or software failures. This includes checkpointing, task retries, and robust scheduling.
- **Error Handling:** Engines provide mechanisms for handling issues such as invalid inputs, out-of-memory errors, or timeouts without disrupting other active requests.

- **Parallelism (Multi-GPU):** Large models often cannot fit on a single GPU. Inference engines handle model parallelism and pipeline parallelism to distribute computation across multiple GPUs or nodes, while minimizing communication overhead.

### 1.5.1 Optimizations in Inference Engines

- **Memory Storage Optimizations:** Inference engines carefully manage GPU memory by caching key-value pairs (KV cache), reusing memory buffers, and applying quantization or weight-sharing techniques to reduce footprint.
- **Offloading:** Portions of the model state or intermediate activations can be offloaded to CPU or other storage when not actively needed on the GPU. This allows inference of models larger than GPU memory capacity.

## 1.6 Prefill vs Decode

LLM inference consists of two phases:

- **Prefill:** The input/prompt is ingested in parallel. All tokens are processed together to build the key-value (KV) cache, enabling the generation of the first output token.
- **Decode:** Subsequent tokens are generated auto-regressively. Each new token is computed sequentially using the KV cache from earlier steps.

In short, *prefill is parallel and one-time*, while *decode is sequential and repeated.*





Figure 1.5: Prefill vs Decode

## 1.7 Metrics

The performance of LLM inference is typically measured using two key metrics:

### 1.7.1 Throughput

- Defined as the number of tokens processed per second.
- Reflects system efficiency and GPU utilization across multiple requests.

### 1.7.2 Latency

- Measures the responsiveness of the system.
- **Time to first token (TTFT):** Corresponds to the prefill phase, i.e., the delay before the first output token is produced.
- **Time between tokens:** Corresponds to the decode phase, i.e., the per-token delay during sequential generation.

## 1.8 KV Caching

- **Query (Q):** A representation of the current token, used to score its relevance against all past tokens. During decoding, we only compute the query for the token currently being processed.
- **Key (K):** Keys act like labels for tokens in the sequence. They are used to match queries and determine which past tokens are relevant.
- **Value (V):** Values are the actual token representations. Once relevance scores are computed (using Q and K), the corresponding values are aggregated to produce the output representation.

In causal self-attention, the attention for the current token depends on the keys (K) and values (V) of all past tokens.

- **Without caching:** K and V for all previous tokens are recomputed at every decoding step, causing redundant work.
- **With caching:** K and V are generated once during prefill/decoding and stored. At each new step, only the K and V for the latest token are computed, while past values are reused.

# Chapter 2

# Flash Attention

# Chapter 3

# vLLM

## 3.1 Automatic Prefix Caching in vLLM

# Chapter 4

# SwiftLLM

# Chapter 5

# SGLang

# Chapter 6

# Experiments

## 6.1 System Prompt in Cache Experiment

The basic application which we want to cater is inferencing in cases where the system prompt is common across multiple queries. And therefore, we want to utilize caching by already filling the KV-Cache with the system prompt, and then putting user queries on the top of it.

### 6.1.1 Example 1

I picked the 200-word summary of the demand paging lecture as the system prompt to be provided to the LLM. The model which we used was `TinyLlama/TinyLlama-1.1B-Chat-v1.0` (1.1 billion parameters). The system prompt provided was:

> The lecture discusses demand paging, a key concept in virtual memory management. Instead of loading all pages of a process into memory, only the required pages are brought in, while the rest may stay in swap space on disk. This allows processes to use address spaces larger than physical memory and enables efficient memory utilization.
> Each process has a page table, with entries containing a valid bit (indicating whether the page is part of the process) and a present bit (whether it is currently in memory). If valid=0, the process makes an illegal access. If valid=1 but present=0, a page fault occurs. The OS then allocates a memory frame, possibly evicts a victim page using a page replacement policy, updates the page table, and resumes execution.
> Victim pages may be file-backed or anonymous, and may be dirty (modified) or clean. Dirty pages require writing back to disk before eviction. Policies like FIFO and LRU determine which pages to evict; LRU is effective due to locality, while FIFO can suffer from Belady's anomaly.
> Excessive page faults can cause thrashing, where the system spends more time swapping pages than doing useful work. To prevent this, the OS ensures that each process's working set fits in memory.

The time taken to fill the system prompt, and find the key-value cache tensors, along with making clones (so that we feed different clones to different queries) was around 0.339 seconds.

We then make two queries to the LLM, by taking KV-Cache as a generation call input, we restrict the output length to 100 tokens

**Query 1:** What is the difference between a valid bit and a present bit?

**Response 1:** The difference between a valid bit and a present bit is that a valid bit indicates that a page is part of a process, while a present bit indicates that a page is currently in memory.

**Query 2:** Why does thrashing occur in demand paging systems?

**Response 2:** Thrashing occurs in demand paging systems because excessive page faults can cause the system to spend more time swapping pages than doing useful work. This is because demand paging systems allocate memory frames to processes based on their page table entries, which are either valid or present. If a process has a page fault, it must be allocated a memory

The total time taken by the LLM to run these two queries (with cached system prompt) was 2.1 seconds.

However, if we do not cache the system prompt, and instead make two separate LLM calls, with ((system prompt + query1) and (system prompt + query2)), then the total time taken increases to 2.94 seconds.

### 6.1.2 Example 2

Let us take another example, this time with a summary of the semaphores lecture. The system prompt provided was:

The lecture introduces semaphores, a synchronization primitive similar to condition variables, used to coordinate threads. A semaphore maintains a counter, initialized to some value. The down (wait) operation decrements the counter and blocks the thread if it becomes negative, while the up (post) operation increments the counter and wakes a blocked thread. The counter cannot be directly accessed, only modified via these operations.
Semaphores can be used for mutual exclusion (binary semaphores), functioning like locks. They are also useful for synchronization between threads, e.g., enforcing execution order (T1 before T2) or ensuring two threads finish one step before starting another. Incorrect usage can cause deadlocks, such as when both threads wait on each other.
The producer-consumer problem is revisited using semaphores. Two semaphores track empty and filled buffer slots, while a binary semaphore (mutex) ensures mutual exclusion on buffer access. Misuse, like holding locks during blocking down calls, can also lead to deadlocks.
Guidelines emphasize careful initialization, ensuring every down has a corresponding up, and using separate semaphores for signaling and locking. The lecture also covers batched processing with semaphores, showing how request threads and a batch processor can coordinate efficiently.
Semaphores thus provide flexible yet tricky synchronization, requiring careful design to avoid deadlocks.

The time taken to fill the system prompt, and find the key-value cache tensors, along with making clones (so that we feed different clones to different queries) was around 0.347 seconds.

We then make two queries to the LLM, by taking KV-Cache as a generation call input, we restrict the output length to 100 tokens

**Query 1:** How does the down operation on a semaphore synchronize threads during execution?

**Response 1:** A semaphore is a synchronization primitive that maintains a counter, initialized to some value. The down operation decrements the counter and blocks the thread if it becomes negative. The up operation increments the counter and wakes a blocked thread. The counter cannot be directly accessed, only modified via these operations. Semaphores can be used for mutual exclusion (binary semaphores), functioning like locks. They

**Query 2:** Why is an extra binary semaphore (mutex) needed in producer-consumer implementation?

**Response 2:** An extra binary semaphore (mutex) is needed in producer-consumer implementation because the producer and consumer threads can access the same buffer at the same time. This can lead to deadlocks if the buffer is not properly protected.

The total time taken by the LLM to run these two queries (with cached system prompt) was 2.774 seconds.

However, if we do not cache the system prompt, and instead make two separate LLM calls, with ((system prompt + query1) and (system prompt + query2)), then the total time taken increases to 2.957 seconds.

### 6.1.3 Observations

- As we can see, there is roughly an improvement of 0.2-0.7 seconds for an experiment of 2 queries, which is also intutively clear, because we are just passing over the system prompt once.
- As we increase the size of the system prompt, and the number of tokens we generate, the difference becomes even wider.
- The time taken to feed through the system prompt, and cloning the KV cache values, can be ignored safely because we can do this before we get the actual user queries.
- The first query of the second example didn't get a superior response, however this is independent from our experiment settings, and depends more on the type of model we use, for example increasing the number of parameters (using a larger model) would definitely help.

### 6.1.4 Analysis over different steps and using different metrics

I now use a profiler to actually figure out at what all places, the most amount of time is being spent:

Table 6.1: Profiler Output

| Name | Self CPU % | Self CPU | CPU total % | CPU total | CPU time avg | Self CUDA | Self CUDA % | CUDA total | CUDA time avg | # of Calls |
|---|---|---|---|---|---|---|---|---|---|---|
| aten::matmul | 2.67% | 56.256ms | 30.07% | 632.976ms | 40.575us | 0.000us | 0.00% | 589.952ms | 37.817us | 15600 |
| aten::linear | 1.16% | 24.342ms | 30.78% | 647.989ms | 41.806us | 0.000us | 0.00% | 589.802ms | 38.052us | 15500 |
| aten::mm | 14.46% | 304.341ms | 22.68% | 477.495ms | 30.806us | 579.871ms | 69.41% | 589.802ms | 38.052us | 15500 |
| cutlass kernel (relu bf16) | 0.00% | 0.000us | 0.00% | 0.000us | 0.000us | 234.992ms | 28.13% | 234.992ms | 65.385us | 3594 |
| ampere_bf16_128x64_sliced1x2 | 0.00% | 0.000us | 0.00% | 0.000us | 0.000us | 124.274ms | 14.87% | 124.274ms | 66.457us | 1870 |
| ampere_bf16_128x128_stages_32x1 | 0.00% | 0.000us | 0.00% | 0.000us | 0.000us | 94.240ms | 11.28% | 94.240ms | 44.621us | 2112 |
| aten::mul | 6.55% | 137.891ms | 10.29% | 216.715ms | 10.728us | 61.543ms | 7.37% | 61.560ms | 3.048us | 20200 |
| aten::copy_ | 3.97% | 83.637ms | 8.32% | 175.218ms | 9.679us | 50.846ms | 6.09% | 50.857ms | 2.809us | 18103 |
| ampere_bf16_128x64_stages_64x3 | 0.00% | 0.000us | 0.00% | 0.000us | 0.000us | 44.572ms | 5.34% | 44.572ms | 19.481us | 2288 |
| aten::scaled_dot_product_attention | 0.84% | 17.683ms | 5.51% | 116.049ms | 52.749us | 0.000us | 0.00% | 44.127ms | 20.058us | 2200 |
| aten::_scaled_dot_product_flash_attention | 0.63% | 13.224ms | 4.67% | 98.366ms | 44.712us | 0.000us | 0.00% | 44.127ms | 20.058us | 2200 |
| aten::_flash_attention_forward | 1.00% | 21.077ms | 3.49% | 73.410ms | 33.368us | 44.073ms | 5.28% | 44.127ms | 20.058us | 2200 |
| flash_fwd_kernel | 0.00% | 0.000us | 0.00% | 0.000us | 0.000us | 43.833ms | 5.25% | 43.833ms | 20.125us | 2178 |
| elementwise_mul_kernel | 0.00% | 0.000us | 0.00% | 0.000us | 0.000us | 37.673ms | 4.51% | 37.673ms | 2.833us | 13300 |
| ampere_bf16_64x64_sliced1x4 | 0.00% | 0.000us | 0.00% | 0.000us | 0.000us | 34.059ms | 4.08% | 34.059ms | 28.669us | 1188 |
| aten::clone | 0.87% | 18.407ms | 6.48% | 136.324ms | 15.491us | 0.000us | 0.00% | 26.201ms | 2.977us | 8800 |
| elementwise_copy_kernel | 0.00% | 0.000us | 0.00% | 0.000us | 0.000us | 26.198ms | 3.14% | 26.198ms | 2.977us | 8800 |
| aten::add | 4.45% | 93.743ms | 7.17% | 150.912ms | 11.347us | 24.648ms | 2.95% | 24.657ms | 1.854us | 13300 |
| aten::to | 0.93% | 19.568ms | 8.33% | 175.368ms | 12.345us | 0.000us | 0.00% | 24.656ms | 1.736us | 14205 |
| aten::_to_copy | 1.29% | 27.125ms | 7.40% | 155.800ms | 16.747us | 0.000us | 0.00% | 24.656ms | 2.650us | 9303 |

Now we go over each of the rows, and further analyze the values:

1. `aten::matmul` = Pytorch's high level matrix multiplication. Runs on CPU side, but calls matrix multiply functions (`aten::mm`) on CUDA.
2. `aten::linear` = The linear layer, has large CUDA compute
3. `cutlass kernel (relu bf16)` = Stands for general matrix multiplication, entirely on CUDA
4. `ampere_...` = Specialized Ampere architecture GEMM kernel in BF16 precision for different tile sizes
5. `aten::mul` = Element-wise matrix multiplication, very high call count
6. `aten::copy_` = Copying tensors, very high call count
7. `aten::_flash_attention_forward` = The forward pass of flash attention

### 6.1.5 Profiling across pipeline stages

| Stage | Time (s) |
|---|---|
| Tokenize system prompt | 0.0052 |
| System forward (KV cache fill) | 0.3342 |
| Tokenize query | 0.0003 |
| Per token (mean / first) | 0.0148 / 0.0390 |
| Generation total | 0.7517 |
| Decode tokens | 0.0002 |

Table 6.2: Profiling results for various pipeline stages

## 6.2 Batch of Requests

We will measure the time taken to process a batch of requests, by varying the batch size:

Total number of queries: 24

| **Technique Used** | **Time (s)** |
|---|---|
| Transformers (batch size = 1) | 30.21 |
| Transformers (batch size = 2) | 19.51 |
| Transformers (batch size = 3) | 18.64 |
| vLLM (no system prompt pre-filling) | 0.45 |
| SGLang (fork) | 1.03 |
| SGLang (run_batch) | 0.40 |
| NEO | 0.55 |

Table 6.3: Measuring the time taken to process a batch of requests using different techniques

## 6.3 Throughput and Latency Measurements across different techniques

Here is the experiment setup:

- Model: `TinyLlama/TinyLlama-1.1B-Chat-v1.0`
- System Prompt: Roughly 1500 tokens (adopted from Ostep MLFQ schedulung chapter)
- Queries: 100 queries, each of length 10-20 tokens
- Max Output Length: 80 tokens
- Techniques Compared: vLLM (with and without automatic prompt caching), SGLang, swiftLLM

Here is how we generate the load:

**Algorithm 1:** Workload Generation at Target QPS

**Input:** LLM model `llm`, list of `prompts`, parameters `sampling_params`, target QPS `qps`
**Output:** Latencies of requests
Initialize empty list `latencies` ;
Set `interval` $\leftarrow 1/$`qps` ;
Set `start_time` $\leftarrow$ current time ;
Set index $i \leftarrow 0$ ;
Initialize empty `backlog` ;
Set `next_time` $\leftarrow$ current time ;
**while** $i <$ *length(`prompts`)* **do**
  Set `now` $\leftarrow$ current time ;
  Compute `intervals_passed` $\leftarrow \lfloor (now - next_time)/interval \rfloor + 1$ ;
  `// By the time we reached here, a few intervals might have passed, so we add that many prompts to the backload`
  **for** $k = 1$ **to** *`intervals_passed`* **do**
    **if** $i <$ *length(`prompts`)* **then**
      Append `prompts[i]` to `backlog` ;
      Increment $i$ ;
  **if** *`backlog` is not empty* **then**
    Set `batch_start` $\leftarrow$ current time ;
    Call `llm.generate(backlog, sampling_params)` ;
    Set `batch_latency` $\leftarrow$ current time $-$ `batch_start` ;
    `// All the requests in the backloag have the same latency because they were processed in a batch`
    **foreach** *request in `backlog`* **do**
      Append `batch_latency` to `latencies` ;
    Clear `backlog` ;
  Update `next_time` $\leftarrow$ `next_time` + `intervals_passed` $\times$ `interval` ;
  `// If we are ahead of the schedule, we sleep until the next request time`
  Set `sleep_time` $\leftarrow \max(0, next_time -$ `current time`$)$ ;
  `sleep(sleep_time)` ;
**return** (`latencies`) ;

We primarily measure the following metrics:

- **Throughput (QPS)**: Total number of requests / Total time taken
- **Average Latency (s)**: Average time taken per request, basically the time a user will have to wait
- **P95 Latency (s)**: 95th percentile latency across all requests, this helps us understand the tail latency, which in turn blocks the next batch of requests





Figure 6.1: Throughput





Figure 6.2: Average Latency





Figure 6.3: P95 Latency

## 6.4 LLM Request Timelines





Figure 6.4: 20 Requests per second





Figure 6.5: 25 Requests per second





Figure 6.6: All requests at once

### 6.4.1 Chunked Prefill Enabled





Figure 6.7: Request Timeline with GPU Metrics





Figure 6.8: Chunked Prefill Enabled - 100 Requests per second





Figure 6.9: Chunked Prefill Enabled - All requests at once

## 6.5 Maximum Throughput with vLLM

All requests sent together





Figure 6.10: Number of batch outputs - chunked prefill enabled

Total time taken: 3.84s (100 requests)
Throughput Observed: 26.04 QPS





Figure 6.11: Number of batch outputs - chunked prefill disabled

Total time taken: 4.97s (100 requests)
Throughput Observed: 20.12 QPS

## 6.6 Nsight Systems GPU Metrics

| Metric | Description |
|---|---|
| GPC Clock Frequency | GPU core clock (Graphics Processing Cluster). Determines SM execution speed. |
| SYS Clock Frequency | System clock domain of the GPU, affecting memory controllers, PCIe, and copy engines. |
| GR Active | Fraction of time the graphics engine is active (rendering or compute dispatch). |
| Sync Compute In Flight | Number of synchronous compute kernels currently executing (blocking). |
| Async Compute In Flight | Number of asynchronous compute kernels currently executing in parallel (non-blocking). |
| SM Active | Fraction of time at least one warp is active on any Streaming Multiprocessor (SM). |
| SM Issue Instructions | Fraction of cycles where SMs issued at least one instruction. Indicates pipeline utilization. |
| Tensor Active Instructions | Fraction of executed instructions that used Tensor Cores (e.g., matrix multiply). |
| SM Warp Occupancy | Ratio of active warps to the maximum possible per SM. Measures parallel utilization. |
| DRAM Bandwidth | Achieved global memory bandwidth (GB/s). Indicates memory throughput and potential bottlenecks. |
| PCIe RX/TX Throughput | Host-to-Device (RX) and Device-to-Host (TX) data transfer rates over PCIe. |
| PCIe Read/Write BAR1 Requests | CPU requests to GPU memory aperture (BAR1). Reads = CPU fetching from GPU, Writes = CPU writing to GPU. |

Table 6.4: Nsight Systems GPU Metrics

## 6.7 Throughput vs Load Comparison For vLLM





Figure 6.12: Throughput vs Load





Figure 6.13: Throughput vs Load for different models for heavy workloads

## 6.8 Families of Requests

| **Model Chosen** | **10 families, each with 1000 queries** | **1 family with 10000 requests** |
|---|---|---|
| Qwen 0.5B | 294.228 req/s | 308.750 req/s |
| Llama 7B | 43.923 req/s | 124.347 req/s |
| LongChat 13B | 22.415 req/s | 70.097 req/s |

## 6.9 Compute Utilization across various max batch sizes





Figure 6.14: SM Active and SM Occupancy across different max batch sizes

## 6.10 GPU Memory Breakdown

| **Component** | **Meaning** | **Memory Occupied** |
|---|---|---|
| Weights | Model parameters of the neural network. Static during inference. | 0.93 GiB |
| Peak Activation | Temporary tensors generated during forward pass. Depends on batch size and sequence length. | 4.07 GiB |
| Non-Torch | GPU memory used outside PyTorch tensors (framework/library overhead, buffers). | 0.02 GiB |
| CUDA Graph | Memory reserved for CUDA Graphs to optimize kernel execution and reduce CPU-GPU overhead. | 0.41 GiB |
| KV Cache: Intersection (Prefix) | Cached attention keys/values shared across requests (common prefix). | 1,280 tokens / 0.0157 GiB |
| KV Cache: Extras for Requests | Cached attention keys/values unique for each request. | 640 tokens (10 requests $\times$ 64 tokens) / 0.0078 GiB |
| KV Cache: Free | Remaining unused KV cache memory. | 2,672,880 tokens / 32.8445 GiB |

Table 6.5: GPU Memory Breakdown and KV Cache Usage

# Chapter 7

# Maths behind LLMs

## 7.1 Transformer FLOPs

The motivation for this section comes from Casson (2023). Counting the number of floating-point operations (FLOPs) in Transformers is a useful way to estimate compute requirements and measure efficiency.

### 7.1.1 FLOPs Calculation

Let's explain each operation and variable here:

- Embed: learned token embeddings and learned positional embeddings. $d_{model}$ is the dimensionality of the residual stream.
- Attention: QKV: linear layer in multi-head self-attention to project input into queries, keys, and values. $n_{layers}$ is the number of layers. $d_{attn}$ is the dimensionality of the output of multi-headed attention which is equal to $d_{key} \times n_{heads}$. $d_{key}$ is the dimension of the key, query, and value projections. $n_{heads}$ is the number of attention heads in a layer. In practice, Transformers are implemented such that $d_{attn} = d_{model}$.
- Attention: Mask: dot-product between query and keys. $n_{ctx}$ is the context/sequence length.
- Attention: Project: linear layer to project concatenated attention heads output to $d_{model}$.
- Feedforward: two linear layers in the MLP block. $d_{ff}$ is the size of the output dimensionality of the first linear layer. $d_{ff} = 4d_{model}$ is commonly used.
- De-embed: linear layer to obtain logits over vocabulary. $n_{vocab}$ is the number of tokens in the vocabulary.

Combining all the non-embedding FLOPs terms gets us

$$C_{forward} = 2N + 2n_{layer}n_{ctx}d_{attn}$$

| Operation | Parameters | FLOPs per Token |
|---|---|---|
| Embed | $(n_{\text{vocab}} + n_{\text{ctx}})d_{\text{model}}$ | $4d_{\text{model}}$ |
| Attention: QKV | $n_{\text{layer}}d_{\text{model}}3d_{\text{attn}}$ | $2n_{\text{layer}}d_{\text{model}}3d_{\text{attn}}$ |
| Attention: Mask | – | $2n_{\text{layer}}n_{\text{ctx}}d_{\text{attn}}$ |
| Attention: Project | $n_{\text{layer}}d_{\text{attn}}d_{\text{model}}$ | $2n_{\text{layer}}d_{\text{attn}}d_{\text{model}}$ |
| Feedforward | $n_{\text{layer}}2d_{\text{model}}d_{\text{ff}}$ | $2n_{\text{layer}}2d_{\text{model}}d_{\text{ff}}$ |
| De-embed | – | $2d_{\text{model}}n_{\text{vocab}}$ |
| **Total (Non-Embedding)** | $N = 2d_{\text{model}}n_{\text{layer}}(2d_{\text{attn}} + d_{\text{ff}})$ | $C_{\text{forward}} = 2N + 2n_{\text{layer}}n_{\text{ctx}}d_{\text{attn}}$ |

Figure 7.1: FLOPs Calculation Breakdown (from Casson (2023))

### 7.1.2 Model parameters (TinyLlama-1.1B-Chat)

$$
\begin{aligned}
L &= 22 \quad \text{(number of transformer layers)} \\
n_{\text{heads}} &= 32 \\
d_{\text{ff}} &= 5632 \quad \text{(intermediate / FFN size)} \\
V &= 32000 \quad \text{(vocabulary size)} \\
n_{\text{ctx}} &= 2048 \quad \text{(context / sequence length)}
\end{aligned}
$$

### 7.1.3 FLOPs Calculation for TinyLlama-1.1B-Chat

$C_{forward} = 2N + 2n_{layer}n_{ctx}d_{attn} = 2.2\times10^9 + 1.84549376\times10^8 = 2.3845\times10^9$ FLOPs.

### 7.1.4 Efficiency Calculation

We ran inference on TinyLlama-1.1B-Chat using a single Nvidia RTX6000 Ada GPU. Based on the docs from Nvidia (ada), the theoretical peak performance for FP16 is 1457 TFLOPs.

### 7.1.5 Efficiency Calculation

We ran inference on TinyLlama-1.1B-Chat using a single NVIDIA RTX6000 Ada GPU. Based on the docs from NVIDIA (ada), the theoretical peak performance for FP16 is 1457 TFLOPs.

So, the time taken for a forward pass of $n_{ctx} = 2048$ tokens should be:

$$
\begin{aligned}
T &= \frac{C_{forward} \times n_{ctx}}{\text{Peak TFLOPs}} \\
&= \frac{(2.3845 \times 10^9) \times 2048}{1.457 \times 10^{15}} \\
&= \frac{4.879 \times 10^{12}}{1.457 \times 10^{15}}
\end{aligned}
$$

$$= 3.35 \times 10^{-3} \text{ seconds } (\approx 3.35 \text{ ms})$$

During our experiments, we observed that the actual time taken for a forward pass of 100 prompts, each with a context length of 2048 tokens, was approximately 4.4s. Therefore, the time taken for a single forward pass with a context length of 2048 tokens is approximately 0.044s (or 44ms).

Thus, the efficiency can be calculated as:

$$\text{Efficiency} = \frac{\text{Theoretical Time}}{\text{Actual Time}} = \frac{3.35 \text{ ms}}{44 \text{ ms}} \approx 7.6\%$$

### 7.1.6 Summary of the nomenclature used

| Variable | Meaning |
|---|---|
| $d_{model}$ | Dimensionality of the residual stream (hidden size of the Transformer). |
| $L$ or $n_{layers}$ | Number of Transformer layers (blocks). |
| $n_{heads}$ | Number of attention heads in each multi-head attention layer. |
| $d_{key}$ | Dimensionality of each head's key, query, and value vectors. |
| $d_{attn}$ | Dimensionality of the concatenated multi-head attention output. Typically $d_{attn} = d_{key} \times n_{heads} = d_{model}$. |
| $n_{ctx}$ | Context length or sequence length, i.e., number of tokens processed in one forward pass. |
| $d_{ff}$ | Size of the hidden layer in the feedforward (MLP) block. Commonly $d_{ff} = 4d_{model}$. |
| $n_{vocab}$ or $V$ | Vocabulary size: number of tokens in the tokenizer vocabulary. |
| $N$ | Total number of trainable parameters in the model. |
| $C_{forward}$ | FLOPs required for a single forward pass per token. |

Table 7.1: Variables used in FLOPs

# Chapter 8

# QLora

# Bibliography

Llmservingsim: A hw/sw co-simulation infrastructure for llm inference serving at scale. URL https://arxiv.org/pdf/2408.05499.

Understanding the workload characteristics of large language model development. URL https://www.usenix.org/publications/loginonline/understanding-workload-characteristics-large-language-model-development.

Nvidia rtx 6000 ada generation. URL https://www.nvidia.com/content/dam/en-zz/Solutions/design-visualization/rtx-6000/proviz-print-rtx6000-datasheet-web-2504660.pdf.

How llms generate text for the rest of us. URL https://pm.dartus.fr/posts/2025/how-llm-generate-text/.

Adam Casson. Transformer flops. 2023. URL https://adamcasson.com/posts/transformer-flops.