MPFT: Multipath Reliable File Transfer

Computer Networks project. A file is split into chunks, sent in parallel over several TCP connections ("paths"), and written on the receiver only after SHA-256 verification. The transfer survives a dead path, corrupted data and interruption (resume).


Problem statement

A single TCP connection ties a transfer to one route. If that route stalls or breaks the transfer stops, a damaged file is only discovered at the end, and an interrupted transfer starts again from zero. Most hosts have more than one usable route (WiFi plus hotspot, several connections). MPFT uses them together and recovers from failures at chunk level.

Objectives

1. Aggregate bandwidth by sending chunks over N parallel TCP paths with automatic load balancing.
2. Detect and repair corruption per chunk (SHA-256, NACK, retransmit).
3. Survive path failure by requeueing in-flight chunks on the remaining paths.
4. Resume interrupted transfers without resending verified data.
5. Measure all of this with an emulated network, graphs, a dashboard and Wireshark.

Architecture



Details: docs/ARCHITECTURE.md, docs/TOPOLOGY.md.

Protocol summary

20-byte big-endian header (`MP`, version, type, session id, chunk index, payload length, CRC-32 of the header), then payload. Types: HELLO, MANIFEST (JSON with chunk hashes), MANIFEST_ACK (chunks already held), CHUNK, ACK, NACK, DONE, ERROR. Paths pull chunk indexes from a shared queue (faster paths carry more). Full spec: docs/PROTOCOL.md.

Requirements

macOS (or any OS with Python), Python 3.11+. Core uses only the standard library. Extras (`requirements.txt`): pytest, matplotlib, fastapi, uvicorn, markdown, httpx.

Quick start

```
python3 -m venv .venv && source .venv/bin/activate && pip install -r requirements.txt
head -c 50000000 /dev/urandom > /tmp/big.bin

python -m mpft receive --listen 127.0.0.1:9000 --out downloads        # terminal 1
python -m mpft send /tmp/big.bin --to 127.0.0.1:9000 --paths 4        # terminal 2
shasum -a 256 /tmp/big.bin downloads/big.bin
```

Flags: `--paths N`, `--chunk-size 256k`, `--to host:port[,host:port...]`, `--listen`, `--out`, `--bind`, `--csv file`.

Emulated paths

```
python -m mpft emulate --config topology.example.json     # ports 9201-9203 forward to the receiver on 9000
python -m mpft send /tmp/big.bin --to 127.0.0.1:9201,127.0.0.1:9202,127.0.0.1:9203
```

Per path: `delay_ms`, `jitter_ms`, `rate_mbit`, `drop_after_s` (path dies), `corrupt_rate`.

Two Macs over Tailscale

Receiver: `python -m mpft receive --listen 0.0.0.0:9000 --out downloads`. Sender: `python -m mpft send file --to 100.x.y.z:9000 --paths 4`. Setup, firewall prompt, hotspot fallback and caveats about college WiFi and CGNAT: docs/REMOTE.md. (Not yet tested on real hardware.)

Dashboard


```
python -m mpft dashboard          # http://127.0.0.1:8080, reads status/*.json
```

Tests and experiments

```
pytest -q                                          # 20 tests, about 12 s
python experiments/run_experiments.py              # 50 MB, about 3 minutes; --size-mb, --only baseline,failure
python experiments/plot_results.py                 # PNGs into results/
```

Results (50 MB, emulated paths, one run each)

Experiment	Result
1 / 2 / 4 / 8 paths	23 / 45 / 89 / 172 Mbit/s
Paths 80/20/5 Mbit/s	bytes carried 74 % / 20 % / 6 %
One of 3 paths dies at 1.5 s	completes, SHA-256 verified, recovery 0.15 s
1 % and 5 % chunk corruption	2 and 12 retransmissions, all verified
Resume after kill at 40 %	80 of 200 chunks skipped, 5.7 s vs 9.2 s



Full tables and analysis: docs/TEST_REPORT.md. Raw data: `results/*.csv`.

Wireshark

`wireshark/mpft.lua` decodes MPFT (`mpft.type`, `mpft.session`, `mpft.chunk`, `mpft.len`, `mpft.crc`). Capture instructions and screenshot checklist: wireshark/CAPTURE.md.

Demo

5-minute script with exact commands: docs/DEMO_SCRIPT.md. Viva questions: docs/VIVA_PREP.md. Code tour: docs/WALKTHROUGH.md.

Limitations

- Paths are emulated on one machine; results are not real-network measurements.
- The emulator does not simulate true packet loss (TCP would hide it); corruption is injected above TCP.
- No encryption or authentication by default (use Tailscale/VPN).
- One chunk in flight per path (stop-and-wait), so a single path under-uses its link.
- Experiments ran once per setting, without confidence intervals.
- Wireshark dissector is syntax-checked only and the Tailscale run is untested here; both need a manual check.

Team contributions

See docs/CONTRIBUTIONS.md.