

Network Security

- IPsec -
- Firewalls -

Dr. John Keeney

3BA33

Background

Slides Sources: Henric Johnson, Charlie Kaufman, Wikipedia, Andre E. Bar'yudin, Lawrie Brown, Munehiro Fukuda, Sue Moon.

Recommended Reading:

- Stallings, W., Cryptography and Network Security: Principles and Practice, 2nd edition. Prentice Hall, 1999
- Pfleeger, C., Security in Computing. Prentice Hall, 1997.
- Kurose, J., Ross, K., Computer Networking: A Top Down Approach Featuring the Internet. Addison-Wesley, 2002.
- RFC4301-4309
- Chapman, D., and Zwicky, E. Building Internet Firewalls. O'Reilly, 1995
- Cheswick, W., and Bellovin, S. Firewalls and Internet Security: Repelling the Wily Hacker. Addison-Wesley, 2000
- Wikipedia

25/04/2007

2


IP Security

- have considered some application specific security mechanisms
 - eg. S/MIME, PGP, SSL/TLS
- however there are security concerns that cut across protocol layers
- would like security implemented by the network for all applications

25/04/2007

3


TCP/IP Example



25/04/2007

4


IPv4 Header



25/04/2007

5

IPv6 Header



25/04/2007

6

IPsec: Network Layer Security

- Network-layer secrecy:
 - sending host encrypts the data in IP datagram
 - TCP and UDP segments; ICMP and SNMP messages.
- Network-layer authentication
 - destination host can authenticate source IP address
- Applicable to use over LANs, across public & private WANs, & for the Internet
- Optional in IPv4, Mandatory in IPv6
 - Designed for IPv6, back-ported to IPv4

25/04/2007

7

IPsec: Network Layer Security

- Tunnel mode versus Transport mode
 - Transport Mode provides a secure connection between two endpoints as it encapsulates IP's **payload**. The IP header is neither modified nor encrypted. Requires IPsec support at each host.
 - Tunnel Mode encapsulates the **entire** IP packet to provide a virtual "secure hop" between two gateways. Encrypted Packet is encapsulated into a new IP packet. Requires IPsec support at end hosts.
- Two options: AH (authentication) and ESP (encapsulated security)
 - the two main wire-level protocols used by IPsec
 - Authenticate (AH) the data flowing over the connection.
 - Encrypt & Authenticate (ESP) the data flowing over the connection.
 - Typically used independently,
 - possible (but uncommon) to use them both together.

25/04/2007

8

IPSec provides

- Access Control
- Transparent to applications (below transport layer (TCP, UDP))
- Data origin authentication
- Rejection of replayed packets
- Confidentiality (encryption)
- Limited traffic flow confidentiality
- Provide security for individual users
- IPSec can assure that:
 - A router or neighbour advertisement comes from an authorized router
 - A redirect message comes from the router to which the initial packet was sent
 - A routing update is not forged

25/04/2007

9

Security Associations

- For both AH and ESP, source/destination handshake creates a network-layer logical channel called a security association (SA)
- a one-way relationship between sender & receiver that affords security for traffic flow
- Each SA unidirectional.
- A security association is simply the bundle of algorithms and parameters (such as keys) that is being used to encrypt a particular flow.
- The actual choice of algorithm is left up to the users.
- A security parameter index (SPI) is provided along with the destination address to allow the security association for a packet to be looked up in a database of SAs at the receiver.
- Before sender can use IPSec to communicate with a receiver, sender must know index value of a SA on receiver
 - Index values owned by destinations, not globally known!
 - SAs can have lifetimes by reusing index values

25/04/2007

10

Authentication Header (AH)


- Authentication by adding a new Header
- provides support for data integrity & authentication of IP packets
 - end system/router can authenticate user/app
 - prevents address spoofing attacks by tracking sequence numbers
 - No encryption
- based on use of a MAC
 - MD5 or SHA-1
- parties must share a secret key
- protocol field: 51
- AH header inserted between IP header, data field.
 - intermediate routers process datagrams as usual

25/04/2007

11

Authentication Header

- Provides support for data integrity and authentication (MAC code) of IP packets.
- Guards against replay attacks.
- Contains:
 - connection identifier
 - authentication data: source- signed message digest calculated over original IP datagram.
 - next header field: specifies type of data (e.g., TCP, UDP, ICMP)




25/04/2007

12

IP header AH header data (e.g., TCP, UDP segment)


Before applying AH



25/04/2007

13


Transport Mode AH Authentication



25/04/2007

14

Tunnel Mode AH Authentication




25/04/2007

15

AH in Transport Mode

IPSec in AH Transport Mode




25/04/2007

16

AH in Tunnel Mode

IPSec in AH Tunnel Mode




25/04/2007

17


Encapsulating Security Payload: ESP

- Authentication and Encryption by encrypting and encapsulating the datagram rather than adding a header
- ESP provides confidentiality services
- can optionally provide the same authentication services as AH
- Data & ESP trailer encrypted.
- Next header field is in ESP trailer.
- ESP authentication field is similar to AH authentication field.
- Protocol = 50.
- Encryption
 - 3DES, RC5, IDEA, 3IDEA, CAST, Blowfish
- Authentication:
 - MD5, SHA-1



25/04/2007


ESP Encryption and Authentication



25/04/2007

19


ESP Encryption and Authentication



25/04/2007

20


ESP in Transport Mode



25/04/2007

21

ESP in Tunnel Mode



25/04/2007

22

Transport vs Tunnel Mode ESP

- transport mode is used to encrypt & optionally authenticate IP data
 - data protected but header left in clear
 - can do traffic analysis but is efficient
 - good for ESP host to host traffic
- tunnel mode encrypts entire IP packet
 - add new header for next hop
 - good for VPNs, gateway to gateway security

25/04/2007

23

Summary

	Transport Mode SA	Tunnel Mode SA
AH	Authenticates IP payload and selected portions of IP header and IPv6 extension headers	Authenticates entire inner IP packet plus selected portions of outer IP header
ESP	Encrypts IP payload and any IPv6 extension header	Encrypts inner IP packet
ESP with authentication	Encrypts IP payload and any IPv6 extension header. Authenticates IP payload but not IP header	Encrypts inner IP packet. Authenticates inner IP packet.

25/04/2007

24

Key management

- ESP and AH use *session keys*
- Sessions are called *Security Associations*
 - Indexed by protocol, IP address, SPI
- Two types:
 - Manual
 - Can manually config AH/ESP keys
 - sysadmin manually configures every system
 - Automated
 - for on demand creation of keys for SA's in large systems
 - Oakley Key Determination Protocol
 - based on Diffie-Hellman key exchange
 - address weaknesses of DH, e.g man-in-the-middle, DoS etc
 - Internet Security Association and Key Management Protocol (ISAKMP)
 - defines procedures and packet formats to establish, negotiate, modify, & delete SAs
 - independent of key exchange protocol, encryption alg, & authentication method

25/04/2007

25

Benefits of IPsec

- in a firewall/router provides strong security to all traffic crossing the perimeter
- is resistant to bypass
- is below transport layer, hence transparent to applications
- can be transparent to end users
- can provide security for individual users if desired

25/04/2007

26

IPsec redux

- Deployment of IPsec limited
 - Global PKI infrastructure hard to set up
 - Wrong layer for security
 - Session/Application-layer, rather than Network layer
 - Fixes a “solved” problem
 - SSL & SSH work well
- IPsec success: VPNs
 - Use tunnel mode of IPsec

25/04/2007

27


25/04/2007

28

Firewalls

firewall

isolates organization's internal net from larger Internet, allowing some packets to pass, blocking others.



25/04/2007

29

What is a Firewall?

- a **choke point** of control and monitoring
- interconnects networks with differing trust
- All traffic from in and out must pass through the firewall (physically blocking all access to the local network except via the firewall)
- imposes restrictions on network services
 - only authorised traffic is allowed
- auditing and controlling access
 - can implement alarms for abnormal behavior
- is itself immune to penetration
- provides **perimeter defence**

25/04/2007

30

Firewall Limitations

- cannot protect from attacks bypassing it
- cannot protect against internal threats
 - E.g. disgruntled employee
- cannot protect against transfer of all virus infected programs or files
 - because of huge range of O/S & file types

25/04/2007

31

Firewall Characteristics

- Four general techniques:
 - Service control
 - Determines the types of Internet services that can be accessed, inbound or outbound
 - Direction control
 - Determines the direction in which particular service requests are allowed to flow
 - User control
 - Controls access to a service according to which user is attempting to access it
 - Behavior control
 - Controls how particular services are used (e.g. filter e-mail)

25/04/2007

32


Types of Firewalls

- Three common types of Firewalls:
 - Packet-filtering routers
 - Application-level gateways
 - Circuit-level gateways

25/04/2007

33

Firewalls – Packet Filters



25/04/2007

34

Firewalls – Packet Filters

- simplest of components
- foundation of any firewall system
- Two default policies (discard or forward)
 - that not expressly permitted is prohibited
 - that not expressly prohibited is permitted
- Applies a set of rules to each incoming and outgoing IP packet (no context) and then forwards or discards the packet
- The packet filter is typically set up as a list of rules based on matches to fields in the IP or TCP header

25/04/2007

35

Packet Filters Example

- Example 1: block incoming and outgoing datagrams with IP protocol field = 17 and with either source or dest port = 23.
 - All incoming and outgoing UDP flows and telnet connections are blocked.
- Example 2: Block inbound TCP segments with ACK=0.
 - Prevents external clients from making TCP connections with internal clients, but allows internal clients to connect to outside.

25/04/2007

36

Attacks on Packet Filters

- IP address spoofing
 - fake source address to be trusted
 - add filters on router to block
- source routing attacks
 - attacker sets a route other than default
 - block source routed packets
- tiny fragment attacks
 - split header info over several tiny packets
 - either discard or reassemble before check

25/04/2007

37

Firewalls – Stateful Packet Filters

- examine each IP packet in context
 - keeps tracks of client-server sessions
 - checks each packet validly belongs to one
- better able to detect bogus packets out of context

25/04/2007

38


Packet Filters

- Advantages:
 - Simplicity
 - Transparency to users
 - High speed
- Disadvantages:
 - Difficulty of setting up packet filter rules
 - Lack of Authentication

25/04/2007

39

Firewalls - Application Level Gateway (or Proxy)



25/04/2007

40

Firewalls - Application Level Gateway (or Proxy)

- use an application specific gateway / proxy
 - acts as a relay of application-level traffic
- has full access to protocol
 - user requests service from proxy
 - proxy validates request as legal
 - then actions request and returns result to user
- need separate proxies for each service
 - some services naturally support proxying
 - others are more problematic
 - custom services generally not supported

25/04/2007

41

Application Level Gateway Example

- Example: allow select internal users to telnet outside.
 1. Require all telnet users to telnet through gateway.
 2. For authorized users, gateway sets up telnet connection to dest host. Gateway relays data between 2 connections
 3. Router filter blocks all telnet connections not originating from gateway.

25/04/2007

42


Application Level Gateway (or Proxy)

- Advantages:
 - Higher security than packet filters
 - Only need to scrutinize a few allowable applications
 - Easy to log and audit all incoming traffic
- Disadvantages:
 - Additional processing overhead on each connection (gateway as splice point)
 - client software must know how to contact gateway.
 - e.g., must set IP address of proxy in Web browser

25/04/2007

43

Firewalls - Circuit Level Gateway



25/04/2007

44

Firewalls - Circuit Level Gateway


- relays two TCP connections
- imposes security by limiting which such connections are allowed
- once created usually relays traffic without examining contents
- typically used when trust internal users by allowing general outbound connections
- SOCKS commonly used for this

25/04/2007

45

Firewall Configuration example

- In addition to the use of simple configuration of a single system (single packet filtering router or single gateway), more complex configurations are possible
- e.g. Firewall consists of three systems:
 - An external packet-filtering router
 - A bastion host
 - A system identified by the firewall administrator as a critical strong point in the network's security
 - The bastion host serves as a platform for an application-level or circuit-level gateway
 - An internal packet-filtering router



25/04/2007

46

Firewall Configuration example

- Configuration for the packet-filtering router:
 - Only packets from and to the bastion host are allowed to pass through the router
- The bastion host performs authentication and proxy functions
- Greater security than single configurations because of two reasons:
 - This configuration implements both packet-level and application-level filtering (allowing for flexibility in defining security policy)
 - An intruder must generally penetrate two separate systems
- This configuration also affords flexibility in providing direct Internet access (public information server, e.g. Web server)

25/04/2007

47