

```
[ec2-user@ip-172-31-85-87 ~]$
```

root@ip-172-31-85-87:~

[root@ip-172-31-85-87 ~]# ip -br addr

lo UNKNOWN 127.0.0.1/8 ::1/128

ens5 UP 172.31.85.87/20 metric 512 fe80::10e8:74ff:feba:e4a3/64

[root@ip-172-31-85-87 ~]#



EN



5:09 PM
9/11/2026

```
[root@ip-172-31-85-87 ~]# ip link
```

```
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN mode DEFAULT group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
2: ens5: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 9001 qdisc mq state UP mode DEFAULT group default qlen 1000
    link/ether 12:e8:74:ba:e4:a3 brd ff:ff:ff:ff:ff:ff
    altname enp0s5
    altname eni-08e81fc7cece4a59c
    altname device-number-0.0
```

```
[root@ip-172-31-85-87 ~]#
```



root@ip-172-31-85-87:~

```
[root@ip-172-31-85-87 ~]# ip route
default via 172.31.80.1 dev ens5 proto dhcp src 172.31.85.87 metric 512
172.31.0.2 via 172.31.80.1 dev ens5 proto dhcp src 172.31.85.87 metric 512
172.31.80.0/20 dev ens5 proto kernel scope link src 172.31.85.87 metric 512
172.31.80.1 dev ens5 proto dhcp scope link src 172.31.85.87 metric 512
[root@ip-172-31-85-87 ~]#
```



EN



5:10 PM
9/11/2026

root@ip-172-31-85-87:~

```
[root@ip-172-31-85-87 ~]# cat /etc/resolv.conf
```

```
# This is /run/systemd/resolve/resolv.conf managed by man:systemd-resolved(8).
```

```
# Do not edit.
```

```
#
```

```
# This file might be symlinked as /etc/resolv.conf. If you're looking at  
# /etc/resolv.conf and seeing this text, you have followed the symlink.
```

```
#
```

```
# This is a dynamic resolv.conf file for connecting local clients directly to  
# all known uplink DNS servers. This file lists all configured search domains.
```

```
#
```

```
# Third party programs should typically not access this file directly, but only  
# through the symlink at /etc/resolv.conf. To manage man:resolv.conf(5) in a  
# different way, replace this symlink by a static file or a different symlink.
```

```
#
```

```
# See man:systemd-resolved.service(8) for details about the supported modes of  
# operation for /etc/resolv.conf.
```

```
nameserver 172.31.0.2
```

```
search ec2.internal
```

```
[root@ip-172-31-85-87 ~]#
```



```
[root@ip-172-31-85-87 ~]# ip addr
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host noprefixroute
        valid_lft forever preferred_lft forever
2: ens5: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 9001 qdisc mq state UP group default qlen 1000
    link/ether 12:e8:74:ba:e4:a3 brd ff:ff:ff:ff:ff:ff
    altname enp0s5
    altname eni-08e81fc7cece4a59c
    altname device-number-0.0
    inet 172.31.85.87/20 metric 512 brd 172.31.95.255 scope global dynamic ens5
        valid_lft 3229sec preferred_lft 3229sec
    inet6 fe80::10e8:74ff:feba:e4a3/64 scope link proto kernel_ll
        valid_lft forever preferred_lft forever
[root@ip-172-31-85-87 ~]#
```

root@ip-172-31-85-87:~

```
[root@ip-172-31-85-87 ~]# ping -c 4 8.8.8.8
PING 8.8.8.8 (8.8.8.8) 56(84) bytes of data.
64 bytes from 8.8.8.8: icmp_seq=1 ttl=116 time=1.09 ms
64 bytes from 8.8.8.8: icmp_seq=2 ttl=116 time=1.07 ms
64 bytes from 8.8.8.8: icmp_seq=3 ttl=116 time=1.10 ms
64 bytes from 8.8.8.8: icmp_seq=4 ttl=116 time=1.07 ms

--- 8.8.8.8 ping statistics ---
4 packets transmitted, 4 received, 0% packet loss, time 3004ms
rtt min/avg/max/mdev = 1.072/1.083/1.098/0.011 ms
[root@ip-172-31-85-87 ~]#
```



EN



5:11 PM
9/11/2026

```
[root@ip-172-31-85-87 ~]# ip -4 addr
```

```
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
2: ens5: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 9001 qdisc mq state UP group default qlen 1000
    altname enp0s5
    altname eni-08e81fc7cece4a59c
    altname device-number-0.0
    inet 172.31.85.87/20 metric 512 brd 172.31.95.255 scope global dynamic ens5
        valid_lft 3043sec preferred_lft 3043sec
[root@ip-172-31-85-87 ~]#
```

root@ip-172-31-85-87:~

[root@ip-172-31-85-87 ~]# hostname -I

172.31.85.87

[root@ip-172-31-85-87 ~]#



EN



5:14 PM
9/11/2026

root@ip-172-31-85-87:~

```
[root@ip-172-31-85-87 ~]# ip route
default via 172.31.80.1 dev ens5 proto dhcp src 172.31.85.87 metric 512
172.31.0.2 via 172.31.80.1 dev ens5 proto dhcp src 172.31.85.87 metric 512
172.31.80.0/20 dev ens5 proto kernel scope link src 172.31.85.87 metric 512
172.31.80.1 dev ens5 proto dhcp scope link src 172.31.85.87 metric 512
[root@ip-172-31-85-87 ~]#
```



EN



5:15 PM
9/11/2026

root@ip-172-31-85-87:~

[root@ip-172-31-85-87 ~]# ip route|grep default

default via 172.31.80.1 dev ens5 proto dhcp src 172.31.85.87 metric 512

[root@ip-172-31-85-87 ~]#



EN



5:18 PM
9/11/2026

```
[root@ip-172-31-85-87 ~]# ip route|grep default
default via 172.31.80.1 dev ens5 proto dhcp src 172.31.85.87 metric 512
[root@ip-172-31-85-87 ~]# ping -c 4 172.31.85.87
PING 172.31.85.87 (172.31.85.87) 56(84) bytes of data.
64 bytes from 172.31.85.87: icmp_seq=1 ttl=127 time=0.029 ms
64 bytes from 172.31.85.87: icmp_seq=2 ttl=127 time=0.028 ms
64 bytes from 172.31.85.87: icmp_seq=3 ttl=127 time=0.029 ms
64 bytes from 172.31.85.87: icmp_seq=4 ttl=127 time=0.027 ms

--- 172.31.85.87 ping statistics ---
4 packets transmitted, 4 received, 0% packet loss, time 311ms
rtt min/avg/max/mdev = 0.027/0.028/0.029/0.000 ms
[root@ip-172-31-85-87 ~]#
```

root@ip-172-31-85-87:~

[root@ip-172-31-85-87 ~]# ip -br addr

lo UNKNOWN 127.0.0.1/8 ::1/128

ens5 UP 172.31.85.87/20 metric 512 fe80::10e8:74ff:feba:e4a3/64

[root@ip-172-31-85-87 ~]#



EN



5:19 PM
9/11/2026

root@ip-172-31-85-87:~

```
[root@ip-172-31-85-87 ~]# ip route
default via 172.31.80.1 dev ens5 proto dhcp src 172.31.85.87 metric 512
172.31.0.2 via 172.31.80.1 dev ens5 proto dhcp src 172.31.85.87 metric 512
172.31.80.0/20 dev ens5 proto kernel scope link src 172.31.85.87 metric 512
172.31.80.1 dev ens5 proto dhcp scope link src 172.31.85.87 metric 512
[root@ip-172-31-85-87 ~]#
```



EN



5:20 PM
9/11/2026

root@ip-172-31-85-87:~

[root@ip-172-31-85-87 ~]# ip -br addr

lo UNKNOWN 127.0.0.1/8 ::1/128

ens5 UP 172.31.85.87/20 metric 512 fe80::10e8:74ff:feba:e4a3/64

[root@ip-172-31-85-87 ~]#



EN



5:25 PM
9/11/2026

root@ip-172-31-85-87:~

[root@ip-172-31-85-87 ~]# hostname -I

172.31.85.87

[root@ip-172-31-85-87 ~]#



EN



5:27 PM
9/11/2026

```
[root@ip-172-31-85-87 ~]# ip -4 addr
```

```
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
2: ens5: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 9001 qdisc mq state UP group default qlen 1000
    altname enp0s5
    altname eni-08e81fc7cece4a59c
    altname device-number-0.0
    inet 172.31.85.87/20 metric 512 brd 172.31.95.255 scope global dynamic ens5
        valid_lft 3273sec preferred_lft 3273sec
[root@ip-172-31-85-87 ~]#
```



root@ip-172-31-85-87:~

```
[root@ip-172-31-85-87 ~]# ip route
default via 172.31.80.1 dev ens5 proto dhcp src 172.31.85.87 metric 512
172.31.0.2 via 172.31.80.1 dev ens5 proto dhcp src 172.31.85.87 metric 512
172.31.80.0/20 dev ens5 proto kernel scope link src 172.31.85.87 metric 512
172.31.80.1 dev ens5 proto dhcp scope link src 172.31.85.87 metric 512
[root@ip-172-31-85-87 ~]#
```



EN



5:28 PM
9/11/2026

root@ip-172-31-85-87:~

[root@ip-172-31-85-87 ~]# curl -4 ifconfig.me

184.73.105.109[root@ip-172-31-85-87 ~]#



EN



5:29 PM
9/11/2026

```
[root@ip-172-31-85-87 ~]# ip link
```

```
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN mode DEFAULT group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
2: ens5: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 9001 qdisc mq state UP mode DEFAULT group default qlen 1000
    link/ether 12:e8:74:ba:e4:a3 brd ff:ff:ff:ff:ff:ff
    altname enp0s5
    altname eni-08e81fc7cece4a59c
    altname device-number-0.0
```

```
[root@ip-172-31-85-87 ~]#
```



root@ip-172-31-85-87:~

```
[root@ip-172-31-85-87 ~]# ip route
default via 172.31.80.1 dev ens5 proto dhcp src 172.31.85.87 metric 512
172.31.0.2 via 172.31.80.1 dev ens5 proto dhcp src 172.31.85.87 metric 512
172.31.80.0/20 dev ens5 proto kernel scope link src 172.31.85.87 metric 512
172.31.80.1 dev ens5 proto dhcp scope link src 172.31.85.87 metric 512
[root@ip-172-31-85-87 ~]#
```



EN



5:30 PM
9/11/2026

root@ip-172-31-85-87:~

```
[root@ip-172-31-85-87 ~]# ping -c 4 8.8.8.8
PING 8.8.8.8 (8.8.8.8) 56(84) bytes of data.
64 bytes from 8.8.8.8: icmp_seq=1 ttl=117 time=0.934 ms
64 bytes from 8.8.8.8: icmp_seq=2 ttl=117 time=0.927 ms
64 bytes from 8.8.8.8: icmp_seq=3 ttl=117 time=0.936 ms
64 bytes from 8.8.8.8: icmp_seq=4 ttl=117 time=0.942 ms

--- 8.8.8.8 ping statistics ---
4 packets transmitted, 4 received, 0% packet loss, time 3058ms
rtt min/avg/max/mdev = 0.927/0.934/0.942/0.005 ms
[root@ip-172-31-85-87 ~]#
```



```
[root@ip-172-31-85-87 ~]# ping -c 4 google.com
PING google.com (142.250.31.138) 56(84) bytes of data:
64 bytes from bj-in-f138.1e100.net (142.250.31.138): icmp_seq=1 ttl=108 time=1.10 ms
64 bytes from bj-in-f138.1e100.net (142.250.31.138): icmp_seq=2 ttl=108 time=1.12 ms
64 bytes from bj-in-f138.1e100.net (142.250.31.138): icmp_seq=3 ttl=108 time=1.11 ms
64 bytes from bj-in-f138.1e100.net (142.250.31.138): icmp_seq=4 ttl=108 time=1.10 ms

--- google.com ping statistics ---
4 packets transmitted, 4 received, 0% packet loss, time 3005ms
rtt min/avg/max/mdev = 1.102/1.109/1.124/0.008 ms
[root@ip-172-31-85-87 ~]#
```



root@ip-172-31-85-87:~

```
[root@ip-172-31-85-87 ~]# cat /etc/resolv.conf
# This is /run/systemd/resolve/resolv.conf managed by man:systemd-resolved(8).
# Do not edit.
#
# This file might be symlinked as /etc/resolv.conf. If you're looking at
# /etc/resolv.conf and seeing this text, you have followed the symlink.
#
# This is a dynamic resolv.conf file for connecting local clients directly to
# all known uplink DNS servers. This file lists all configured search domains.
#
# Third party programs should typically not access this file directly, but only
# through the symlink at /etc/resolv.conf. To manage man:resolv.conf(5) in a
# different way, replace this symlink by a static file or a different symlink.
#
# See man:systemd-resolved.service(8) for details about the supported modes of
# operation for /etc/resolv.conf.
```

```
nameserver 172.31.0.2
search ec2.internal
```

```
[root@ip-172-31-85-87 ~]#
```



```
[root@ip-172-31-85-87 ~]# service httpd status
```

```
Redirecting to /bin/systemctl status httpd.service
```

```
• httpd.service - The Apache HTTP Server
```

```
Loaded: loaded (/usr/lib/systemd/system/httpd.service; disabled; preset: disabled)
```

```
Active: active (running) since Fri 2026-09-11 12:03:35 UTC; 39s ago
```

```
Docs: man:httpd.service(8)
```

```
Main PID: 2443 (httpd)
```

```
Status: "Total requests: 0; Idle/Busy workers 100/0;Requests/sec: 0; Bytes served/sec: 0 B/sec"
```

```
Tasks: 177 (limit: 1059)
```

```
Memory: 18.6M
```

```
CPU: 119ms
```

```
CGroup: /system.slice/httpd.service
```

```
├─2443 /usr/sbin/httpd -DFOREGROUND
```

```
├─2500 /usr/sbin/httpd -DFOREGROUND
```

```
├─2501 /usr/sbin/httpd -DFOREGROUND
```

```
├─2503 /usr/sbin/httpd -DFOREGROUND
```

```
└─2523 /usr/sbin/httpd -DFOREGROUND
```

```
Sep 11 12:03:35 ip-172-31-85-87.ec2.internal systemd[1]: Starting httpd.service - The Apache HTTP Server...
```

```
Sep 11 12:03:35 ip-172-31-85-87.ec2.internal systemd[1]: Started httpd.service - The Apache HTTP Server.
```

```
Sep 11 12:03:35 ip-172-31-85-87.ec2.internal httpd[2443]: Server configured, listening on: port 80
```

```
[root@ip-172-31-85-87 ~]#
```



```
[root@ip-172-31-85-87 ~]# ss -tulnp
```

Netid	State	Recv-Q	Send-Q	Local Address:Port	Peer Address:Port
Process					
udp	UNCONN	0	0	127.0.0.1:323	0.0.0.0:*
users: (("chronyd",pid=1895,fd=5))					
udp	UNCONN	0	0	172.31.85.87:ens5:68	0.0.0.0:*
users: (("systemd-network",pid=1704,fd=17))					
udp	UNCONN	0	0	:::1:323	:::*
users: (("chronyd",pid=1895,fd=6))					
udp	UNCONN	0	0	[fe80::10e8:74ff:feba:e4a3]:ens5:546	:::*
users: (("systemd-network",pid=1704,fd=19))					
tcp	LISTEN	0	128	0.0.0.0:22	0.0.0.0:*
users: (("sshd",pid=1866,fd=7))					
tcp	LISTEN	0	128	:::22	:::*
users: (("sshd",pid=1866,fd=8))					
tcp	LISTEN	0	511	*:80	*:*
users: (("httpd",pid=2523,fd=4), ("httpd",pid=2503,fd=4), ("httpd",pid=2501,fd=4), ("httpd",pid=2443,fd=4))					

```
[root@ip-172-31-85-87 ~]#
```

root@ip-172-31-85-87:~

```
[root@ip-172-31-85-87 ~]# service firewalld status  
Redirecting to /bin/systemctl status firewalld.service  
Unit firewalld.service could not be found.  
[root@ip-172-31-85-87 ~]#
```



EN



5:36 PM
9/11/2026

us-east-1.console.aws.amazon.com/ec2/home?region=us-east-1#InstanceDetails:instanceId=i-0d16a02d787cf8988

aws

Search

[Alt+S]

Ask Amazon Q

United States (N. Virginia)

Sakshi M Jadhav (595981035584)

Sakshi M Jadhav

EC2

Instances

i-0d16a02d787cf8988

EC2

Dashboard

AWS Global View

Events

Instances

Instance Types

Launch Templates

Spot Requests

Savings Plans

Reserved Instances

Dedicated Hosts

Capacity Reservations

Capacity Manager

Images

AMIs

AMI Catalog

sg-0440bfa5811e93db0 (launch-wizard-11)

Inbound rules

Filter rules

Name	Security group rule ID	Port range	Protocol	Source
-	sgr-07beb0b548fdc3889	22	TCP	0.0.0.0/0

Outbound rules

Filter rules

Name	Security group rule ID	Port range	Protocol	Destination
-	sgr-0fa7b6894c67133bd	All	All	0.0.0.0/0

CloudShell

Agent Toolkit for AWS

Console Mobile App

© 2026, Amazon Web Services, Inc. or its affiliates.

Privacy

Terms

Cookie preferences

EN

5:36 PM

9/11/2026