



## Today's agenda

- ↳ Intro to arrays
- ↳ Return sum of `arr[]` elements.
- ↳ Array with functions
- ↳ Swap 2 indexes.



# AlgoPrep





1000 numbers?

# Array

collection of variables.


1

910 = "

```
↳ type[] name = new type[size];
```

```
ex: int[] arr = new int[100];
```

↳ `int[] arr = new int[10];`






// Input in array

Q) Create an array of length 5 with values 10 20 30 40 50  
 $n=5$



```
1 // "static void main" must be defined in a public class.
2 public class Main {
3     public static void main(String[] args) {
4         Scanner scn = new Scanner(System.in);
5         int n = scn.nextInt();
6
7         int[] arr = new int[n];
8
9         for(int i = 0; i < n; i++){
10             arr[i] = scn.nextInt();
11         }
12
13     }
14 }
```



stdin

5

10 20 30 40 50

Share

Live

Add Snippet

→ initialize array on your own.

`int[] arr = {1, 2, 3, 4, 5};`

→ `arr.length` = no. of elements in array.

→ if `arr` is of length `n`,

1st index = 0

last index =  $n-1$





## Q) How to Print all the elements of arr.

Run Code

Untitled

Save

Java

```
1 // "static void main" must be defined in a public class.
2 public class Main {
3     public static void main(String[] args) {
4         Scanner scn = new Scanner(System.in);
5         int n = scn.nextInt();
6
7         int[] arr = new int[n];
8         for(int i = 0; i < n; i++){
9             arr[i] = scn.nextInt();
10        }
11
12        for(int i = 0; i < n; i++){
13            System.out.print(arr[i] + " ");
14        }
15
16
17    }
18 }
```

Output: Finished

Clear Console

Finished in 148 ms

1020304050

Finished in 175 ms

10 20 30 40 50

stdin

5

10 20 30 40 50

Share

Live

Add Snippet



# AlgoPrep





## Q) Sum of array

↳ Read an array of  $N$  length and Print the sum of all elements.

Ex: arr[4]: <sup>0</sup>10 <sup>1</sup>-1 <sup>2</sup>3 <sup>3</sup>-7 → 5

### Pseudo code

// "static void main" must be defined in a public class.

```
public class Main {  
    public static void main(String[] args) {  
        Scanner scn = new Scanner(System.in);  
        int n = scn.nextInt();
```

```
        int[] arr = new int[n];  
        for(int i = 0; i < n; i++){  
            arr[i] = scn.nextInt();  
        }
```

```
        int sum = 0;  
        for(int i = 0; i < n; i++){  
            sum = sum + arr[i];  
        }
```

```
        System.out.println(sum);
```

```
    }
```

Sum = 0

$n=4$

arr[4]: <sup>0</sup>10 <sup>1</sup>-1 <sup>2</sup>3 <sup>3</sup>-7

i	i < n	Sum
0	+	10
1	+	9
2	+	12
3	+	5
4	6 → exit	

T.C:  $2n$   
↓  
 $O(n)$

S.C:  $1/2$   
↓  
 $O(1)$

input & output is not your space





How arrays are actually stored?

```
int main() {  
    int n=10;  
    int[] arr = {10, 2, 3};  
}
```

→ System.out.println(arr[2]);

3

main {

arr: #ref

n: 10

Stack

Heap

#ref

0	1	2
10	20	30

Break till 10:34 PM





Q) Swap the values of 2 variables.

$a = 10$        $b = 20$        $\rightarrow$        $a = 20$        $b = 10$

// incorrect way

```
main ( ) {  
    int a = 10;  
    int b = 20;
```

```
    a = b;  
     $\rightarrow$  b = a;
```

```
}
```

20  
~~10~~  
a

20  
b

// Correct way

```
main ( ) {  
    int a = 10;  
    int b = 20;  
    int temp = a;
```

```
    a = b;  
     $\rightarrow$  b = temp;
```

```
}
```

temp  $\rightarrow$  10

20  
~~10~~  
a

10  
~~20~~  
b





## // function game

### Quiz

```
main() {
```

```
    int a = 10;
```

```
    int b = 20;
```

```
    Swap(10, 20);
```

```
    System.out.println(a); → 10
```

```
    System.out.println(b); → 20
```

```
}
```

```
public static void Swap(int a, int b) {  
    int temp = a;  
    a = b;  
    b = temp;  
}
```

```
}
```

Swap

main

~~temp = 10  
b = 20 10  
a = 10 20~~

b = 20  
a = 10

↳ variables of 2 functions are not connected.





## Quiz

main() {

int[] arr: {10, 20}

Swap(arr);  
#ref 1

System.out.println(arr[0]); → 20

→ System.out.println(arr[1]); → 10

}

Heap

#ref	0	1
	10	20

~~temp = 10~~  
~~arr = #ref 1~~

Public static void Swap(int[] arr) {

int temp = arr[0];

arr[0] = arr[1];

arr[1] = temp;

main

arr = #ref 1

Stack

↳ arrays across functions are connected.





## Q) Swap indices

↳ Given array of length  $N$  and two indices  $idx1$  and  $idx2$ , swap the element of those two indices.

Ex:  $arr[5] : \{ 5, 15, 25, 25, 45 \}$

$idx1 = 1$        $idx2 = 3$

```
int temp = arr[idx1];  
arr[idx1] = arr[idx2];  
→ arr[idx2] = temp;
```

temp → 15

