

Application Load Balancer

Create Security Group

aws

Search

[Alt+S]

United States (N. Virginia)

Account ID: 0950-7410-7161

Sakshi Jain

EC2

Security Groups

Create security group

Basic details

Security group name [Info](#)
Application-load-balancer
Name cannot be edited after creation.

Description [Info](#)
Load Balancer

VPC [Info](#)
vpc-041fdc7813f9e9c5d

Inbound rules [Info](#)

Type Info	Protocol Info	Port range Info	Source Info	Description - optional Info	
HTTP	TCP	80	An...	0.0.0.0/0	Delete
SSH	TCP	22	An...	0.0.0.0/0	Delete

Create 3 Instance for Home page

aws

Search

[Alt+S]

United States (N. Virginia)

Account ID: 0950-7410-7161

Sakshi Jain

EC2

Instances

Launch an instance

Launch an instance [Info](#)

Amazon EC2 allows you to create virtual machines, or instances, that run on the AWS Cloud. Quickly get started by following the simple steps below.

Name and tags [Info](#)

Name
Home-Instance [Add additional tags](#)

Application and OS Images (Amazon Machine Image) [Info](#)

An AMI contains the operating system, application server, and applications for your instance. If you don't see a suitable AMI below, use the search field or choose [Browse more AMIs](#).

Search our full catalog including 1000s of application and OS images

Recents Quick Start

Summary

Number of instances [Info](#)
1

Software Image (AMI)
Amazon Linux 2023 AMI 2023.9.2...[read more](#)
ami-0cae6d6fe6048ca2c

Virtual server type (instance type)
t3.micro

Firewall (security group)
New security group

Cancel [Launch instance](#) [Preview code](#)

aws

Search

[Alt+S]

United States (N. Virginia)

Account ID: 0950-7410-7161

Sakshi Jain

EC2 > Instances > Launch an instance

▼ Key pair (login) Info

You can use a key pair to securely connect to your instance. Ensure that you have access to the selected key pair before you launch the instance.

Key pair name - required

Practice

Create new key pair

▼ Network settings Info

Edit

Network Info

vpc-041fdc7813f9e9c5d

Subnet Info

No preference (Default subnet in any availability zone)

Auto-assign public IP Info

Enable

Firewall (security groups) Info

A security group is a set of firewall rules that control the traffic for your instance. Add rules to allow specific traffic to reach your instance.

Create security group

Select existing security group

We'll create a new security group called 'launch-wizard-1' with the following rules:

☒ Allow SSH traffic from

Helps you connect to your instance

Anywhere

0.0.0.0/0

☐ Allow HTTPS traffic from the internet

To set up an endpoint, for example when creating a web server

☒ Allow HTTP traffic from the internet

To set up an endpoint, for example when creating a web server

▼ Summary

Number of instances Info

1

Software image (AMI)

Amazon Linux 2023 AMI 2023.9.2...read more

ami-0cae6d6fe6048ca2c

Virtual server type (instance type)

t3.micro

Firewall (security group)

New security group

Storage (volumes)

1 volume(s) - 8 GiB

Cancel

Launch instance

Preview code

aws

Search

[Alt+S]

United States (N. Virginia)

Account ID: 0950-7410-7161

Sakshi Jain

EC2 > Instances > Launch an instance

Metadata response hop limit Info

2

Allow tags in metadata Info

Select

User data - optional Info

Upload a file with your user data or enter it in the field.

Choose file

```
#!/bin/bash
sudo yum install httpd -y
sudo systemctl start httpd
sudo systemctl enable httpd
echo<h1>This is My HomePage $HOSTNAME</h1>> > /var/www/html/index.html
```

☐ User data has already been base64 encoded

▼ Summary

Number of instances Info

3

When launching more than 1 instance, consider EC2 Auto Scaling

Software image (AMI)

Amazon Linux 2023 AMI 2023.9.2...read more

ami-0cae6d6fe6048ca2c

Virtual server type (instance type)

t3.micro

Firewall (security group)

New security group

Storage (volumes)

1 volume(s) - 8 GiB

Cancel

Launch instance

Preview code

Create 2 Instance for Phone page

aws

Search

[Alt+S]

Europe (Stockholm)

Account ID: 0950-7410-7161

Sakshi Jain

EC2 > Instances > Launch an instance

1 2 3

Launch an instance [Info](#)

Amazon EC2 allows you to create virtual machines, or instances, that run on the AWS Cloud. Quickly get started by following the simple steps below.

Name and tags [Info](#)

Name

Phone-Instance

Add additional tags

▼ Application and OS Images (Amazon Machine Image) [Info](#)

An AMI contains the operating system, application server, and applications for your instance. If you don't see a suitable AMI below, use the search field or choose **Browse more AMIs**.

Search our full catalog including 1000s of application and OS images

Recents [Quick Start](#)

▼ Summary

Number of instances [Info](#)

2

When launching more than 1 instance, [consider EC2 Auto Scaling](#)

Software Image (AMI)

Amazon Linux 2023 AMI 2023.9.2...[read more](#)

ami-0c7d68785ec07306c

Virtual server type (instance type)

t3.micro

Firewall (security group)

Cancel

Launch instance

[Preview code](#)

aws

Search

[Alt+S]

Europe (Stockholm)

Account ID: 0950-7410-7161

Sakshi Jain

EC2 > Instances > Launch an instance

1 2 3

▼ Network settings [Info](#)

Edit

Network [Info](#)

vpc-09b6bff8ffa12c928

Subnet [Info](#)

No preference (Default subnet in any availability zone)

Auto-assign public IP [Info](#)

Enable

Firewall (security groups) [Info](#)

A security group is a set of firewall rules that control the traffic for your instance. Add rules to allow specific traffic to reach your instance.

Create security group

Select existing security group

We'll create a new security group called 'launch-wizard-4' with the following rules:

☒ Allow SSH traffic from

Helps you connect to your instance

Anywhere

0.0.0.0/0

☐ Allow HTTPS traffic from the internet

To set up an endpoint, for example when creating a web server

☒ Allow HTTP traffic from the internet

To set up an endpoint, for example when creating a web server

▼ Summary

Number of instances [Info](#)

2

When launching more than 1 instance, [consider EC2 Auto Scaling](#)

Software Image (AMI)

Amazon Linux 2023 AMI 2023.9.2...[read more](#)

ami-0c7d68785ec07306c

Virtual server type (instance type)

t3.micro

Firewall (security group)

New security group

Storage (volumes)

Cancel

Launch instance

[Preview code](#)

[Alt+S]

Europe (Stockholm)
Account ID: 0950-7410-7161
Sakshi Jain

EC2

Instances

Launch an instance

User data - optional

Info

Upload a file with your user data or enter it in the field.

Choose file

```
#!/bin/bash
sudo yum install httpd -y
sudo systemctl start httpd
sudo systemctl enable httpd
mkdir -p /var/www/html/phone/
echo "<h1>This Is My PhonePage $HOSTNAME</h1>" > /var/www/html/phone/index.html
```

☐ User data has already been base64 encoded

Summary

Number of instances

Info

When launching more than 1 instance, [consider EC2 Auto Scaling](#)

Software Image (AMI)

Amazon Linux 2023 AMI 2023.9.2...[read more](#)
 ami-0c7d68785ec07306c

Virtual server type (instance type)

t3.micro

Firewall (security group)

New security group

Storage (volumes)

Cancel

Launch instance

Preview code

Create 2 Instance for Laptop page

aws

Search

[Alt+S]

Europe (Stockholm)
Account ID: 0950-7410-7161
Sakshi Jain

EC2

Instances

Launch an instance

Allow tags in metadata

Info

Select

User data - optional

Info

Upload a file with your user data or enter it in the field.

Choose file

```
#!/bin/bash
sudo yum install httpd -y
sudo systemctl start httpd
sudo systemctl enable httpd
sudo mkdir -p /var/www/html/laptop/
echo "<h1>This Is My LaptopPage $HOSTNAME</h1>" > /var/www/html/laptop/index.html
```

Summary

Number of instances

Info

When launching more than 1 instance, [consider EC2 Auto Scaling](#)

Software Image (AMI)

Amazon Linux 2023 AMI 2023.9.2...[read more](#)
 ami-0c7d68785ec07306c

Virtual server type (instance type)

t3.micro

Firewall (security group)

New security group

Storage (volumes)

1 volume(s) - 8 GiB

Cancel

Launch instance

Preview code

Create Target Group for Home Instance

aws

Search

[Alt+S]

Europe (Stockholm)

Account ID: 0950-7410-71

Saksh

EC2

Target groups

Create target group

Instances

Supports load balancing to instances in a VPC. Integrate with Auto Scaling Groups or ECS services for automatic management.

Suitable for:

ALB

NLB

GWLB

IP addresses

Supports load balancing to VPC and on-premises resources. Facilitates routing to IP addresses and network interfaces on the same instance. Supports IPv6 targets.

Suitable for:

ALB

NLB

GWLB

Lambda function

Supports load balancing to a single Lambda function. ALB required as traffic source.

Suitable for:

ALB

Application Load Balancer

Allows use of static IP addresses and PrivateLink with an Application Load Balancer. NLB required as traffic source.

Suitable for:

NLB

Target group name

Name must be unique per Region per AWS account.

Home-Group

Accepts: a-z, A-Z, 0-9, and hyphen (-). Can't begin or end with hyphen. 1-32 total characters; Count: 10/32

Protocol

Port

Select Home Instance

aws

Search

[Alt+S]

Europe (Stockholm)

Account ID: 0950-7410-7161

Sakshi Jain

EC2

Target groups

Create target group

Step 1

Create target group

Step 2 - recommended

Register targets

Step 3

Review and create

Register targets - recommended

This is an optional step to create a target group. However, to ensure that your load balancer routes traffic to this target group you must register your targets.

Available instances (3/7)

Filter instances

	Instance ID	Name	State	Security groups
☐	i-0f36bbdff08b5152	laptop-instance	Running	launch-wizard-5
☐	i-05fb83b368021f076	laptop-instance	Running	launch-wizard-5
☐	i-041aa58a41550a9aa	Phone-Instance	Running	launch-wizard-4
☐	i-0f84031c7830bfb3e	Phone-Instance	Running	launch-wizard-4
☒	i-007606c7e8f6bf532	Home-Instance	Running	launch-wizard-3
☒	i-08324e6a7770bb6e5	Home-Instance	Running	launch-wizard-3
☒	i-07fa7e3f88fac0228	Home-Instance	Running	launch-wizard-2

aws [Search] [Alt+S] Europe (Stockholm) Sakshi Jain

EC2 > Target groups > Create target group

Include as pending below

3 selections are now pending below. Include more or register targets when ready.

Review targets

Targets (3) [Remove all pending](#)

Filter targets Show only pending < 1 >

Instance ID	Name	Port	State	Security groups	Zone	Private IPv4 address
i-007606c7e8f6bf532	Home-Instance	80	Running	launch-wizard-3	eu-north-1a	172.31.19.119
i-08324e6a7770bb6e5	Home-Instance	80	Running	launch-wizard-3	eu-north-1a	172.31.19.51
i-07fa7e3f88fac0228	Home-Instance	80	Running	launch-wizard-2	eu-north-1a	172.31.21.35

3 pending [Cancel](#) [Previous](#) [Next](#)

aws [Search] [Alt+S] Europe (Stockholm) Account ID: 0950-7410-7161 Sakshi Jain

EC2 > Target groups > Create target group

Health check details

Health check protocol HTTP	Health check path /	Health check port traffic-port	Interval 30 seconds
Timeout 5 seconds	Healthy threshold 5	Unhealthy threshold 2	Success codes 200

Step 2: Register targets

[Edit](#)

Targets (3)

Instance ID	Name	Port	Zone
i-007606c7e8f6bf532	Home-Instance	80	eu-north-1a
i-08324e6a7770bb6e5	Home-Instance	80	eu-north-1a
i-07fa7e3f88fac0228	Home-Instance	80	eu-north-1a

[Cancel](#) [Previous](#) [Create target group](#)

Do the same process for Phone and Laptop Instance

aws [Search] [Alt+S] Europe (Stockholm) Account ID: 0950-7410-7161 Sakshi Jain

EC2 > Target groups

Target groups (3) [Info](#) [What's new?](#) [Actions](#) [Create target group](#)

Filter target groups

☐	Name	ARN	Port	Protocol	Target type	Load balancer
☐	Laptop-Group	arn:aws:elasticloadbalancin...	80	HTTP	Instance	None associated
☐	Phone-Group	arn:aws:elasticloadbalancin...	80	HTTP	Instance	None associated
☐	Home-Group	arn:aws:elasticloadbalancin...	80	HTTP	Instance	None associated

0 target groups selected

Select a target group above.

Create Application Load Balancer

aws

Search

[Alt+S]

Europe (Stockholm)

Account ID: 0950-7410-7161

Sakshi Jain

EC2

Load balancers


Compare and select load balancer type

Compare and select load balancer type

A complete feature-by-feature comparison along with detailed highlights is also available. [Learn more](#)


Load balancer types

Application Load Balancer [Info](#)



Choose an Application Load Balancer when you need a flexible feature set for your applications with HTTP and HTTPS traffic. Operating at the request level, Application

Network Load Balancer [Info](#)



Choose a Network Load Balancer when you need ultra-high performance, TLS offloading at scale, centralized certificate deployment, support for UDP, and static IP addresses for

Gateway Load Balancer [Info](#)



Choose a Gateway Load Balancer when you need to deploy and manage a fleet of third-party virtual appliances that support GENEVE. These appliances enable you to improve

aws

Search

[Alt+S]

Europe (Stockholm)

Account ID: 0950-7410-7161

Sakshi Jain

EC2

Load balancers

Create Application Load Balancer

Create Application Load Balancer [Info](#)

The Application Load Balancer distributes incoming HTTP and HTTPS traffic across multiple targets such as Amazon EC2 instances, microservices, and containers, based on request attributes. When the load balancer receives a connection request, it evaluates the listener rules in priority order to determine which rule to apply, and if applicable, it selects a target from the target group for the rule action.

How Application Load Balancers work

Basic configuration

Load balancer name

Name must be unique within your AWS account and can't be changed after the load balancer is created.

Application-Balancer

A maximum of 32 alphanumeric characters including hyphens are allowed, but the name must not begin or end with a hyphen.

Scheme [Info](#)

Scheme can't be changed after the load balancer is created.

☒ Internet-facing

- Serves internet-facing traffic.
- Has public IP addresses.
- DNS name resolves to public IPs.
- Requires a public subnet.

☐ Internal

- Serves internal traffic.
- Has private IP addresses.
- DNS name resolves to private IPs.
- Compatible with the IPv4 and Dualstack IP address types.

Load balancer IP address type [Info](#)

Select the front-end IP address type to assign to the load balancer. The VPC and subnets mapped to this load balancer must include the selected IP address types. Public IPv4 addresses have an additional cost.

☒ IPv4

Includes only IPv4 addresses.

☐ Dualstack

Includes IPv4 and IPv6 addresses.

☐ Dualstack without public IPv4

Includes public IPv6 addresses and private IPv4 and IPv6 addresses. Compatible with Internet-facing load balancers only.

Network mapping [Info](#)

The load balancer routes traffic to targets in the selected subnets, and in accordance with your IP address settings.

VPC [Info](#)

The load balancer will exist and scale within the selected VPC. The selected VPC is also where the load balancer targets must be hosted unless routing to Lambda or on-premises targets, or if using VPC peering. To confirm the VPC for your targets, view [target groups](#).

vpc-09b6bfb8fa12c928 (default) [Create VPC](#)

IP pools [Info](#)

You can optionally choose to configure an IPAM pool as the preferred source for your load balancers IP addresses. Create or view Pools in the [Amazon VPC IP Address Manager console](#).

☐ Use IPAM pool for public IPv4 addresses

The IPAM pool you choose will be the preferred source of public IPv4 addresses. If the pool is depleted IPv4 addresses will be assigned by AWS.

Availability Zones and subnets [Info](#)

Select at least two Availability Zones and a subnet for each zone. A load balancer node will be placed in each selected zone and will automatically scale in response to traffic. The load balancer routes traffic to targets in the selected Availability Zones only.

☒ eu-north-1a (eun1-az1)

Subnet

Only CIDR blocks corresponding to the load balancer IP address type are used. At least 8 available IP addresses are required for your load balancer to scale efficiently.

subnet-0791f94763c174151 (IPv4 subnet CIDR: 172.31.16.0/20)

☒ eu-north-1b (eun1-az2)

Subnet

Only CIDR blocks corresponding to the load balancer IP address type are used. At least 8 available IP addresses are required for your load balancer to scale efficiently.

subnet-03c9d4d9cfe50a6d (IPv4 subnet CIDR: 172.31.32.0/20)

☒ eu-north-1c (eun1-az3)

Subnet

Only CIDR blocks corresponding to the load balancer IP address type are used. At least 8 available IP addresses are required for your load balancer to scale efficiently.

Use created security group and add Home-Group as Target Group

Security groups [Info](#)

A security group is a set of firewall rules that control the traffic to your load balancer. Select an existing security group, or you can [create a new security group](#).

Security groups

Select up to 5 security groups

Application-load-balancer sg-09b6bfb8fa12c928

Listeners and routing [Info](#)

A listener is a process that checks for connection requests using the port and protocol you configure. The rules that you define for a listener determine how the load balancer routes requests to its registered targets.

Listener HTTP:80 [Remove](#)

Protocol HTTP **Port** 80

Default action [Info](#)

The default action is used if no other rules apply. Choose the default action for traffic on this listener.

Routing action

☒ Forward to target groups ☐ Redirect to URL ☐ Return fixed response

Forward to target group [Info](#)

Choose a target group and specify routing weight or [create target group](#).

Target group	Weight	Percent
Home-Group Target type: Instance, IPv4 Target stickiness: Off	1	100%

Goto Listener and Rules an add rule for Phone and Laptop Page

aws [Search] [Alt+S] Europe (Stockholm) Account ID: 0950-7410-7161 Sakshi Jain

EC2 > Load balancers > Application-Balancer

AMI Catalog

- ▼ Elastic Block Store
 - Volumes
 - Snapshots
 - Lifecycle Manager
- ▼ Network & Security
 - Security Groups
 - Elastic IPs
 - Placement Groups
 - Key Pairs
 - Network Interfaces
- ▼ Load Balancing
 - Load Balancers
 - Target Groups
 - Trust Stores
- ▼ Auto Scaling
 - Auto Scaling Groups

Settings

1c (eu-n1-az3)
subnet-03c99dad9cfe50a6d eu-north-1b (eu-n1-az2)
subnet-0791f94763c174151 eu-north-1a (eu-n1-az1)

Load balancer ARN
arn:aws:elasticloadbalancing:eu-north-1:095074107161:loadbalancer/app/Application-Balancer/c0ebdbda4dddb5d

DNS name info
Application-Balancer-699065276.eu-north-1.elb.amazonaws.com (A Record)

Listeners and rules (1/1) Info

A listener checks for connection requests on its configured protocol and port. Traffic received by the listener is routed according to the default action and any additional rules.

Filter listeners

☒	Protocol:Port	Default action	Rules	ARN	Security policy	Default SSL/TLS certificate
☒	HTTP:80	Forward to target group Home-Group 1 (100%) Target group stickiness: Off	1 rule	ARN	Not applicable	Not applicable

Listeners and rules (1/1) Info

A listener checks for connection requests on its configured protocol and port. Traffic received by the listener is routed according to the default action and any additional rules.

Filter listeners

☒	Protocol:Port	Default action	Rules	ARN	Security policy	Default SSL/TLS certificate
☒	HTTP:80	Forward to target group Home-Group 1 (100%) Target group stickiness: Off	1 rule	ARN	Not applicable	Not applicable

Manage rules Add rule Edit rules Reprioritize rules

Add Path for Phone

aws [Search] [Alt+S] Europe (Stockholm) Account ID: 0950-7410-7161 Sakshi Jain

EC2 > Load balancers > Application-Balancer > HTTP:80 listener > Add rule

Step 2 Set rule priority

Step 3 Review and create

Requests that reach this rule are evaluated against its conditions. If a request matches all of the rule conditions, then a secondary evaluation is done to perform any specified transforms, and finally the request is routed according to the rule's actions.

► Listener details: HTTP:80

► Name and tags info

Tags can help you manage, identify, organize, search for and filter resources.

Conditions (1 value) Info

Define 1-5 condition values. Additional conditions can't be added once the limit is reached.

▼ Path (value) = /phone/*

Match pattern type

☒ Value matching Match with glob syntax, using * and ? as wildcards.

☐ Regex matching Match with regex syntax.

Path condition value

Case sensitive:

= /phone/*

Valid characters are a-z, A-Z, 0-9 and special characters. Path must be 1-128 characters.

+ Add OR condition value

Rule limits

Remove

aws

Search

[Alt+S]

Europe (Stockholm)

Account ID: 0950-7410-7161

Sakshi Jain

EC2 > Load balancers > Application-Balancer > HTTP:80 listener > Add rule

You can add up to 2 more transforms.

Actions

Info

Requests matching all rule conditions route according to the rule actions.

Routing action

☒ Forward to target groups

☐ Redirect to URL

☐ Return fixed response

Forward to target group

Info

Choose a target group and specify routing weight or [create target group](#).

Target group

Home-Group

Target type: Instance, IPv4 | Target stickiness: Off

HTTP

Weight

1

0-999

Percent

100%

+ Add target group

You can add up to 4 more target groups.

Target group stickiness

Info

Enables the load balancer to bind a user's session to a specific target group. To use stickiness the client must support cookies. If you want to bind a user's session to a specific target, turn on the Target Group attribute Stickiness.

☐ Turn on target group stickiness

Cancel

Next

aws

Search

[Alt+S]

Europe (Stockholm)

Account ID: 0950-7410-7161

Sakshi Jain

EC2 > Load balancers > Application-Balancer > HTTP:80 listener > Add rule

Step 1
Add rule

Step 2
Set rule priority

Step 3
Review and create

Set rule priority

Info

Each rule has a priority. The default rule is evaluated last. You can change the priority of a non-default rule at any time. You can't change the priority of the default rule.

► Listener details: HTTP:80

Listener rules (2)

Info

Rule limits

Reset priorities

Add gap between priorities

Traffic received by the listener is routed according to the default action and any additional rules. Rules are evaluated in priority order from the lowest value to the highest value.

Priority	Name tag	Conditions (If)	Transforms	Actions (Then)
1	-	Path (value) = <code>/phone/*</code>	-	- Forward to target group Phone-Group: 1 (100%) - Target group stickiness: Off
Last (default)	Default	If no other rule applies	-	- Forward to target group Home-Group: 1 (100%) - Target group stickiness: Off

Cancel

Previous

Next

aws

Search

[Alt+S]

Europe (Stockholm)

Account ID: 0950-7410-7161

Sakshi Jain

EC2 > Load balancers > Application-Balancer > HTTP:80 listener > Add rule

Tags can help you manage, identify, organize, search for and filter resources.

Conditions (1 value)

Info

Rule limits

Define 1-5 condition values. Additional conditions can't be added once the limit is reached.

▼ Path (value) = `/Laptop/*`

Remove

Match pattern type

☒ Value matching

Match with glob syntax, using `*` and `?` as wildcards.

☐ Regex matching

Match with regex syntax.

Path condition value

Case sensitive.

= `/Laptop/*`

Valid characters are a-z, A-Z, 0-9 and special characters. Path must be 1-128 characters.

+ Add OR condition value

Add condition

▼

You can add up to 4 more condition values for this rule.

aws [Search] [Alt+S] Europe (Stockholm) Account ID: 0950-7410-7161 Sakshi Jain

EC2 > Load balancers > Application-Balancer > HTTP:80 listener > Add rule

You can add up to 2 more transforms.

Actions info

Requests matching all rule conditions route according to the rule actions.

Routing action

☒ Forward to target groups ☐ Redirect to URL ☐ Return fixed response

Forward to target group info

Choose a target group and specify routing weight or [create target group i2](#).

Target group

Laptop-Group HTTP

Target type: Instance, IPv4 | Target stickiness: Off

Weight **Percent**

0-999

[+ Add target group](#)

You can add up to 4 more target groups.

Target group stickiness info

Enables the load balancer to bind a user's session to a specific target group. To use stickiness the client must support cookies. If you want to bind a user's session to a specific target, turn on the Target Group attribute Stickiness.

☐ Turn on target group stickiness

[Cancel](#) [Next](#)

aws [Search] [Alt+S] Europe (Stockholm) Account ID: 0950-7410-7161 Sakshi Jain

EC2 > Load balancers > Application-Balancer > HTTP:80 listener > Add rule

Step 1 Add rule
Step 2 **Set rule priority**
Step 3 Review and create

Set rule priority info

Each rule has a priority. The default rule is evaluated last. You can change the priority of a non-default rule at any time. You can't change the priority of the default rule.

► **Listener details: HTTP:80**

Listener rules (3) info [Rule limits](#) [Reset priorities](#) [Add gap between priorities](#)

Traffic received by the listener is routed according to the default action and any additional rules. Rules are evaluated in priority order from the lowest value to the highest value.

Priority	Name tag	Conditions (If)	Transforms	Actions (Then)
2	-	Path (value) = /Laptop/*	-	Forward to target group Laptop-Group i2: 1 (100%) Target group stickiness: Off
1	-	Path (value) = /phone/*	-	Forward to target group Phone-Group i2: 1 (100%) Target group stickiness: Off
Last (default)	Default	If no other rule applies	-	Forward to target group Home-Group i2: 1 (100%) Target group stickiness: Off

[Cancel](#) [Previous](#) [Next](#)


Run DNS of Load Balancer You will get your webpage
For Home Page



For Phone Page



For Laptop page



Laptop page from ip-172-31-4-133.ap-south-1.compute.internal