Name — Himani Taneja

Student ID - 20052047

University Roll no - 2023058

Que - 2

```c
# include < stdio.h >
int main ()
{

int bt [20], p [20], wt [20], tat [20], i,
j, n, total = 0, pos, temp;

float avg_wt, avg_tat;
Print (" Enter number of process:");
Scanf (".%d", &n);
Printf ("\n Enter Burst Time: \n");
for (i = 0; i < n; i++)
{

Print ("p %.d:", i+1 );
Scanf ("%.d", & bt [i]);
p [i] = i + 1;

}
for (i = 0; i < n; i++)
{
```

Himani

```
Pos = i;
for (i = i+1; j< n; j++)
{
    if (bt [j] < bt [pos])
        Pos = j;
}
temp = bt [i];
bt [i] = bt [pos];
bt [pos] = temp;
temp = p (i);
p [i] = p [ pos];
p [pos] = temp;
}

wt [0] = 0;
for (i = 1; i< n; i++)
{
    wt [i] = 0;
    for (j = 0; j< i; j++)
    wt [i] += bt [j];
    total += wt [i];
}

avg-wt = (float) total /n ;
total = 0;
```

Himani

```c
Print (" \n Process \t Burst Time \t Waiting
Time \t Turnaround Time");
    for (i=0; i< n; i++)
    {
        tat [i] = bt [i] + wt [i];
        total + = tat [i];
        Print (" \np %d \t lt %d \t \t
%d \t \t \t %d", p [i], bt [i], wt [i], tat [i]);
    }
    avg_tat = (float) total /n;
Printf (" \n \n Average Waiting Time = % f ",
    avg_wt );
Print (" \n Average Turnaround Time = % f \n",
    avg_tat );
}
```

Himani

```
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48      printf("\n\nAverage Waiting Time=%f",avg_wt);
49      printf("\nAverage Turnaround Time=%f\n",avg_tat);
50  }
51
```

```
"D:\bsc.it\c program\timepass 3.exe"
Enter number of process:4

Enter Burst Time:
p1:10
p2:2
p3:1
p4:4

Process      Burst Time      Waiting Time    Turnaround Time
p3             1                0                 1
p2             2                1                 3
p4             4                3                 7
p1             10               7                 17

Average Waiting Time=2.750000
Average Turnaround Time=7.000000

Process returned 0 (0x0)   execution time : 19.949 s
Press any key to continue.
```