NAME = Priyanshu Uniyal. Subject = Operating System. (1).
ROLL No = 20051020.
COURSE = BSc IT
SEMESTER = 2nd.

Ans = (1). #include<stdio.h>
int main()
{
int bt[20], p[20], wt[20], tat[20], i, j, n, total = 0, pos, temp;
float avg_wt, avg_tat;
Printf("Enter number of proces:");
Scanf("%d", &n);
printf("\n Enter Burst Time:\n");
for(i=0; i<n; i++)
{
Printf("p %d:", i+1);
Scanf("%d", &bt[i]);
p[i]=i+1;
}
for(i=0; i<n; i++)
{ pos=i;
for(j=i+1; j<n; j++)
{ if(bt[j]<bt[pos])
pos=j;
} temp=bt[i];
bt[i]=bt[pos];

Priyanshu
22/10/2023

```
        bt[pos] = temp;
        temp = p[i];
        p[i] = p[pos];
        p[pos] = temp;
    }
    wt[0] = 0;
    for(i=1; i<n; i++)
    {
        wt[i] = 0;
        for(j=0; j<i; j++)
            wt[i] += bt[j];
        total += wt[i];
    }
    avg_wt = (float) total / n;
    total = 0;
    printf("\nProcess\t Burst Time \t Waiting time \t Turnaround Time");
    for(i=0; i<n; i++)
    {
        tat[i] = bt[i] + wt[i];
        total += tat[i];
        printf("\np%d \t\t %d \t\t %d \t\t %d", p[i], bt[i], wt[i], tat[i]);
    }
    avg_tat = (float) total / n;
    printf("\n\n Average waiting time = %f", avg_wt);
```

Priyanka
22/06/2021

printf("\n Average Turnaround Time = %f \n", avg_tat); ③.
}

OUTPUT :-

Enter number of process:
Enter Burst Time.
P1 : P2 : P3 : P4 :

Process	Burst Time	Waiting Time.
Turnaround Time.		
P3	1	0	1
P2	2	1	3
P4	4	3	7
P1	10	7	17

Average Waiting Time = 2.750000
Average Turn around Time = 7.000000.

Priyanshu
22/01/2021