Name - Abhay Suman
University Rollno - 2023011
Course - Bsc-IT 2B.

Q2.

```
#include <stdio.h>
 int main ()
  {
   int bt [20], p[20], wt [20], tat[20], i, j, n, total = 0, pos, temp;
   float avg-wt, avg-tat;
    Print f (" Enter number of processes: ");
    Scanf ("%d", &n);
    Printf ("\n Enter Burst Time: \n");
  for (i = 0; i <n; i++)
  {
   printf ("P%d: ", i+1);
   Scan f ("%d", & bt [i]);
     p [i] = i+1;
  }
   for (i = 0; i<n ; j++)
     {
       if (bt [j] < bt [pos])
          pos = j;
     }

       temp = bt [i];
       bt[i] = bt [pos];
       bt [pos] = temp;
       temp = p[i];
```

```
    P[i] = p[pos];
    P[pos] = temp;
}
wt[0] = 0;
for (i=1; i<n; i++)
  {
    wt[i] = 0;
    for (j=0; j<i; j++)
    wt[i] += bt[j];
    Total += wt[i];
    [illegible]
  }
avg_wt = (float) total / n;
  total = 0;
  Printf ("\n Process\t  Borst Time \t Waiting Time \t Turnaround Time");
  for (i=0; i<n; i++)
  {
   tat[i] = bt[i] + wt[i];
   Total += tat[i];
   Printf ("\np %d \t\t %d \t\t %d \t\t %d", P[i], bt[i], wt[i],
   tat[i]);
}
  avg_tat = (float) total / n;
Printf ("\n\n Average Waiting Time = %f", avg_wt);
Printf ("\nAverage Turnaround Time = %f\n", avg_Tat);
}
```

```
Enter number of process:4

Enter Burst Time:
p1:10
p2:2
p3:1
p4:4

Process     Burst Time          Waiting Time    Turnaround Time
p3                1                   0                   1
p2                2                   1                   3
p4                4                   3                   7
p1                10                  7                   17

Average Waiting Time=2.750000
Average Turnaround Time=7.000000

Process returned 0 (0x0)   execution time : 19.949 s
Press any key to continue.
```