Name :- Hansraj Jaguri
Roll number :- 2023056
Subject :- operating system
Student id :- 20134037
section = B

Answer

Ans-1.

```
#include <assert.h>
#include <ctype.h>
#include <limits.h>
#include <math.h>
#include <stddef.h>
#include <stdlib.h>
#include <string.h>

char *readline();
char* ltrim(char*);
char* rtrim(char*);
char** split_string(char);
int parse_int(char*);
int minimumAverage(int customer_row, int
customer_column, int** customer) {
}
int main()
{ FILE *fptr=
  fopen(getenv("Output_Path"), "w");
   int n =
 Parse_int(ltrim(rtrim(readline())));
  int** customer = malloc(n* sizeof(int*));
   for (int i=0; i<n; i++) {
       *(customer+i)= malloc(2*(sizeof(int)));
 Char **customer_item temp = split_string
      (rtrim(readline()));
for(int j=0; j<2!j++){
   int customers_item = parse_int(*(custom
   _item_temp+j));
```

```
(custom+i)=malloc(2*(sizeof(int)));
Char** customers_item_temp=split_
String(rtrim(readline()));
for(int j=0; j<2; j++){
    int (*(customer_item temp+j));
    (customer+i)+j]= customers_item;
}
int result = minimum Average(n,2 customer
fprint(fptr,"%.d\n",result);
fClose(fptr);
return 0;
}
Char* readline(){
size_t alloc_length=1024;
size_t data_length=0;
Char * data = malloc(alloc_length);
While(true){
char* cursor = data+ data_length;
Char* line = fgets(cursor alloc_length
- data_length, stdine);
if(!line){
break;
}
data = realloc(data alloc_length);
if(!data){
data='\0'
break
}return 0;
}
```