complete java class code example of each combination of intermediate and terminal operations

filter() boolean checks + collect() accumulate elements

filter() null checks + collect() accumulate elements

filter() comparisons + collect() accumulate elements

filter() method calls returning boolean + collect() accumulate elements

distinct() rely on equals() / hashcode() + collect() accumulate elements

distinct() immutable objects + collect() accumulate elements

map() transform objects + collect() accumulate elements

map() create new objects + collect() accumulate elements

map() call pure functions + collect() accumulate elements

flatmap() return stream + collect() accumulate elements

flatmap() split data + collect() accumulate elements

flatmap() expand collections + collect() accumulate elements

sorted() natural ordering + collect() accumulate elements

sorted() custom comparator + collect() accumulate elements

sorted() multi-field compare + collect() accumulate elements

peek() logging + collect() accumulate elements

peek() debugging + collect() accumulate elements

peek() metrics + collect() accumulate elements

Below are **all 18 programs converted to Java 1.5 compatible code**.

Since Java 1.5:

- ❌ No Stream API
- ❌ No Optional
- ❌ No lambda expressions
- ❌ No method references
- ❌ No List.of(), Map.of()
- ❌ No Objects.hash()
- ❌ No Comparator.comparing()

We replace everything with:

- ✔ for-each loops
- ✔ Iterator
- ✔ Collections / Arrays
- ✔ HashSet for distinct
- ✔ Manual sorting with Comparator
- ✔ Null checks
- ✔ Primitive counters instead of AtomicInteger

Below are **complete, self-contained Java class examples** for **every requested Stream combination**, each focusing on **one intermediate operation + collect()**.

---

1 filter()— boolean checks + collect()

```
import java.util.*;

public class FilterBooleanCheckExample {
   public static void main(String[] args) {

      List < Integer > numbers = Arrays.asList(10, 15, 20, 25, 30);
      List < Integer > evenNumbers = new ArrayList < Integer > ();

      for (Integer n: numbers) {
         if (n % 2 == 0) {
            evenNumbers.add(n);
         }
      }

      System.out.println(evenNumbers);
   }
}
```

---

2 filter()— null checks + collect()

```
import java.util.*;

public class FilterNullCheckExample {
   public static void main(String[] args) {

      List < String > names = Arrays.asList("Anurag", null, "Bharti", null);
      List < String > nonNullNames = new ArrayList < String > ();

      for (String name: names) {
         if (name != null) {
            nonNullNames.add(name);
         }
      }

      System.out.println(nonNullNames);
   }
}
```

---

3 filter()— comparisons + collect()

```
import java.util.*;

public class FilterComparisonExample {
   public static void main(String[] args) {

      List < Integer > salaries = Arrays.asList(20000, 35000, 50000);
      List < Integer > highSalaries = new ArrayList < Integer > ();

      for (Integer salary: salaries) {
         if (salary > 30000) {
            highSalaries.add(salary);
         }
      }

      System.out.println(highSalaries);
   }
}
```

---

4 filter()— method calls returning boolean + collect()

```
import java.util.*;

public class FilterMethodCallExample {

   static class User {
      String name;
      boolean active;

      User(String name, boolean active) {
         this.name = name;
         this.active = active;
      }

      boolean isActive() {
         return active;
      }
   }

   public static void main(String[] args) {

      List < User > users = new ArrayList < User > ();
      users.add(new User("Anurag", true));
      users.add(new User("Ravi", false));

      List < User > activeUsers = new ArrayList < User > ();

      for (User user: users) {
         if (user.isActive()) {
            activeUsers.add(user);
         }
      }

      System.out.println(activeUsers.size());
   }
}
```

---

5 distinct()— rely on equals() / hashCode() + collect()

```
import java.util.*;

public class DistinctWithEqualsExample {

   static class Person {
      String name;

      Person(String name) {
         this.name = name;
      }

      public boolean equals(Object o) {
         if (o instanceof Person) {
            Person p = (Person) o;
            return name.equals(p.name);
         }
         return false;
      }

      public int hashCode() {
         return name.hashCode();
      }
   }

   public static void main(String[] args) {

      List < Person > people = new ArrayList < Person > ();
      people.add(new Person("Anurag"));
      people.add(new Person("Anurag"));
      people.add(new Person("Ravi"));

      Set < Person > set = new LinkedHashSet < Person > (people);
      List < Person > unique = new ArrayList < Person > (set);

      System.out.println(unique.size());
   }
}
```

---

6 distinct()— immutable objects + collect()

```
import java.util.*;

public class DistinctImmutableExample {
   public static void main(String[] args) {

      List < String > values = Arrays.asList("A", "B", "A", "C");

      Set < String > set = new LinkedHashSet < String > (values);
      List < String > unique = new ArrayList < String > (set);

      System.out.println(unique);
   }
}
```

---

7 map()— transform objects + collect()

```
import java.util.*;

public class MapTransformExample {
   public static void main(String[] args) {

      List < String > names = Arrays.asList("anurag", "bharti");
      List < String > upper = new ArrayList < String > ();

      for (String name: names) {
         upper.add(name.toUpperCase());
      }

      System.out.println(upper);
   }
}
```

---

8 map()— create new objects + collect()

```
import java.util.*;

public class MapCreateObjectExample {

   static class UserDTO {
      String name;

      UserDTO(String name) {
         this.name = name;
      }
   }

   public static void main(String[] args) {

      List < String > names = Arrays.asList("Anurag", "Ravi");
      List < UserDTO > dtos = new ArrayList < UserDTO > ();

      for (String name: names) {
         dtos.add(new UserDTO(name));
      }

      System.out.println(dtos.size());
   }
}
```

---

9 map()— call pure functions + collect()

```
import java.util.*;

public class MapPureFunctionExample {

   static int square(int n) {
      return n * n;
   }

   public static void main(String[] args) {

      List < Integer > numbers = Arrays.asList(2, 3, 4);
      List < Integer > squares = new ArrayList < Integer > ();

      for (Integer n: numbers) {
         squares.add(square(n));
      }
      System.out.println(squares);
```

```
    }
}
```

---

10 flatMap() — return Stream + collect()

```
import java.util.*;

public class FlatMapStreamExample {
    public static void main(String[] args) {

        List < List < Integer >> lists = new ArrayList < List < Integer >> ();
        lists.add(Arrays.asList(1, 2));
        lists.add(Arrays.asList(3, 4));

        List < Integer > result = new ArrayList < Integer > ();

        for (List < Integer > inner: lists) {
            result.addAll(inner);
        }

        System.out.println(result);
    }
}
```

---

11 flatMap()— split data + collect()

```
import java.util.*;

public class FlatMapSplitExample {
    public static void main(String[] args) {

        List < String > sentences = Arrays.asList("Java Stream", "Flat Map");
        List < String > words = new ArrayList < String > ();

        for (String s: sentences) {
            String[] split = s.split(" ");
            for (String word: split) {
                words.add(word);
            }
        }

        System.out.println(words);
    }
}
```

---

12 flatMap()— expand collections + collect()

```
import java.util.*;

public class FlatMapExpandExample {
   public static void main(String[] args) {

      Map < String, List < String >> data = new HashMap < String, List < String >> ();
      data.put("A", Arrays.asList("1", "2"));
      data.put("B", Arrays.asList("3"));

      List < String > values = new ArrayList < String > ();

      for (List < String > list: data.values()) {
         values.addAll(list);
      }

      System.out.println(values);
   }
}
```

---

13 sorted()— natural ordering + collect()

```
import java.util.*;

public class SortedNaturalExample {
   public static void main(String[] args) {

      List < Integer > numbers = new ArrayList < Integer > (
         Arrays.asList(5, 1, 3));

      Collections.sort(numbers);

      System.out.println(numbers);
   }
}
```

---

14 sorted()— custom comparator + collect()

```
import java.util.*;

public class SortedCustomComparatorExample {
   public static void main(String[] args) {

      List < String > names = new ArrayList < String > (
         Arrays.asList("Anurag", "Ravi", "Alok"));

      Collections.sort(names, Collections.reverseOrder());

      System.out.println(names);
   }
}
```

---

15 sorted()— multi - field compare + collect()

```
import java.util.*;

public class SortedMultiFieldFindFirst {

   static class Employee {
      String name;
      int age;

      Employee(String name, int age) {
         this.name = name;
         this.age = age;
      }
   }

   public static void main(String[] args) {

      List<Employee> list = new ArrayList<Employee>();
      list.add(new Employee("Anurag", 30));
      list.add(new Employee("Anurag", 25));
      list.add(new Employee("Ravi", 35));

      Collections.sort(list, new Comparator<Employee>() {
         public int compare(Employee e1, Employee e2) {
            int nameCompare = e1.name.compareTo(e2.name);
            if (nameCompare != 0) return nameCompare;
            return e1.age - e2.age;
         }
      });

      Employee first = list.size() > 0 ? list.get(0) : null;

      System.out.println(first != null ? first.name + " " + first.age : "NONE");
   }
}
```

---

16 peek()— logging + collect()

```
import java.util.*;

public class PeekLoggingExample {
   public static void main(String[] args) {

      List < Integer > numbers = Arrays.asList(1, 2, 3);
      List < Integer > result = new ArrayList < Integer > ();

      for (Integer n: numbers) {
         System.out.println("Processing: " + n);
         result.add(n);
      }

      System.out.println(result);
   }
}
```

---

17 peek()— debugging + collect()

```
import java.util.*;

public class PeekDebugExample {
   public static void main(String[] args) {

      List < Integer > numbers = Arrays.asList(10, 20, 30);
      List < Integer > result = new ArrayList < Integer > ();

      for (Integer n: numbers) {
         if (n == 20) {
            System.out.println("Breakpoint value: " + n);
         }
         result.add(n);
      }

      System.out.println(result);
   }
}
```

---

18 peek()— metrics + collect()

```
import java.util.*;

public class PeekMetricsExample {
   public static void main(String[] args) {

      List < Integer > numbers = Arrays.asList(5, 10, 15);
      List < Integer > result = new ArrayList < Integer > ();

      int counter = 0;

      for (Integer n: numbers) {
         counter++;
         result.add(n);
      }

      System.out.println("Processed count: " + counter);
   }
}
```