complete java class code example of each combination of intermediate and terminal operations

filter() boolean checks + foreach() printing

filter() null checks + foreach() printing

filter() comparisons + foreach() printing

filter() method calls returning boolean + foreach() printing

distinct() rely on equals() / hashcode() + foreach() printing

distinct() immutable objects + foreach() printing

map() transform objects + foreach() printing

map() create new objects + foreach() printing

map() call pure functions + foreach() printing

flatmap() return stream + foreach() printing

flatmap() split data + foreach() printing

flatmap() expand collections + foreach() printing

sorted() natural ordering + foreach() printing

sorted() custom comparator + foreach() printing

sorted() multi-field compare + foreach() printing

peek() logging + foreach() printing

peek() debugging + foreach() printing

peek() metrics + foreach() printing

Below are **all 18 programs converted to Java 1.5 compatible code**.

Since Java 1.5:

- ❌ No Stream API
- ❌ No Optional
- ❌ No lambda expressions
- ❌ No method references
- ❌ No List.of(), Map.of()
- ❌ No Objects.hash()
- ❌ No Comparator.comparing()

We replace everything with:

- ✔ for-each loops
- ✔ Iterator
- ✔ Collections / Arrays
- ✔ HashSet for distinct
- ✔ Manual sorting with Comparator
- ✔ Null checks
- ✔ Primitive counters instead of AtomicInteger

Below are **complete, standalone Java class examples** for **each requested Stream combination**, where:

- **One clear intermediate operation** is demonstrated
- **forEach() is the terminal operation**
- **Purpose = Printing output (not logging, not collecting)**
- Java **8+ compatible**
- Clean, interview-ready, minimal noise

---

1 filter() boolean checks + forEach() Printing

```
import java.util.*;

public class FilterBooleanForEachPrint {
   public static void main(String[] args) {

      List<Integer> numbers = new ArrayList<Integer>();
      numbers.add(10);
      numbers.add(15);
      numbers.add(20);
      numbers.add(25);

      for (Integer n : numbers) {
         if (n % 2 == 0) {
            System.out.println(n);
         }
      }
   }
}
```

---

2 filter() null checks + forEach() Printing

```
import java.util.*;

public class FilterNullForEachPrint {
   public static void main(String[] args) {

      List<String> names = new ArrayList<String>();
      names.add("Anurag");
      names.add(null);
      names.add("Amit");

      for (String name : names) {
         if (name != null) {
            System.out.println(name);
         }
      }
   }
}
```

---

3 filter() comparisons + forEach() Printing

```
import java.util.*;

public class FilterComparisonForEachPrint {
   public static void main(String[] args) {

      List<Integer> salaries = new ArrayList<Integer>();
      salaries.add(20000);
      salaries.add(40000);
      salaries.add(60000);

      for (Integer s : salaries) {
         if (s >= 30000) {
            System.out.println(s);
         }
      }
   }
}
```

---

4 filter() method call returning boolean + forEach() Printing

```
import java.util.*;

public class FilterMethodForEachPrint {

   static class User {
      String name;
      boolean active;

      User(String name, boolean active) {
         this.name = name;
         this.active = active;
      }

      boolean isActive() {
         return active;
      }
   }

   public static void main(String[] args) {

      List<User> users = new ArrayList<User>();
      users.add(new User("Anurag", true));
      users.add(new User("Ravi", false));

      for (User u : users) {
         if (u.isActive()) {
            System.out.println(u.name);
         }
      }
   }
}
```

---

5 distinct() rely on equals() / hashCode() + forEach() Printing

```
import java.util.*;

public class DistinctEqualsForEachPrint {

   static class Person {
      String name;

      Person(String name) {
         this.name = name;
      }

      public boolean equals(Object o) {
         if (o instanceof Person) {
            Person p = (Person) o;
            return name.equals(p.name);
         }
         return false;
      }

      public int hashCode() {
         return name.hashCode();
      }
   }

   public static void main(String[] args) {

      List<Person> people = new ArrayList<Person>();
      people.add(new Person("Anurag"));
      people.add(new Person("Anurag"));
      people.add(new Person("Ravi"));

      Set<Person> unique = new HashSet<Person>(people);

      for (Person p : unique) {
         System.out.println(p.name);
      }
   }
}
```

6 distinct() immutable objects + forEach() Printing

```
import java.util.*;

public class DistinctImmutableForEachPrint {
   public static void main(String[] args) {

      List<String> languages = new ArrayList<String>();
      languages.add("Java");
      languages.add("Java");
      languages.add("Python");

      Set<String> unique = new HashSet<String>(languages);

      for (String lang : unique) {
         System.out.println(lang);
      }
   }
}
```

---

7 map() transform objects + forEach() Printing

```
import java.util.*;

public class MapTransformForEachPrint {
   public static void main(String[] args) {

      List<String> names = new ArrayList<String>();
      names.add("anurag");
      names.add("amit");

      for (String name : names) {
         System.out.println(name.toUpperCase());
      }
   }
}
```

---

8 map() create new objects + forEach() Printing

```
import java.util.*;

public class MapNewObjectForEachPrint {

   static class UserDTO {
      String name;

      UserDTO(String name) {
         this.name = name;
      }
   }

   public static void main(String[] args) {

      List<String> names = new ArrayList<String>();
      names.add("Anurag");
      names.add("Amit");

      for (String name : names) {
         UserDTO dto = new UserDTO(name);
         System.out.println(dto.name);
      }
   }
}
```

---

9 map() call pure functions + forEach() Printing

```
import java.util.*;

public class MapPureFunctionForEachPrint {

   static int square(int n) {
      return n * n;
   }

   public static void main(String[] args) {

      List<Integer> numbers = new ArrayList<Integer>();
      numbers.add(2);
      numbers.add(3);
      numbers.add(4);

      for (Integer n : numbers) {
         System.out.println(square(n));
      }
   }
}
```

---

10 flatMap() return Stream + forEach() Printing

```
import java.util.*;

public class FlatMapStreamForEachPrint {
   public static void main(String[] args) {

      List<List<Integer>> lists = new ArrayList<List<Integer>>();

      lists.add(Arrays.asList(1, 2));
      lists.add(Arrays.asList(3, 4));

      for (List<Integer> inner : lists) {
         for (Integer n : inner) {
            System.out.println(n);
         }
      }
   }
}
```

---

11 flatMap() split data + forEach() Printing

```
import java.util.*;

public class FlatMapSplitForEachPrint {
   public static void main(String[] args) {

      List<String> sentences = new ArrayList<String>();
      sentences.add("Java Stream");
      sentences.add("Flat Map");

      for (String sentence : sentences) {
         String[] words = sentence.split(" ");
         for (String word : words) {
            System.out.println(word);
         }
      }
   }
}
```

---

12 flatMap() expand collections + forEach() Printing

```
import java.util.*;

public class FlatMapExpandForEachPrint {
   public static void main(String[] args) {

      Map<String, List<String>> data = new HashMap<String, List<String>>();
      data.put("A", Arrays.asList("x", "y"));
      data.put("B", Arrays.asList("z"));

      for (List<String> list : data.values()) {
         for (String value : list) {
            System.out.println(value);
         }
      }
   }
}
```

---

13 sorted() natural ordering + forEach() Printing

```
import java.util.*;

public class SortedNaturalForEachPrint {
   public static void main(String[] args) {

      List<Integer> numbers = new ArrayList<Integer>();
      numbers.add(5);
      numbers.add(1);
      numbers.add(3);

      Collections.sort(numbers);

      for (Integer n : numbers) {
         System.out.println(n);
      }
   }
}
```

---

14 sorted() custom comparator + forEach() Printing

```
import java.util.*;

public class SortedCustomForEachPrint {
   public static void main(String[] args) {

      List<String> names = new ArrayList<String>();
      names.add("Anurag");
      names.add("Ravi");
      names.add("Amit");

      Collections.sort(names, new Comparator<String>() {
         public int compare(String a, String b) {
            return b.compareTo(a);                    // reverse
         }
      });

      for (String name : names) {
         System.out.println(name);
      }
   }
}
```

---

15 sorted() multi-field compare + forEach() Printing

```
import java.util.*;

public class SortedMultiFieldForEachPrint {

   static class Employee {
      String name;
      int age;

      Employee(String name, int age) {
         this.name = name;
         this.age = age;
      }
   }

   public static void main(String[] args) {

      List<Employee> employees = new ArrayList<Employee>();
      employees.add(new Employee("Anurag", 30));
      employees.add(new Employee("Anurag", 25));
      employees.add(new Employee("Ravi", 35));

      Collections.sort(employees, new Comparator<Employee>() {
         public int compare(Employee e1, Employee e2) {

            int nameCompare = e1.name.compareTo(e2.name);
            if (nameCompare != 0) {
               return nameCompare;
            }

            return e1.age - e2.age;
         }
      });

      for (Employee e : employees) {
         System.out.println(e.name + " " + e.age);
      }
   }
}
```

16 peek() logging + forEach() Printing

```
import java.util.*;

public class PeekLoggingForEachPrint {
   public static void main(String[] args) {

      List<Integer> list = Arrays.asList(1, 2, 3);

      for (Integer n : list) {
         System.out.println("Peek: " + n);
         System.out.println(n);
      }
   }
}
```

---

17 peek() debugging + forEach() Printing

```
import java.util.*;

public class PeekDebugForEachPrint {
   public static void main(String[] args) {

      List<Integer> list = Arrays.asList(10, 20, 30);

      for (Integer n : list) {

         if (n == 20) {
            System.out.println("Debug hit");
         }

         System.out.println(n);
      }
   }
}
```

---

18 peek() metrics + forEach() Printing

```
import java.util.*;

public class PeekMetricsForEachPrint {
   public static void main(String[] args) {

      List<Integer> list = Arrays.asList(5, 10, 15);
      int counter = 0;

      for (Integer n : list) {
         counter++;
         System.out.println(n);
      }

      System.out.println("Total processed: " + counter);
   }
}
```